

## Refrigerator/Freezer Thermometer

The McKesson triple display digital thermometer simultaneously shows the current, minimum and maximum temperatures and updates continuously. An audible and visual alarm will trigger when the temperatures goes above or below the set temperatures. The minimum/maximum feature monitors critical temperatures for any period of time, such as overnight or weekends. To comply with regulatory requirements, time-stamped thermometers provide the date and time when the temperature being monitored exceeds the minimum and maximum settings and in real time. Also, an audible alarm will sound and the flashing LED will be visible. Each thermometer is certified, serialized and traceable to NIST in Thermco's ISO17025 (Accreditation No. 69071) Calibration Laboratory and accredited by ILAC-MRA to assure accuracy and compliance with regulatory agencies.

### Features and Benefits

**MCK821RFV and MCK821RFV2**  
**Refrigerator/Freezer Thermometer**  
**TRIPLE DISPLAY | SINGLE & DUAL PROBE**

- Visual LED and audible beeping alarms
- Bio-safe glycol/water probe medium
- Standard size vaccine bottles
- NIST traceable
- Min-Max temp with time and date stamp
- Readings in memory
- Low/high alarm limit setting
- Not made with natural rubber latex

### Specification:

Measuring range: -50 ~ 70°C (-58 ~ 158°F)

Display accuracy: ±0.3°C (±0.5°F)

Display resolution: 0.1°

Display update: 10 seconds

Alarm Setting resolution: 0.1°

Time accuracy: ±1 second per day

Time display format: 12 or 24 hours format

Date display format: d/m/y or m/d/y user option

Effective calendar period: 2013 ~ 2099

Battery life: ~8000 hours

Working temperature: 0 ~ 50°C / 32 ~ 122°F

Display size: 47 (W) x 39 (H) mm

Sensor cable length: 3200 mm

Sensor bottle size: 19.5 (Φ) x 40 (H) mm PE bottle

Product size: 75 (W) x 124 (H) x 19 (D) mm

Accessories: x2 1.5 volt, type AAA battery • x1 sensor in bottle



## Refrigerator/Freezer Thermometer

The McKesson triple display digital thermometer simultaneously shows the current, minimum and maximum temperatures and updates continuously. An audible alarm will sound when the temperature rises above or goes below the set temperatures. The minimum/maximum feature monitors critical temperature for any period of time, such as overnight or weekends. Reset buttons are conveniently located on the front panel for ease of use. Each thermometer is certified and traceable to NIST. Each thermometer is serialized. The thermometer probe is housed in an unbreakable plastic bottle or vial filled with a bio-safe glycol/water or sand buffering media which maintains the thermometer reading when the instrument door is opened. The thermometer and the bottle housing the probe have dual magnets allowing attachment to doors or walls of the instrument. Other features include a flip-open stand, wall-mounting key hole and an included AAA alkaline battery. The instrument can display temperatures in Celsius or Fahrenheit.

### Features and Benefits

#### MCK895RFV

#### Refrigerator/Freezer Thermometer

#### TRIPLE DISPLAY | SINGLE PROBE | LARGE DIGIT

- NIST traceable
- Bio-safe glycol/water probe medium
- Minimum and maximum reading memories with real time and date stamp
- Low/high alarm limit setting programmable in 1° increments
- Audible and LED alarm feature provides alert when temperature exceeds set points
- Low/high alarm limit setting
- Not made with natural rubber latex

#### Specification:

Measuring range: • (Internal Sensor ) 0 to 50°C (32 to 122°F)

• (External probe) -50 to 70°C (-58 to 158°F)

Display Accuracy: ±0.5°C / ±0.9°F over full range

Display Resolution: 0.1°

Display Refresh Rate: 10 seconds

Battery: 1.5v, type AAA x1 piece

Display size: 79w x 65h mm

Thermometer size: 96w x 108h x 19d mm



## Refrigerator/Freezer Thermometer

### Features and Benefits

#### MCK895WRFT

#### Wireless Refrigerator/Freezer Thermometer

TRIPLE DISPLAY | SINGLE PROBE | LARGE DIGIT

- NIST traceable
- Monitor refrigerators and freezers up to 30 feet away with wireless temperature sensor
- 164 Foot open field / 32 Foot Inside Fridge wireless distancem
- Triple display shows current, minimum and maximum temperatures
- Programmable low and high alarm limit
- 3 channels temp measurement: Internal - devices with ambient temp, External - probe with bottle, wireless - Bluetooth transmitterts
- Not made with natural rubber latex



### Specification:

Measuring range: -58° to +158°F (-50° to +70°C) External Bottle Sensor, -40° to +122°F (-40° to +50°C) Wireless Bottle Sensor

Display Accuracy:  $\pm 0.5^{\circ}\text{C}$  /  $\pm 0.9^{\circ}\text{F}$  over full range

Display Resolution: 0.1°

Display Refresh Rate: Every 10 seconds / Every 30 Seconds in Wireless Mode

Battery: 1.5v, type AAA x1 piece

Display size: 79w x 65h mm

Thermometer size: 96w x 108h x 19d mm

## Refrigerator/Freezer Thermometer

The McKesson versatile fridge/freezer dual channel thermometer records the date and time of the minimum and maximum readings, while independently monitoring user programmable high and low alarms. The unit incorporates an audible and visual LED programmable alarm that indicates when the temperature is outside the set limits. The alarm is programmable in 1° increments. Three foot micro-cable permits refrigerator or freezer doors to close without obstruction. Each thermometer is housed in an ABS case and has two magnetic pads for appliance mounting and a flip out desk stand. It's a perfect device for measuring and tracking temperatures related to the cold storage of food, chemicals, pharmaceuticals, vaccines, and more.


### Features and Benefits

#### MCK8100MATB

#### Refrigerator/Freezer Thermometer

#### DUAL PROBE

- NIST traceable
- Traceable certificate supplied
- Bio-safe glycol/water probe medium
- Minimum and maximum reading memories with real time and date stamp
- Low/high alarm limit setting programmable in 1° increments
- Audible and LED alarm feature provides alert when temperature exceeds set points
- Replaceable sensor in bottles
- Not made with natural rubber latex



#### Specification:

Measuring range: -40 to 70°C (-40 to 158°F)

Display accuracy: ±1°C

Display resolution: 0.1°

Display update: 10 seconds

Display Refresh Rate: 10 seconds

Programmable Alarm: 1° increments

Alarm Duration Counter: 99 hours and 59 minutes

Probe Cord Length: 1,000mm

Display Size: 90(w) x 16(h) mm

Product Size: 135(w) x 45(h) x 23(d) mm

Battery: x2 1.5v, type AAA

## Refrigerator/Freezer Thermometer

The McKesson data logger thermometer is designed to meet today's CDC and VFC requirements for vaccine storage and monitoring. It is a self contained data logger that requires no PC software to generate a complete Excel CVS report. Monitor both the ambient room and refrigerator (or freezer) temperatures simultaneously. It includes a large, easy-to-read display for viewing the current room and external bottle probe temperatures, min and max recorded temperatures, time and battery strength. Each thermometer is certified, serialized and traceable to NIST in Thermco's own ISO17025 Calibration Laboratory, accredited by ILAC-MRA to assure accuracy and compliance with all regulatory requirements. (Accreditation No. 69071)

### Features and Benefits

**MCK80021P & MCK80022P**  
**Refrigerator/Freezer Thermometer(s)**  
**DATA LOGGER | SINGLE & DUAL PROBE**

- NIST/ILAC-MRA traceable
- Traceable certificate supplied
- Log 24 million readings on 2G micro SD card
- Retrieve data from logger with removable SD memory card or by USB cable to PC
- Logger records int/ext min/max temps into memory
- Battery life approximately 10 months in continuous operation with no alarm triggered
- Exceeds government vaccine monitoring guidelines CDC / VFC
- Not made with natural rubber latex



### Specification:

Measuring range: External: -30 ~ 70°C (-22 ~ 158°F) (bottle probe)  
 Internal: 0 ~ 50°C (32 ~ 122°F)

Display accuracy: ±0.5°C / ±0.9°F over full range

Display resolution: 0.1°

Display reading update: 10 seconds

Memory: Removable 2G micro SD card / Max 170 files (.csv)

Memory capacity: 24 million readings

Data logging interval: Once per minute to once per 720 minutes user option

Alarm limit setting resolution: 0.1°

Default alarm value: Low: 0°C, High: 50°C

Time accuracy: ±1 second per day

Time display format: 12 / 24 hours format user option

Effective calendar period: 2014 ~ 2099

Battery: 1.5 volt, type AA or equivalent x3 pieces

Battery life: Approximately 2000 hours in continuous operation with no alarm triggered

Working ambient temperature: 0 ~ 50°C (32 ~ 122°F)

Display size: 70(W) x 64(H) mm

External sensor cable length: 2000 mm

External sensor bottle size: 19.5(Φ) x 40(H) mm PE bottle

Product size: 94(W) x 110(H) x 26(D) mm

+Accessories:

- 1.5 volt, type AA battery x3, External bottle sensor x1
- Mini USB cable 1000mm length x1, 100-240V power adapter x1
- Micro SD card USB adapter x1



## ORDERING INFORMATION

| MFR #       | DESCRIPTION  | QTY        |
|-------------|--|------------|
| MCK821RFV   | Refrigerator/Freezer Thermometer, Triple Display, Single Probe, Large Digit, Thermometer range is -58 To 158° F (-50 To 70° C)   | 1 ea, 1 bx |
| MCK821RFV2  | Refrigerator/Freezer Thermometer, Triple Display, Dual Probe, Large Digit, Thermometer range is -58 To 158° F (-50 To 70° C)   | 1 ea, 1 bx |
| MCK895RFV   | Refrigerator/Freezer Thermometer, Single Probe, Large Digit, Thermometer range is -58 To 158° F (-50 To 70° C)   | 1 bx       |
| MCK895WRFT  | Wireless Refrigerator/Freezer Thermometer, Triple Display, Single Probe, Large Digit, Thermometer range is -58° to +158°F (-50° to +70°C), External Bottle Sensor range is -40° to +122°F (-40° to +50°C), Wireless Bottle Sensor Internal Sensor / 2 Bottle Probes Flip-out Stand / Wall Mount Battery Operated | 1 bx       |
| MCK8100MATB | Refrigerator/Freezer Thermometer, Dual Probe Thermometer range is -58 To 158° F (-50 To 70° C)   | 1 ea, 1 bx |
| MCK80021P   | Refrigerator/Freezer Thermometer, Data Logger, Single Probe, Software-less Reporting, Thermometer range is -58 to 158° F (-50 To 70° C)  | 1 ea, 1 bx |
| MCK80022P   | Refrigerator/Freezer Thermometer, Data Logger, Dual Probe, Software-less Reporting, Thermometer range is -58 to 158° F (-50 To 70° C) -58 to 158° F (-50 To 70° C)   | 1 ea, 1 bx |
| MCKACCF A1  | Wi-Fi/SD Card, Flash-Alert, 16 GB, Software-Less Reporting, For use with the McKesson Dual Probe Data Logger Refrigerator/ Freezer Thermometer, MFR # MCK80022P  | 1 ea       |
| MCKACCRTAMB | Ambient Room Temperature Sensor, For use with the McKesson Dual Probe Data Logger Refrigerator/ Freezer Thermometer, MFR # MCK80022P   | 1 ea       |

### Satisfaction Guaranteed

For complete details, please visit  
[mms.mckesson.com/mckesson-brands](https://mms.mckesson.com/mckesson-brands).

With McKesson Brands, you'll never have to compromise. We deliver quality products at competitive prices, backed by our 100% satisfaction guarantee. We have decades of experience in the market, and we offer you support and work to help ensure you have the products you need, when you need them—making it even easier for you to provide the best care for your patients.

The product information contained in this document, including the product images and additional product materials, was collected from various supplier sources. All product claims and specifications are those of the product suppliers and have not been independently verified by McKesson Medical-Surgical or its affiliates ("McKesson"). McKesson is not responsible for errors or omissions in the product information.

The properties of a product may change or be inaccurate following the posting or printing of the product information in the document, either in the print or online version. Caution should be exercised when using or purchasing any products from McKesson's online or print documents by closely examining the product packaging and the labeling prior to use.

Due to product changes, information listed in this document is subject to change without notice. This information is placed solely for your convenience in ordering and McKesson disclaims all responsibility for its completeness and accuracy, whether or not the inaccuracy or incompleteness is due to fault or error by McKesson.

McKesson Medical-Surgical  
9954 Mayland Drive  
Richmond, VA 23233  
[mms.mckesson.com/mckesson-brands](https://mms.mckesson.com/mckesson-brands)

Post-Acute Care and Home Health  
800.347.2456

Home Medical Equipment  
888.822.8111

Primary Care  
866.625.2679

McKesson Brands Support  
800.777.4908