SAFETY DATA SHEET

Air Wick Freshmatic - Sparkling Citrus



1. Product and company identification

Product name	: Air Wick Freshmatic - Sparkling Citrus
Distributed by	: Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600
	Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9 CANADA Telephone: +1 905 283 7000
Emergency telephone number (Medical)	: 1-800-338-6167
Emergency telephone number (Transport)	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887
Website:	: http://www.rbnainfo.com

Product use : Air care, continuous action (solid and liquid)

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS #	:	D8375562 v1.0
Formulation #	:	3137543 v1.0

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
AirCare Product Consumer Use	

2. Hazards identification

 Classification of the substance or mixture
 : FLAMMABLE AEROSOLS - Category 1

 GASES UNDER PRESSURE - Compressed gas EYE IRRITATION - Category 2A

GHS label elements

 Code #
 :
 FF3137543
 SDS #
 :
 D8375562 v1.0
 Date of issue
 :
 4/8/2020
 1/15

 (D8375562) NA
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .
 .</

2. Hazards identification

Hazard pictograms	
Signal word	: Danger
Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.
Precautionary statements	
General	 Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
Response	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal	: Not applicable.
Supplemental label elements	: None known.
Hazards not otherwise classified	: None known.

3. Composition/information on ingredients

Substance/mixture : Mixture		
Ingredient name	%	CAS number
ethanol	≥60 - ≤80	64-17-5
butane	≥10 - ≤30	106-97-8
propane	≥5 - ≤10	74-98-6
Linalool	<1	78-70-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary first aid measures **Eve contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Date of issue : 4/8/2020 Code # : FF3137543 SDS # : D8375562 v1.0 2/15 (D8375562) NA

Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

moot importante of impte		
Potential acute health	<u>effects</u>	
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/	symptoms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may
	be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5. Fire-fighting measures

Specific hazards arising from the chemical	: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Conditions for safe storage, including any incompatibilities	:	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name		Exposure limits
ethanol		ACGIH TLV (United States, 3/2018).
		STEL: 1000 ppm 15 minutes.
		OSHA PEL 1989 (United States, 3/1989).
		TWA: 1000 ppm 8 hours.
		TWA: 1900 mg/m ³ 8 hours.
		NIOSH REL (United States, 10/2016).
		TWA: 1000 ppm 10 hours.
		TWA: 1900 mg/m ³ 10 hours.
		OSHA PEL (United States, 5/2018).
		TWA: 1000 ppm 8 hours.
		TWA: 1900 mg/m ³ 8 hours.
butane		OSHA PEL 1989 (United States, 3/1989).
		TWA: 800 ppm 8 hours.
		TWA: 1900 mg/m ³ 8 hours.
		NIOSH REL (United States, 10/2013).
		TWA: 800 ppm 10 hours.
		TWA: 1900 mg/m ³ 10 hours.
		ACGIH TLV (United States, 6/2013).
		STEL: 1000 ppm 15 minutes.
propane		OSHA PEL 1989 (United States, 3/1989).
		TWA: 1800 mg/m ³ 8 hours.
		TWA: 1000 ppm 8 hours.
		NIOSH REL (United States, 10/2016).
		TWA: 1000 ppm 10 hours.
		TWA: 1800 mg/m ³ 10 hours.
		OSHA PEL (United States, 5/2018).
		TWA: 1000 ppm 8 hours.
		TWA: 1800 mg/m ³ 8 hours.
		ACGIH TLV (United States, 3/2018). Oxyger Depletion [Asphyxiant].
ode # : FF3137543 SDS #	: D8375562 v1.0	Date of issue : 4/8/2020 5/15

8. Exposure controls/personal protection

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

9. Physical and chemical properties

(D8375562) NA

<u>Appearance</u>	
Physical state	: Liquid. [Aerosol.]
Color	: Colorless to light yellow.
Odor	: Fragrant.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Code # : FF3137543	SDS # : D8375562 v1.0 Date of issue : 4/8/2020 6/15

9. Physical and chemical properties

Boiling point	: Not available.
Flash point	: Closed cup: <0°C (<32°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.
Aerosol product	
Type of aerosol	: Spray

10 Stability and	reactivity	
Heat of combustion	: 30.44 kJ/g	
l ype of aerosol	: Spray	

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
Linalool	LD50 Dermal	Rabbit	5610 mg/kg	-
	LD50 Dermal	Rat	5610 mg/kg	-
	LD50 Oral	Rat	2790 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

11. Toxicological information

Product/ingredient name	Result		Species	Score	Exposure	Observation
ethanol	Eyes - Mo	derate irritar	t Rabbit	-	0.066666667 minutes 100	-
	Eyes - Mil	d irritant	Rabbit	-	milligrams 24 hours 500 milligrams	-
	Eyes - Mo	derate irritar	it Rabbit	-	100 microliters	-
	Skin - Mild irritant		Rabbit	-	400 milligrams	-
	Skin - Moderate irritant		t Rabbit	-	- 24 hours 20 milligrams	
Linalool	Eyes - Mo	Eyes - Moderate irritant Rabbit - 1 hours 0.		1 hours 0.1 Mililiters	-	
	Eyes - Mo	derate irritar	nt Rabbit	-	100 microliters	-
	Skin - Mo	derate irritan	t Guinea pig	-	24 hours 100 milligrams	-
	Skin - Mile	d irritant	Human	-	72 hours 32 Percent	-
	Skin - Mile	d irritant	Man	-	48 hours 16 milligrams	-
	Skin - Mile	d irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Sev	vere irritant	Rabbit	-	24 hours 100 milligrams	-
<u>Conclusion/Summary</u> Skin	: Based o	n available d	ata, the classificatio	on criteria are	e not met.	
Eyes Beenireter			Method: Causes s	-		
Respiratory Sensitization Not available.	. Daseu o	n avaliable u	ata, the classificatio		not met.	
<u>Conclusion/Summary</u> Skin	. Deced o	n availabla d	ata tha alaasifisatia	n oritorio oro	not mot	
Respiratory			ata, the classification ata, the classification ata, the classification ata.			
<u>Autagenicity</u> Not available.						
Conclusion/Summary	: Based o	n available d	ata, the classificatio	on criteria are	e not met.	
Carcinogenicity Not available.						
Conclusion/Summary <u>Classification</u>	: Based o	n available d	ata, the classificatio	on criteria are	e not met.	
Product/ingredient name	OSHA	IARC	NTP			
ethanol	-	1	-			

Not available.

D8375562 v1.0	
11. Toxicological i	nformation
Conclusion/Summary Teratogenicity Not available.	: Based on available data, the classification criteria are not met.
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Specific target organ toxicit Not available.	t <u>y (single exposure)</u>
Specific target organ toxicit Not available.	t <u>y (repeated exposure)</u>
Aspiration hazard Not available.	
Information on the likely routes of exposure	: Not available.
Potential acute health effects	
Eye contact	- Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Sumptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following:
	pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health efformation of the second	<u>ects</u>
Conclusion/Summary	: Based on available data, the classification criteria are not met.
General	: No known significant effects or critical hazards.
Code # : FF3137543 (D8375562) NA	SDS # : D8375562 v1.0 Date of issue : 4/8/2020 9/15

11. Toxicological information

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
ethanol	7000	N/A	N/A	124.7	N/A
butane	N/A	N/A	N/A	658	N/A
Linalool	2790	5610	N/A	N/A	N/A

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
	Acute LC50 11000000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
Linalool	Acute EC50 36.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 28.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Linalool	-	62.4 % - Re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Linalool					Readily	

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low
butane	2.89	-	low
propane	1.09	-	low
Linalool	2.84	-	low

12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

	TDG Classification	DOT Classification	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1	2.1
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional inform DOT Classificat TDG Classificat	ion : <u>Limited of</u> <u>Packagin</u> <u>Quantity</u> <u>Special p</u> ion : Product of Goods Ro <u>Explosiv</u>	quantity No. In instruction Exceptions Imitation Passenger air provisions N82 classified as per the follow egulations: 2.13-2.17 (Cla e Limit and Limited Qua er Carrying Road or Rai	craft/rail: 75 kg. Cargo ring sections of the Tra iss 2). Intity Index 1	
IMDG	: Emergen	icy schedules F-D, S-U provisions 63, 190, 277, 3		
ΙΑΤΑ	Cargo Air	<u>limitation</u> Passenger and craft Only: 150 kg. Packa er Aircraft: 30 kg. Packagi	ging instructions: 203.	Packaging instructions: 20 Limited Quantities -

Passenger Aircraft: 30 kg. Packaging instructions: Y203. Special provisions A145, A167, A802

14. Transport information

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

15. Regulatory information

U.S. Federal regulations	: 0	Clean Water Act (CW	/A) 311: isopentyl acetate; cyclohexane
	C	Clean Air Act (CAA)	112 regulated flammable substances: butane; propane
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: N	Not listed	
Clean Air Act Section 602 Class I Substances	: N	lot listed	
Clean Air Act Section 602 Class II Substances	: N	lot listed	
DEA List I Chemicals (Precursor Chemicals)	: N	lot listed	
DEA List II Chemicals (Essential Chemicals)	: N	lot listed	
SARA 302/304			
Composition/information	<u>on in</u>	<u>gredients</u>	
No products were found.			
SARA 304 RQ	: N	lot applicable.	
<u>SARA 311/312</u>			
Classification	G	AMMABLE AEROSO ASES UNDER PRES /E IRRITATION - Ca	SURE - Compressed gas
Composition/information	<u>on in</u>	<u>gredients</u>	
Name		%	Classification
1			

%	Classification
≥60 - ≤80	FLAMMABLE LIQUIDS - Category 2
	EYE IRRITATION - Category 2A
≥10 - ≤30	FLAMMABLE GASES - Category 1
	GASES UNDER PRESSURE - Compressed gas
≥5 - ≤10	FLAMMABLE GASES - Category 1
	GASES UNDER PRESSURE - Compressed gas
<1	FLAMMABLE LIQUIDS - Category 4
	SKIN IRRITATION - Category 2
	EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1B
	≥60 - ≤80 ≥10 - ≤30 ≥5 - ≤10

State regulations

Massachusetts


: The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL; BUTANE; PROPANE

Code #	: FF3137543	SDS #	: D8375562 v1.0	Date of issue	: 4/8/2020	12/15
	(D8375562) NA					

15. Regulatory in	formation
New York	: None of the components are listed.
New Jersey	 The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE; PROPANE
Pennsylvania	 The following components are listed: DENATURED ALCOHOL; ETHANOL; BUTANE; PROPANE
<u>California Prop. 65</u>	
This product does not	require a Safe Harbor warning under California Prop. 65.
Label elements CPSC	
Signal word Hazard statements Precautionary measures	 CAUTION EYE IRRITANT. CONTENTS UNDER PRESSURE. KEEP OUT OF REACH OF CHILDREN. May be harmful if directly inhaled. May cause allergic reaction in some individuals. DO NOT spray towards face or body. DO NOT get in eyes. Avoid contact with skin. CONTAINER MAY EXPLODE IF HEATED. DO NOT puncture or incinerate container. DO NOT expose to heat or store at temperatures above 120F (49C). DO NOT position near heat or electrical sources. DO NOT spray into open flames. DO NOT spray directly onto surfaces. In case of contact with surfaces, wipe immediately with damp cloth. Use in well ventilated rooms away from sleeping areas. For adult use only. Product is not a toy. Contains propellants, petroleum solvent and fragrance.
CCCR	
Signal word Hazard statements	 EXTREME DANGER VERY FLAMMABLE. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. MAY IRRITATE EYES AND SKIN.
Precautionary measures	 Do not smoke. Do not puncture. Do not burn. Do not get in eyes, on skin, or on clothing. KEEP OUT OF REACH OF CHILDREN AND PETS. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat.
Additional information / Red	<u>commendations</u>
Additional information	: If swallowed, DO NOT INDUCE VOMITING. IMMEDIATELY call a Physician or Poison Control Center. If in eyes, IMMEDIATELY rinse eyes with water. Remove any contact lenses and continue rinsing eyes r at least 15 minutes. If irritation persists, get medical attention. If on skin, wash with soap and water. Discontinue use IMMEDIATELY and get medical attention if a reaction develops. Contains petroleum solvents, propellants and fragrance oils.
Recommendations	 NOTE TO PARENTS: Use only as directed. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.
Recommendations	: No known significant effects or critical hazards.

16. Other information

Hazardous Material Information System (U.S.A.)



Code # : FF3137543 (D8375562) NA SDS #

13/15

16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



NFPA (30B) aerosol Flammability Level 3

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
Date of issue	: 4/8/2020
Date of previous issue	: No previous validation
Version	: 1
Prepared by	: Reckitt Benckiser LLC. Product Safety Department 1 Philips Parkway Montvale, New Jersey 07646-1810 USA. FAX: 201-476-7770

Indicates information that has changed from previously issued version. <u>Notice to reader</u>

SDS # : D8

16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.