

1. Identification

Product identifier	Motor Medic Heavy Duty Brake Fluid - DOT 3	
Other means of identification		
SDS number	M4412	
Part No.	M4412, M4432, M4434, M4440, M4449	
Tariff code	3819.00.0010	
Recommended use	DOT 3 Brake Fluid	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	RSC Chemical Solutions	
Address	600 Radiator Road Indian Trail, NC 28079 United States	
Telephone	Customer Service:	(704) 821-7643
	Technical:	(704) 684-1811
Website	www.rscbrands.com	
E-mail	Not available.	
Emergency phone number	Emergency Telephone:	(303) 623-5716
	Emergency Contact:	RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity (the unborn child)	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	Causes serious eye irritation. Suspected of damaging the unborn child.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
2-(2-butoxyéthoxy) Éthanol		112-34-5	5 - < 10
Diethyleneglycol		111-46-6	5 - < 10
Polyethyleneglycol		25322-68-3	5 - < 10
Diethylene Glycol Methyl Ether		111-77-3	1 - < 3
Diethylenglykolmonoethylether		111-90-0	1 - < 3
Other components below reportable levels			70 - < 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Diethyleneglycol (CAS 111-46-6)	TWA	10 mg/m ³	
Diethylenglykolmonoethyl ether (CAS 111-90-0)	TWA	140 mg/m ³	
Polyethyleneglycol (CAS 25322-68-3)	TWA	25 ppm 10 mg/m ³	Particulate.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Clear.

Physical state

Liquid.

Form

Liquid.

Color

Yellow to light amber

Odor

Mild

Odor threshold

Not available.

pH

10 - 11.5

Melting point/freezing point

-90.58 °F (-68.1 °C) estimated

Initial boiling point and boiling range

446.72 °F (230.4 °C) estimated

Flash point

Not available.

Evaporation rate

< 0.01 BuAc

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.01 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	442 °F (227.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	8.33 - 9.02 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	23.19 % estimated
Specific gravity	1 - 1.07

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)		
Acute		
Dermal		
LD50	Rabbit	2700 mg/kg

Components	Species	Test Results
Oral		
LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	4500 mg/kg
Diethylene Glycol Methyl Ether (CAS 111-77-3)		
Acute		
Dermal		
LD50	Rabbit	6540 mg/kg
Oral		
LD50	Guinea pig	4160 mg/kg
		4.16 g/kg
	Mouse	8222 mg/kg
	Rabbit	7.19 g/kg
	Rat	5500 mg/kg
Diethyleneglycol (CAS 111-46-6)		
Acute		
Dermal		
LD50	Rabbit	11890 mg/kg
Oral		
LD50	Cat	3300 mg/kg
	Dog	9000 mg/kg
	Guinea pig	8700 mg/kg
	Mouse	13.3 g/kg
	Rabbit	26.9 g/kg
	Rat	12565 mg/kg
Diethylenglykolmonoethylether (CAS 111-90-0)		
Acute		
Dermal		
LD50	Guinea pig	5900 mg/kg
	Mouse	6000 mg/kg
	Rabbit	8476 mg/kg
	Rat	6000 mg/kg
Oral		
LD50	Guinea pig	3000 mg/kg
	Mouse	6.58 g/kg
	Rabbit	3620 mg/kg
	Rat	1920 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results	
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)			
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	1300 mg/l, 96 hours
Diethylene Glycol Methyl Ether (CAS 111-77-3)			
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	7500 mg/l, 96 hours
Diethyleneglycol (CAS 111-46-6)			
Aquatic			
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>)	> 32000 mg/l, 96 hours
Diethylenglykolmonoethylether (CAS 111-90-0)			
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 10000 mg/l, 96 hours
Polyethyleneglycol (CAS 25322-68-3)			
Aquatic			
Fish	LC50	Atlantic salmon (<i>Salmo salar</i>)	> 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-(2-butoxyéthoxy) Éthanol	0.56
Diethylenglykolmonoethylether	-0.54

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)	Listed.
Diethylene Glycol Methyl Ether (CAS 111-77-3)	Listed.
Diethylenglykolmonoethylether (CAS 111-90-0)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - No
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-(2-butoxyéthoxy) Éthanol	112-34-5	5 - < 10
Diethylene Glycol Methyl Ether	111-77-3	1 - < 3
Diethylenglykolmonoethylether	111-90-0	1 - < 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)
Diethylene Glycol Methyl Ether (CAS 111-77-3)
Diethylenglykolmonoethylether (CAS 111-90-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)
Diethylene Glycol Methyl Ether (CAS 111-77-3)
Diethylenglykolmonoethylether (CAS 111-90-0)

US. Massachusetts RTK - Substance List

Diethylene Glycol Methyl Ether (CAS 111-77-3)

US. New Jersey Worker and Community Right-to-Know Act

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Diethylene Glycol Methyl Ether (CAS 111-77-3)

Diethylenglykolmonoethylether (CAS 111-90-0)

US. Pennsylvania Worker and Community Right-to-Know Law

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Diethylene Glycol Methyl Ether (CAS 111-77-3)

Diethyleneglycol (CAS 111-46-6)

Diethylenglykolmonoethylether (CAS 111-90-0)

US. Rhode Island RTK

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Diethylene Glycol Methyl Ether (CAS 111-77-3)

Diethylenglykolmonoethylether (CAS 111-90-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.


International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-13-2015
Version #	01
HMIS® ratings	Health: 2* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0
NFPA ratings	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.