GLOBAL SWEEPER OPERATOR'S INSPECTION REPORT SHEET

Sweeper# Date

THIS SIDE IS FOR PRE-TRIP ONLY. (MUST BE CHECKED BEFORE GETTING INTO THE SWEEPER)

This listed items should be checked out at the start of your shift everyday. Problems should be corrected and reported to your supervisor prior to use. Every box should have an \underline{X} to indicate that it has been checked out and has no problems. This form must be completed and signed.

ems be	elow must be checked out	CHECKED
1	L - UNDER THE HOOD:	
•	Engine Oil (proper level/type)	
•	Belts (no tears or cuts)	
•	Fan (no damage, not loose)	
•	Pulleys, Tensioner	
•	Radiator or Oil Cooler for leaks	
•	Coolant Tank (check level and for leaks)	
•	Air Filter (Empty end cap service as required)	
•	Water Spray Strainer (clean, check seal)	
•	Safety Switches at Engine Compartment	
2	2 - AROUND THE SWEEPER:	
•	Check Under Sweeper for Leaks	
•	Body Damage (dents/scratches)	
•	In Cab Filter	
•	Brake Fluid Reservoir	
•	Headlights	
•	Turn Signal/Stop/Safety /Reverse Lights	
•	Windshield, Wiper Blade, Washer Fluid	
•	Front Steer Tires/Wheels/ILug Nuts	
•	Front Axle Hub Oil/Grease	
•	Front and Gutter Broom Water Spray Bars	
•	Front Deflector/s	
•	Mirrors	
•	Door Handle	
•	Curb Side Cab Steps	
•	R&LGB Light	
•	R&LGB ShaftTilt Bearings (grease lines)	
•	Leaf Gate-rollers, arms, deflector curtains	
•	Lube R/LGB Lift Pulleys and Swing Bearings	
•	Lube and Check R/L Gutter Broom Shocks	
•	Lube R&L Gutter Broom Dish	
•	R&LGB Adjustment Chain (secured)	
•	Fuel Cap (secured, check fill neck and cap	
	for cleanliess)	
•	Dirt Shoe Adjustment/Wear (grease daily)	
•	Dirt Shoe Chains (secured)	
•	Pick Up Broom Arm Pivot Bearings (lube)	
•	Lube Pick Up Broom Bearing	
•	Remove any debris PUB Bearing Shaft	

st be comp	oletea ana signea.	OUECUE
	Items below must be checked out	CHECKED
•	Grease Lines (ALL)	
•	Rear Tire (pressure, tread depth)	
•	Rear Wheels, Lug Nuts	
•	Hydraulic Cap Seal	
•	Hydraulic Fluid Level	
•	Radiator Cap	
•	Back Up Camera	
•	Light Bar	
•	Bumper Pads	
•	Dump Chute and Linkages	
•	Hopper Dump Door Lift Rods	
•	Pick Up Broom Motor(remove shaft debris)	
•	Pick up Broom Lift Linkeages	
•	Pick Up Broom Adjustment	
•	Pick up Broom Float Spring	
•	Park Brake Actuator (be sure it's working	
	properly and linkage is secured)	
•	Park Brake Cable and Boots	
•	Check Hydraulic Manifold Compartment	
	for cleanliness and leaks	
•	Vehicle # and City Logo (both sides)	
3 -	- UNDERNEATH THE HOPPER	
•	Safety Supports	
•	Lift Cylinders	
•	Rubber Seal Around Elevator	
•	Elevator Belts and Sprockets	
•	Squeegee Rubbers	
•	Elevator Flight Brackets	
•	Elevator Bottom Arch Deflectors	
•	Elevator Top Arch	
•	Dirt Deflector On Dirt Shoe	
•	Dirt Deflector On Dirt Shoe	
•	Optional Auto Lube (filled and working-	
	Do not overfill Reservoir)	
•	Drain Any Water From Primary Fuel Filter	
•	Pumps/Filters (leaks or lose lines)	
•	Cooler Fans (operation and cleanliness)	
•	Turbo/Exhaust Manifold for Debris	
_	All Hopper Safety Switch	

NAME:	SIGNATURE:
INAIVIE.	SIGNATURE.

GLOBAL SWEEPER OPERATOR'S INSPECTION REPORT SHEET

Continue Pre-Trip Under Hooper	CHECKED	must be completed and signed. • Rear Tire (pressure, tread depth)
Elevator Motor	CHECKED	Wheels
4 - INSIDE THE CAB:		Lug Nuts
Trash/Debris		Hubs (leaks and cap)
Sweeper In Park		Hydraulic Cap
Sweeping Functions or off		Dump Chute Linkage
(sweeper will not start with switch's on)		Dump Chute
Seat Belt		Gutter Brooms (if need to be changed)
Mirror		Main Broom (if need to be changed)
Windows/ Windsheild Wipers		Pick Up Broom Motor
Gauges/Horn		Clear Debris in Gutter Broom
POST TRIP INSPECTIONS BELOW	•	Clear Debris in Main Broom
1- INSIDE THE CAB:		Park Brake Actuator (be sure it's working
Sweeper In Park		properly and linkage is secured)
(if not in park sweeper won't start)		Vehicle # and City Logo (both sides)
Trash/Debris		COMMENTS:
Switches (all are off)		
Windshield (chips or cracks)		
 Windows (closed and secured) 		
 Mirrors 		
 City Radio On and Working 		
2 - AROUND THE SWEEPER:		
 Check Under Sweeper for Leaks 		
 Body Damage (dents/scratches) 		
 Headlights 		
 Turn Signals 		
• Windshield		
Front Steer Tires		
• Wheels		
Lug Nuts/Bearing Hub Covers		
• Fuel Cap (secured)		
Grease Lines (ALL) 1 Burn a pattern to check your brooms or		

5 Always have your hopper safety supports in whenever you're hopper is in the air for maintenance or wash-up.

NAME: SIGNATURE:	
NAME. SIGNATURE:	