

Adjustable White Motion Puck and Light Bar Owner's Manual


BL-PMTN-W Adjustable White Motion Puck Light | BL-BMTN-W Adjustable White Motion Light Bar



Puck Light

Battery Installation:

1. To open, when looking at the back, twist back cover counter-clockwise and remove.
2. Insert 3 AA batteries (follow the illustration inside the battery compartment). Ensure the batteries are inserted so that the flat ends are making contact with the springs.
3. To close, replace the cover and turn clockwise.



Mounting Installation:

Mounting with magnets to metal tabs with 3M adhesive


Determine mounting location (Caution – adhesive tape may remove paint or damage the surface when removed.)

1. On the metal tab, peel and remove the tape backer to expose adhesive. Place bare metal side against the magnet on the back of the puck light.
2. Make sure the area where you want to attach the light is clean and clear of debris and dust.
3. Place the puck light in the desired mounting location. Firmly press the adhesive tape against your surface to mount the light.

Light Bar

Battery Installation:

1. To open, when looking at the back, press the two tabs along edge of battery cover to release. Gently lift the cover about 1 inch, and slide tabs out to release and remove.
2. Insert 6 AA batteries (follow the illustration inside the battery compartment). Ensure the batteries are inserted so that the flat ends are making contact with the springs.
3. To close, replace the cover by sliding the two tabs into the open side slits, and gently close the other side until the tabs snap into place securing the cover.



Mounting Installation:

Mounting with magnets to metal tabs with 3M adhesive

Determine mounting location (Caution – adhesive tape may remove paint or damage the surface when removed.)

1. On the metal tabs, peel and remove the tape backer to expose adhesive. Place bare metal sides against the two magnets on the back of the light bar.
2. Make sure the area where you want to attach the light is clean and clear of debris and dust.
3. Place the light bar in the desired mounting location. Firmly press the adhesive tape against your surface to mount the light.

Manual Light Operation:

Determine if you want the light to operate on motion in any light condition, or only in the dark. Inside the battery compartment is a button to change operation of light sensing on or off. The light will flash once to confirm the "light sensing on" setting, and flash twice to confirm the "light sensing off" setting.

1. Tap the lens to power on the light. The light will return to its last-used brightness and white color setting.
2. If the last used setting was not 3000K (warm white) and 100% brightness, then tapping the lens again will return the light to 3000K at full brightness. Repeated taps will cycle through white color temperatures: 4000K > 5000K > 3000K.
3. To Dim – tap and hold the lens, the light will smoothly dim from 100% to 10% or until you release the lens at your desired light level. Release and re-press the lens to restart the dimming cycle in the opposite direction. When holding the lens to dim, the light will stop at its lowest and highest dim levels.
4. Once you have the white light color temperature chosen and the brightness, the light will turn off after 30 seconds of no motion and operate at the last setting each time it sees motion.
5. Light bar has a swiveling motion eye that allows you to focus the sensor to be more or less sensitive.

Warning

To reduce the risk of electrical shock, do not put the unit in water or other liquid. To clean, use a soft dry cloth. Do not place or store light where it can fall or be pulled into a tub or sink.

Battery Precautions

1. Use only the size and type of batteries specified.
2. Always purchase the correct size and grade of battery most suitable for the intended use.
3. Be sure to follow the correct polarity when installing the batteries as indicated in the battery compartment.
4. Do not mix alkaline, standard (Carbon-Zinc), or rechargeable (Nickel Cadmium) batteries.
5. Replace all batteries of a set at the same time. Do not mix old and new batteries.
6. Clean the battery contacts and also those of the device prior to battery installation.
7. Do not dispose of batteries in fire.
8. Remove batteries if consumed or if product is to be left unused for an extended period of time.
9. Follow instructions for recycling for the batteries you use. (Lithium-ion batteries must be disposed of at a household hazardous waste collection point (check with your local landfill) or battery recycling drop off location, NOT placed in the trash.)

Limited Warranty

Under normal use and conditions, AmerTac provides to the original purchaser of this product a one year express warranty that is set forth in the Limited Warranty stated in full at www.amertac.com/warranties.

**amertac**

©2021 AmerTac™
250 Boulder Dr.
Breinigsville, PA 18031
610-336-1330

www.amertac.com

Made in China
BO_TL_052_0521