



2-INCH DOWNLIGHTING

Downlight

Wall Wash


Adjustable

2-INCH DOWNLIGHTING



Rediscover why Prescolite's award-winning 2-inch aperture LED recessed family continues to be the perfect solution for the most demanding architectural lighting applications.

DOWNLIGHT



ADJUSTABLE



WALL WASH



ACTUAL SIZE

SMALL. SLEEK. SIGNIFICANT.

More versatile than ever before, the upgraded and expanded D2 Series provides discreet precision and power for seamless integration into the space.



The 14-story *Study Cascade*, the design's centerpiece featuring interconnected staircases and technologically advanced collaboration spaces, is illuminated throughout with *Prescolite D2 Series 2-inch LED luminaires*.

ON THE COVER:

Roy and Diana Vagelos Education Center
Tillotson Design Associates, New York City

Prescolite's 2-inch aperture downlights and adjustable luminaires complement the space and the angles of this state-of-the-art medical and graduate education building without interfering or overpowering the architectural atmosphere they create. In this application, the lighting enhances the architect's vision.



"The small aperture and degree of adjustability all worked in our favor to complement the complex geometries of the architecture while at the same time minimizing glare and delivering comfortable light levels throughout. The finished product is STUNNING."


- Scott Baillie-Hinojosa, Tillotson Design Associates



D2LED LENS DOWNLIGHT

15L	1500 Delivered Lumens
WFL45	Wide Flood 45°
SL	Regressed Solite Lens

D2LED



DISCRETE YET POWERFUL

D2LED offers a wide range of regressed and flush mount lens options that are ideal for exterior entryways and canopies. With lumen outputs rivaling downlights of much larger aperture size, the D2LED provides high performance without sacrificing aesthetic appeal.

FEATURED OPTIONS

SUITABLE FOR WET LOCATIONS 
Ideal for indoor or outdoor covered ceilings

DELIVERED LUMEN OUTPUTS
900, 1200, 1500

REGRESSED LENS OPTIONS
Clear, Diffuse, Solite, Prismatic

FLUSH MOUNT LENS OPTION
Diffuse

D2LED OPEN DOWNLIGHT


15L	1500 Delivered Lumens
FL35	Flood 35°
30K8	3000 Kelvin, 80+ CRI

14FT

11FT

9FT

D2LED OPEN



FLEXIBILITY AND VISUAL COMFORT

Create quiet ceilings in varying heights with limitless combinations of designer finishes and colors coupled with multiple lumen outputs, beams and CCT/CRI. High quality craftsmanship and superior color consistency assures longevity for years to come.

FEATURED OPTIONS

LUMEN OUTPUT

900, 1200, 1500

COLOR RENDERING INDEX

80+ or 95+ CRI

BEAM DISTRIBUTIONS


Medium 25°, Flood 35°, Wide Flood 45°

DIMMING OPTIONS

0-10V 10%, EcoSystem 1%, 0-10V <1%

D2LED WALL WASH

12L	1200 Delivered Lumens
WW	Standard Wall Wash
35K9	3500 Kelvin, 95 CRI



D2LED WW

RE-EXPERIENCE THE ART OF LIGHT

Create a smooth and uniform layer of light from ceiling to floor with no striations. The optical light pipe design of the D2LED standard wall wash allows wide illumination on the wall surface while still contributing valuable lumens to the room side.

FEATURED OPTIONS

DELIVERED LUMEN OUTPUT

700, 900, 1200

WALL WASH DISTRIBUTION

Standard Wall/Room

COLOR CONSISTENCY

<2 SDCM

A2LED ADJUSTABLE

9L	900 Delivered Lumens
FL35	Flood 35°
WT	White Trim Flange

A2LED

IDEAL FOR SLOPED CEILINGS

The innovative dual-slide aiming mechanism of the A2LED enables 360° rotation and 30° vertical tilt to direct the light where it is needed without the use of tools. As with all D2 Series luminaires, no housing is required making it a great choice for tight spaces such as stairways.

D2LED SHIELDED WALL WASH

7L	700 Lumens
SWW	Shielded Wall Wash
27K9	2700 Kelvin, 95 CRI



D2LED SWW

INDUSTRY LEADING WALL WASH

Prescolite's exclusive Shielded Wall Wash option for the D2LED takes our industry leading wall wash to the next level. The optical design of the louver shield directs all light toward the wall while eliminating any peripheral brightness at the ceiling plane, making it the quietest wall wash on the market.

AB2LED ADJUSTABLE

12L	1200 Delivered Lumens
FL35	Flood 35°
PH	1-1/8" Pinhole



AB2LED



INTERCHANGEABLE OPTICS

Proprietary upper reflector options as well as three lower trim style choices including open, slot, and the smallest pinhole aperture on the market allow high-end style with precision.

CREATE BEAUTY AND DRAMA

Accentuate with pinpoint accuracy from below the ceiling. The AB2LED adjustable offers exceptional versatility with field interchangeable optics and an array of media that will empower and inspire.

FEATURED OPTIONS

ADJUSTABILITY

361° Horizontal, 0-35° vertical tilt in 1" ceiling

FIELD INTERCHANGEABLE BEAM DISTRIBUTION

Medium 25°, Flood 35°, Wide Flood 45°

UP TO 2 MEDIA ACCESSORY OPTIONS


Multiple Lenses, Color Filters, and/or Hexcell Louver

ADDITIONAL OPTIONS

REFLECTOR AND COLOR OPTIONS


CONE FINISHES				CONE COLORS				FLANGE COLORS		
STANDARD		Specular		STANDARD		Clear		STANDARD		Varies
SS		Semi-Specular		PW		Pewter				
MFC		American Matte™		BL		Black		CT		Clear Flange
								WT		White Flange
V		Kurt Versen Specular		WE		Wheat		BT		Black Flange
VS		Kurt Versen Softglow®		LW		Light Wheat				
VSS		Kurt Versen SoftSheen™		WC		Painted White				
				BC		Painted Flat Black				

FLANGE OPTIONS



MINIMAL FLANGE OVERLAY

Using a standard size 2-7/8" diameter hole saw provides consistent installation of the aesthetically pleasing minimal reflector flange.



FLUSH MOUNT MUD-IN RING ACCESSORY


FMR2 accessory can be used with all D2 Series downlights, wall wash and adjustables for an upscale ceiling plane appearance.

HOUSING OPTIONS


All D2 Series downlights, wall wash and adjustables are provided standard as install from below with no housing required and fully serviceable from below the ceiling.



NON-IC RATED
(STANDARD)



NON-IC RATED
ACCESSORY



IC RATED
ICAT OR CHICAGO PLENUM
ACCESSORY

AB2LED FEATURES



ADJUSTMENT

Easily adjust horizontal rotation and vertical tilt from below the ceiling with a standard Phillips screwdriver.



VERTICAL TILT

0-361° horizontal rotation and 0-35° vertical tilt in up to 1" ceiling thickness eliminates dead spots.




INTERCHANGEABLE OPTICS

Proprietary upper reflectors feature twist and lock retention and are field interchangeable between 25°, 35° and 45°.




DEGREE INDICATOR

Aim with precision and consistency from below the ceiling with the visual degree indicator.



INDEXED TRIM ALIGNMENT

Lower trim styles are indexed and feature magnetic retention for consistent alignment.




UP TO 2 LENS/MEDIA


Choose from several lenses, color filters or a hexcell louver for use with the AB2 media holder.

DOWNLIGHT

D2LED



Regressed Hexcell
Flat Black Cone & Flange
(Example below)




D2LED
Open Specular

EXAMPLE: D2LED-2D9LED9L30K8WFL45BCBTHB

1. J-TUBE ASSEMBLY		2. VOLTAGE		3. OPTIONS		4. LIGHT ENGINE		5. OUTPUT		6. LED COLOR		7. CRI					
D2LED	J-Tube Assembly with Standard 0-10V 10% Dimming	STANDARD	120/277V	STANDARD	0-10V 10% dimming	2D9LED	2" Open Reflector/ Light Engine Assembly with Xicato module	9L	900 Delivered Lumens	27K	2700 Kelvin	8	Nominal 80+ CRI				
				EDM ⁴	Hi-Lume 1% EcoSystem LED Driver		12L	1200 Delivered Lumens	30K	3000 Kelvin	9	Nominal 95+ CRI					
									35K	3500 Kelvin	40K	4000 Kelvin					
DM01 ⁴	eldoLED 0-10V dimming to less than 1%		15L ⁴	1500 Delivered Lumens													
8. BEAM ANGLE		9. REFLECTOR FINISH		10. REFLECTOR COLORS ³		11. FLANGE OPTIONS ³		12. LENS ²		13. ACCESSORIES							
MD25	Nominal 25°	STANDARD	Specular	STANDARD	Clear Alzak	STANDARD	Anodized Trim Flange	CL	Clear, Regressed	FMR2	2" Flush Mount Ring						
FL35	Nominal 35°	SS	Semi-specular	CG	Champagne Gold Alzak	WT	White Trim Flange	DL	Diffuse, Regressed	D2FRM	Mounting Frame						
WFL45	Nominal 45°	MFC	American Matte™	BL	Black Alzak					BT	Flat Black Trim Flange	HB	Hexcell Black, Regressed	D2ICAT ⁴	IC Rated, Air Tight housing		
		VS	Kurt Versen Softglow®	LW	Light Wheat Alzak									FLU ³	Diffuse, Flush	D2CP ⁴	CCEA compliant Chicago Plenum housing
		VSS	Kurt Versen SoftSheen™	PW	Pewter Alzak												
				BC	Painted Flat Black Cone			PL	Prismatic, Regressed	LiteGear ¹	Inverter, single phase central lighting, 125VA-250VA						
				WC	Painted White Cone			SL	Solite, Regressed	LPS Series ¹	LitePower micro-inverter, 20VA-55VA						


NOTES

- ¹ See spec sheet for Central Inverter Compatibility note and web links
- ² Lens options available with WFL45 Beam Only
- ³ For FLU option, no reflector color section is required. Either WT or BT flange must be selected
- ⁴ EDM, DM01 and 15L models are not compatible with D2ICAT or D2CP. See spec sheet for important product life/warranty information when using D2ICAT or D2CP with 12L 95 CRI



WALL WASH

D2LED WW



D2LED
Wall Wash Specular




Shielded Wall Wash
Flat Black Cone & White Flange
(Example below)

EXAMPLE: D2LED-2D9LED9L30K9SWWBCWT

1. J-TUBE ASSEMBLY		2. VOLTAGE		3. OPTIONS		4. LIGHT ENGINE		5. OUTPUT		6. LED COLOR		7. CRI	
D2LED	J-Tube Assembly with Standard 0-10V 10% Dimming	STANDARD	120/277V	STANDARD	0-10V 10% dimming	2D9LED	2" Open Reflector/ Light Engine Assembly with Xicato module	7L	700 Delivered Lumens	27K	2700 Kelvin	8	Nominal 80+ CRI
				EDM ²	Hi-Lume 1% EcoSystem LED Driver		9L	900 Delivered Lumens	30K	3000 Kelvin	9 ¹	Nominal 95+ CRI	
							12L ²	1200 Delivered Lumens	35K	3500 Kelvin			
				DM01 ²	eldoLED 0-10V dimming to less than 1%				40K	4000 Kelvin			
8. BEAM ANGLE		9. REFLECTOR FINISH		10. REFLECTOR COLORS ³		11. FLANGE OPTIONS ³		12. ACCESSORIES					
WW	Wall Wash	STANDARD	Specular	STANDARD	Clear Alzak	STANDARD	Anodized Trim Flange	FMR2	2" Flush Mount Ring				
SWW	Shielded Wall Wash	SS	Semi-specular	CG	Champagne Gold Alzak	WT	White Trim Flange	D2FRM	Mounting Frame				
		MFC	American Matte™	BL	Black Alzak			D2ICAT ²	IC Rated, Air Tight housing				
		VS	Kurt Versen Softglow®	LW	Light Wheat Alzak			D2CP ²	CCEA compliant Chicago Plenum housing				
		VSS	Kurt Versen SoftSheen™	PW	Pewter Alzak			LiteGear ³	Inverter, single phase central lighting, 125VA-250VA				
				BC	Painted Flat Black Cone				LitePower micro-inverter, 20VA-55VA				
				WC	Painted White Cone			LPS Series ³					


NOTES

- ¹ 95+ CRI not available on 12L
- ² EDM, DM01 and 12L models are not compatible with D2ICAT or D2CP. See spec sheet for important product life/warranty information when using D2ICAT or D2CP with 9L 95 CRI
- ³ See spec sheet for Central Inverter Compatibility note and web links




ADJUSTABLE

A2LED



SLOPED CEILING
STANDARD CUT



A2LED
Standard Cut Specular


EXAMPLE: A2LED-2A9LED9L35K8FL35

1. J-TUBE ASSEMBLY		2. VOLTAGE		3. OPTIONS		4. LIGHT ENGINE		5. OUTPUT		6. LED COLOR		7. CRI	
A2LED	J-Tube Assembly with Standard 0-10V 10% Dimming	STANDARD	120/277V	STANDARD	0-10V 10% Dimming	2A9LED	2" Open Reflector/ Light Engine Assembly with Xicato module	7L	700 Delivered Lumens	27K	2700 Kelvin	8	Nominal 80+ CRI
		EDM ⁵			Hi-Lume 1% EcoSystem LED Driver			9L	900 Delivered Lumens	30K	3000 Kelvin	9 ¹	Nominal 95+ CRI
								12L	1200 Delivered Lumens	40K	4000 Kelvin		
DM01 ⁵			eldoLED 0-10V dimming to less than 1%										

8. BEAM ANGLE		9. LOWER REFL. FINISH ²		10. LOWER REFL. COLORS ³		11. FLANGE OPTIONS ³		12. ACCESSORIES	
FL35	Nominal 35°	STANDARD	Specular	STANDARD	Clear Alzak	STANDARD	Anodized Trim Flange	FMR2	2" Flush Mount Ring
		SS	Semi-specular	CG	Champagne Gold Alzak	WT	White Trim Flange	D2FRM	Mounting Frame
		MFC	American Matte™	BL	Black Alzak			D2ICAT ^{4,5}	IC Rated, Air Tight housing
		VS	Kurt Versen Softglow®	LW	Light Wheat Alzak	BT	Flat Black Trim Flange	D2CP ^{4,5}	CCEA compliant Chicago Plenum housing
		VSS	Kurt Versen SoftSheen™	PW	Pewter Alzak	CT	Clear Trim Flange	LiteGear ⁶	Inverter, single phase central lighting, 125VA-250VA
				BC	Painted Flat Black Cone			LPS Series ⁶	LitePower micro-inverter, 20VA-55VA
				WC	Painted White Cone				

NOTES

- ¹ 95+ CRI not available on 12L
- ² Upper reflector finish is always Specular
- ³ With Alzak colors, flange will match lower reflector finish unless WT or BT is specified. CT is only applicable for painted cones (WC or BC) and WT, BT or CT must be specified.
- ⁴ Available with 7L 80+ CRI only
- ⁵ EDM or DM01 not compatible with D2ICAT or D2CP
- ⁶ See spec sheet for Central Inverter Compatibility note and web links




ADJUSTABLE


AB2LED



AIM FROM
BELOW OPEN



AIM FROM
BELOW SLOT



AIM FROM
BELOW PINHOLE



AB2LED
Open Semi-Specular

Open Specular
with two accessory media

Pinhole
White Cone & Flange
(Example below)


EXAMPLE: AB2LED-2AB9LED12L30K8MD25PHWCWT

1. J-TUBE ASSEMBLY		2. VOLTAGE		3. OPTIONS		4. LIGHT ENGINE		5. OUTPUT		6. LED COLOR		7. CRI	
AB2LED	J-Tube Assembly with Standard 0-10V 10% Dimming	STANDARD	120/277V	STANDARD	0-10V 10% Dimming	2AB9LED	2" Open Reflector/ Light Engine Assembly with Xicato module	7L	700 Delivered Lumens	27K	2700 Kelvin	8	Nominal 80+ CRI
				EDM ⁵	Hi-Lume 1% EcoSystem LED Driver			9L	900 Delivered Lumens	30K	3000 Kelvin	9 ¹	Nominal 95+ CRI
								12L	1200 Delivered Lumens	35K	3500 Kelvin		
				DM01 ⁶	eldoLED 0-10V dimming to less than 1%					40K	4000 Kelvin		

8. BEAM ANGLE		8. LOWER TRIM STYLE		9. LOWER REFL. FINISH ³		10. LOWER REFL. COLORS ^{3,4}		11. FLANGE OPTIONS ⁴		12. ACCESSORIES	
MD25	Nominal 25°	STANDARD	Angle Cut	STANDARD	Specular	STANDARD	Clear Alzak	STANDARD	Clear Anodized Trim Flange	FMR2	2" Flush Mount Ring
FL35	Nominal 35°	PH ²	Pinhole	SS	Semi-specular	CG	Champagne Gold Alzak	WT	White Trim Flange	AB2AH ⁵	AB2 Accessory Holder
WFL45	Nominal 45°	SLT ²	Slot	MFC	American Matte™	BL	Black Alzak			BT	Flat Black Trim Flange
				VS	Kurt Versen Softglow®		LW	Light Wheat Alzak	CT		
				VSS	Kurt Versen SoftSheen™	PW	Pewter Alzak				GRLL11
						BC	Painted Flat Black Cone			H11BL	Hexcell Louver Black
						WC	Painted White Cone			LL11	Linear Spread Lens
										PL11	Prismatic Diffusion Lens
										D2FRM	Mounting Frame
										D2ICAT ^{6,7}	IC Rated, Air Tight housing
										D2CP ^{6,7}	CCEA compliant

NOTES

- ¹ 95+ CRI not available with 12L
- ² Pinhole or Slot options are available with painted finishes only. Specify WC or BC for insert color with BT or WT for flange color.
- ³ Upper reflector is always Specular
- ⁴ For all reflector colors except Clear Alzak, flange color must be specified, either CT, WT or BT
- ⁵ AB2AH is required for all media, accepts up to 2 media, 0.25" max total thickness. Not compatible with WFL45
- ⁶ EDM and DM01 not compatible with D2ICAT or D2CP
- ⁷ Available with 7L 80+ CRI only





ARCHITECTURAL AREA LIGHTING

BEACON PRODUCTS

COLUMBIA LIGHTING

COMPASS

DUAL-LITE

HUBBELL CONTROL SOLUTIONS

HUBBELL OUTDOOR LIGHTING

KIM LIGHTING

KURT VERSEN

LITECONTROL

PRESCOLITE



701 Millennium Blvd. Greenville, SC 29607
Tel 864.678.1000
www.prescolite.com

PR1101 04/21

Copyright © 2021 Prescolite, a division of Hubbell Lighting, Inc. All rights reserved. Please refer to online specifications for most up-to-date content as specifications are subject to change without notice.