



N4WNS N8WNS

4 Channel NVR with Digital Deterrent®

8 Channel NVR with Digital Deterrent®

N16WNS 16 Channel NVR with Digital Deterrent®

N4WNS1TB	N8WNS1TB	N16WNS2TB
N4WNS2TB	N8WNS2TB	N16WNS3TB
N4WNS3TB	N8WNS3TB	N16WNS4TB
N4WNS4TB	N8WNS4TB	N16WNS6TB
N4WNS6TB	N8WNS6TB	N16WNS9TB
N4WNS9TB	N8WNS9TB	





















Storage from 1TB up to 9TB

For the latest mobile apps and CMS software go to: www.specotech.com/DVRApps



Features

EZ Camera: quickly discovers and installs IP cameras

EZ Setup: for quick system setup

EZ Network: for quick set-up on a network

EZ Search: quickly search events from thumbnails

EZ Record: quickly setup recording resolutions and recording type EZ Copy: auto copy what you are playing onto a USB flash drive

- · Plug & play feature with Speco's OnSIP/VIP cameras
- ONVIF support*
- Dual network ports for isolating IP camera network traffic and remote network
- Supports all H.264 compression profiles (baseline, main and high)
- · A patented DVR solution that easily mounts in equipment closets or electrical rooms for covert installations
- · Network video recorder with free DDNS server
- · Easy and simple graphical user interface
- Digital Deterrent® for triggering audio message via motion detection or sensor
- · 2-way audio communication
- · Programmable recording on motion detection, sensor, schedule, continuous and manual
- Full HD (1920 x 1080) recording and playback
- · Supports wireless access point for viewing and configuration
- · Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting, Technology for HDD)
- 4/8/16 channel selectable local or IP camera audio recording
- · Covert camera operation provides enhanced security and administrator control

EZ Set-Up Wizards!

One click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.

- Date/Time Recording method Recording video quality Network
- · Password to secure installation authorization
- · Easy firmware upgrade by USB port or network
- · User Access: up to 4 concurrent users
- Remote monitoring / recording / playback / configuration / software upgrades and PTZ control via internet
- · Supports multiple PC based browsers such as Internet Explorer, Google Chrome, Firefox and Safari
- · Network accessible via SpecoTech Multi-Client Software, Secure Guard® CMS and Speco Player Mobile Viewer
- PC and MAC® compatible
- · 3 year warranty
- Free Apps with support for view on iPhone[®], iPad[®] or Android[™] iPhone and Android are trademarks of Apple & Google respectively.

Specifications

Recording Resolutions: D1, 1280x720, 1920x1080

3 internal hard drives

4/8/16 channel audio input, 1 channel audio output

Motion detection, sensor, schedule, continuous and manual recording

Video Outputs: 1 HDMI, 1 VGA, 1 MAIN

USB 2.0 port for snapshot and video clip exporting

Multiple language on-screen menus

IR remote control included

Network software supports Static IP, DHCP and DDNS

Network hardware supports 10/100/1000Mbps

Power Requirement: 12VDC @ 5A Operating Temperature: 41° F - 104° F Dimensions: 13.5" (W) x 17" (H) x 3.5" (D)

Weight: 12 lbs.

Optional Accessories



IR Repeater Kit



USB Wireless Access Point

*visit www.specotech.com/onvif.html for latest ONVIF support

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 8/2/13

N4WNS / N8WNS / N16WNS Technical Specifications: NS Plug & Play Wall Mount Network Video Recorder



	Mode	el	N4WNS	N8WNS	N16WNS	
	la accet	IP Camera	4	8	16	
	Input	Resolution		Max. 1920 x 1080		
Video		Main Monitor		VGA and HDMI		
	Output	Sub Monitor		CVBS		
		IP Camera (network)	4	8	16	
	Input	Local Input (RCA)	4	8	16	
Audio	Output	Local Output (RCA)		1		
		Audio Codec	G.711			
Event -		IP Camera (network)	4	8	16	
	Sensor In	Local Input (terminal block)		4		
	Local Alarm Output (terminal block)		1			
	Motion Detection (from IP camera)		Yes			
Serial -	RS-232C		1			
	RS-485		1			
	LAN (IP Camera, Auto Connection)		10/100 Base-T 10/100/1000 Base-T			
Network	WAN (IP Camera, Remote Access)		10/100 Base-T	10/100/1000 E		
	***************************************	Protocols		HCP, HTTP, NTP, SMTP, TRP, RTSP, ONVIF		
		Compression		H.264 (baseline, main and high profile)		
		D1	120fps	240fps	480fps	
	Resolution &	1280 x 720	120fps	240fps	480fps	
Recording	Frame Rate	1920 x 1080	120fps	240fps	480fps	
Recording				Continuous / Motion / Sensor / Schedule / Manual		
		Recording Mode Pre-Recording				
		-	Max. 20 minutes			
	Post Recording		Max. 60 seconds			
Playback Backup	Search		EZSearch, Date/Time, Event, Archive, Log			
	Multi-Decoding		1, 4 1, 4, 8 1,4,8,16			
	Playback Speed Media		x0.25, x0.5, x2, x4, x8, x16, x32, x64			
	File Format		USB Drive, External HDD, Network			
			BMP, AVI, Proprietary Format			
	Large Backup Capacity of 1 HDD		Yes (max. 24 hours) 3TB 3TB			
	HDD	Internal HDDs	316			
Storage	TIDD	e-SATA		3		
	USB USB		1 3			
User I/F	 	Input Method	IR, Mouse, Keyboard Controller			
Oser I/I	1					
Features	Digital Deterrent®		Up to 8 audio files Yes (free Speco DDNS)			
		Dynamic DNS		Yes (free Speco DDNS) Yes		
	Digital Zoom		Yes			
		DLS (day light savings)		Yes		
	NTP (network time protocol)		Yes			
	S.M.A.R.T					
	Internal Beep		Yes Yes			
-	Multi-Language E-mail Notification		Yes			
			iPad® / iPhone® / Android™			
	Smartphone Viewer		Windows (IE, Chrome, Firefox, Safari)			
Network	PC Web Viewer		SpecoTech Multi-Client Viewer and Secure Guard® CMS			
Access	PC Client					
	MAC Client		Speco Client for MAC and Secure Guard® CMS			
Davis	Remote Setup and Upgrade Yes					
Power	Power Supply Voltage 12VDC, 5A					
Temperature	Operating Temperature 41° F – 104° F / During Storage: 14° F – 122° F					
Weight	ı Unit	Weight (gross weight)		12 lbs.		

Please note that specifications and unit exterior design are subject to change without notification.