



# EcoTouch® Insulation for Certified R Metal Building with PureFiber® Technology

## Product Data Sheet



- R-10 3.4"     R-19 6.3"
- R-11 3.7"     R-25 8.0"
- R-13 4.3"     R-30 9.25"
- R-16 5.3"

### Description

Owens Corning™ EcoTouch® Insulation for Certified R Metal Building with PureFiber® Technology is a light density fibrous glass blanket designed to be laminated with a variety of appropriate facings. Certified R is available in standard R-values of 10, 11, 13, 16, 19, 25 and 30. Standard roll widths are 36", 48", 60" and 72". Selected Made-to-Order widths are also available.

### Key Features

- Certified thermal performance<sup>1</sup>
- Excellent recovery provides outstanding thermal and acoustical performance
- Soft to the touch
- Uses a minimum of 65% recycled content
- GREENGUARD Gold Certified
- Easy to handle and laminate

### Physical Properties

Property	Test Method	Result
Thermal Resistance	ASTM C177/C518	Product R-value
Surface Burning	UL 723/ASTM E84	Flame spread index < 25 Smoke developed index < 50
Combustion Characteristics	ASTM E136	Non-combustible
Water Vapor Sorption	ASTM C1104	≤ 0.2% by volume
Fungi Resistance	ASTM C1338	Passes
Corrosiveness	ASTM C665	Passes
Odor Emission	ASTM C1304	Passes

<sup>1</sup> The surface burning characteristics of these products have been determined in accordance with UL 723. The standard should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest 5 rating.

### Product Applications

Owens Corning™ EcoTouch® Insulation for Certified R Metal Building is used as part of the insulation system in the roofs and side walls of metal buildings. It is designed to be laminated with a variety of facings to provide attractive interior finishes, abuse resistance, and assistance in control of moisture.

### Availability

Owens Corning™ EcoTouch® Insulation for Certified R Metal Building is fabricated and distributed by a nation wide network of independent laminators assuring prompt service and delivery. Contact your Owens Corning Sales Representative for the names of insulation laminators servicing your area.

### Installation

Several methods are used to insulate metal buildings. The usual method is to apply the insulation over the structural members (purlins and girts) and inside the exterior panels. This method generally accommodates single layer installations. Methods are

also available to apply insulation between purlins so as to accommodate greater insulation thicknesses and better thermal performance.

### Technical Information

Owens Corning™ EcoTouch® Insulation for Certified R Metal Building is manufactured in compliance with ASTM C991, "Standard Specification for Flexible Fibrous Glass Insulation for Metal Buildings." This standard includes all performance and physical properties required of thermal insulation for use in metal building construction (see Physical Properties Table).

Owens Corning™ EcoTouch® Insulation for Certified R Metal Building is regularly tested to ensure compliance to the NAIMA 202-96 (Rev. 2000) Standard. Sampling and testing is performed by the National Association of Home Builders Home Innovation Research Lab (NAHB-RC). The product is labeled on the top surface of each roll with the nominal R-value and the "NAIMA 202-96" (Rev. 2000) to indicate compliance.

<sup>1</sup> Applies to the insulation component only.



# EcoTouch® Insulation for Certified R Metal Building with PureFiber® Technology

## Product Data Sheet

The NAIMA 202-96 (Rev. 2000) standard specifies thermal performance which provides the capability of obtaining nominal thermal resistance (R-values) after laminating. The actual thermal performance obtained from the laminated product will depend primarily on the recovered thickness. Note that these nominal R-values are for the insulation only and do not include the effects of facings, air films, compression of insulation at framing members, conductance through fasteners, or other heat transfer paths particular to an installation.

The recovered thickness achieved will depend on a number of variables determined in the laminating process and hence are outside of Owens Corning's control. To address these issues, a number of leading metal building insulation laminators produce products which meet the National Insulation Association's "Certified Faced Insulation Standard" (NIA 404). Samples of faced products are periodically tested by a nationally recognized laboratory and determined to meet the NIA standard.

### Standards, Codes Compliance

- ASTM C991-08, Standard Specification for Flexible Fibrous Glass Insulation for Metal Buildings; Type II.
- NAIMA 202-96 (Rev. 2000) Standard for Flexible Fiber Glass Insulation to be Laminated for Use in Metal Buildings.

### Certifications and Sustainable Features of EcoTouch® Insulation for Certified R Metal Building

- Certified by SCS Global Services to contain a minimum of 65% recycled glass content, 18% pre-consumer and 47% post-consumer.
- Certified to meet indoor air quality standards under the stringent GREENGUARD Indoor Air Quality Certification Program, and the GREENGUARD Gold Certification.

### Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high-quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives. More information can be found at <http://sustainability.owenscorning.com>.

#### Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobalservices.com](http://www.SCSglobalservices.com).

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg).



**OWENS CORNING INSULATING SYSTEMS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO, USA 43659  
**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 15086-U. Printed in U.S.A. December 2014. THE PINK PANTHER™ & © 1964-2014 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2014 Owens Corning. All Rights Reserved.

