



NANLITE

LumiPad 25

- Soft Light LED Panel
- An impressively compact and bright soft light LED panel
- Adjustable color temperature from 3200-5600K
- Output 930 Lux of 5600K daylight-balanced light @1 meter
- Maximum output of 2140 lumens
- CRI/TLCI of 95/93
- 0 to 100% dimming

Studio Quality Lighting

NanLite LumiPad series LED panels create diffuse, color accurate, studio lighting with minimal set up and zero complications. Perfect for live streaming, vlogging, photography lighting, video lighting, photo booths and more.

Full Creative Control

Easily achieve beautiful results without adding plastic filters or cloth diffusion. The LumiPad 25's control knobs enable you to dial in brightness from 0-100% and temperature from warm to cold (3200K-5600K).

Slim Design and High Output


At only 1.2 inches thick and weighing just 2.2lbs the LumiPad 25 is impressively bright at 2140 lumens.

Multiple Power Options

The LumiPad 25 can be powered by either an AC adapter (not included) or 2x compatible Sony NP-F style batteries such as NP-F550 / F750 / F960 (Not Included) so you can operate in any location regardless power availability.



Technical Data	Power Consumption	25W		
	Power Supply	15V/6A DC		
	Lumen Output 5600K	2140LUM		
	CRI (Ra)	95		
	TLCI	93		
	Color Temperature	3200K-5600K		
	Battery Type	NP-F550/F750/F950 (Not Included)		
	Battery Run Times at 100%	NP-F550	F750	F950
		0.7 hours	1.3 hours	1.7 hours
	Dimming	0 to 100% continuous		
	Control	Local control		
	Dimensions	13.6 X 2.2 X 12.2 in		
	Weight	2.2 lb		
	Cooling System	Passive		
	Mount	1/4-20 and Cold shoe		
	Warranty	Limited 1-Year		



Distance	1M	2M	3M
5600K	930 lux 86 fc	232 lux 21 fc	104 lux 10 fc
3200K	867 lux 80 fc	216 lux 20 fc	97 lux 9 fc