



THE STD-FC-550 CAN BE CONFIGURED WITH **DIESEL OR GASOLINE** BULK FUEL TANK.

BRAND	Standard - GSE
MODEL	STD-FC-550
CAPACITY	550-Gallon
YEAR	2,019
CONDITION	New
DELIVERY	3-4 Weeks

FEATURES

- Tank Capacity: 550 gallon
- Heavy-Duty solid steel tank construction with powder coat finish
- Double wall skid tank - UL Certification listed
- Low profile and hot dip galvanized chassis
- 15 GPM Solar powered pump
- Pipe for the updraft vent
- Heavy duty fifth wheel steering
- Safe drop tow bar
- Standard GSE hubs and solid tires 4.00-8
- Level & leak gauge
- Static grounding reel
- Fire extinguisher - 10 lbs.
- Fuel hose with safety fuel nozzle and nozzle holder
- Spill container and fill cap
- 2 emergency vents
- TIMBREN suspension system with Rubber spring technology. Anti-overturning axles





Fire extinguisher & Static grounding reel



2 Emergency vents opening



Spill container & Fill cap



Solar Panel 8W



TIMBREN suspension system
Anti-overturning axles



Leak gauge



Level gauge



Transfer Pump

SOLAR PANEL SPECS

Optimal charge/discharge performance - the system will run for 45 minutes with 6 hours peak sun per day or 22 minutes with 3 hours peak sun per day. Maximum run time without recharge -full battery discharge will occur after 1.8 hours of pump operation.

- Rated Power: 8W continuous output with 6 hours peak sun
- Solar Panel Size: 12VDC 30W
- Battery System : 12VDC @ 36Ah
- Battery Reserve Time @ Rated Power: 27 hours

15 GPM PUMP

- 15 GPM - 12V DC Pump
- 3/4" x 12' Hose
- Manual nozzle
- Ground Wire
- 2 wire battery cable
- Telescoping steel suction pipe

SHIPPING DIMENSIONS

Length 135" x Width 63"x Height 72"
Weight: 2,150 lbs.