



General Catalogue 2017-

Electrical Construction Materials

Please contact:

Panasonic Eco Solutions Vietnam Co., Ltd

- 7th Floor, Etown 1, 364 Cong Hoa Str., Ward 13, Tan Binh Dist., HCMC
- Tel: +84-8-3813-4591
- Fax: +84-8-3813-4595
- Website: <http://panasonic.net/es/vn>

Produced by:

- Panasonic Eco Solutions Vietnam Co., Ltd.
- Panasonic Manufacturing Ayuthaya Co., Ltd.
- Panasonic Eco Solutions Steel (Thailand) Co., Ltd.
- Panasonic Ecology Systems Co., Ltd.
- Panasonic Ecology System Guangdong Co., Ltd.
- Panasonic Ecology Systems (Thailand) Co., Ltd.
- Panasonic Manufacturing Malaysia Berhard
- PT Panasonic Manufacturing Indonesia
- Panasonic Corporation Eco Solutions Company

Showroom Hochiminh

Address: 10 Truong Dinh Str., Ben Thanh Ward, Dist.1, HCMC
Tel: 08 3822 9866

Showroom Hanoi

Address: 83 Lang Str., Nga Tu So Ward, Dong Da Dist., Hanoi
Tel: 04 3564 2660













Panasonic®





To the next stage.

Panasonic has been present in the Vietnam market over many years. During all this time, our customers have come to appreciate Panasonic and our extensive range of products from Home Appliances to Wiring Devices. Playing a key role in Panasonic company history since 1918, Panasonic has established a reputation for safety, durability and comfort around the world. As Panasonic continues to develop new product technologies along with highly advanced manufacturing abilities, our concepts regarding safety and comfort continue to evolve. Panasonic's uncompromising commitment makes it possible to offer our Vietnam customers a higher level of satisfaction with any of our diverse product categories.



*Panasonic Original Product
1918
Attachment plug*

P16		HALUMIE
P20		GEN X
P24		COSMO-ART SERIES
P28		FULL-COLOR WIDE SERIES REFINA
P34		FULL-COLOR WIDE SERIES REFINA BS-TYPE
P38		FULL-COLOR WIDE SERIES
P44		FULL-COLOR SERIES
P49		INDUSTRIAL SOCKET
P61		EXTENSION CORD WITH SAFETY SHUTTER & BREAKER
P62		FLOOR OUTLET SERIES
P66		PASSIVE INFRARED SENSOR
P68		SMOKE DETECTOR
P69		DOOR-PHONE
P71		AUTOMATIC TIME SWITCH
P75		MCB/RcBO-DIN TYPE
P77		ELB BREAKER

P79		GD BREAKER
P87		WHITE CONDUIT
P91		FULL 2 WAY
P93		FACTORY LINE SYSTEMS
P97		PHOTOVOLTAIC MODULE HIT®
P98		AUTO DOOR
P107		VENTILATING FAN
P126		RANGE HOOD
P129		HAND DRYER
P131		AIR CURTAIN
P133		AIR MOVING EQUIPMENT
P136		CEILING FAN
P144		WALL FAN
P156		HEATER VENTILATING
P161		AIR PURIFIER
P162		PUMP

Company Profile

Since the Panasonic Corporation was founded in 1918, it has based corporate activities on a Basic Management Objective. Through its business activities, Panasonic strives to help society progress and develop so as to improve the well-being of people throughout the world. By keeping focused on people, we intend to enrich their lifestyles as we move forward together with our customers.

Panasonic Eco Solutions Company handles diverse businesses. The Energy Systems Business supplies everything from wiring devices and distribution switchboards to photovoltaic modules, storage battery systems and energy management devices. The Lighting Business innovates illumination in an energy-efficient manner with LED lighting bulbs, fixtures and other devices. The Housing Systems Business's comprehensive range of residential equipment and building materials create comfortable living environments. The Environmental Systems Business helps to reduce environmental impact by maintaining good air quality and by purifying contaminated water and soil.

We are helping to create an environment in which people around the world can live in comfort while minimizing environmental harm. Harmoniously combining ecology and comfort is our vision. We seek to achieve this by creating solutions in residential and non-residential (buildings and public facilities) fields, leveraging Panasonic Group's extensive product lines. As we address issues our worldwide customers face with Panasonic solutions, we contribute to realizing a sustainable society.

Panasonic — dedicated to eco-conscious manufacturing.

Manufacturing eco-conscious products that do not harm humans and the environment have always been a priority for Panasonic. Conforming to the RoHS directive originating from the EU, Panasonic restricts the usage of hazardous substances that might adversely affect the environment and humans such as lead, cadmium, chromium, mercury, etc. Panasonic contributes to creating a greener environment with lead-free welding, cadmium-free contacts and hexavalent chromium-free plating.


Panasonic Eco Solutions Company (Osaka, Japan)



Products Concept

Panasonic's "Five-Elements" Design Concept

The integrated system that our product development process is based on makes it possible to produce consistently high-quality products. It begins with assessing market needs accurately goes on to develop advanced basic technologies and extends to product planning, design and production, all the way to sales and after-sales activities.



- Sensing technology
- Mechanism technology
- Sound technology
- Information and Telecommunication technology
- Imaging technology
- Wireless technology
- Semiconductor technology

- Durability evaluation technology
- User interface evaluation technology
- Offending evaluation technology
- Substance analysis technology

- Component processing technology
- Assembly technology
- Environmental compatibility technology
- Process development technology
- Measurement technology


Panasonic's products will continue to work in diverse settings all around the world.






Home and lifestyle environments, as well as business environments which evolve every day.

The Panasonic group has made available to you safe and secure products which you can use in various places, whether it is your home, or office, or in various institutions or public areas.


Our rich and varied product range offers true value to our customers. We shall continue to offer you the best in smart living.




Home



-  HALUMIE
-  GEN X
-  VENTILATING FAN
-  CEILING FAN
-  WALL FAN
-  AIR PURIFIER
-  PUMP
-  DOOR PHONE
-  MCB/RCBO

Condominium




-  HALUMIE
-  VENTILATING FAN
-  CEILING FAN
-  MCB/RCBO/GD BREAKER


Office

Factory

Shopping Center



HALUMIE



FULL-COLOR WIDE SERIES



PASSIVE INFRARED SENSOR



EXTENSION CORD



FLOOR OUTLET SERIES



FULL-2WAY REMOTE LIGHTING CONTROL SYSTEM



MCB/RCBO/GD BREAKER



FULL-COLOR WIDE SERIES



INDUSTRIAL SOCKET



PASSIVE INFRARED SENSOR




FACTORY LINE SYSTEMS



AUTOMATIC TIME SWITCH



FLOOR OUTLET SERIES



PHOTOVOL TAIC MODULE HIT®



VENTILATING FAN



MCB/RCBO/GD BREAKER



FULL-COLOR WIDE SERIES



TWIST LOCK



AUTOMATIC TIME SWITCH



FLOOR OUTLET SERIES



VENTILATING FAN



AIR CURTAIN



AUTO DOOR



MCB/RCBO/GD BREAKER




WORLDWIDE STANDARDS

Safety design conforming to IEC standards

Switches conform to the IEC60669-1 standard (16A 250V~). Socket Outlets conform to the IEC60884-1 standard. MCB/RCBO conform to the IEC60898, IEC60947-2, IEC601009 standard. All devices guarantee protection against electric shock and are designed for endurance, service longevity and safety.

Based on Internationally Accepted Standards



Manufactured based on the industrial norms for environmental conservation and quality assurance prescribed by ISO. We undertake the manufacture of products using processes with high quality and high safety which have cleared the IEC.

Examination and registration card.



ISO9001

ISO9001

ISO9001

Panasonic now conforms with Conformity Regulation (CR) mark



All Panasonic fans are borne CR mark issued by Vietnam Certification Center (Quacert) in comply with QCVN 4:2009/BKHCN

Electrical Construction Materials




Easy To Install

Panasonic-designing one-touch action products that are easy to install.

The All One-Touch Action design concept that attaches devices to body plates and plate bodies to the plate covers makes the installation process easier than ever, saving both time and labor.

1-TOUCH Construction



Không bán


■ Device & Plate Body



■ Plate Body & Plate Cover



Highly efficient, because of improvements in the utility box. Sufficient space has been provided to house the connectors, and this has resulted in a higher efficiency than ever before.



Various Terminals Available

We offer a wide range of terminals to suit the electrical cabling requirements of every country.

Panasonic has made available various terminals to suit the cabling environment anywhere in the world. With a structure which can be handled with more safety than ever before. Connections can be smoothly made, which leads to labor saving.

■ Types of Electrical Cables and Terminals

Terminal	ICON	APPLICABLE WIRE
Quick Connect Terminal	 Quick & Safety Solid Wire only 1.5-2.5mm ²	 Solid OK
	 Solid Wire :1.5-2.5mm ² Stranded Wire :1.5-2.5mm ²	 Solid Stranded OK

Terminal	ICON	APPLICABLE WIRE
Global Terminal	 Solid Wire :1.5-4.0mm ² Stranded Wire :1.5-4.0mm ²	 Solid Stranded OK
Pillar Terminal II	 1.5-4.0mm ² Solid, Stranded and Flexible wire	 Flexible OK

Safety

Safety design conforming to IEC standards

Switches conform to the IEC60669-1 standard(16A 250V~). Socket Outlets conform to the IEC60884-1 standard. All devices guarantee protection against electric shock and are designed for endurance, service longevity and safety.

Switches

- Designed for long service life (compliant with IEC standard) with 40,000 testing operations at 16A 250V~ full rating.
- Heat-resistant, highly conductive material used for the terminal plate reduces temperature increases in the terminal section.




Terminal Section Temperature rise

IEC60669-1 Standard value		Conditions
Initial	45K max.	20A current
Use as 40,000 testing operations		16A current

Socket Outlets

- Wide socket outlet secures insulation distance between contacts and external metal parts improving safety. (Compliant with IEC standard which requires insulation distance over 4.5mm)
- Long-life design, capable of 10,000 strokes at 16A 250V ~ full rating.
- Heat-resistant, highly conductive material is used for the blade sockets and terminal point to reduce temperature increase.



Terminal Section Temperature Rise

IEC60884-1 Standard value		Conditions
Initial	45K max.	20A current
After 10,000 Strokes		16A current

Insulation Resistance

EC60884-1 Standard value	
Initial	5M Ω min.
After 10,000 Strokes	

Withdrawal Forces

IEC60884-1 Standard value		
After 10,000 Strokes	3 blades	54N max.
	2 blades	50N max.
	Single blades	2N min.

Electric Strength


IEC60884-1 Standard value	
Initial	2,000V 1 min.
After 10,000 Strokes	1,500V 1 min.

Security And Comfort

1 Flame-retardant Material Urea Resin Vật liệu chống cháy

Utilizing urea resin improves flame resistance and outstanding anti-tracking prevents electric shocks.

Completely Insulated Construction



*1. Acrylonitrile Butadiene Styrene
*2. Poly Butylene Terephthalate

Protection Against Electric shock


Enclosure Material Characteristics (Reference)

	Urea	PBT	Polycarbonate
Tracking Performance	Excellent	Good	Poor
Heat Deformation	Good	Good	Fair
Self-Extinguishment	Good	Good	Good

2 Durable & Smooth Operations Direct Driving Mechanism

Panasonic's proprietary method helps stabilizing the pressure applied to the contacts to ensure low heat and minimize the arc energy. This process reduces the risk of contact fuse and provides longer lasting resistance.


Direct Driving Mechanism



Since the bound time of the contact is short when it is switched "ON", low arc energy is produced.

The contact does not fuse easily, and therefore its consumption is low.

Seesaw Type of Switching System




Since the bound time of the contact is long, a considerable amount of arc energy is produced.

The contact fuses easily, creating high consumption.

3 Quick & Secure Connection Quick-Conenect Terminal

These terminals improve site construction quality since fewer tightening screws are required, simplifying connections.


Reduces the execution time considerably




Tensile strength after connection

IEC60669-1 IEC60884-1 Standard Value	Wire	Strength
30N min.	1.5 mm ² 4.0 mm ²	30N min. or more

FULL-COLOR
WIDE / Halumie
SERIES



Switch



Receptacle




Product Positioning

(Series of Wiring Devices)

Whether living room, office, public space or any other facility, Panasonic enhances its appearance.

A wide range of switch and socket product series, each with its distinctive designs, color variations and operational ease is offered to ideally match installation requirements.



NEW
HALUMIE



Halumie designs to harmonize with any living space

Slimmer and easier-to-use setting the standard for advanced wiring device designs.

GEN X



Flat panel with ultrathin design

Perfect asymmetric design of 2mm thick high quality aluminum plate. GEN X represents the top Panasonic wiring devices series.

COSMOART



Exceptional appearance and easy use

This high quality series features a striking appearance with maximum ease-of-use, adding a beautiful touch to modern interiors.

**FULL-COLOR
WIDE SERIES
REFINA**



Wide color range suits modern interiors

The many colors available are perfect to match with wall colors and textures. From grainy-textured wood type finishes to sophisticated colors, this series adds a stylish touch anywhere, whether living, dining, study or bedroom.

**FULL-COLOR
WIDE SERIES**



The beauty of simplicity

Elegant and aesthetically pleasing, this popular series is sure to complement any interior scheme.

**FULL-COLOR
SERIES**



The standard of excellence for any installation

This versatile series is right for residential as well as office and commercial applications.

New slim designs to harmonize with any living space

Slimmer and easier-to-use setting the standard
for advanced wiring device designs



NEW

Halumie



DESIGNS IN HARMONY WITH LIVING SPACES

Simple and elegant design matches any room interior.



ALWAYS PLEASANT TO THE TOUCH

Advanced mechanism allows smoother ON/OFF switching. Designed for easiest possible operation.



ALWAYS RELIABLE AND BEAUTIFUL

Made of a material that resists color fading even when constantly bathed in room light or sunlight.

Switches

WEVH5511

Switch "B" Single Pole
16AX 250V~



WEVH5521

Switch "B" Single Pole
16AX 250V~



WEVH5531

Switch "B" Single Pole
16AX 250V~



WEVH5512

Switch "C" 3Way
16AX 250V~



WEVH5522

Switch "C" 3Way
16AX 250V~



WEVH5532

Switch "C" 3Way
16AX 250V~



WEVH5003

Switch "D" Double Pole
16AX 250V~



WEVH5004

Switch "E" 4Way
16AX 250V~



Switches (Pillar Terminal)

WEVH5151-51

Illuminated Switch "B"
Single Pole
16AX 250V~



WEVH5152-51

Illuminated Switch "C"
3Way
16AX 250V~



WEVH5511-7

Switch "B" Single Pole
16AX 250V~



WEVH5521-7

Switch "B" Single Pole
16AX 250V~



WEVH5531-7

Switch "B" Single Pole
16AX 250V~



WEVH5512-7

Switch "C" 3Way
16AX 250V~



WEVH5522-7

Switch "C" 3Way
16AX 250V~



WEVH5532-7

Switch "C" 3Way
16AX 250V~



WEVH5151-7

Illuminated Switch "B"
Single Pole
16AX 250V~



WEVH5152-7

Illuminated Switch "C"
3Way
16AX 250V~



WEVH5033-7

Glow Switch "D" Double Pole
20A 250V~



WEVH5542-7

Twin Switch "C" 3Way
10AX 250V~





Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²



Quick Connect Terminal
Solid Wire Only: 1.5-2.5mm²

Pillar Terminal II
★ Solid, Stranded and Flexible Wire: 1.5-4mm²

Receptacles and Accesories

WEV1081SW
WEV1081-7SW ★

Universal Receptacle with Safety Shutter
16A 250V~



WEV1091SW
Universal Receptacle
16A 250V~



WEV1181SW
WEV1181-7SW ★

Grounding Universal Receptacle with Safety Shutter
16A 250V~



WEV1582SW
WEV1582-7SW ★

Grounding Duplex Universal Receptacle with Safety Shutter
16A 250V~



WEV24886SW
CAT6 Data Modular Jack



WEV2488SW
CAT5E Data Modular Jack



WEV2364SW
Telephone Modular Jack (6P 4C)



WEV2501SW
DIN Type Television Terminal



WEG3023SW
Telephone Wire Chip for 9mm Diameter 16mm Diameter



WEG3020SW
Blank Chip



WEVH5401-011
Entrance Bell
10A 250V~



Dimmer Switch

WEG575151SW
Dimmer Switch (Incandescent Light Control)
500W 220V~
※ Off Function Type



Plates

WEVH68010
1 gang - 1 device plate



WEVH68020
1 gang - 2 devices plate



WEVH68030
1 gang - 3 devices plate



WEVH680290
1 gang - 1 device plate for WEV1181SW/ WEV1191SW/ 2P MCB only



WEVH68910
Single cover plate



WEVH8061
1 gang plate for HB breaker



WEVH68040
2 gangs - 4 devices plate



WEVH68060
2 gangs - 6 devices plate



Flat panel with ultrathin design

Exclusive switch series with ultrathin panel and refined appearance adding elegance to your interiors.



Gen-X



SOPHISTICATED SURFACE WITH A SUPER-SLIM DESIGN

Ideal asymmetric design using
2mm-thick, high-quality aluminum plate.



HEAT-RESISTANT, EASY-TO-USE LATEST SWITCH MECHANISM

On/Off with just a soft push of the switch. Built
for trouble-free operation.

Switches

WTEGP51552S-1-G

A type
Illuminated Switch "C" 3 Way
1-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



WTEGP52562S-1-G

A type
Illuminated Switch "C" 3 Way
2-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



WTEGP53572S-1-G

A type
Illuminated Switch "C" 3 Way
3-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



WTEGP54562S-1-G

A type
Illuminated Switch "C" 3 Way
4-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



WTEGP55582S-1-G

A type
Illuminated Switch "C" 3 Way
5-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



WTEGP56572S-1-G

A type
Illuminated Switch "C" 3 Way
6-Device with Plate
16AX 250~
(Neon Lamp: 220V~)



Receptacles and Accessories

WEG15829B-G

Grounding Duplex Universal
Receptacle with Safety Shutter
16A 250V~



WEV2364B

Telephone Modular Jack
(6P 4C)



WEV2488B

CAT5E Data Modular Jack



WEV2501B

DIN Type Television Terminal



WEG3020B-G

Blank Chip



WEG1181BK-G

Grounding Universal Receptacle
with Safety Shutter
16A 250V~





Quick Connect Terminal II
 Solid Wire: 1.5-2.5mm²
 Stranded Wire: 1.5-2.5mm²



Global Terminal
 Solid Wire: 1.5-4mm²
 Stranded Wire: 1.5-4mm²

Dimmer Switches

WEG57813B-1-G

Dimmer Switch
 (Incandescent and Low Voltage Halogen with Transformer 12V Light Control)
 220 VAC 300W



WEG57816B-1-G

Dimmer Switch
 (Incandescent and Low Voltage Halogen with Transformer 12V Light Control)
 220 VAC 500W



Plates

WTFB6503S-1-G

1 gang, 3 devices plate



WTEG6506S-1-G

2-Gang 6-Device



WTEG6506S-G

2-Gang 6-Device



WTEG6503S-1-G

1-Gang 3-Device



Switches

WTFBP51552S-1-G

BS type
 Illuminated switch "C",
 3 ways, 1 device with plate



WTFBP52562S-1-G

BS type
 Illuminated switch "C",
 3 ways, 2 devices with plate



WTFBP53572S-1-G

BS type
 Illuminated switch "C",
 3 ways, 3 devices with plate



EGG331

Weather Proof Push Bottom for Door Chime
 1A 220V~



EGG335

Weather Proof Push Bottom for Door Chime
 Dark Brown
 1A 220V~



EBG888

Door Chime
 220V~ Two Tone 9.5W, 50 Hz.
 Easy-to-Hear 82 dB Chime



Exceptional appearance and easy use

Sophisticated modern design and superb ease-of-use




COSMO ART



CREATES A MODERN, APPEALING LOOK WHEN INSTALLED

European design sensibility meets Japanese craftsmanship for a finish that stands by itself.



HEAT-RESISTANT, EASY-TO-USE LATEST SWITCH MECHANISM

On/Off with just a soft push of the switch.
Built for trouble-free operation.

Switches

WTAG7152CHSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GRAY



WTAG7152CLSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR BLUE



WTAG7152CDSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GREEN



WTAG7252CHSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GRAY



WTAG7252CLSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR BLUE



WTAG7252CDSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GREEN



WTAG7352CHSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GRAY



WTAG7352CLSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR BLUE



WTAG7352CDSW

Illuminated Switch "C" 3Way
16AX 250V~(Neon Lamp 220V~)

WTAG6101SW(Plate)

1-Gang 3-Device



CLEAR GREEN



Receptacles and Accesories

WEV1081SW

Universal Receptacle
With Safety Shuttler
16A 250V~



WEV1091SW

Universal Receptacle
16A 250V~



WEG1001SW

Receptacle
16A 250V~



Dimmer Switches

WEG575151SW

Dimmer Switch
(Incandescent Light Control)
500W 220V~
※ Off Function Type



WEG575181

Dimmer Switch
(Incandescent Light Control)
800W 220V~
※ Off Function Type





Quick Connect Terminal
Solid Wire Only: 1.5-2.5mm²



Quick Connect Terminal II
Solid Wire: 1.5-2.5mm²
Stranded Wire: 1.5-2.5mm²



Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²

Pillar Terminal II
★ Solid, Stranded and Flexible Wire: 1.5-4mm²

WEG1090SW

Round Pin Receptacle
16A 250V~



WEV1181SW

Grounding Universal Receptacle
with Safety Shutter
16A 250V~



WEV1582SW

Grounding Duplex Universal Receptacle
with Safety Shutter
16A 250V~



WEV24886SW

CAT6 Data Modular Jack



WEV2488SW

CAT5E Data Modular Jack



WEV2364SW

Telephone Modular Jack
(6P 4C)



WEV2501SW

DIN Type Television Terminal



WTNG4101W

Audio Srew Terminals
(Single)



WTNG4102W

Audio Srew Terminals
(Double)



EGG331

Weather Proof Push Bottom for
Door Chime
1A 220V~



EGG335

Weather Proof Push Bottom for
Door Chime
Dark Brown
1A 220V~



EBG888

Door Chime
220V~ Two Tone 9.5W, 50 Hz.
Easy-to-Hear 82 dB Chime



Portable Card Switch

Receptacles (Pillar Terminal)

WTC5631WK-8

Portable Card Switch
(2-channel) 2A 220V~



WEV1081-7SW

Universal Receptacle
with Safety Shutter
16A 250V~



WEV1181-7SW

Grounding Universal Receptacle
with Safety Shutter
16A 250V~



WEV1582-7SW

Grounding Duplex Universal
Receptacle with Safety Shutter
16A 250V~



Plates for Receptacles

Plates for Switches

WTAG6803SW

1-Gang 3-Device



WTAG6101SW

1-Gang 3-Device



WTAG6102SW

2-Gang 6-Device




Wide color range suits modern interiors

Subtle and stylish color coordination
enhancing your living environments



FULL-COLOR
WIDE
SERIES
Refina



**WIDE COLOR PALETTE
TO PERFECTLY MATCH
LIFESTYLE INTERIORS**

Luxurious appearance with wide color variations creating attractive living spaces.



**HEAT-RESISTANT,
EASY-TO-USE LATEST
SWITCH MECHANISM**

Simple switch mechanism made trouble-free.











Various Combination : 7 Plate Colors × 7 Switch Colors



Metallic Pearl White [M][W][Z]
 Metallic White [M][W]
 Metallic Gray [M][H]
 Metallic Black [M][B]
 Metallic Gold [M][Y]
 Metallic Brown [M][F]
 Metallic Dark Brown [M][A]

The last 2 characters in □□ of Refina product numbers show the item color.

Switches

<p>WEG5511 [M][H] Switch "B" Single Pole 16AX 250V~</p> 	<p>WEG5521 [M][H] Switch "B" Single Pole 16AX 250V~</p> 	<p>WEG5531 [M][H] Switch "B" Single Pole 16AX 250V~</p> 	<p>WEG5512 [M][H] Switch "C" 3Way 16AX 250V~</p> 
<p>WEG5522 [M][H] Switch "C" 3Way 16AX 250V~</p> 	<p>WEG5532 [M][H] Switch "C" 3Way 16AX 250V~</p> 	<p>WEG5551 [M][H] Illuminated Switch "B" Single Pole 16AX 250V~ (Neon Lamp: 220V~)</p> 	<p>WEG5561 [M][H] Illuminated Switch "B" Single Pole 16AX 250V~ (Neon Lamp: 220V~)</p> 
<p>WEG5571 [M][H] Illuminated Switch "B" Single Pole 16AX 250V~ (Neon Lamp: 220V~)</p> 	<p>WEG5552 [M][H] Illuminated Switch "C" 3Way 16AX 250V~ (Neon Lamp: 220V~)</p> 	<p>WEG5562 [M][H] Illuminated Switch "C" 3Way 16AX 250V~ (Neon Lamp: 220V~)</p> 	<p>WEG5572 [M][H] Illuminated Switch "C" 3Way 16AX 250V~ (Neon Lamp: 220V~)</p> 
<p>WEV55337SW Glow Switch "D" Double Pole 3-Device 20A 250V~</p> 	<p>WEC5542-7SW Twin Switch "C" 3Way 10AX 250V~</p>  <div style="display: flex; align-items: center; margin-top: 10px;">  WEC5542-7  WEC5542-7  </div>		

Outlet with Switches NEW



Global Terminal
 Solid Wire: 1.5-4mm²
 Stranded Wire: 1.5-4mm²

Pillar Terminal II
 Solid, Stranded and Flexible Wire: 1.5-4mm²



WEGP1282

Grounding Duplex Universal Receptacle with Safety Shutter and Switch



Metallic White
WEGP1282MW

● Metallic White **[M][W]**

○ Metallic Pearl White **[M][W][Z]**



Metallic Gray
WEGP1282MH

● Metallic Gray **[M][H]**

● Metallic Dark Brown **[M][A]**



Metallic Brown
WEGP1282MF

● Metallic Brown **[M][F]**

● Metallic Gold **[M][Y]**



Metallic Black
WEGP1282MB

● Metallic Black **[M][B]**

WEV5511SW
 Switch "B" Single Pole
 16AX 250V~

WEV5521SW
 Switch "B" Single Pole
 16AX 250V~

WEV5531SW
 Switch "B" Single Pole
 16AX 250V~

WEV5512SW
 Switch "C" 3Way
 16AX 250V~

WEV5522SW
 Switch "C" 3Way
 16AX 250V~

WEV5532SW
 Switch "C" 3Way
 16AX 250V~

WEV5511-7SW
 Switch "B" Single Pole
 16AX 250V~

★

WEV5521-7SW
 Switch "B" Single Pole
 16AX 250V~

★

WEV5531-7SW
 Switch "B" Single Pole
 16AX 250V~

★

WEV5512-7SW
 Switch "C" 3Way
 16AX 250V~

★

WEV5522-7SW
 Switch "C" 3Way
 16AX 250V~

★

WEV5532-7SW
 Switch "C" 3Way
 16AX 250V~

★

Receptacles

WEV1081SW

Universal Receptacle
with Safety Shutter
16A 250V~



WEV1081H



WEV1091SW

Universal Receptacle
16A 250V~



WEV1091H



WEG1001SW

Receptacle
16A 250V~



WEV1001H



WEG1090SW

Round Pin Receptacle
16A 250V~



WEV1090H



WEV1181SW

Grounding Universal Receptacle
with Safety Shutter
16A 250V~



WEV1181H



WEV1582SW

Grounding Duplex Universal Receptacle
with Safety Shutter
16A 250V~



WEV1582H



Pillar Terminal

WEV1081-7SW

Universal Receptacle
with Safety Shutter
16A 250V~



WEV1081-7H



WEV1181-7SW

Grounding Universal Receptacle
with Safety Shutter
16A 250V~



WEV1181-7H



Accessories

WEV1582-7SW

Grounding Duplex Universal Receptacle
with Safety Shutter
16A 250V~



WEV1582-7H



WEV24886SW

CAT6 Data Modular Jack



WEV24886H

WEV2488SW

CAT5E Data Modular Jack



WEV2488H

WEV2364SW

Telephone Modular Jack



WEV2364H

WEV2501SW

DIN Type Television Terminal



WEV2501H

EGG331

Weather Proof Push Bottom for
Door Chime
1A 220V~



EGG335

Weather Proof Push Bottom for
Door Chime
Dark Brown
1A 220V~



EBG888

Door Chime
220V~ Two Tone
9.5W, 50 Hz.
Easy-to-Hear 82
dB Chime





Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²

Pillar Terminal II
★ Solid, Stranded and Flexible Wire: 1.5-4mm²

Plates

Unit: mm

<p>FULL-COLOR WIDE SERIES Refina A-TYPE</p> 	 <p>Plastic Plate 1-Gang 1-Device</p>	 <p>Plastic Plate 1-Gang 2-Device</p>	 <p>Plastic Plate 1-Gang 3-Device</p>	 <p>Plastic Plate 1-Gang Center 2-Device</p>
 <p>Snow White</p>	WEV68010SW	WEV68020SW	WEV68030SW	WEV680290SW
 <p>Metallic Pearl White</p> <p>M W Z</p>	WEG68010MWZ	WEG68020MWZ	WEG68030MWZ	WEG680290MWZ
 <p>Metallic White</p> <p>M W</p>	WEG68010MW	WEG68020MW	WEG68030MW	WEG680290MW
 <p>Metallic Gray</p> <p>M H</p>	WEG68010MH	WEG68020MH	WEG68030MH	WEG680290MH
 <p>Metallic Black</p> <p>M B</p>	WEG68010MB	WEG68020MB	WEG68030MB	WEG680290MB
 <p>Metallic Gold</p> <p>M Y</p>	WEG68010MY	WEG68020MY	WEG68030MY	WEG680290MY
 <p>Metallic Brown</p> <p>M F</p>	WEG68010MF	WEG68020MF	WEG68030MF	WEG680290MF
 <p>Metallic Dark Brown</p> <p>M A</p>	WEG68010MA	WEG68020MA	WEG68030MA	WEG680290MA

The last 2 or 3 characters in of Refina product number show the item color.

Receptacles and Accesories

WEV1081-7H
 Universal Receptacle
 with Safety Shutter
 16A 250V~
WEB7811 **M** **W** (Plate)
 1-Gang 1-Device

★



WEV1081H
 Universal Receptacle
 with Safety Shutter
 16A 250V~
WEB7812 **M** **W** (Plate)
 1-Gang 2-Device




WEV1181H
 Grounding Universal Receptacle
 with Safety Shutter
 16A 250V~
WEB7812 **M** **W** (Plate)
 1-Gang 2-Device




WEV1582-7H
 Grounding Duplex Universal
 Receptacle with Safety Shutter
 16A 250V~
WEB7813 **M** **W** (Plate)
 1-Gang 3-Device

★



WEV1191H
 Grounding Universal Receptacle
 16A 250V~
WEG5151-51HK
 Illuminated Switch "B" Single Pole
 16AX 250V~-(Neon Lamp 220V~)
WEB7813 **M** **W** (Plate)
 1-Gang 3-Device





WEV2501H
 DIN Type Television Terminal
 16A 250V~
WEV2364H
 Telephone Modular Jack (6P 4C)
WEB7812 **M** **W** (Plate)
 1-Gang 2-Device




WEV2501H
 DIN Type Television Terminal
WEB7811 **M** **W** (Plate)
 1-Gang 1-Device



WEV2364H
 Telephone Modular Jack (6P 4C)
WEB7811 **M** **W** (Plate)
 1-Gang 1-Device



WEV2488H
 CAT5E Data Modular Jack
WEB7811 **M** **W** (Plate)
 1-Gang 1-Device



WEV24886H
 CAT6 Data Modular Jack
WEB7811 **M** **W** (Plate)
 1-Gang 1-Device



WEG575181H
 Dimmer Switch
 (Incandescent Light Control)
 800W 220V~
WEB7812 **M** **W** (Plate)
 1-Gang 2-Device






Quick Connect Terminal
Solid Wire Only: 1.5-2.5mm²



Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²

Pillar Terminal II
★ Solid, Stranded and Flexible Wire: 1.5-4mm²

WEV1081-7SW

Universal Receptacle with Safety Shutter
16A 250V~

WEB7811SW (Plate)

1-Gang 1-Device



WEV1081-7SW

Universal Receptacle with Safety Shutter
16A 250V~

WEB7812SW (Plate)

1-Gang 2-Device



WEV1081-7SW

Universal Receptacle with Safety Shutter 16A 250V~

WEV1181-7SW

Grounding Universal Receptacle with Safety Shutter 16A 250V~

WEB7813SW (Plate)

1-Gang 3-Device



WEV1582-7SW

Grounding Duplex Universal Receptacle with Safety Shutter
16A 250V~

WEB7813SW (Plate)

1-Gang 3-Device



WEV1081-7SW

Universal Receptacle with Safety Shutter 16A 250V~

WEV5531-7SW

1Way SP Switch "B" 16AX 250V~

WEB7812SW (Plate)

1-Gang 2-Device



WEV2501SW

DIN Type Television Terminal

WEV2364SW

Telephone Modular Jack (6P 4C)

WEB7812SW (Plate)

1-Gang 2-Device



WEV2501SW

DIN Type Television Terminal

WEB7811SW (Plate)

1-Gang 1-Device



WEV2488SW

CAT5E Data Modular Jack

WEB7811SW (Plate)

1-Gang 1-Device



WEV2488SW

CAT6 Data Modular Jack

WEB7811SW (Plate)

1-Gang 1-Device



WEV2364SW

Telephone Modular Jack (6P 4C)

WEV2488SW

CAT5E Data Modular Jack

WEB7812SW (Plate)

1-Gang 2-Device



WEG575181

Dimmer Switch (Incandescent Light Control)
800W 220V~

WEB7812SW (Plate)

1-Gang 2-Device



WEG5151-51SWK

Illuminated Switch "B" Single Pole

WEB7811SW (Plate)

1-Gang 1-Device



WEV5001-7SW

Switch "B" Single Pole
16AX 250V~

WEB7813SW (Plate)

1-Gang 3-Device



WEG5401-7SW












Push Bottom "B" Single Pole
10A 250V~

WEB7811SW (Plate)

1-Gang 1-Device



Switches (with plate)

<p>COLOR</p>	 1-Gang 1Way SP Switch "B" 16AX 250V~ ★	 2-Gang 1Way SP Switch "B" 16AX 250V~ ★	 3-Gang 1Way SP Switch "B" 16AX 250V~ ★	 1-Gang 2Way SP Switch "C" 16AX 250V~ ★	 2-Gang 2Way SP Switch "C" 16AX 250V~ ★	 3-Gang 2Way SP Switch "C" 16AX 250V~ ★
 Snow White	WEBP515117SW	WEBP525217SW	WEBP535317SW	WEBP515127SW	WEBP525227SW	WEBP535327SW
 Metallic Pearl White M W Z	WEBP515117MWZ	WEBP525217MWZ	WEBP535317MWZ	WEBP515127MWZ	WEBP525227MWZ	WEBP535327MWZ
 Metallic White M W	WEBP515117MW	WEBP525217MW	WEBP535317MW	WEBP515127MW	WEBP525227MW	WEBP535327MW
 Metallic Gray M H	WEBP515117MH	WEBP525217MH	WEBP535317MH	WEBP515127MH	WEBP525227MH	WEBP535327MH
 Metallic Black M B	WEBP515117MB	WEBP525217MB	WEBP535317MB	WEBP515127MB	WEBP525227MB	WEBP535327MB
 Metallic Gold M Y	WEBP515117MY	WEBP525217MY	WEBP535317MY	WEBP515127MY	WEBP525227MY	WEBP535327MY
 Metallic Brown M F	WEBP515117MF	WEBP525217MF	WEBP535317MF	WEBP515127MF	WEBP525227MF	WEBP535327MF
 Metallic Dark Brown M A	WEBP515117MA	WEBP525217MA	WEBP535317MA	WEBP515127MA	WEBP525227MA	WEBP535327MA

The last 2 characters in □□ of Refina product numbers show the item color.

Plates

Unit: mm

<p>FULL-COLOR WIDE SERIES Refina BS-TYPE</p> 	 <p>1-Gang 1-Device</p>	 <p>1-Gang 2-Device</p>	 <p>1-Gang 3-Device</p>
 <p>Snow White</p>	WEB7811SW	WEB7812SW	WEB7813SW
 <p>Metallic Pearl White</p> <p>MWZ</p>	WEB7811MWZ	WEB7812MWZ	WEB7813MWZ
 <p>Metallic White</p> <p>MW</p>	WEB7811MW	WEB7812MW	WEB7813MW
 <p>Metallic Gray</p> <p>MH</p>	WEB7811MH	WEB7812MH	WEB7813MH
 <p>Metallic Black</p> <p>MB</p>	WEB7811MB	WEB7812MB	WEB7813MB
 <p>Metallic Gold</p> <p>MY</p>	WEB7811MY	WEB7812MY	WEB7813MY
 <p>Metallic Brown</p> <p>MF</p>	WEB7811MF	WEB7812MF	WEB7813MF
 <p>Metallic Dark Brown</p> <p>MA</p>	WEB7811MA	WEB7812MA	WEB7813MA

The last 2 characters in of Refina product numbers show the item color.

The beauty of simplicity

Clean lines result in a sharp-looking design adding an attractive touch to your living room and office



FULL COLOR
WIDE
SERIES



**ELEGANTLY SIMPLE
SQUARISH DESIGN**

Add a refreshing accent to any room. Bold, modern plates with square shapes available in various configurations to suit residential and commercial requirements.



**HEAT-RESISTANT,
EASY-TO-USE LATEST
SWITCH MECHANISM**

Panasonic's standard design wiring device with simple, trouble-free switch mechanism.

Switches

<p>WEV5001SW Switch "B" Single Pole 16AX 250V~</p> <p>WEV5001H</p>  	<p>WEV5002SW Switch "C" 3 Way 16AX 250V~</p> <p>WEV5002H</p>  	<p>WEG5003KSW Switch "D" Double Pole 16AX 250V~</p> <p>WEG5003HK</p>  	<p>WEG5004KSW Switch "E" 4 Way 16AX 250V~</p> <p>WEG5004HK</p>  
<p>WEG5151-51SWK Illuminated Switch "B" Single Pole 16AX 250V (Neon Lamp: 220V~)</p> <p>WEG5151-51HK</p>  	<p>WEG5152-51SWK Illuminated Switch "C" 3Way 16AX 250V (Neon Lamp: 220V~)</p> <p>WEG5152-51HK</p>  	<p>WEG5141SW Glow Switch "B" Single Pole 2 Wire 6AX 250V~</p> <p>WEG5141H</p>  	<p>WEG5341SW Glow Switch "B" Single Pole 3 Wire 6AX 250V~</p> <p>WEG5341H</p>  

Switches (Pillar Terminal)

<p>WEV5001-7SW Switch "B" Single Pole 16AX-250V~</p> <p>WEV5001-7H</p>  <p>★</p>	<p>WEV5002-7SW Switch "C" 3 Way 16AX-250V~</p> <p>WEV5002-7H</p>  <p>★</p>	<p>WEG5151-7SW Illuminated Switch "B" Single Pole 16AX 250V (Neon Lamp: 220V~)</p> <p>WEG5151-7H</p>  <p>★</p>	<p>WEG5152-7SW Illuminated Switch "C" 3Way 16AX 250V (Neon Lamp: 220V~)</p> <p>WEG5152-7H</p>  <p>★</p>
---	---	---	---

Receptacles and Accessories

<p>WEG3032GSW (Green) Pilot Lamp 220V~</p> <p>WEG3032GH (Green)</p>  	<p>WEG3032SW (White) Pilot Lamp 220V~</p> <p>WEG3032WH (White)</p>  	<p>WEG3032RSW (Red) Pilot Lamp 220V~</p> <p>WEG3032RH (Red)</p>  	<p>WEG5400-7 Push Bottom NC Contact Type 10A 250V~</p> 
<p>WEG3023SW Telephone Wire Chip for 9mm Diameter 16 Diameter</p> <p>WEG3023H</p> 	<p>WEG3020SW Blank Chip</p> <p>WEG3020H</p> 	<p>WEV5033-7SW Glow switch (2 poles) 250VAC - 20A</p> <p>WEV5033-7H</p>  	



Quick Connect Terminal
Solid Wire Only: 1.5-2.5mm²



Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²

Pillar Terminal II
★ Solid, Stranded and Flexible Wire: 1.5-4mm²

WEV1081SW
Universal Receptacle with Safety Shutter
16A 250V~

WEV1081H




WEV1091SW
Universal Receptacle
16A 250V~

WEV1091H




WEG1001SW
Receptacle
16A 250V~

WEG1001H




WEG1090SW
Round Pin Receptacle
16A 250V~

WEG1090SH




WEV1181SW
Grounding Universal Receptacle with Safety Shutter
16A 250V~

WEV1181H




WEV1582SW
Grounding Duplex Universal Receptacle with Safety Shutter
16A 250V~

WEV1582H




WEV24886SW
CAT6 Data Modular Jack

WEV24886H




WEV2488SW
CAT5E Data Modular Jack

WEV2488H




WEV2364SW
Telephone Modular Jack (6P 4C)

WEV2364H




WEV2501SW
DIN Type Television Terminal

WEV2501H




WEG5401-7SW
Push Bottom "B" Single Pole
10A 250V~

WEG5401H-7




EGG331
Weather Proof Push Bottom for Door Chime
1A 220V~



EGG335
Weather Proof Push Bottom for Door Chime
Dark Brown
1A 220V~



EBG888
Door Chime
220V~ Two Tone 9.5W, 50 Hz.
Easy-to-Hear 82 dB Chime



Receptacles (Pillar Terminal)

WEV1081-7SW
Universal Receptacle with Safety Shutter
16A 250V~

WEV1081-7H



★

WEV1181-7SW
Grounding Universal Receptacle with Safety Shutter
16A 250V~

WEV1181-7H



★

WEV1582-7SW
Grounding Duplex Universal Receptacle with Safety Shutter
16A 250V~

WEV1582-7H



★

Dimmer Switches

WEG575151SW

Dimmer Switch
(Incandescent Light Control)
500W 220V~
※Off Funtion Type



WEG575151H



WEG575181

Dimmer Switch
(Incandescent Light Control)
800W 220V~
※Off Funtion Type



WEG575181H



WEG5002SWK-021

Hotel Use Switch "C" for Indication
"Don't Disturb"
16AX 250V~



WEB1051W

Shaver Receptacle (white)
Input: 16A 220V~
Output: 240V/110V-20VA



WEB5781WK

Electronic Key Card Switch (White)
16AX 220V~



WEG5001SWK-031

Hotel Use Switch "B" for
Indication "Make up Room"
16AX 250V~



WEG5401-011SW

Entrance Bell
10A 250V~



WEV2488SW

CAT5E Data Modular Jack



WEV2364SW

Telephone Modular Jack (6P 4C)



WEV2501SW

DIN Type Television Terminal



WEG3032G-031

Pilot Lamp for Indication
"Make up Room" Green 220V~




WEG3032R-021

Pilot Lamp for Indication "Don't Disturb"
Red 220V~



Wiring diagram - "Don't Disturb" - Make up Room" - Bell Switch"





Quick Connect Terminal
Solid Wire Only: 1.5-2.5mm²







Quick Connect Terminal II
Solid Wire: 1.5-2.5mm²
Stranded Wire: 1.5-2.5mm²



Global Terminal
Solid Wire: 1.5-4mm²
Stranded Wire: 1.5-4mm²

Plates

Unit: mm

<p>FULL-COLOR WIDE SERIES</p>	 Plastic Plate 1-Gang 1-Device	 Plastic Plate 1-Gang 2-Device	 Plastic Plate 1-Gang 3-Device	 Plastic Plate 1-Gang Center 2-Device	 Plastic Plate 1-Gang Cover
<p>Standard plate</p>  Snow White	WEV68010SW	WEV68020SW	WEV68030SW	WEV68290SW	WEV68910SW
<p>Metal plate</p>  Aluminum  Stainless	WEG6501-1	WEG6502-1	WEG6503-1	WEG65029-1	WEG6591-1
	WEG6601-1	WEG6602-1	WEG6603-1	WEG66029-1	WEG6691-1
<p>Metallic</p>  Metallic Pearl White  Metallic White	WEG68010MWZ	WEG68020MWZ	WEG68030MWZ	WEG680290MWZ	
	WEG68010MW	WEG68020MW	WEG68030MW	WEG680290MW	
	WEG68010MH	WEG68020MH	WEG68030MH	WEG680290MH	
	WEG68010MB	WEG68020MB	WEG68030MB	WEG680290MB	
	WEG68010MY	WEG68020MY	WEG68030MY	WEG680290MY	
	WEG68010MF	WEG68020MF	WEG68030MF	WEG680290MF	
	WEG68010MA	WEG68020MA	WEG68030MA	WEG680290MA	
<p>Weather proof plates</p>  Metal IPX3  Plastic IP55	Metal	Metal	Metal	Metal	
	WEG7801	WEG7802	WEG7803	WEG78029	
	Plastic	Plastic	Plastic	Plastic	
	WEG7901	WEG7902	WEG7903	WEG79029	
<p>Weather proof cover plates (Horizontal Type)</p>  Metal IP55  Plastic IP55			Metal		
			WEG8881		
			Plastic		
			WEG8981		

*IP=Ingress Protection (when flap is closed).

The standard of excellence for any installation

Simple design compatible with any interior plan.



FULL-COLOR SERIES



WIDE RANGE OF COLORS TO SELECT FROM FOR PERFECT COLOR COORDINATION.

Designed for compatibility with any international wiring standards and installation requirements.



HEAT-RESISTANT, EASY-TO-USE LATEST SWITCH MECHANISM

A basic Panasonic wiring device with simple, trouble-free switch mechanism.

FULL-COLOR SERIES A-TYPE

Switches

WNV5001-7W

Switch "B" Single Pole
16AX-250V~




WNG5061-701W

Appellation Switch "B" Single Pole
16AX 250V~



WNG5021W-7

Twin Switch "B" Single Pole
10AX 250V~



WNV5002-7W

Switch "C" 3 way
16AX-250V~




WNG5003W-7

Switch "D" Double Pole
10AX-250V~



WNG5004W-7

Switch "E" 4 way
10AX-250V~



WN5241W-801

Appellation Glow
Switch "B"
Single Pole
4A 300V~



WNG5051W-751

Illuminated Appellation
Switch "B" Single Pole
16AX 250V
(Neon Lamp: 220V)~



WNG5052W-751

Illuminated Appellation
Switch "C" 3 Way
16AX 250V
(Neon Lamp: 220V)~



WNG5401W-7K

Push Bottom "B" Single Pole
10A 300V~



WNG5343W-761

Glow Switch "D" Double Pole
for Water Heater
20AX 250V~



WBG5408699W

Glow Switch "D" Double Pole
45A-250V~



WBG5414699W-SP

Glow Switch "D" Double Pole
20AX-250V~



WBG5414699W

Glow Switch "D" Double Pole
for A/C
20AX-250V~



WNH5611-801

Tablet Switch
10A 250V~



Dimmer Switches

WNGP575152

Dimmer Switch with
Blank Chip and Modern Plate
(Incandescent Light Control)
500W 220-240V~



WNGP575283W

Dimmer Switch with
Modern Plate
(Incandescent Light Control)
800W 220-240V~





Receptacles and Accessories

WNV1081-7W

Universal Receptacle with Safety Shutter
16A-250V~



WNV1091-7W

Universal Receptacle
10A-250V



WN1090-7K-W

Round Pin Receptacle
10A-250V~



WN1001-7K-W

Receptacle
10A 250V~



WN1101-7W

3 Wire Grounding Receptacle
10A-250V~



WNG15923-7W

Grounding Duplex Universal Receptacle
16A 250V~



NR3170W-8

CAT6 Data Modular Jack



NRV3160W

Enhanced CAT5E Data Modular Jack



WNTG15649W

Telephone Modular Jack
(6P 4C)




WZV1201W

Television Terminal
(Current Passing Type)




WN3020W

Blank Chip



WN3023W

Telephone Wire Chip



Switches

WSG3001

Surface Mounting Switch "B"
Single Pole
10A 300V~



Receptacles

WKG1092-250

Surface Mounting Universal Duplex Receptacle
10A 250V~



WKG1091-250














Surface Mounting Universal Receptacle
10A 250V~










FULL-COLOR SERIES A-TYPE

Plates

Unit: mm

FULL-COLOR SERIES A-TYPE	Modern Plate	Aluminum Plate		Stainless Plate
		Screw Visible	Screw Invisible	Screw Visible
	Without Mounting Strap	With Mounting Strap	With Mounting Strap	With Mounting Strap
 1-Gang 1-Device				
 1-Gang 2-Device	WZV7841W	WN7501-8	WN6501K-8	WN7601-8
 1-Gang 2-Device	WZV7842W	WN7502-8	WN6502K-8	WN7602-8
 1-Gang 3-Device	WZV7843W	WN7503-8	WN6503K-8	WN7603-8
 2-Gang 4-Device	WZV7844W	WN7504-8	WN6504K-8	WN7604-8
 2-Gang 6-Device	WZV7846W	WN7506-8	WN6506K-8	WN7606-8
 1-Gang Cover	—	WN7591-8	—	WN7691-8
 1-Gang for HB	WZV7061W	—	—	—
 1-Gang for HB Snow White	WEV7061SW	—	—	—





Weather Proof Plates IPX3						
Metal	Plastic					
						
		Metal	WN7801K-8	WN7802K-8	WN7803K-8	WN7821K-8
		Plastic	WN7901-8	WN7902-8	WN7903-8	WN7921-8

*IP=Ingress Protection (when flap is closed).

INDUSTRIAL SOCKET



Locking Receptacles and Weather Proof Locking Receptacles





NOTE Note: For locking flush mounting receptacles (20A and 30A) indicated by a ※1 mark, because no more than one plug can be plugged in at the same time if the receptacles are installed in a multi-receptacle plate, use single plates and install the number needed.				Locking Flush Mounting Receptacles  WF2420BK		Locking Surface Mounting Receptacles  WK2315K		Weather Proof Locking Receptacles (JIS Weather Proof Type)  WK6430 		Applicable Electrical Wire	
Form	Rating	Black		Milky White		Black		Milky White			
		2P	15A 125V	WF2215BK	WF2215WK	WF2220BK※1	WF2220WK※1	WK22215	WK22215W		—
3P	20A 250V	WF2320BK※1	WF2320WK※1	WF2331B※1	WF2331W※1	WK2320K	WK2320W	WK6320	—	—	Ø2,Ø2.6 3.5mm ² ,5.5mm ²
	30A 250V	WF2330B※1	WF2330W※1	—	—	—	—	—	—	—	Ø2.6,Ø3.2 5.5mm ² ,8mm ²
	60A 250V	WF2360B	WF2360W	—	—	—	—	—	—	—	8mm ² ,14mm ²
Grounding 2P (Previously 3P)	15A 125V	WF2315BK	WF2315WK	WF2330B※1	WF2330W※1	WK2330	WK2330W	WK6330	—	—	Ø1.6,Ø2 2mm ² ,3.5mm ²
	20A (L6-20) 250V	WF2520B※1	WF2520W※1	—	—	—	—	—	—	—	Ø2,Ø2.6 3.5mm ² ,5.5mm ²
	30A (L6-30) 250V	WF2330B※1	WF2330W※1	—	—	—	—	—	—	—	Ø2.6,Ø3.2 5.5mm ² ,8mm ²
Grounding 3P (Previously 4P)	20A 250V	WF2420BK※1	WF2420WK※1	—	—	—	—	—	—	—	Ø2,Ø2.6 3.5mm ² ,5.5mm ²
	30A (L15-30) 250V	WF2430B※1	WF2430W※1	—	—	—	—	—	—	—	Ø2.6,Ø3.2 5.5mm ² ,8mm ²
	60A 250V	WF2460B	WF2460W	—	—	—	—	—	—	—	8mm ² ,14mm ²

★ The 3P 30A and the grounding 3P 30A receptacles conform to NEMA standards and are not exchangeable with some of the receptacles used domestically in Japan.
 ★★ "Multi-Level Weather Proof Valve" is adopted
 Numbers indicated by a [] mark are the NEMA standard number.

Features

The Japan Electric Association Code has been revised (8001-1990), with the distinction between grounding poles and grounded-side pins clearly identified. In addition, although not stipulated in the Japan Electric Association Code, these receptacles have been established by the standards of the Japan Wiring Devices Association.

Explanation of The Revisions (Related Sections)


20A	Revisions in The Internal Wiring Standards	Before Revision	After Revision	30A	Standards of The Japan Association of Wiring Fixture Manufacturers*1	Our Previous Product	Newly Established
		 <p>Could be used as the grounding pole.</p> <p>Newly established</p>	 <p>JIS module</p> <p>For 3P only</p> <p>New pole arrangement</p> <p>Grounding pole</p> <p>(Conforms to NEMA L6-20)</p>			 <p>Changed.</p> <p>Also used as a grounding pole.</p> <p>(Conforms to NEMA L6-30)</p>	 <p>New Pole Arrangement</p> <p>Exchangeable with the NEMA L11-30 module</p> <p>Grounding side pole [W]</p> <p>3P 30A Product name changed to grounding 2P 30A</p> <p>Conforms to NEMA L6-30</p> <p>Grounding pole</p>

The diagram above is indicating the face of receptacles.

Pole arrangements which are not stipulated in the Japan Electric Association Code are selected according to the standards of the Japan Wiring Devices Association.

Dimensions (units: mm)

• Locking Flush Mounting Receptacles



WF2420BK-W WF2460B-W


Model No.	Dimension A	Dimension B	Dimension C	Dimension D
2P WF2215BK-WK	36.5	59	34.5	19.8
2P WF2220BK-WK	36.5	59	34.5	25.5
3P WF2320BK-WK	38.8	59.5	34.5	25.5
3P WF2331B-W	42.6	67.7	40.5	27.7
Grounding 2P (Previously 3P) WF2315BK-WK	37.7	59	34.5	24
Grounding 2P WF2520B-W	38.9	59.5	34.5	25.5
Grounding 2P WF2330B-W	42	69.1	40.5	30
Grounding 3P WF2420BK-WK	43	61	40.5	25.5
Grounding 3P (Previously 4P) WF2430B-W	42	67	40.5	30

* for appropriate plates, please refer to pages 39 & 45

Applicable Box for WF2360-WF2460

Applicable box Use a medium deep-type square receptacle box together with a square double switch cover (inner square 13 mm)


• Locking Surface Mounting Receptacle



WK2215 WK2220K WK2320K WK2331B-W
 WK2215W WK2320W

WK2315K WK2315W WK2520B-W WK2330 WK2420K
 WK2330W WK2430

• Weather Proof Locking Receptacle










Model No.	Dimension A
3P WK6320	34.5
3P WK6331	40.5
Grounding 2P (Previously 3P) WK6315	34.5
Grounding 2P (Previously 3P) WK6520	34.5
Grounding 2P (Previously 3P) WK6330	40.5
Grounding 3P (Previously 4P) WK6420	40.5
Grounding 3P (Previously 4P) WK6430	40.5

All products have entirely the same specifications as those sold in Japan.

INDUSTRIAL SOCKET

Locking Weather Proof Rubber Cord Connectors, Plugs, Bodies, Locking Plugs, and Locking Cord Connectors

Applicable Wire Types: Rubber Cabtire Cable (Type 2 or less), Round Rubber Cabtire Cord, Vinyl Cabtire Cable, and Round Vinyl Cabtire Cord

Locking Plugs		Tough Plugs		Flush Cord Locking Corner Plugs "Horizontal Type"	Applicable Electrical Wire	Locking Water Proof Rubber Cord Connector Plugs and Cord Connector Bodies (JIS Weather Proof Type)			
						Plug WF8420K 	Body WA5429K 	Set WA5420K 	 Multi-Level Weather Proof Valve Improves cord insertability without losing weatherproofing performance.
Black	Milky White	Black	Milky White	Flush Cord Locking Corner Plugs "Horizontal Type"		Plugs	Bodies	Set	Applicable Electrical Wire's Outer Diameter (Ø)
WF6215	WF6215W	—	—	—	1.25mm ² 2mm ²	WF8215K ★★	WA5219K ★★	WA5215K ★★	9.6-12
—	—	WF62153B	WF62153W	—	1.25mm ² 2mm ² -5mm ²	—	—	—	—
WF6220	WF6220W	—	—	—	2mm ² 3.5mm ²	WF8220K ★★	WA5229K	WA5220K	10.5-13.5
WF6320	WF6320W	—	—	—	2mm ² 3.5mm ²	WF8320K ★★	WA5329K ★★	WA5320K ★★	11-14.5
—	—	—	—	WF3324 (Horizontal Type)	—	—	—	—	—
WF6331B	WF6331W	—	—	—	3.5mm ² 5.5mm ²	WF8331 ★★ ★(L11-30)	WA5338 ★★ ★(L11-30)	WA5331 ★★ ★(L11-30)	13-16
—	—	—	—	—	8mm ² 14mm ²	WF8360	WA5369	WA5360	17.5-22
WF6315	WF6315W	—	—	—	1.25mm ² 2mm ²	WF8315K ★★	WA5319K ★★	WA5315K ★★	10.5-13
—	—	WF3315B	WF3315W	—	—	—	—	—	—
—	—	—	—	WF3314 (Horizontal Type)	—	—	—	—	—
—	—	—	—	WF3524 (Horizontal Type)	2mm ² 3.5mm ²	WF8520 ★★	WA5529 ★★	WA5520 ★★	11-14.5
WF6330	WF6330W	—	—	—	3.5mm ² 5.5mm ²	WF8330	WA5339	WA5330	13-16
—	—	—	—	WF3334 (Horizontal Type)	—	—	—	—	—
WF6420	WF6420W	—	—	—	2mm ² 3.5mm ²	WF8420K ★★	WA5429K ★★	WA5420K ★★	12-16
—	—	—	—	WF3424 (Horizontal Type)	—	—	—	—	—
WF6430	WF6430W	—	—	—	3.5mm ² 5.5mm ²	WF8430	WA5439	WA5430	14-17.5
—	—	—	—	WF3434 (Horizontal Type)	—	—	—	—	—
—	—	—	—	—	8mm ² 14mm ²	WF8460	WA5469	WA5460	19.5-24

Note: • For outdoor wiring exposed to rain, use either rubber cabtire cable or vinyl cabtire cable.
• For indoor locations exposed to moisture or high humidity, use rubber cabtire cable.
• If you use stranded wire on screw terminal, please don't solder up the copper wires at the terminal.
There is a possibility that heating will occur since long time use may bring about oxidizing on surface of solder and make the contact between terminal and solder defective.


Features

Locking corner plugs are suitable for large kitchen equipment and other electrical equipment.

- Horizontal type can make electrical code line compact
- Even if in the narrow space, you can arrange equipment in order.



WF3424



Horizontal type can make electrical code line compact

For the connection of the power supply to electrical equipment in factories, etc. 2P 15A locking weatherproof rubber cord connector. (Locking flat plugs + weatherproof construction + compact size)








Applicable wire : 1.25-2mm²
(outer diameter 9.6 -12mm)

WF8715
2P 15A Locking weatherproof rubber plug 15A 125V

WA6219
2P 15A Locking weatherproof rubber cord connector body 15A 125V

WA6215
2P 15A Locking weatherproof rubber cord connector (set) 15A 125V

• Locking Plugs		• Flush Cord Locking Corner Plugs "Horizontal Type"		• Locking Water Proof Rubber Plugs		• Locking Water Proof Rubber Bodies		• Locking Water Proof Rubber Cord Connectors (Complete Set)			
											
Model No.	Dimension A	Dimension B	Dimension C	Model No.	Dimension A	Dimension B	Dimension C	Model No.	Dimension A		
2P	WF6215W	34	34	19	WF3314	52	32	38	2P	WA5215K	148.5
	WF6220	36	41	21	WF3524	63	37	46		WA5220K	161
	WF6320	38	46	23	WF3334	73.25	43	56.5		WA5320K	169.1
	WF6331B	57.5	62.5	44	WF3324	63	37	46		WA5331	208.5
	WF6315W	36	38.5	21	WF3424	73.25	43	56.5		WA5360	320
	WF3315B-W	49.5	38	—	WF3434	73.25	43	56.5		WA5315K	159
	WF6330W	57.5	62.5	44						WA5520	183.8
	WF6420W	40	56	25						WA5330	208.5
	WF6430W	57.5	62.5	44						WA5420K	187.5
										WA5430	208.5
										WA5460	320
3P	WF8215K	62	41	12							
	WF8220K	66	47.2	13.5							
	WF8320K	68.8	53	14.5							
	WF8331	93.5	69.5	16							
	WF8360	178	80.5	22							
	WF8315K	64.5	46	13.5							
	WF820K	78.2	46	14.5							
	WF830	93.5	69.5	16							
	WF8420K	79	63.6	16							
	WF8430	93.5	69.5	17.5							
	WF8460	178	80.5	24							
	WA5219K	89	44	12							
	WA5229K	98	51.5	13.5							
	WA5329K	103.5	56.5	14.5							
	WA5338	118.5	74.5	16							
	WA5369	171.5	74	22							
	WA5319K	97	49	13							
	WA5529	112	53.5	14.5							
	WA5339	118.5	74.5	16							
	WA5429K	112	67.5	16							
	WA5439	118.5	74.5	17.5							
	WA5469	171.5	74	24							

All products have entirely the same specifications as those sold in Japan.

High-Capacity Flush Mounting Receptacles, Surface Mounting Receptacles, Plugs, and Cord Connectors

Applicable Wire Types: Rubber Cabtire Cable (Type 2 or less), Round Rubber Cabtire Cord, Vinyl Cabtire Cable, and Round Vinyl Cabtire Cord

Note Note: For models WF1220BK/WK, WF1230BK/WK, WF1320BK/WK, WF1420BK/WK indicated by a ※1 mark, due to the size of the plugs, no more than one plug can be plugged in at the same time if the receptacles are installed in a multi-receptacle switch box. Therefore, if two or more circuits are to be used at the same time, use single switch boxes and install the number needed.		Flush Mounting Receptacles		Surface Mounting Receptacles		Applicable Electrical Wire	Plugs		Tough Plugs		Plugs "Horizontal Type"		Applicable Electrical Wire		
		WF1220BK		WK36301B					WF5420		WF52153B			WF56301B	
		Form	Rating	Black	Milky White		Black	Milky White	Plugs		Tough Plugs			Plugs "Horizontal Type"	
		Black	Milky White	Black	Milky White			Black	Milky White	Black	Milky White				
2P	⊕	15A 125V	—	—	—	—	—	WF5215	WF5215W	—	—	—	—	1.25mm ² , 2mm ²	
	⊖	15A 250V	—	—	—	—	—	—	—	WF52153B	WF52153W	—	—	1.25mm ² , 2mm ² , 3.5mm ²	
	⊕	20A 250V	WF1220BK ※1	WF1220WK ※1	WK1220B	WK1220W	∅2.6, ∅3.2, 3.5mm ² , 5.5mm ²	WF5220 WF52201 Compact Type	WF5220W	—	—	—	—	2mm ² , 3.5mm ²	
	⊖	30A 250V	WF1230BK ※1	WF1230WK ※1	WK1230	—	∅2.6, ∅3.2, 5.5mm ² , 8mm ²	WF5230	WF5230W	—	—	—	—	3.5mm ² , 5.5mm ²	
3P	⊕	15A 250V	WF1315BK	WF1315WK	WK1315	—	∅1.6, ∅2.2mm ² , 3.5mm ²	WF5315	WF5315W	—	—	—	—	1.25mm ² , 2mm ²	
	⊖	20A 250V	WF1320BK ※1	WF1320WK ※1	WK1320	—	∅2.6, ∅3.2, 3.5mm ² , 5.5mm ²	WF5320	WF5320W	—	—	—	—	2mm ² , 3.5mm ²	
	⊕	30A 250V	WF1330BK	WF1330WK	WK1330	—	∅2.6, ∅3.2, 5.5mm ² , 8mm ²	WF5330	WF5330W	—	—	—	—	3.5mm ² , 5.5mm ²	
Grounding 2P	⊕	15A 125V	—	—	—	—	—	WF7002	WF7002W	—	—	—	—	1.25mm ² , 2mm ²	
	⊖	15A 250V	—	WF3012WK (Cream)	—	—	∅1.6, ∅2.2mm ² , 3.5mm ²	WF7011	WF7011W	—	—	—	—	1.25mm ² , 2mm ²	
	⊕	30A 250V	WF3630B	WF3630W	WK3630	—	∅2.6, ∅3.2, 5.5mm ² , 8mm ²	WF5630	WF5630W	—	—	—	—	3.5mm ² , 5.5mm ²	
	⊖		—	—	WK36301B Thin Type	WK36301W Thin Type		—	—	—	—	WF56301B Horizontal Type	WF56301W Horizontal Type		
Grounding 3P (Previously 4P)	⊕	15A 250V	WF1415BK	WF1415WK	WK1415	—	∅1.6, ∅2.2mm ² , 3.5mm ²	WF5415	WF5415W	—	—	—	—	1.25mm ² , 2mm ²	
	⊖	20A 250V	WF1420BK ※1	WF1420WK ※1	WK1420	—	∅2.6, ∅3.2, 3.5mm ² , 5.5mm ²	WF5420	WF5420W	—	—	—	—	2mm ² , 3.5mm ²	
	⊕	30A 250V	WF1430BK	WF1430WK	WK1430	—	∅2.6, ∅3.2, 5.5mm ² , 8mm ²	WF5430	WF5430W	—	—	—	—	3.5mm ² , 5.5mm ²	

Note: Electrical wire indicated in parentheses () cannot be used for surface mounting receptacles.

Dimensions (units: mm)

Flush Mounting Receptacles

WF1220BK+W, WF1230BK+W, WF1320BK+W, WF1420BK+W, WF1315BK+W, WF1320BK+W, WF1330BK+W, WF3012WK, WF1415BK+W, WF1420BK+W, WF1430BK+W, WF1330BK+W, WF1430BK+W, WF3630B+W

Model No.	Dimension A	Dimension B	Dimension C	Dimension D
2P WF1220BK+W	38.8	60	34.5	24.1
2P WF1230BK+W	42	64.8	40.5	35.3
3P WF1315BK+W	37.7	59.5	34.5	21
3P WF1320BK+W	37.6	60	34.5	24.1
Grounding 2P WF3012WK	38	—	34.5	19.5
Grounding 3P (Previously 4P) WF1415BK+W	40.4	59	34.5	21
Grounding 3P (Previously 4P) WF1420BK+W	40.8	59	34.5	24.1
Grounding 3P (Previously 4P) WF1430BK+W	40.8	59	34.5	24.1

* for appropriate plates, please refer to pages 39 & 45

•Surface Mounting Receptacles

WK1220B+W, WK3630, WK1415, WK1420, WK1430, WK36301B+W, WK3730B+W, WF56301B+W, WF5730B+W

•Plugs

WF5015B+W, WF5115B+W, WF52153B+W

Model No.	Dimension A	Dimension B	Dimension C
2P WF5215+W	34.2	34	20
2P WF5220+W	41.2	53	27
2P WF52201+W	38.2	45.5	24
2P WF5230+W	50.9	63	33
2P WF5315+W	35.2	46	21
3P WF5320+W	41.2	53	27
3P WF5330+W	50.9	68	33
3P WF7002+W	35.2	39	21
Grounding 2P WF7011+W	35.2	39	21
Grounding 2P WF5430+W	61.5	63.5	47.5
Grounding 2P (Previously 4P) WF5415+W	35.2	46	21
Grounding 2P (Previously 4P) WF5420+W	41.2	53	27
Grounding 2P (Previously 4P) WF5430+W	50.9	73	33

All products have entirely the same specifications as those sold in Japan.

INDUSTRIAL SOCKET

Locking Weather Proof Rubber Cord Connectors, Plugs, Bodies, Locking Plugs, and Locking Cord Connectors

Applicable Wire Types: Rubber Cabtire Cable (Type 2 or less), Round Rubber Cabtire Cord, Vinyl Cabtire Cable, and Round Vinyl Cabtire Cord

			Weather Proof Rubber Cord Connector Plugs and Cord Connector Bodies (JIS Rain-Proof Type)				Rubber Plug (non-Weather Proof Type)	Applicable Electrical Wire	Cord Connectors (Body)	Cord Connectors (Complete Sets)	Applicable Electrical Wire
			Plug (WF7420K)	Body (WA3429K)	Set (WA3420K)	WF7005K	WA1219		WA1215		
Form	Rating		Plugs	Cord Connector Body	Complete Set	Applicable Wire Outer Diameter	Plugs	Black	Black		
2P	⊕	15A 125V	WF7215K	WA3219K	WA3215K	9.6~12	WH4007 WF4215	1.25mm ² , 2mm ²	WA1219	WA1215 (Body WA1219) (Plug WF5215)	1.25mm ² , 2mm ²
	⊖	15A 250V	—	—	—	—	WF4212	1.25mm ² , 2mm ²	—	—	
	⊕	20A 250V	WF7220	WA3229	WA3220	10.5~13.5	WF4220	2mm ² , 3.5mm ²	WA1229	WA1220 (Body WA1229) (Plug WF5220)	2mm ² , 3.5mm ²
	⊕	30A 250V	WF7230	WA3239	WA3230	12~15	WF4230	3.5mm ² , 5.5mm ²	—	—	
3P	⊕	15A 250V	WF7315	WA3319	WA3315	10.5~13	WF4315	1.25mm ² , 2mm ²	WA1319	WA1315 (Body WA1319) (Plug WF5315)	1.25mm ² , 2mm ²
	⊕	20A 250V	WF7320	WA3329	WA3320	11~14.5	WF4320	2mm ² , 3.5mm ²	WA1329	WA1320 (Body WA1329) (Plug WF5320)	2mm ² , 3.5mm ²
	⊕	30A 250V	WF7330	WA3339	WA3330	13~16	WF4330	3.5mm ² , 5.5mm ²	—	—	
Grounding 2P	⊕	15A 125V	WF75159	WA3519K	WA35159	10.5~13	WF7005K WF7004	0.75mm ² ~2mm ² 1.25mm ² , 2mm ²	WA1519	WA1515 (Body WA1519) (Plug WF7002)	1.25mm ² , 2mm ²
	⊖	15A 250V	WF7615	WA3619	WA3615	10.5~13	WF7013	1.25mm ² , 2mm ²	WA1619	WA1615 (Body WA1619) (Plug WF7011)	1.25mm ² , 2mm ²
	⊕	30A 250V	WF7630	WA3639	WA3630	13~16	WF4630	3.5mm ² , 5.5mm ²	—	—	
	⊖		—	—	—	—	—		—	—	
Grounding 3P (Previously 4P)	⊕	15A 250V	WF7415	WA3419	WA3415	11.5~14	WF4415	1.25mm ² , 2mm ²	WA1419	WA1415 (Body WA1419) (Plug WF5415)	1.25mm ² , 2mm ²
	⊕	20A 250V	WF7420K	WA3429K	WA3420K	12~16	WF4420	2mm ² , 3.5mm ²	WA1429	WA1420 (Body WA1429) (Plug WF5420)	2mm ² , 3.5mm ²
	⊕	30A 250V	WF7430	WA3439	WA3430	14~17.5	WF4430	3.5mm ² , 5.5mm ²	—	—	


- Note:
- For outdoor wiring exposed to rain, use either rubber cabtire cable or vinyl cabtire cable.
 - For indoor locations exposed to moisture or high humidity, use rubber cabtire cable.
 - If you use stranded wire on screw terminal, please don't solder up the copper wires at the terminal. There is a possibility that heating will occur since long time use may bring about oxidizing on surface of solder and make the contact between terminal and solder defective.

• Cord Connectors	• Weather Proof Rubber Plugs	• Weather Proof Rubber Cord Connectors	• Weather Proof Rubber Cord Connector Bodies	• Rubber Plugs																																																																																																																																																																																																																																																																																																																																																													
<table border="1"> <thead> <tr> <th>Model No.</th> <th>Dimension A</th> <th>Dimension B</th> <th>Dimension C</th> <th>Dimension D</th> </tr> </thead> <tbody> <tr> <td>2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA1215</td> <td>87.5</td> <td>34</td> <td>39</td> <td></td> </tr> <tr> <td>WA1220</td> <td>107.5</td> <td>53</td> <td>52</td> <td></td> </tr> <tr> <td>3P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA1315</td> <td>91.5</td> <td>45</td> <td>42</td> <td></td> </tr> <tr> <td>WA1320</td> <td>107.5</td> <td>53</td> <td>52</td> <td></td> </tr> <tr> <td>Grounding 2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA1515</td> <td>91.5</td> <td>39</td> <td>42</td> <td></td> </tr> <tr> <td>Grounding 3P (Previously 4P)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA1615</td> <td>91.5</td> <td>39</td> <td>42</td> <td></td> </tr> <tr> <td>WA1415</td> <td>91.5</td> <td>46</td> <td>42</td> <td></td> </tr> <tr> <td>WA1420</td> <td>107.5</td> <td>53</td> <td>52</td> <td></td> </tr> </tbody> </table>	Model No.	Dimension A	Dimension B	Dimension C	Dimension D	2P					WA1215	87.5	34	39		WA1220	107.5	53	52		3P					WA1315	91.5	45	42		WA1320	107.5	53	52		Grounding 2P					WA1515	91.5	39	42		Grounding 3P (Previously 4P)					WA1615	91.5	39	42		WA1415	91.5	46	42		WA1420	107.5	53	52		<table border="1"> <thead> <tr> <th>Model No.</th> <th>Dimension A</th> <th>Dimension B</th> <th>Dimension C</th> <th>Dimension D</th> </tr> </thead> <tbody> <tr> <td>2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF7215K</td> <td>60</td> <td>39</td> <td>12</td> <td></td> </tr> <tr> <td>WF7220</td> <td>90</td> <td>54</td> <td>13.5</td> <td></td> </tr> <tr> <td>WF7230</td> <td>120</td> <td>69.5</td> <td>15</td> <td></td> </tr> <tr> <td>3P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF7315</td> <td>78</td> <td>48</td> <td>12.5</td> <td></td> </tr> <tr> <td>WF7320</td> <td>90</td> <td>54</td> <td>14.5</td> <td></td> </tr> <tr> <td>WF7330</td> <td>120</td> <td>69.5</td> <td>16</td> <td></td> </tr> <tr> <td>Grounding 2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF75159</td> <td>60</td> <td>39</td> <td>13</td> <td></td> </tr> <tr> <td>WF7615</td> <td>78</td> <td>48</td> <td>12.5</td> <td></td> </tr> <tr> <td>WF7630</td> <td>102</td> <td>73</td> <td>16</td> <td></td> </tr> <tr> <td>Grounding 3P (Previously 4P)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF7415</td> <td>78</td> <td>48</td> <td>14</td> <td></td> </tr> <tr> <td>WF7420K</td> <td>91</td> <td>61</td> <td>16</td> <td></td> </tr> <tr> <td>WF7430</td> <td>120</td> <td>69.5</td> <td>17.5</td> <td></td> </tr> </tbody> </table>	Model No.	Dimension A	Dimension B	Dimension C	Dimension D	2P					WF7215K	60	39	12		WF7220	90	54	13.5		WF7230	120	69.5	15		3P					WF7315	78	48	12.5		WF7320	90	54	14.5		WF7330	120	69.5	16		Grounding 2P					WF75159	60	39	13		WF7615	78	48	12.5		WF7630	102	73	16		Grounding 3P (Previously 4P)					WF7415	78	48	14		WF7420K	91	61	16		WF7430	120	69.5	17.5		<table border="1"> <thead> <tr> <th>Model No.</th> <th>Dimension A</th> </tr> </thead> <tbody> <tr> <td>2P</td> <td></td> </tr> <tr> <td>WA3215K</td> <td>123</td> </tr> <tr> <td>WA3220</td> <td>197</td> </tr> <tr> <td>WA3230</td> <td>264</td> </tr> <tr> <td>3P</td> <td></td> </tr> <tr> <td>WA3315</td> <td>170.5</td> </tr> <tr> <td>WA3320</td> <td>197</td> </tr> <tr> <td>WA3330</td> <td>264</td> </tr> <tr> <td>Grounding 2P</td> <td></td> </tr> <tr> <td>WA35159</td> <td>126</td> </tr> <tr> <td>WA3615</td> <td>169.5</td> </tr> <tr> <td>WA3630</td> <td>229</td> </tr> <tr> <td>Grounding 3P (Previously 4P)</td> <td></td> </tr> <tr> <td>WA3415</td> <td>170.5</td> </tr> <tr> <td>WA3420K</td> <td>193</td> </tr> <tr> <td>WA3430</td> <td>264</td> </tr> </tbody> </table>	Model No.	Dimension A	2P		WA3215K	123	WA3220	197	WA3230	264	3P		WA3315	170.5	WA3320	197	WA3330	264	Grounding 2P		WA35159	126	WA3615	169.5	WA3630	229	Grounding 3P (Previously 4P)		WA3415	170.5	WA3420K	193	WA3430	264	<table border="1"> <thead> <tr> <th>Model No.</th> <th>Dimension A</th> <th>Dimension B</th> <th>Dimension C</th> <th>Dimension D</th> </tr> </thead> <tbody> <tr> <td>2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA3219K</td> <td>74</td> <td>46</td> <td>12</td> <td></td> </tr> <tr> <td>WA3229</td> <td>120</td> <td>67</td> <td>13.5</td> <td></td> </tr> <tr> <td>WA3239</td> <td>160</td> <td>85</td> <td>15</td> <td></td> </tr> <tr> <td>WA3319</td> <td>105</td> <td>58</td> <td>13</td> <td></td> </tr> <tr> <td>3P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA3329</td> <td>120</td> <td>67</td> <td>14.5</td> <td></td> </tr> <tr> <td>WA3339</td> <td>160</td> <td>85</td> <td>16</td> <td></td> </tr> <tr> <td>Grounding 2P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA3519K</td> <td>75</td> <td>46</td> <td>13</td> <td></td> </tr> <tr> <td>WA3619</td> <td>105</td> <td>58</td> <td>13</td> <td></td> </tr> <tr> <td>WA3639</td> <td>143</td> <td>83</td> <td>16</td> <td></td> </tr> <tr> <td>Grounding 3P (Previously 4P)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WA3419</td> <td>105</td> <td>58</td> <td>14</td> <td></td> </tr> <tr> <td>WA3429K</td> <td>120</td> <td>73</td> <td>16</td> <td></td> </tr> <tr> <td>WA3439</td> <td>160</td> <td>85</td> <td>17.5</td> <td></td> </tr> </tbody> </table>	Model No.	Dimension A	Dimension B	Dimension C	Dimension D	2P					WA3219K	74	46	12		WA3229	120	67	13.5		WA3239	160	85	15		WA3319	105	58	13		3P					WA3329	120	67	14.5		WA3339	160	85	16		Grounding 2P					WA3519K	75	46	13		WA3619	105	58	13		WA3639	143	83	16		Grounding 3P (Previously 4P)					WA3419	105	58	14		WA3429K	120	73	16		WA3439	160	85	17.5		<table border="1"> <thead> <tr> <th>Model No.</th> <th>Dimension A</th> <th>Dimension B</th> <th>Dimension C</th> </tr> </thead> <tbody> <tr> <td>2P</td> <td></td> <td></td> <td></td> </tr> <tr> <td>WH4007</td> <td>53</td> <td>34</td> <td>10.5</td> </tr> <tr> <td>WF4215</td> <td>50</td> <td>32</td> <td>13</td> </tr> <tr> <td>WF4212</td> <td>54</td> <td>39</td> <td>12</td> </tr> <tr> <td>WF4220</td> <td>68</td> <td>50</td> <td>13.5</td> </tr> <tr> <td>WF4230</td> <td>90</td> <td>68.2</td> <td>15</td> </tr> <tr> <td>WF4315</td> <td>60</td> <td>45.2</td> <td>13</td> </tr> <tr> <td>3P</td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF4320</td> <td>68</td> <td>50.2</td> <td>14.5</td> </tr> <tr> <td>WF4330</td> <td>90</td> <td>68.2</td> <td>16</td> </tr> <tr> <td>Grounding 2P</td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF7005K</td> <td>50</td> <td>32</td> <td>13</td> </tr> <tr> <td>WF7004</td> <td>50</td> <td>39</td> <td>10</td> </tr> <tr> <td>WF7013</td> <td>50</td> <td>39</td> <td>10</td> </tr> <tr> <td>WF4630</td> <td>100</td> <td>69.5</td> <td>16</td> </tr> <tr> <td>Grounding 3P (Previously 4P)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>WF4415</td> <td>60</td> <td>45.2</td> <td>14</td> </tr> <tr> <td>WF4420</td> <td>70</td> <td>52.2</td> <td>16</td> </tr> <tr> <td>WF4430</td> <td>90</td> <td>68.2</td> <td>17.5</td> </tr> </tbody> </table>	Model No.	Dimension A	Dimension B	Dimension C	2P				WH4007	53	34	10.5	WF4215	50	32	13	WF4212	54	39	12	WF4220	68	50	13.5	WF4230	90	68.2	15	WF4315	60	45.2	13	3P				WF4320	68	50.2	14.5	WF4330	90	68.2	16	Grounding 2P				WF7005K	50	32	13	WF7004	50	39	10	WF7013	50	39	10	WF4630	100	69.5	16	Grounding 3P (Previously 4P)				WF4415	60	45.2	14	WF4420	70	52.2	16	WF4430	90	68.2	17.5
Model No.	Dimension A	Dimension B	Dimension C	Dimension D																																																																																																																																																																																																																																																																																																																																																													
2P																																																																																																																																																																																																																																																																																																																																																																	
WA1215	87.5	34	39																																																																																																																																																																																																																																																																																																																																																														
WA1220	107.5	53	52																																																																																																																																																																																																																																																																																																																																																														
3P																																																																																																																																																																																																																																																																																																																																																																	
WA1315	91.5	45	42																																																																																																																																																																																																																																																																																																																																																														
WA1320	107.5	53	52																																																																																																																																																																																																																																																																																																																																																														
Grounding 2P																																																																																																																																																																																																																																																																																																																																																																	
WA1515	91.5	39	42																																																																																																																																																																																																																																																																																																																																																														
Grounding 3P (Previously 4P)																																																																																																																																																																																																																																																																																																																																																																	
WA1615	91.5	39	42																																																																																																																																																																																																																																																																																																																																																														
WA1415	91.5	46	42																																																																																																																																																																																																																																																																																																																																																														
WA1420	107.5	53	52																																																																																																																																																																																																																																																																																																																																																														
Model No.	Dimension A	Dimension B	Dimension C	Dimension D																																																																																																																																																																																																																																																																																																																																																													
2P																																																																																																																																																																																																																																																																																																																																																																	
WF7215K	60	39	12																																																																																																																																																																																																																																																																																																																																																														
WF7220	90	54	13.5																																																																																																																																																																																																																																																																																																																																																														
WF7230	120	69.5	15																																																																																																																																																																																																																																																																																																																																																														
3P																																																																																																																																																																																																																																																																																																																																																																	
WF7315	78	48	12.5																																																																																																																																																																																																																																																																																																																																																														
WF7320	90	54	14.5																																																																																																																																																																																																																																																																																																																																																														
WF7330	120	69.5	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 2P																																																																																																																																																																																																																																																																																																																																																																	
WF75159	60	39	13																																																																																																																																																																																																																																																																																																																																																														
WF7615	78	48	12.5																																																																																																																																																																																																																																																																																																																																																														
WF7630	102	73	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 3P (Previously 4P)																																																																																																																																																																																																																																																																																																																																																																	
WF7415	78	48	14																																																																																																																																																																																																																																																																																																																																																														
WF7420K	91	61	16																																																																																																																																																																																																																																																																																																																																																														
WF7430	120	69.5	17.5																																																																																																																																																																																																																																																																																																																																																														
Model No.	Dimension A																																																																																																																																																																																																																																																																																																																																																																
2P																																																																																																																																																																																																																																																																																																																																																																	
WA3215K	123																																																																																																																																																																																																																																																																																																																																																																
WA3220	197																																																																																																																																																																																																																																																																																																																																																																
WA3230	264																																																																																																																																																																																																																																																																																																																																																																
3P																																																																																																																																																																																																																																																																																																																																																																	
WA3315	170.5																																																																																																																																																																																																																																																																																																																																																																
WA3320	197																																																																																																																																																																																																																																																																																																																																																																
WA3330	264																																																																																																																																																																																																																																																																																																																																																																
Grounding 2P																																																																																																																																																																																																																																																																																																																																																																	
WA35159	126																																																																																																																																																																																																																																																																																																																																																																
WA3615	169.5																																																																																																																																																																																																																																																																																																																																																																
WA3630	229																																																																																																																																																																																																																																																																																																																																																																
Grounding 3P (Previously 4P)																																																																																																																																																																																																																																																																																																																																																																	
WA3415	170.5																																																																																																																																																																																																																																																																																																																																																																
WA3420K	193																																																																																																																																																																																																																																																																																																																																																																
WA3430	264																																																																																																																																																																																																																																																																																																																																																																
Model No.	Dimension A	Dimension B	Dimension C	Dimension D																																																																																																																																																																																																																																																																																																																																																													
2P																																																																																																																																																																																																																																																																																																																																																																	
WA3219K	74	46	12																																																																																																																																																																																																																																																																																																																																																														
WA3229	120	67	13.5																																																																																																																																																																																																																																																																																																																																																														
WA3239	160	85	15																																																																																																																																																																																																																																																																																																																																																														
WA3319	105	58	13																																																																																																																																																																																																																																																																																																																																																														
3P																																																																																																																																																																																																																																																																																																																																																																	
WA3329	120	67	14.5																																																																																																																																																																																																																																																																																																																																																														
WA3339	160	85	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 2P																																																																																																																																																																																																																																																																																																																																																																	
WA3519K	75	46	13																																																																																																																																																																																																																																																																																																																																																														
WA3619	105	58	13																																																																																																																																																																																																																																																																																																																																																														
WA3639	143	83	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 3P (Previously 4P)																																																																																																																																																																																																																																																																																																																																																																	
WA3419	105	58	14																																																																																																																																																																																																																																																																																																																																																														
WA3429K	120	73	16																																																																																																																																																																																																																																																																																																																																																														
WA3439	160	85	17.5																																																																																																																																																																																																																																																																																																																																																														
Model No.	Dimension A	Dimension B	Dimension C																																																																																																																																																																																																																																																																																																																																																														
2P																																																																																																																																																																																																																																																																																																																																																																	
WH4007	53	34	10.5																																																																																																																																																																																																																																																																																																																																																														
WF4215	50	32	13																																																																																																																																																																																																																																																																																																																																																														
WF4212	54	39	12																																																																																																																																																																																																																																																																																																																																																														
WF4220	68	50	13.5																																																																																																																																																																																																																																																																																																																																																														
WF4230	90	68.2	15																																																																																																																																																																																																																																																																																																																																																														
WF4315	60	45.2	13																																																																																																																																																																																																																																																																																																																																																														
3P																																																																																																																																																																																																																																																																																																																																																																	
WF4320	68	50.2	14.5																																																																																																																																																																																																																																																																																																																																																														
WF4330	90	68.2	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 2P																																																																																																																																																																																																																																																																																																																																																																	
WF7005K	50	32	13																																																																																																																																																																																																																																																																																																																																																														
WF7004	50	39	10																																																																																																																																																																																																																																																																																																																																																														
WF7013	50	39	10																																																																																																																																																																																																																																																																																																																																																														
WF4630	100	69.5	16																																																																																																																																																																																																																																																																																																																																																														
Grounding 3P (Previously 4P)																																																																																																																																																																																																																																																																																																																																																																	
WF4415	60	45.2	14																																																																																																																																																																																																																																																																																																																																																														
WF4420	70	52.2	16																																																																																																																																																																																																																																																																																																																																																														
WF4430	90	68.2	17.5																																																																																																																																																																																																																																																																																																																																																														
<p>• Rubber Cord Connectors (Non-Weather Proof) 15A 125V</p>		<p>Complete Set, Plug, Cord Connector Body</p> <p>WA2215(Set) WF4215(Plug) WA2219 (Cord Connector) Body</p> <p>Applicable Wire 1.25mm²~2mm²</p>																																																																																																																																																																																																																																																																																																																																																															


All products have entirely the same specifications as those sold in Japan.

Switches

Contact Structure




Switch, Single Pole



Example of Switches
WEV5001SW WNV5001-7W WEVH5511
WNG5051W-751 WEV5001-75W WEVH5511-7
WEG5151-75W


Switch, 3Way

Operation of one fixture 2 locations.



Example of Switches
WEV5001SW WNV5002-7W WEV5002-7SW
WNG5052W-751 WEG5152-51KSW WEG51527SW
WEVH5512 WEVH5512-7


Switch, Double Pole



Example of Switches
WEG5003KSW WEVH5003
WNG5003W-7


Switch, 4Way

Operation of one fixture from 3 locations in combination with 3way switches.



Example of Switches
WEG5004KSW WEVH5004
WNG5004W-7


Glow Switch(3Way)




Example of Switches
WEG6341

Wiring Instructions(Combination with Pilot Lamp)


Pilot Lamp Location Indicator



Switch On/Pilot Lamp On




Switch Off/Pilot Lamp On




Door Chime

EGG331/EGG335/EBG888



Dimmer Unit

WEG575151SW WNGP575253
WEG575181 WNGP575283




Easy Installation (WEV2488SW/WEV2488H/WEV24886SW/WEV24886H)

1 2Way Connection

Toolless

Wire Connection by Using Captip




- Use tool when connecting wires 0.65mm
- Cut the excess wires with nippers after connection

Using Wiring Tool




- Excess wires can be cut with the blade edge of the tool

2 Easy to Remove the Cap



- After connecting the core wires, press the cap down until you hear a click.

4 No Need to Untwist the Wires



- No need to untwist the wires on setting to the slots.
- Minimum untwisting makes uniform installation quality & transmission performance.

3 Cable Fixing System

Cable Fixing System




- Fix the cable steadily during installation.
- Prevent overpeeling of the Sheath of the cable to avoid failures/malfunctions


Pin/Pair Assignment

		T568A	T568B
①	W • BL	5	5
	BL	4	4
②	W • O	3	1
	O	6	2
③	W • G	1	3
	G	2	6
④	W • BR	7	7
	BR	8	8

Straight Connection with T568A



Cross Connection for 10BASE-T/100BASE-TX












DIMENSION OF WIRING DEVICES


Halumie

Plates


Unit: mm

 <p>HALUMIE</p>	 <p>Plastic Plate 1-Gang 1-Device</p>	 <p>Plastic Plate 1-Gang 2-Device</p>	 <p>Plastic Plate 1-Gang 3-Device</p>	 <p>Plastic Plate 1-Gang Cover</p>
		<p>WEVH68010</p>  <p>Plastic Plate 1-Gang Center 2-Device</p>	<p>WEVH68020</p>  <p>Plastic Plate 2-Gang 4-Device</p>	<p>WEVH68030</p>  <p>Plastic Plate 2-Gang 6-Device</p>
	<p>WEVH680290</p>	<p>WEVH68040</p>	<p>WEVH68060</p>	<p>WEVH8061</p>


WEVH5511




WEVH5521




WEVH5531




WEVH5512




WEVH5522




WEVH5532




WEVH5003




WEVH5004




WEVH5151-51




WEVH5152-51



WEVH5111-7



WEVH5521-7




DIMENSION OF WIRING DEVICES


Halumie

Unit: mm


WEVH5531-7




WEVH5512-7




WEVH5522-7




WEVH5532-7




WEVH5151-7




WEVH5152-7




WEVH5033-7




WEVH5542-7




WEV1081SW
WEV1091SW
WEV1081-7SW




WEV1181SW
WEV1181-7SW




WEV1582SW
WEV1582-7SW




WEV24886SW
WEV2488SW




WEV2364SW




WEV2501SW




WEG3023SW




WEG3020SW




WEVH5401-011




WEG575151SW




WTEGP51552S-1-G




WTEGP54562S-1-G



WTEGP55582S-1-G




WTEGP56572S-1-G




COSMO ART


WTAG7152



WTC5631WK-8




WTNG4101W/WTNG4102W




*For receptacles & accessories please see FULL-COLOR WIDE series.




WEV5511SW



WEV5521SW



WEV5531SW




DIMENSION OF WIRING DEVICES


FULL COLOR
WIDE
SERIES

Unit: mm


WEV5001SW
WEG5003KSW
WEV5001-7SW




WEV5002SW
WEG5004KSW
WEV5002-7SW




WEG5151-51SWK
WEG5152-51SWK
WEG5341SW
WEG51517-7SW
WEG51527-7SW




WEG5141SW




WEG5400-7SW
WEG5401-7SW




WEG575151SW




WEG575181




WEG3032SW(White)
WEG3032RSW(Red)
WEG3032GSW(Green)




WEG3023SW




WEG3020SW




EGG331/EGG335




EBG888




WEG1001SW




WEV1081SW
WEV1091SW
WEV1081-7SW




WEG1090SW




WEV1181SW
WEV1191SW
WEV1181-7SW




WEV1582SW
WEV1592SW
WEV1582-7SW




WEV2501SW




WEV2364SW




WEV24886SW
WEV2488SW




WEB1051W




WEB5781WK




WEB5151-7SW □□



WEB5252-7SW □□




WEB535317 □□




The last 2 characters in □□ of Refina product numbers show the item color.

FULL - COLOR SERIES


WNV5001-7W




WNV5002-7W




WNG5003-7W




WNG5004-7W




WNG5051W-751




WNG5052W-751




WNG5241W-801




WNG5021W-7



WNG5061-701W




WNG5401W-7K




FULL-COLOR SERIES


WBG5408699W




WBG5414699W-SP
WBG5414699W




WNG5343W-761




WNGP575283W




WNGP575152W




WNH5611-801




WN3020W




WN3023W




WNV1081-7W
WNV1091-7W




WNG15923-7W




WN1090-7K-W




WN1001-7KW




WN1101-7W




WNTG15649W




NRV3160W




WZV1201W




WSG3001



WK1091-250



WKG1092-250



High safety that comply with Thai industrial standard (TIS) and civilized design in Japan

EXTENSION CORD with Safety Shutter & Breaker



5M CORD LENGTH



Flexible Cord Terminal

Is able to distort 10,000 times at 45 angles and 100 times at 60 N to protect copper inside from being twisted.



Glow Switch

Durable built in switch for Power ON Indication.



Switch Cover

Embedded style switch with cover to protect from unintended switching.



Highly Insulated Flexible Wire

1.5 mm² PVC type flexible wire with thick insulation.



Box Cover

Made of ABS Resin which is heat resistant UI 94 std., is sturdy and durable.



Round Pin Type Receptacle with Shutter&Ground

- Copper clad is produced by piece to piece, without connecting point. That leads to be a good conductor.
- Receptacle is made of Urea Resin. Urea Resin property are sturdy, high heat resistant and inflammable.
- Durable socket can be plugged in more than 10,000 times.
- Twin Safety Shutter springs prevent electric shock (Shutter will not open unless both are pressed). Easy to plug in both Flat pin type, even with heavy weight.



Full Rating

Total electric power which can applied to this product is 3,500 watts, 16A/250V



Safe Connection

- Flat pin with Grounding type of plug.
- High strength material cannot be easily deformed by frequent plugging.



Circuit Breaker

- Electric can be cut off automatically when overload of electric power (white button will protrude instantly).
- Easy to re-preform by pressing the circuit breaker (No need any replaced fuse).
- Circuit breaker is designed to be underneath to protect from accidental touch.

Specification

- Electrical outlet conform with IEC 60884-1 which be able to plug insert at least 10,000 strokes
- Full rating 16A 250V, 3,500 watts
- 3 main plug in, 5 main plug in, 6 main plug in, 1.5 mm² wire size for 16A 250V with 5 m of wire length
- Circuit Breaker can cut electric off automatically when overload of 3,500 watts and re-perform easily by press the reset button (After adjust to proper electric power)
- Switch with glow status, endurable and can be on/off for over 40,000 strokes

WCHG 28334

Extension Cord (3 Sockets)



WCHG 28352

Extension Cord (5 Sockets)



WCHG 2836

Extension Cord (6 Sockets)



Nice Appearance and Safety Design for Floor Management

FLOOR OUTLET SERIES



POP-UP FLOOR OUTLET **IP-44**

DU5983LT9-1

Grounding Duplex Universal with Safety Shutter with Outlet Box and Box Protector 16A 250V~



DU5993LT9-1

Grounding Duplex Universal with Outlet Box and Box Protector 16A 250V~



DU5990LT9-1

Grounding Duplex Universal with Outlet Box and Box Protector 16A 250V~



DU6993LT9-1

Duplex Telephone Modular Jack 6P4C with Outlet Box and Box Protector



DU6935LT9-1

Telephone Modular Jack 6P 4C and CAT5E Modular Jack with Outlet Box and Box Protector



DU6955LT9-1

Duplex CAT5E Modular Jack with Outlet Box and Box Protector



DU59833LT9-1

Grounding Universal with Safety Shutter 16A 250V~ and Telephone Modular Jack 6P4C with Outlet Box and Box Protector



DU59835LT9-1

Grounding Universal with Safety Shutter 16A 250V~ and CAT5E Modular Jack with Outlet Box and Box Protector



DU6966LT9-1

Duplex CAT6 Modular Jack with Outlet Box and Box Protector



FLOOR OUTLET (Aluminum Diecast) **IP-44**

DUF1260LTK-1

Grounding Duplex Universal with Safety Shutter with Outlet Box and Box Protector 16A 250V~



DUF1270LTK-1

Grounding Duplex Universal with Outlet Box and Box Protector 16A 250V~



DUF3221LTK-1

Grounding Universal with Safety Shutter 16A 250V~ and Telephone Modular Jack 6P4C with Outlet Box and Box Protector





DUF1200LTK-1

Blank with Outlet Box and Box Protector
This Floor Outlet can be supplied without Socket



DUF2229LTK-1

Duplex Telephone Modular Jack 6P4C
with Outlet Box and Box Protector



DUF2214LTK-1

Telephone Modular Jack 6P4C and
CAT5E Modular Jack with Outlet Box
and Box Protector



DUMF3200LT-1

Double Duplex without Inside
Wiring Devices for Full Color WIDE Series



DUF3234LTK-1

Grounding Universal with Safety Shutter 16A 250V-
And CAT5E Modular Jack with box Protector and Outlet Box



DUF5200LT-1

Floor Outlet blank (without socket outlet)
With cover unit and outlet box




DUF2259LTK-1

Duplex CAT5E Modular Jack
with Outlet Box and Box Protector



Safety

Safety constructed
conforming to the
IEC 60884-1



- IP 4 4 — This product conforms the water and dust protection level IP44 (IEC60529) by the cover are closed.
Harmful ingress of water ; Level 4 Protection against liquid spills (No damage by water splash from any direction)
Harmful ingress of solid obstacles ; Level4 Protection against substance bigger than 1.0mm. (Hard to enter substances such as cable, cloth, paper, board pieces)

*Installed Receptacles have Full Color Wide Series

FLOOR OUTLET SINGLE IP-24

DU8102HTC-1

Grounding Universal with Safety
Shutter with Cover Unit
16A 250-



DU8100HTC-1

Grounding Duplex Universal
with Cover Unit
16A 250V-



DU5102HTC-1

Grounding Single Parallel
with Cover Unit
16A 250-



FLOOR OUTLET

DU61233HTC-1

Duplex Telephone Modular Jack 6P4C Cover Unit



DU61223HTC-1

Telephone Modular Jack 6P4C and TV Terminal Cover Unit



DU7199HTC-1*

GFloor Outlet Blank for Double Device with Cover Unit



FLOOR OUTLET DUPLEX IP-24

DU8183HTK-1-1

Grounding Duplex Universal with Safety Shutter with Outlex Box and Box Protector 16A 250-



DU81931HTK-1

Grounding Duplex Universal with Outlex Box and Box Protector 16A 250-



DU5103HTK-1

Grounding Duplex Parallel with Outlex Box and Box Protector 16A 250-



DU81835HTK-1

Grounding Universal with Safety Shutter and CAT5E Modular Jack with Outlex Box and Box Protector 16A 250-



DU61233HTK-1

Duplex Telephone Modular Jack 6P4C with Outlex Box and Box Protector 16A 250-



DU61235HTK-1

Telephone Modular Jack 6P4C and CAT5E Modular Jack with Outlex Box and Box Protector



DU61355HTK-1

Duplex CAT5E Modular Jack with Outlex Box and Box Protector




DU61466HTK-1

Duplex CAT6 Modular Jack with Outlex Box and Box Protector



DU8199HTK-1*

Floor Outlet, Blank for Triple Device with Cover Unit





*Installed Receptacles have PS mark.


How to mount

After putting the concrete on, make the hole to install the product.


- (1) Hammer the center part of where the box is installed and make the hole for installation.
- (2) After chipping the concrete away, loosen cover unit screws and take the box protector off.




Pop-up floor outlet duplex dimension




Floor outlet (Aluminum Diecast) dimension



Floor outlet single dimension



Floor outlet duplex dimension




New innovation with
New energy-saving lighting control

PASSIVE INFRARED SENSOR




FULL-COLOR
WIDE
SERIES

Looks Slim with The Compact Plate



Saves Energy Preventing Forgotten on Lights



Features

- 1) High sensitive detection with sensor
- 2) Long life 100,000 On/Off
- 3) Safety and Easy with Quick Connect Terminal
- 4) Stand by power consumption less than 2W


Applicable locations :



Corridor



Restroom



Entrance hall



Locker



Quick Connect Terminal II
 Solid Wire: 1.5-2.5mm²
 Stranded Wire: 1.5-2.5mm²

Stand-alone Type

WTKG2311

Passive Infrared Sensor
 (Ceiling Surface Mount Type)
 3A 220-240V~
 10 sec - 30 mins. Time Delay
 Day Light Sensor



WTKG2310

Passive Infrared Sensor
 (Ceiling Flush Mount Type)
 3A 220-240V~
 1 min Time Delay



Interconnectable Type

WTKG2411

Master


Passive Infrared Sensor
 (Master Unit)
 3A 220-240V~




WTKG2911

Auxiliary

Passive Infrared Sensor
 (Auxiliary Unit)
 DC12V




Demonstration



(up to 4 auxiliary units can be connected with 1 master unit)

Specifications

Model no.	WTKG2310/WTKG2411/WTKG2911	WTKG2311
Detectable scope	Ceiling 	Adjusting method of detection area Can adjust the detection area
Supplementary of Detect scope by hood	None	Ceiling
Dimension	 $\varnothing 85 \times 12 + 58.8$ (L=70.8mm)	 $\varnothing 120 \times 33.5 + 17$ (L=50.5mm)
Rating	3A 220-240V~	
Rated Power Consumption	Less than 2W	
Load Capacity	Incandescent Lamp 660W Fluorescent Lamp 330W	
Applicable Standard	IEC60669 - 2 - 1	
Ambient Temperature	-10°C to +40°C	
Wiring Connection	Quick Connect Terminal	
Size of Installation Hole (cm)	7.0 (+0.5)	7.2 (+0.5)
Applicable Wire	1.5mm ² - 2.5mm ² Rigid Copper Wire Only	
Applicable Boxes	Square Box 2 inch or more Octagon Box 2 inch or more	1.5 inch or more 1.5 inch or more
Time-Out Delay	Fixed 1min	Adjustable 10 sec. - 30 min
Detectable Movement Speed	0.3 m/s - 1.0m/s	



Provides prompt notification in the event of a fire

SLIM SMOKE & VOICE ALARM WITH LONG-LIFE-BATTERY




**Whiz, whiz,
Fire, fire**

Rapid indication with a clear “alarm sound” and a “voice” easy to understand.

Approx. 87dB at 1m distance from equipment (at peak value) (measured by our company based on corporate judgment standard)
For alarm sound “Whiz, whiz”, a wide frequency band from 0.3 kHz to 4.0 kHz is adopted for easy catching even by old people and children.


Immediately understands what happened.



When there is a fire

**Whiz, whiz,
Fire, fire**


It's serious.



When failures occur

**Blip, Blip, Blip,
“Problem, Please check.”**


Please replace the unit.



When testing

**Blip,
“Operating normally”**

Fine



When battery is running out

**Blip,
“Low Battery”**

Please replace the unit.



Model No.	SH28455911	
Power Supply	Dedicated Lithium Battery (3V)x1	
Battery Life	Approximately 10 years [*]	
Detecting Method	Smoke Type [Photoelectric Method]	
Class	Type2	
Alarm Sound/ Voice Alarm	Fire	Whiz, whiz, fire, fire!
	Low Battery	“Blip, Low Battery!” x 3 times. “Blip, approx., every 40 seconds after that.”
	Trouble	“Blip, blip, blip, Problem, Please check” x 3 times. “Blip, blip, blip,” approx., every 40 seconds after that.
Alarm Volume	84 dB or more at 1m distance from equipment	
Dimension	Approx. Ø100 mm x 44 mm (Including attachment base)	
Weight (Including Dedicated Lithium Battery)	Approx. 140g.	
Operating Temperature	0 °C to +50 °C	
Installation Location	Ceiling/Wall Surface	

Signal Transmission	—
Contact (No-Voltage)	—

*It may be shorter depending on usage environment.

	Mode	Voice Alarm	Indication
Function	Normal	—	OFF
	Alarm	Whiz Whiz Fire Fire	Blink
	Silent	—	OFF
	Trouble #1	Blip, Blip, Blip, Problem please check	Blink
	Trouble [Silent]	—	Blink
	Low Battery #2	Blip, Low Battery	Blink every 8 seconds
	Low Battery [Silent]	—	Blink every 8 seconds

DOOR PHONE



SMARTPHONE CONNECT MODEL **NEW** Video Intercom System **VL-SVN511VN**



* Easy installation by simply replacing existing doorbell unit Nonpolar 2-wire system.

Smartphone Connect*1

You can use your smartphone or tablet as a sub monitor to respond to visitors and unlock electric locks no matter where you are in the home. You can also monitor doorphone images when you want to check the door entrance.




Answer Visitors and Unlock the Electric Locks



Monitoring

Wi-Fi Connection

In addition to smartphones/tablets, the main monitor can also wirelessly connect to the Wi-Fi router for easy connections without a cable. You can configure Wi-Fi settings using a simplified method (called WPS).



E-mail Notification*2

The main monitor can send e-mail with a time stamp and image of visitors to e-mail addresses registered in advance, enabling you to check who has visited when you are outside the house (even when you are overseas).



Other Features

- Supports iOS and Android™ (free application)*
 - iPhone 5 and later, iPad (iOS 7.0 or later)
 - Android smartphones and tablets (Android 4.0 or later)
- Electric Lock Release Support: VL-RLY1 (12 V AC/DC, less than 1 A)
- Picture Recording (Up to 400 images/50 visitors (8 shots per visitor))
- Night Vision (white coloured LED lights)
- Voice Changer

* Some mobile devices may not be compatible.
* For the latest information about the app and compatible devices, visit the following website.



<http://panasonic.net/pcc/support/intercom/smartphone/>

Options

Door Station (Doorphone) VL-V555 (Surface mount) CMOS 0.3 M pixels Up to 2 	Door Station (Doorphone) VL-V554 (Surface mount) CMOS 1.0 M pixels Up to 2 	Door Station (Doorphone) VL-V522L (Surface mount) Up to 2 	Lobby Station VL-V590 Up to 20 main monitors can be connected. 	PBX This image shows the KX-NS500. Connectable PBX Model Numbers KX-TDA30/100/100D/200/600 series KX-TDE100/200/600 series KX-NS300/500/700/1000 series Please consult your dealer when connecting with a PBX.
---	---	---	--	--

*1 The main monitor must be on the same home Wi-Fi network as a smartphone/tablet (with the dedicated app installed). It is also necessary to run the dedicated app in order to receive visitor's calls on a smartphone/tablet.
*2 To use this function, a main monitor with e-mail sender information registered must be connected to the internet. E-mail may not be able to be sent, depending on the condition of the network.

DOOR PHONE

WIRELESS STANDARD MODEL Wireless Video Intercom System VL-SW251VN



* Easy installation by simply replacing existing doorbell unit Nonpolar 2-wire system.


Wireless Handset (2.4 GHz)

Check visitors and respond promptly from everywhere in the home and even while you are doing something else, by wireless handset.



Night Vision (LED Light)

Door Station is equipped with LED lights (illumination lamp). It enables the colour display of visitors at a distance of about 50 cm at night.



Conventional

Equipped with LED light

Picture Recording (8 Consecutive recorded images each)

Eight consecutive still images of visitors are automatically recorded. (Up to 50 times, 400 images in total) This ensures that you will see every person visiting your home. Images can also be displayed frame-by-frame.



Other Features

- Electric Lock Release Support : AC30V-1A / DC24V-1A (Door Opener)
- Voice Changer
- Intercom Call (between main monitor and sub monitor)

Options

Door Station (Doorphone)
VL-V522L

Up to
2



Wireless Monitor Station
(Sub Monitor)
VL-W605

Up to
4



Lobby Station
VL-V590



Up to 20
main monitors
can be connected.

Repeater for Wireless Monitor
VL-FAN1/VL-FAN2*

Up to
2



* for India

PBX



This image shows
the KX-NS500.

Connectable PBX Model Numbers
KX-TDA30/100/100D/200/600 series
KX-TDE100/200/600 series
KX-NS300/500/700/1000 series

Please consult your dealer when
connecting with a PBX.

Available in a wide variety of models to suit a multitude of environmental and weather conditions.

AUTOMATIC TIME SWITCH



What's an Automatic Time Switch?

An automatic time switch automatically controls the use of electricity according to time. It's a device that lowers both electrical and labour costs.

Automatically Turns the Power On and Off

The Time Switch combines a clock with a switch to automatically turn power on or off at preset times. It is generally built into a lightboard or distribution panel, and controls electricity on a 24-hour or weekly basis. It makes it possible to replace conventional manual control with automated, reliable ON/OFF time management.

Eliminating Electrical Waste Is Also Ecological

Because the power is reliably turned on and off according to a preset time schedule, the amount that was wasted by extended use is saved, and electric bills are effectively lowered.

Cutting Labour Costs Is Also Efficient

Since the job of turning the power on and off is done automatically instead of manually, you can assign your valuable human resources to more important jobs. Human error is also eliminated, so power management is more reliable.

Simply Set the Time for ON/OFF Control

Time management consists of simply setting the times to turn the power on and off. A wide range of uses are possible across various operations, such as lighting, air conditioning, water supply, and livestock feeding.

Example: Managing electricity in the office



From 8:30 AM to 12:00 AM

Turn the power on at the start of the workday. Lighting and air conditioning are turned on to provide a smooth start to office work.



From 0:00 PM to 1:00 PM

Lunchtime. Lighting and air conditioning are turned off while people leave the office for lunch. No power is wasted.



From 1:00 PM to 6:00 PM

Lighting and air conditioning are turned on precisely when lunchtime ends. Then the power is automatically turned off when the workday finishes. Again, no power is wasted.



AUTOMATIC TIME SWITCH

Uses and Advantage of Panasonic Time Switch

Panasonic, with almost 100 years of expertise forged in the Electrical Construction Material field with its Wiring Devices series, has also established a name for itself in the Time Control Devices market during the past 50 years with its Automatic Time Switch.

Thorough Quality Control

In addition to advanced functions, Panasonic focuses its manufacturing efforts on providing high durability and performance for many years of reliable use, and selects materials with full consideration of the global environment. Certification by third-party institutions and compliance with a wide range of international standards attest to these efforts. This approach is also used with Panasonic's Automatic Time Switches, to allow our customers worldwide to experience a new level of comfort and safety for the control of electric equipment.

Meeting IEC Standards

Panasonic's product design has been recognised and certified by many international organisations worldwide, such as the IEC (International Electrotechnical Commission), the top reference for electrical and electronic safety standards. Our Automatic Time Switch has successfully passed and complies with the IEC730-2-7 directives to provide safer and more comfortable use of our line-up to our customers.



Products Compliant with the RoHS Directive

Panasonic's manufacturing processes are based on management standards for chemical substances by complying with the EU RoHS directive in order to provide all of our customers safer products with less impact on the environment.



Example of Use

Example 1 Factories

Time Switches are at work in a wide variety of applications, including production lines, air conditioning systems, and lighting equipment.



Example 2 Public Infrastructure

The number of people in towns and cities varies depending on the time of day. Time Switches enable waste-free management of lighting and other equipment.



Example 3 Offices, Residences and Commercial Facilities

Time Switches can be used to save electricity during the times when lighting and air conditioning are not needed, like at lunchtime and late at night.




Example 4 Agriculture and Livestock

Time Switches can be used to automatically supply food and water at appropriate times each day, to increase working efficiency.



Detailed consideration is given to users in the form of functions that are helpful in ordinary usage, and designs that simplify maintenance.

Easy Operation Check



A power lamp is located on the front panel, so the user can see at a glance whether the unit is operating or not, thus helping to provide safe use.

Easy Battery Replacement



With conventional time switches, the unit must be removed from its installation location, such as in a distribution panel, to replace the batteries. Panasonic's Time Switch lets you easily replace the batteries from the front panel. This makes maintenance considerably easier.

Preventing Entry of Ants and Other Small Insects




Time Switches are sometimes subject to the entry of ants and other small insects, which can cause malfunctions. Panasonic Time Switches have an airtight construction that prevents this problem for long, trouble-free use.

TB35N, TB36N, TB38N, TB39N

Features
(TB35N, TB36N, TB38N, TB39N)

- 24hour program
- Surface and DIN rail mount
- 300 hours reserve battery (TB38N, 39N)
- *Battery exchange from the front side.
- 96 operations per day
- Minimum setting interval is 15 minutes




Applicable Installation Type	Indoor Use			
	Daily			
Series	TB35N series	TB36N series	TB38N series	TB39N series
Item No.	TB35809NE5 (220-240V AC 50Hz)	TB36809NE5 (220-240V AC 50Hz)	TB38809NE7 (220-240V AC 50Hz)	TB39809NE7 (220-240V AC 50Hz)
Drive Method	AC Motor		Quartz Motor	
Power Failure Backup Time	300 hours		300 hours	
Time Precision	Same as AC frequency		±15 sec/month(at 25°C)	
Circuit Configuration	Same Circuit	Separate Circuit	Same Circuit	Separate Circuit
Switch Construction	Single Pole, Single Through (1a Contact)	Single Pole, Double Through (1c Contact)	Single Pole, Single Through (1a Contact)	Single Pole, Double Through (1c Contact)
Load Capacity	250V AC 20A			
Resistive Load	250V AC 10A			
Incandescent Lamp Load	250V AC 12A			
Inductive Load(cos φ 0.7→0.6)	220V AC 1500W			
Motor Load(cos φ 0.7→0.6)	15 minutes			
Minimum Setting Interval	96 operations			
No. of On/Off Operation				

TB11N, TB17N

Features (TB11N, TB17N)

- 24hour program
- On/Off operations are set with separated pins
- With a manual On/Off switch
- 300 hours reserve battery(TB11N)
- *Battery exchange from the front side.




Applicable Installation Type	Indoor Use	
	Daily	
Series	TB17N series	TB11N series
Item No.	TB178NE5 (220-240V AC 50Hz)	TB118NE7 (220-240V AC 50Hz)
Drive Method	AC Motor	Quartz Motor
Power Failure Backup Time	300 hours	
Time Precision	Same as AC frequency	
Circuit Configuration	Same Circuit	
Switch Construction	Single Pole, Single Through (1a Contact)	
Load Capacity	250V AC 15A	
Resistive Load	250V AC 15A	
Incandescent Lamp Load	250V AC 12A	
Inductive Load(cos φ 0.7→0.6)	220V AC 1500W	
Motor Load(cos φ 0.7→0.6)	30 minutes	
Minimum Setting Interval		
No. of On/Off Operation	96 operations	

TB35N, TB38N Steel Box Type

Features (TB35N, TB38N)

- With robust steel box
- 24hour program
- Surface mount
- 300 hours reserve battery(TB38N)
- *Battery exchange from the front side.
- 96 operations per day
- Minimum setting interval is 15 minutes



Applicable Installation Type	Indoor Use	
	Daily	
Series	TB35N series	TB38N series
Item No.	TB358NE5 (220-240V AC 50Hz)	TB388NE7 (220-240V AC 50Hz)
Drive Method	AC Motor	Quartz Motor
Power Failure Backup Time	300 hours	
Time Precision	Same as AC frequency	
Circuit Configuration	Same Circuit	
Switch Construction	Single Pole, Single Through (1a Contact)	
Load Capacity	250V AC 20A	
Resistive Load	250V AC 10A	
Incandescent Lamp Load	250V AC 12A	
Inductive Load(cos φ 0.7→0.6)	220V AC 1500W	
Motor Load(cos φ 0.7→0.6)	15 minutes	
Minimum Setting Interval	96 operations	
No. of On/Off Operation		


AUTOMATIC TIME SWITCH

TB43N Plastic Box Type



Features (TB43N)

- 24hour program
- Surface mount
- Weatherproof type (IP53)
- 300 hours reserve battery (TB43N)
- *Battery exchange from the front side.




Applicable Installation		Outdoor & Indoor Use
Type		Daily
Series		TB43N Series
Item No.		TB43NE7 (220-240V AC 50-60Hz)
Drive Method		Quartz Motor
Power Failure Backup Time		300 hours
Time Precision		±15 sec/month(at 25°C)
Circuit Configuration		Separate Circuit
Switch Construction		Single Pole, Single Through (1a Contact)
Load Capacity	Resistive Load	250V AC 20A
	Incandescent Lamp Load	250V AC 10A
	Inductive Load(cos φ 0.7→0.6)	250V AC 12A
	Motor Load(cos φ 0.7→0.6)	220V AC 1500W
	Minimum Setting Interval	15 minutes
No. of On/Off Operation		96 operations

TB62 DIN Rail Mount Digital Type



Features (TB62)

- Digital type
- Weekly type
- 6 years reserve battery
- With a manual On / Off button
- Possible to lock the manual button
- Holiday setting function
- Manual ±1 hour changeover function
- DIN 2P module




Applicable Installation		Indoor Use	
Type		Weekly	
Series		TB62 series	
Item No.		TB621018A7(1circuit) (220-240V AC 50-60Hz)	TB622018A7(2circuits) (220-240V AC 50-60Hz)
Drive Method		Electronic	
Power Failure Backup Time		6 years	
Time Precision		±15 sec/month(at 25°C)	
Circuit Configuration		Separate Circuit	
Switch Construction		Single Pole, Double Through (1c Contact)	
Load Capacity	Resistive Load	250V AC 16A	
	Inductive Load(cos φ ≥ 0.6)	250V AC 8A	
	Minimum Setting Interval	1 minute	
	No. of On/Off Operation	50 operations [On/Off 25 sets]/circuit	

TB556, TB563 DIN Rail Mount Type



Features (TB556, TB563)

- 24hour program (TB556)
- Weekly program (TB563)
- 300 hours reserve battery (TB556, 563)
- With robust metal setting pins
- DIN 3P module




Applicable Installation		Indoor Use	
Type		Daily	Weekly
Series		TB556 series	TB563 series
Item No.		TB5560187N (220-240V AC 50-60Hz)	TB5630187N (220-240V AC 50-60Hz)
Drive Method		Quartz Motor	
Power Failure Backup Time		300 hours(at 25°C)	
Time Precision		±15 sec/month(at 25°C)	
Circuit Configuration		Separate Circuit	
Switch Construction		Single Pole, Double Through (1c Contact)	
Load Capacity	Resistive Load	250V AC 16A	
	Inductive Load(cos φ ≥ 0.6)	250V AC 3A	
	Minimum Setting Interval	15 minutes	2 hours
	No. of On/Off Operation	96 operations	84 operations

TB21



Features (TB21)

- Easy setting with a mode change switch
- High capacity
- Resistive load : 30A, Inductive load (cos φ=0.6):12A
- 24hours program(TB2118) / Weekly program(TB2128)
- Surface and reserve battery
- 5 years reserve battery




Applicable Installation		Indoor Use	
Type		Daily	Weekly
Series		TB21 series	
Item No.		TB2118E7 (220VAC 50-60Hz)	TB2128E7 (220VAC 50-60Hz)
Drive Method		Electronic	
Power Failure Backup Time		5 years	
Time Precision		±15 sec/month (at 25°C)	
Circuit Configuration		Same circuit (voltage contact output)	
Switch Construction		Single pole, single through (1a Contact)	
Load Capacity	Resistive Load(cos φ=1)	240V AC 30A	
	Inductive Load(cos φ=0.6)	240V AC 12A	
	Minimum Setting Interval	1 minute	
	No. of On/Off Operation	4 operations(On/Off 2sets)	16 operations(On/Off 8sets)

TB27 DIN 72 Panel Mount Type



Features (TB27)


- Easy setting with a mode change switch
- 24hours program(TB271018) / Weekly program(TB272018)
- DIN 72 panel mounting
- 5 years reserve battery



Applicable Installation		Indoor Use	
Type		Daily	Weekly
Series		TB27 series	
Item No.		TB271018E7 (220VAC 50-60Hz)	TB272018E7 (220VAC 50-60Hz)
Drive Method		Electronic	
Power Failure Backup Time		5 years	
Time Precision		±15 sec/month (at 25°C)	
Circuit Configuration		Separate Circuit (no voltage contact output)	
Switch Construction		Single Pole, Double Through (1c Contact)	
Load Capacity	Resistive Load(cos φ=1)	240V AC 16A	
	Inductive Load(cos φ ≥ 0.6)	240V AC 9A	
	Minimum Setting Interval	1 minute	
	No. of On/Off Operation	4 operations(On/Off 2sets)	16 operations(On/Off 8sets)

Compact and high breaking capacity of
Circuit Breaker

MCB/RCBO-DIN TYPE



MCB BD-63R (DIN Type)

Type	BD-63								
Poles & Elements	1P1E		2P2E		3P3E		4P4E		
Instantaneous									
Type	6A	BBD1061CNV	BBD1061DNV	BBD2062CNV	BBD2062DNV	BBD3063CNV	BBD3063DNV	BBD4064CNV	BBD4064DNV
	10A	BBD1101CNV	BBD1101DNV	BBD2102CNV	BBD2102DNV	BBD3103CNV	BBD3103DNV	BBD4104CNV	BBD4104DNV
	16A	BBD1161CNV	BBD1161DNV	BBD2162CNV	BBD2162DNV	BBD3163CNV	BBD3163DNV	BBD4164CNV	BBD4164DNV
	20A	BBD1201CNV	BBD1201DNV	BBD2202CNV	BBD2202DNV	BBD3203CNV	BBD3203DNV	BBD4204CNV	BBD4204DNV
	25A	BBD1251CNV	BBD1251DNV	BBD2252CNV	BBD2252DNV	BBD3253CNV	BBD3253DNV	BBD4254CNV	BBD4254DNV
	32A	BBD1321CNV	BBD1321DNV	BBD2322CNV	BBD2322DNV	BBD3323CNV	BBD3323DNV	BBD4324CNV	BBD4324DNV
	40A	BBD1401CNV	BBD1401DNV	BBD2402CNV	BBD2402DNV	BBD3403CNV	BBD3403DNV	BBD4404CNV	BBD4404DNV
	50A	BBD1501CNV	BBD1501DNV	BBD2502CNV	BBD2502DNV	BBD3503CNV	BBD3503DNV	BBD4504CNV	BBD4504DNV
	63A	BBD1631CNV	BBD1631DNV	BBD2632CNV	BBD2632DNV	BBD3633CNV	BBD3633DNV	BBD4634CNV	BBD4634DNV
Rated Voltage Interrupting Current	AC240/415V 6kA		AC415V 6kA AC240V 10kA		AC415V 6kA		AC415V 6kA		
Weight	6A~32A 0.1kg 40A~63A 0.13kg		6A~32A 0.2kg 40A~63A 0.26kg		6A~32A 0.3kg 40A~63A 0.39kg		6A~32A 0.4kg 40A~63A 0.52kg		

MCB BD-63 Conform to the IEC 60898 standards.

MCB BD-125 (DIN Type)

Type	BD-125								
Poles & Elements	1P1E		2P2E		3P3E		4P4E		
Instantaneous	C	D	C	D	C	D	C	D	
Type	80A	BBD108011C	BBD108011D	BBD208021C	BBD208021D	BBD308031C	BBD308031D	BBD408041C	BBD408041D
	100A	BBD110011C	BBD110011D	BBD210021C	BBD210021D	BBD310031C	BBD310031D	BBD410041C	BBD410041D
	125A	BBD112511C		BBD212521C		BBD312531C		BBD412541C	
Rated Voltage Interrupting Current	AC230V 10kA		AC400V 10kA		AC400V 10kA		AC400V 10kA		
Weight	0.18kg		0.36kg		0.54kg		0.72kg		



MCB BD-125 Conform to the IEC 60947-2 standards.

RCBO BDE-63R (DIN Type)


Type	BDE-63R					
Poles & Elements	2P1E					
Instantaneous	C		D		D	
6A	BBDE20631CNV	BBDE20631DNV	BBDE20641CNV	BBDE20641DNV	BBDE20651CNV	BBDE20651DNV
10A	BBDE21031CNV	BBDE21031DNV	BBDE21041CNV	BBDE21041DNV	BBDE21051CNV	BBDE21051DNV
16A	BBDE21631CNV	BBDE21631DNV	BBDE21641CNV	BBDE21641DNV	BBDE21651CNV	BBDE21651DNV
20A	BBDE22031CNV	BBDE22031DNV	BBDE22041CNV	BBDE22041DNV	BBDE22051CNV	BBDE22051DNV
25A	BBDE22531CNV	BBDE22531DNV	BBDE22541CNV	BBDE22541DNV	BBDE22551CNV	BBDE22551DNV
32A	BBDE23231CNV	BBDE23231DNV	BBDE23241CNV	BBDE23241DNV	BBDE23251CNV	BBDE23251DNV
40A	BBDE24031CNV	BBDE24031DNV	BBDE24041CNV	BBDE24041DNV	BBDE24051CNV	BBDE24051DNV
50A	BBDE25031CNV	BBDE25031DNV	BBDE25041CNV	BBDE25041DNV	BBDE25051CNV	BBDE25051DNV
63A	BBDE26331CNV	BBDE26331DNV	BBDE26341CNV	BBDE26341DNV	BBDE26351CNV	BBDE26351DNV
Rated Voltage	AC240V 6kA					
Rated Voltage (Application Voltage Range)	187V-264V					
Rated residual operating current	30mA		100mA		300mA	
Rated residual non-operating current	15mA		50mA		150mA	
Weight	6A~32A 0.2kg 40A~63A 0.23kg					

RCBO Conform to the IEC 601009 standards.


•MCB (BD-40-63 Series)





Operating time characteristics curve (Ambient temperature 30°C) (6A~63A)





•RCBO (BDE-40-63 Series)



•MCB (BD-125 Series)



Operating time curve (Standard temperature 30°C)



Complete range of products with a compact design.

SAFETY BREAKER EARTH LEAKAGE BREAKER



Earth Leakage Breaker Small Type

Dimension(mm) Appearance Mounting pitch (unit:mm)			Unit: mm
Type	BJS3020NA2	BJS3030NA2	
Rated current (A)	30A		
Number of poles & elements	2P0E		
Rated voltage (AC)	AC120-240V		
Residual operating current (mA)	15mA	30mA	
Residual non-operation current (mA)	7.5mA	15mA	
Rated short-time current	1.5kA		
Phase and wiring configuration	1Ø2W		
Operating time	Within 0.1 sec.		
Handle type	Standard		
Standard Terminal specifications	Solderless terminals (with strap) ø1.6-ø2.6 5.5 - 8 mm ²	Note: When using electrical appliance wire or other stranded wire [1.25 - 3.5 mm ²] use bar lug terminals. WV2500 1.25 - 2 mm ² (WV2501 2.0 - 3.5 mm ²)	Tightening torque: 1.6-2.0N·m 16.3-20.4kgf·cm
Connecting method	For direct installation of electrical wiring		
Weight	0.1 kg		
Overload current tripping mechanism	None		
Approval standard	-		


Note: 1. "Rated short-time current" means that although short-circuit protection is not possible, the internal circuitry and conductors can withstand 1.5kA for 0.02 seconds.
 2. Ambient temperature range for usage: -10°C to +50°C.
 3. Disconnect electrical wiring before measuring insulation resistance between wires.

Dimension(mm) Appearance Mounting pitch (unit:mm)									Unit: mm
Type	BJS1512S	BJS1522S	BJS1532S	BJS2012S	BJS2022S	BJS2032S	BJS3012S	BJS3022S	BJS3032S
Rated current (A)	15A			20A			30A		
Number of poles & elements	2P2E								
Rated voltage (AC)	AC100-240V								
Residual operating current (mA)	10mA	15mA	30mA	10mA	15mA	30mA	10mA	15mA	30mA
Residual non-operation current (mA)	6mA	7.5mA	15mA	6mA	7.5mA	15mA	6mA	7.5mA	15mA
Rated interrupting capacity (Rated short-time current)	1.5kA								
Phase and wiring configuration	1Ø2W, 1Ø3W								
Operating time	Within 0.1 sec.								
Handle type	Long								
Terminal specifications	Solderless terminals (with strap) ø1.6-ø2.6 5.5 - 8 mm ²	Note: When using electrical appliance wire or other stranded wire [1.25 - 3.5 mm ²] use bar lug terminals. WV2500 1.25 - 2 mm ² (WV2501 2.0 - 3.5 mm ²)						Tightening torque: 1.6-2.0N·m 16.3-20.4kgf·cm	
Connecting method	For direct installation of electrical wiring								
Weight	0.09kg								
Overload current tripping mechanism	Thermal operation								


Note: 1. Ambient temperature range for usage: -10°C to +50°C.
 2. Disconnect electrical wiring before measuring insulation resistance between wires.

Small Type



Temperature compensation curves



Operating characteristics curves (with O.C.)




Earth Leakage Breaker J Type

Dimension(mm) Appearance Mounting pitch (unit:mm)							
Type	BJJ230308	BJJ215228	BJJ215328	BJJ220228	BJJ220328	BJJ230228	BJJ230328
Rated current (A)	30A	15A		20A		30A	
Number of poles & elements	2P0E		2P2E				
Rated voltage (AC)	AC120-240V						
Residual operating current (mA)	30mA	15mA	30mA	15mA	30mA	15mA	30mA
Residual non-operation current (mA)	15mA	7.5mA	15mA	7.5mA	15mA	7.5mA	15mA
Rated interrupting capacity (Rated short-time current)	[2.5kA]	1.5kA					
Phase and wiring configuration	1Ø2W	1Ø2W, 1Ø3W					
Operating time	Within 0.1 sec						
Leakage indication method	—	Mechanic button					
Terminal specifications	 Solderless terminals (with strap) ø1.6-ø2.6 5.5 - 8 mm ²		Note: When using electrical appliance wire or other stranded wire (1.25 - 3.5 mm ²) use bar lug terminals WV2500 1.25 - 2 mm ² (WV2501 2.0 - 3.5 mm ²)			Tightening torque: 1.6-2.0N·m 16.3-20.4kgf·cm	
Connecting method	For direct installation of electrical wiring						
Weight	0.2kg						
Overload current tripping mechanism	—	Thermal operation					


Note: 1. "Rated short-time current" means that although short-circuit protection is not possible, the internal circuitry and conductors can withstand 1.5kA for 0.02 seconds
 2. Ambient temperature range for usage: -10°C to +50°C
 3. Disconnect electrical wiring before measuring insulation resistance between wires.

J Type



Temperature compensation curves



Operating characteristics curves (with O.C.)




Safety Breaker HB Type

Dimension(mm) Appearance Mounting pitch (unit:mm)			
Number of poles & elements	2P1E		
Type	6A	10A	BS11106TV
	15A	20A	BS1111TV
	30A	40A	BS1112TV
			BS1113TV
			BS1114TV
Rated voltage (AC)	AC 240V 1.0kA (6A) AC 240V 1.5kA (10-15-20-30-40A)		
Terminal specifications	 Solderless terminals (with strap) ø1.6-ø2.6 5.5 - 8 mm ²		
	Note: When using electrical appliance wire or other stranded wire (1.25 - 3.5 mm ²) use bar lug terminals		
Weight	0.07kg		
Structure	Tripping Mechanism	Thermal operation	
	Arc Quenching Method	Natural Quenching	
Capacity	Interrupting Time	10 ms (100%)	
	Passage of short	23 X 10 ³ A ² sec (100%)	


Note: 1. Use 20A for normal branch circuits, and 30A for high capacity dedicated circuits.
 2. Use 15A or less for machine protection, after consideration of its characteristic: inrush current and usual current.
 3. The data in capacity mentioned above are just for your reference, which are PEW's experimental ones.

HB Type

Temperature compensation curves



Operating characteristics curves (with O.C.)



HGC electric interrupting technique is power connection safety design.
Small dimension, high rated interrupting capacity.

GD BREAKER







Circuit Breaker BBW Type

Frame Size		30AF						50AF					
Type		BBW-30			BBW-30C			BBW-50			BBW-50S		
Appearance					DIN rail mountable 						DIN rail mountable 		
Dimensional diagram page													
Number of Poles		2P		3P	2P		3P	2P		3P	2P		3P
Cat. No. & Rated Current [A] (Nominal Ambient Temperature 40oC)		3A	BBW23Y	BBW33Y	3A	BBW23CKY	BBW33CKY	20A	BBW220Y	BBW320Y	5A	BBW251SKY	BBW351SKY
		5A	BBW25Y	BBW35Y	5A	BBW25CKY	BBW35CKY	30A	BBW230Y	BBW330Y	10A	BBW2101SKY	BBW3101SKY
		10A	BBW210Y	BBW310Y	10A	BBW210CKY	BBW310CKY	40A	BBW240Y	BBW340Y	15A	BBW2151SKY	BBW3151SKY
		15A	BBW215Y	BBW315Y	15A	BBW215CKY	BBW315CKY	50A	BBW250Y	BBW350Y	20A	BBW2201SKY	BBW3201SKY
		20A	BBW220Y	BBW320Y	20A	BBW220CKY	BBW320CKY				30A	BBW2301SKY	BBW3301SKY
		30A	BBW230Y	BBW330Y	30A	BBW230CKY	BBW330CKY				40A	BBW240SKY	BBW340SKY
Rated Insulation Voltage [V]		AC 500V		500V		500V		500V		500V		500V	
Rated Interrupting Capacity [sym]		AC 415V		1.5kA		1.5kA		1.5kA		2.5kA		2.5kA	
		AC 200V		2.5kA		2.5kA		2.5kA		10kA		10kA	
		AC 100V		2.5kA		2.5kA		2.5kA		10kA		10kA	
Dimensions 		a		47	70	50	75	47	70	50	75	50	75
		b		96		96		96		96		96	
		c		52		60		52		60		60	
		ca		67.6		75.6		67.6		75.6		75.6	
Weight of Standard Type		0.3kg		0.4kg	0.3kg		0.4kg	0.3kg		0.4kg	0.3kg		0.4kg

Frame Size		60AF						100AF					
Type		BBW-60			BBW-60S			BBW-100			BBW-100S		
Appearance					DIN rail mountable 			DIN rail mountable 					
Dimensional diagram page													
Number of Poles		2P		3P	2P		3P	2P		3P	2P		3P
Cat. No. & Rated Current [A] (Nominal Ambient Temperature 40oC)		3A	BBW232Y	BBW332Y	60A	BBW260SKY	BBW360SKY	20A	BBW2203KY	BBW3203KY	50A	BBW2501SKY	BBW3501SKY
		5A	BBW252Y	BBW352Y				30A	BBW2303KY	BBW3303KY	60A	BBW2601SKY	BBW3601SKY
		10A	BBW2102Y	BBW3102Y				40A	BBW2402KY	BBW3402KY	75A	BBW275SKY	BBW375SKY
		15A	BBW2152Y	BBW3152Y				50A	BBW2502KY	BBW3502KY	100A	BBW2100SKY	BBW3100SKY
		20A	BBW2202Y	BBW3202Y				60A	BBW2601KY	BBW3601 KY			
		30A	BBW2302Y	BBW3302Y				75A	BBW275KY	BBW375KY			
		40A	BBW2401Y	BBW3401Y				100A	BBW2100KY	BBW3100KY			
		50A	BBW2501Y	BBW3501Y									
		60A	BBW260Y	BBW360Y									
Rated Insulation Voltage [V]		AC 500V		500V		500V		500V		600V		600V	
Rated Interrupting Capacity [sym]		AC 415V		2.5kA		2.5kA		5kA		25kA		25kA	
		AC 200V		5kA		10kA		25kA		50kA		50kA	
		AC 100V		5kA		10kA		25kA		50kA		50kA	
Dimensions 		a		47	70	50	75	75	70	60	90	60	90
		b		96		96		96		155		155	
		c		52		60		60		68		68	
		ca		67.6		75.6		75.6		86		86	
Weight of Standard Type		0.3kg		0.4kg	0.3kg		0.4kg	0.5kg		0.5kg	0.8kg		1.2kg




Circuit Breaker BBW Type





Frame Size		150AF			225AF		
Type		BBW-150S			BBW-225		
Appearance							
Dimensional diagram page							
Number of Poles		2P		3P	2P		3P
Cat. No. & Rated Current (A) (Nominal Ambient Temperature 40oC)		125A	BBW2125SKY	BBW3125SKY	125A	BBW21251KY	BBW31251KY
		150A	BBW2150SKY	BBW3150SKY	150A	BBW21501KY	BBW31501KY
					175A	BBW2175KY	BBW3175KY
					200A	BBW2200KY	BBW3200KY
					225A	BBW2225KY	BBW3225KY
Rated Insulation Voltage (V)		600V			600V		
JIS Rated Interrupting Capacity (sym)		415V		25kA	415V		25kA
		200V		50kA	200V		50kA
		100V		50kA	100V		50kA
Dimensions		a		60	90		105
		b		155		165	
		c		68		86	
		ca		86		110	
		Weight of Standard Type		0.8kg		1.2kg	1.4kg

Frame Size		250AF			400AF		
Type		BBW-250			BBW-400		
Appearance							
Dimensional diagram page							
Number of Poles		2P		3P	2P		3P
Cat. No. & Rated Current (A) (Nominal Ambient Temperature 40oC)		250A	BBW2250KY	BBW3250KY	250A	BBW22501KY	BBW32501KY
					300A	BBW23001KY	BBW33001KY
					350A	BBW2350KY	BBW3350KY
					400A	BBW2400KY	BBW3400KY
Rated Insulation Voltage (V)		600V			600V		
JIS Rated Interrupting Capacity (sym)		415V		25kA	415V		25kA
		200V		50kA	200V		50kA
		100V		50kA	100V		50kA
Dimensions		a		105	140(148)		140(148)
		b		165		260(349)	
		c		86		103	
		ca		110		135	
		Weight of Standard Type		1,4kg		1,6kg	4,0kg

- Note 1) Install breakers with BBW-30, BBW-30C, BBW-50, BBW-50S, BBW-60, BBW-60S, BBW-100 within $\pm 10^\circ$ of perpendicular.
- Note 2) When using 3-pole breaker for 1 ϕ 3W, neutral conductor cannot have open-phase protection.
- Note 3) Please select conformed wire which suit to rated current.
- Note 4) Dimensions with () is the measurement including bar terminal.

Earth Leakage Breaker BKW Type

Frame Size	30AF				50AF					
Type	BKW-30		BKW-30C		BKW-50					
Appearance			DIN rail mountable 							
Dimensional diagram page										
Phase and Wiring Configuration	1Ø2W		3Ø3W 1Ø3W		1Ø2W		3Ø3W 1Ø3W			
Number of Poles	2P		3P		2P		3P			
Cat. No. & Rated Current (A) (Nominal Ambient Temperature 40oC)	3A	BKW23□Y	BKW33□Y	5A	BKW25□CKY	BKW35□CKY	20A	BKW220□1Y	BKW320□1Y	
	5A	BKW25□Y	BKW35□Y	10A	BKW210□CKY	BKW310□CKY	30A	BKW230□1Y	BKW330□1Y	
	10A	BKW210□Y	BKW310□Y	15A	BKW215□CKY	BKW315□CKY	40A	BKW240□Y	BKW340□Y	
	15A	BKW215□Y	BKW315□Y	20A	BKW220□CKY	BKW320□CKY	50A	BKW250□Y	BKW350□Y	
	20A	BKW220□Y	BKW320□Y	30A	BKW230□CKY	BKW330□CKY				
	30A	BKW230□Y	BKW330□Y							
Rated Voltage (AC V)	100-200V Dual use				100-200V Dual use					
High Speed Type	Rated Sensitivity Current (mA)		15,30		15,30		15,30,100		15 (below 30A), 30,100 (above 40A)	
	Thời gian chấp hành (giây)		0.1		0.1		0.1		0.1	
Leakage Indication Method		Mechanical button				Mechanical button				
Rated Interrupting Capacity (sym)	AC	415V	—		—		—		—	
		200V	2.5kA		2.5kA		2.5kA		2.5kA	
		100V	2.5kA		2.5kA		2.5kA		2.5kA	
Dimensions		a	70		50		75		70	
		b	96		96		96		96	
		c	52		60		60		52	
		ca	67.6		75.6		75.6		67.6	
Weight of Standard Type		0.4kg		0.5kg		0.4kg		0.5kg		





Frame Size	100AF				150AF								
Type	BKW-100		BKW-100S		BKW-150S								
Appearance			DIN rail mountable 										
Dimensional diagram page													
Phase and Wiring Configuration	1Ø2W		3Ø3W 1Ø3W		1Ø2W		3Ø3W 1Ø3W		1Ø2W		3Ø3W 1Ø3W		
Number of Poles	2P		3P		2P		3P		2P		3P		
Cat. No. & Rated Current (A) (Nominal Ambient Temperature 40oC)	60A	BKW260□1KY	BKW360□1KY	40A	—	BKW340□2SKY	125A	BKW2125□SKY	BKW3125□SKY				
	75A	BKW275□KY	BKW375□KY	50A	—	BKW350□2SKY	150A	BKW2150□SKY	BKW3150□SKY				
	100A	BKW2100□KY	BKW3100□KY	60A	BKW260□1SKY	BKW360□1SKY							
				75A	BKW275□SKY	BKW375□SKY							
			100A	BKW2100□SKY	BKW3100□SKY								
Rated Voltage (AC V)	100-200V Dual use				100-200V Dual use		100-200V Dual use		100-200V Dual use		100-200V Dual use		
High Speed Type	Rated Sensitivity Current (mA)		30,100-200-500		30,100-200-500		30,100-200-500		30,100-200-500		30,100-200-500		
	Operating Time (sec.)		0.1		0.1		0.1		0.1		0.1		
Leakage Indication Method		Mechanical button				Mechanical button							
Rated Interrupting Capacity (sym)	AC	415V	—		—		—		—		—		
		200V	25kA		50kA		50kA		50kA		50kA		
		100V	25kA		50kA		50kA		50kA		50kA		
Dimensions		a	75		90		90		90		90		
		b	96		155		155		155		155		
		c	60		68		68		68		68		
		ca	75.6		86		86		86		86		
Weight of Standard Type		0.6kg		0.6kg		1.1kg		1.2kg		1.1kg		1.2kg	

■ Rated Voltage Applicable Range

Rated voltage	Applicable Voltage Range
100-200V dual use	80-242V

■ Cat. No. □ Depends on the sensitivity current
2:15mA 3:30mA 4:100mA 9:100-200-500mA Switchover

Earth Leakage Breaker BKW Type


50AF				60AF				
BKW-50C		BKW-50S		BKW-60		BKW-60S		
DIN rail mountable		DIN rail mountable		DIN rail mountable		DIN rail mountable		
								
1Ø2W	3Ø3W 1Ø3W	1Ø2W	3Ø3W 1Ø3W	1-2W	3-3W 1-3W	1-2W	3-3W 1-3W	
2P		3P		2P		3P		
15A	BKW215□1CKY	BKW315□1CKY	15A	BKW215□1SKY	BKW315□1SKY	15A	BKW215□Y	BKW315□Y
20A	BKW220□1CKY	BKW320□1CKY	20A	BKW220□1SKY	BKW320□1SKY	20A	BKW220□Y	BKW320□Y
30A	BKW230□CKY	BKW330□CKY	30A	BKW230□1SKY	BKW330□1SKY	30A	BKW230□Y	BKW330□Y
40A	BKW240□CKY	BKW340□CKY	40A	BKW240□SKY	BKW340□SKY	40A	BKW240□Y	BKW340□Y
50A	BKW250□CKY	BKW350□CKY	50A	BKW250□SKY	BKW350□SKY	50A	BKW250□Y	BKW350□Y
				60A	BKW260□Y	BKW360□Y		
100-200V Dual use		100-200V Dual use		100-200V Dual use		100-200V Dual use		
15,30		15,30,100 (2P) 100-200-500(3P)		15 (dưới 30A), 30,100 (trên 40A)		30,100 (2P) 100-200-500 (3P)		
0.1		0.1		0.1		0.1		
Mechanical button		Mechanical button		Mechanical button		Mechanical button		
—		—		—		—		
2.5kA		10kA		5kA		10kA		
2.5kA		10kA		5kA		10kA		
50	75	50	75	70	50	75		
96		96		96		96		
60		60		52		60		
75.6		75.6		67.6		75.6		
0.4kg	0.5kg	0.4kg	0.5kg	0.4kg	0.5kg	0.4kg	0.5kg	

225AF		250AF		400AF	
BKW-225		BKW-250		BKW-400	
					
3Ø3W 1Ø3W		3Ø3W 1Ø3W		3Ø3W 1Ø3W	
3P		3P			
125A	BKW3125□1KY	250A	BKW3250□KY	250A	BKW3250□1KY
150A	BKW3150□1KY			300A	BKW3300□1KY
175A	BKW3175□KY			350A	BKW3350□KY
200A	BKW3200□KY			400A	BKW3400□KY
225A	BKW3225□KY				
100-200V Dual use		100-200V Dual use		100-200-415V Dual use	
30,100-200-500		30,100-200-500		30,100-200-500	
0.1		0.1		0.1	
Mechanical button		Mechanical button		Mechanical button	
—		—		25kA	
50kA		50kA		50kA	
50kA		50kA		50kA	
105		105		140 (148)	
165		165		260 (349)	
86		86		103	
110		110		135	
1.8kg		1.8kg		4.8kg	


- Note 1) When using 3-pole breaker for 1 Ø 3W configuration apply voltage to two end terminal. In this case neutral conductor cannot have open-phase protection.
- Note 2) When using on frequency control circuit (inverter) be sure to install breaker on primary side of inverter.
- Note 3) Breaker can be connected in reverse. However do not reverse connect 400 when used on a 415V circuit.
- Note 4) Install BKW-30, BKW-30C, BKW-50, BKW-50C, BKW-50S, BKW-60, BKW-60S, BKW-100 within ±10o of perpendicular.
- Note 5) Please select conformed wire which suit to related current.
- Note 6) Dimensions with () is the measurement including bar terminal.

Dimensional diagram


1 BBW-30, BBW-50, BBW-60, BKW-30, BKW-50, BKW-60



Operating characteristic curves



Temperature compensation curve




Note: The method used to detect overcurrent is electromagnetic, so temperature compensation takes the form of an increase or decrease relative to the lead-out time and there is no change in the rated current.


Standard included accessories (frontconnecting type)

Mounting screws	small round-head screws M4 x 0.7 x 35
-----------------	---------------------------------------


2 BBW-30C, BBW-50S, BBW-60S, BKW-30C, BKW-50C, BKW-50S, BKW-60S



Operating characteristic curves



Temperature compensation curve




Note: The method used to detect overcurrent is electromagnetic, so temperature compensation takes the form of an increase or decrease relative to the lead-out time and there is no change in the rated current.


Standard included accessories (frontconnecting type)

Mounting screws	small round-head screws M4 x 0.7 x 34
Insulation barrier	2 pole: 1, 3 pole: 2


3 BBW-100, BKW-100



Operating characteristic curves



Temperature compensation curve




Note: The method used to detect overcurrent is electromagnetic, so temperature compensation takes the form of an increase or decrease relative to the lead-out time and there is no change in the rated current.


Standard included accessories (frontconnecting type)

Mounting screws	small round-head screws M4 x 0.7 x 34
Insulation barrier	2 pole: 1, 3 pole: 2


4 BBW-100S, BKW-100S



Operating characteristic curves



Temperature compensation curve




Note: The method used to detect overcurrent is electromagnetic, so temperature compensation takes the form of an increase or decrease relative to the lead-out time and there is no change in the rated current.


Standard included accessories (frontconnecting type)

Mounting screws	small round-head screws M4 x 0.7 x 35
Insulation barrier	2 pole: 1, 3 pole: 2


5 BBW-150S, BKW-150S



Operating characteristic curves




Temperature compensation curve




Standard included accessories (front-connecting type)

Mounting screws	small round-head screws M4 x 0.7 x 35
Insulation barrier	2 pole: 1, 3 pole: 2


6 BBW-225, BBW-250, BKW-225, BKW-250



Operating characteristic curves




Temperature compensation curve




Standard included accessories (front-connecting type)


Mounting screws	small round-head screws M4 x 0.7 x 35
Insulation barrier	2 pole: 2, 3 pole: 4



Operating characteristic curves




Temperature compensation curve




Standard included accessories (front-connecting type)

Mounting screws	small round-head screws M6 x 1.0 x 100
Insulation barrier	2 pole: 2, 3 pole: 4

Operating characteristic curves




Temperature compensation curve



Cautions for the Use of Breakers


Cautions concerning the operating environment




Keep humidity at or below 85%RH.

Ambient temperature: -10oC to +60oC
 Note: Range is -10oC to +50oC for residential panel breakers
 Relative humidity: 45% to 85%
 Maximum elevation: 2000 m above sea level

- If temperature exceeds 40oC, refer to the current rating table when specifying current rating of the breaker.
- If installed outdoors or in a location exposed to moisture, the breaker must be housed in a suitable enclosure. (Do not use in locations where dew or other condensation will form.)
- It is recommended that the breaker be installed in a location not exposed to direct sunlight, as this can result in incorrect operation.



- The breaker must be installed in a suitable enclosure for use in a location exposed to dirt or dust, etc.
- Avoid installation in locations with acidic or alkaline atmospheres, such as chemical plants or breweries, etc.
- Avoid installation in locations exposed to rainwater or water spray.
- Avoid installation in locations exposed to vibration, shock, or impact, etc.




Cautions concerning installation

Although perpendicular installation of breakers is recommended, installation is also possible as indicated below.

Overload current tripping method	Magnetic	Thermal Thermal and magnetic
	Within ±10o of perpendicular	No restrictions on installation direction


Installation orientation for breakers with magnetic trip.



Side view: 10°±10° Perpendicular

Front view: Power supply side, Horizontal plane, Power supply side

* Do not install on a floor or ceiling.




When drilling holes or stripping insulation, cover the breaker with masking tape or paper to prevent sawdust and other foreign matter from entering the breaker mechanism.

Cautions concerning connections

1. Connection of electrical wires

- When connecting stranded wire, do not solder or bind the ends of the wire.
- Tighten the electrical wires securely. If the wires are not connected securely, overheating of terminals could cause a fire. If the neutral pole of a single-phase, three-wire breaker is not connected securely, an incorrect voltage could cause damage to the load.
- Do not lubricate the screws. Lubrication will reduce the friction of the screws and make it easier for them to come loose, which can result in overheating.
- Lubricating oil can also cause excessive stress on the screws, even when tightened to the specified torque, thus resulting in damage to the screws.
- Connect wires so that they run parallel.
- Select a wire size suitable to carry the rated current of the load.



- When connecting stranded wire, separate the strands before inserting them into the terminal.



- When connecting two or more wires directly, avoid connecting in any combination other than those listed below. No more than three wires. For stranded wire in particular, use a lug terminal wherever possible. Please use solderless terminal in case of M6.
- Possible wire combinations when connecting two wires.

	Single wire	Stranded wire
M5	ø1.6 & ø1.6 mm	3.5 mm ² & 3.5 mm ²
	ø1.6 & ø2.0 mm	3.5 mm ² & 5.5 mm ²
	ø1.6 & ø2.6 mm	3.5 mm ² & 8 mm ²
	ø2.0 & ø2.0 mm	5.5 mm ² & 5.5 mm ²
	ø2.0 & ø2.6 mm	5.5 mm ² & 8 mm ²
	ø2.6 & ø2.6 mm	8 mm ² & 8 mm ²
	ø2.6 & ø2.6 mm	8 mm ² & 14 mm ²

Maintenance and inspection

After usage of breakers begins, perform regular inspections to maintain rated performance and prevent failures.

Recommended replacement frequency
 Wiring breakers: 15 years
 Leakage breakers: 15 years
 Source: "Investigation related to recommended replacement frequency for low-voltage equipment"
 Japan Electrical Manufacturers' Association

Regular inspection guidelines


Environment	Regular inspection guideline (10-year period following installation)
Location where air is always clean and dry	Once every 2 to 3 years
Indoor location with little dust and no corrosive gases	Once each year
Location with little dust where air contains impurities (0.1 ppm or greater) such as sulfurous acid, hydrogen sulfide, salt, or high humidity	Once every 6 months

Type	Inspection location	Inspection item	Notes
Common	Top of breaker, power supply side	Check for problems such as dust accumulation and oil buildup.	After confirming that no power supply voltage is being applied, use cleaner to wipe away any dust and then wipe away any remaining grime with a clean, dry rag.
	Exhaust opening	Check for evidence indicating that the breaker has been tripped by overcurrent in the past.	If there is clear evidence of overvoltage, such as black soot or melted metal, replace the breaker with a new.
	Terminals	<ul style="list-style-type: none"> Tighten terminal screws to ensure they are not loose. Check for evidence indicating abnormally high temperatures or damage due to humidity or corrosive gas. 	<ul style="list-style-type: none"> Apply appropriate torque when tightening. Sight discoloration of the terminal area is not a problem. If the discoloration is extreme or if the insulation is damaged, however, replace the breaker with a new one.
	Handle	Confirm that the breaker closes and opens smoothly.	If the breaker is normally closed, open and close it a few times to ensure stable contact resistance and prevent overheating.
	Body	Check to make sure that the temperature of the breaker body does not exceed 70°C and no smoke or odor is produced when electrical current is flowing.	If there is anything amiss, replace the breaker with a new one.
ELB	Test button	Use the test button to confirm that the breaker operates properly. (When not testing the breaker, avoid using the test button to switch the handle to the off position.)	<ul style="list-style-type: none"> Test the breaker about once each month. When performing operation inspections, also measure using a leak checker to ensure that the current sensitivity and operation time are normal.

■ Cautions when measuring insulation resistance


- For the places marked with a triangle (△) in the table at right, measuring the insulation resistance will not cause damage, but the insulation resistance meter reading will be approximately zero due to the internal circuit. To measure the insulation resistance between wires, first remove the wires from the terminals.
- For leakage breakers or breakers with leakage alarms equipped with the meg measurement switch as an internal function, measurement is possible if the handle is the off position.
- After reconnecting wires, switch the handle to the on position and press the test button to confirm the breaker is operating properly.

Handle position	Insulation resistance measurement (500 V or less)	
	On	Off
Between charger and ground	○	○
Between left and middle poles and between middle and right poles	○	○
	AA breaker with neutral open-phase protection	△
Between left and right poles	Power supply side	△
	Load side	△
Between power supply and load terminals	—	○




Great protection against corrosion and high durability
Labor-saving in installing pipe

WHITE CONDUIT



Superior galvanizing by in-line hot-dip process for greater protection against corrosion. Finished with durable and clear anti-corrosion coating for higher protection outside and higher grade epoxy coating inside.

CROSS-SECTIONAL VIEW OF Panasonic WHITE CONDUIT



Underwriters
Laboratories Inc.®

Features

1. Easy and accurate bending

Panasonic White Conduit is made of high quality steel and processed by high frequency induction welding to prevent cracking when bend.

2. Easy wire pushing and pulling

The high-grade stove epoxy resin coating on the inside wall makes wire-pulling easy, and protects against corrosion.

3. Easy coupling and fast installation

Precise, sharp threads cut by automated machinery mean fast and easy installation. Precise thread also makes our conduit virtually moisture-tight.

4. High corrosion resistance

Pure zinc coating on the exterior wall and stove epoxy resin finish on the inside protects WHITE CONDUIT from corrosion, even by harsh chemicals and sea air.

5. Uniform quality

Flat steel is rolled, zinc-coated and threaded in one continuous automated process for uniform high quality.

WHITE CONDUIT

ANSI/UL

EMT (Electrical Metallic Tubing)

Listed by "UL" File No.E-44051

UL 797

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWE012Y	1/2	17.93	1.02	3,048	1.46	10	500
DWE034Y	3/4	23.42	1.18	3,048	2.21	10	300
DWE100Y	1	29.54	1.37	3,048	3.08	5	200
DWE114Y	1-1/4	38.35	1.57	3,048	4.74	5	125
DWE112Y	1-1/2	44.20	1.57	3,048	5.49	5	100
DWE200Y	2	55.80	1.57	3,048	6.99	3	75
DWE212Y	2-1/2	73.03	1.74	3,048	9.80		40
DWE300Y	3	88.90	1.74	3,048	11.99		30
DWE312Y	3-1/2	101.60	1.97	3,048	15.80		20
DWE400Y	4	114.30	1.99	3,048	17.81		20

IMC (Intermediate Metal Conduit)

Listed by "UL" File No.E-62193

UL 1242

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWM012Y	1/2	20.70	1.79	3,030	2.85	10	300
DWM034Y	3/4	26.14	1.90	3,030	3.94	10	250
DWM100Y	1	32.77	2.16	3,025	5.23	5	125
DWM114Y	1-1/4	41.59	2.16	3,025	7.48	3	75
DWM112Y	1-1/2	47.81	2.29	3,025	8.67	3	75
DWM200Y	2	59.93	2.41	3,025	11.65	—	50
DWM212Y	2-1/2	72.56	3.56	3,010	18.71	—	40
DWM300Y	3	88.29	3.56	3,010	22.87	—	30
DWM312Y	3-1/2	100.86	3.56	3,005	26.43	—	20
DWM400Y	4	113.40	3.56	3,005	29.84	—	15

RSC (Rigid Steel Conduit)

Listed by "UL" File No. E-157617


UL 6

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWR012Y/ZY	1/2	21.34	2.64	3,030	3.75	10	300
DWR034Y/ZY	3/4	26.67	2.72	3,030	4.96	10	250
DWR100Y/ZY	1	33.40	3.20	3,025	7.33	5	125
DWR114Y/ZY	1-1/4	42.16	3.38	3,025	9.97	3	75
DWR112Y/ZY	1-1/2	48.26	3.51	3,025	11.94	3	75
DWR200Y/ZY	2	60.33	3.71	3,025	16.00	—	50
DWR212Y/ZY	2-1/2	73.03	4.90	3,010	25.62	—	40
DWR300ZY	3	88.90	5.21	3,010	33.43	—	30
DWR400ZY	4	114.30	5.72	3,005	47.38	—	15
DWR500ZY	5	141.30	6.22	2,995	64.38	—	10
DWR600ZY	6	168.28	6.76	2,995	84.05	—	5

*Note: ZY Items are hot-dip galvanized both inside and outside.

Flexible Conduit

Item No.	Size (inch)	Outside Diameter (mm)	Standard pack (m/Roll)	Weight (kg/pc)
DME012	1/2	21.84 ~ 23.37	30	7.80
DME034	3/4	26.54 ~ 28.07	30	9.70
DME100	1	33.02 ~ 35.05	15	5.80



BS31

Threaded conduit – Medium/Heavy protection (Class 3)

BS31: 1940

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWB0343S	3/4	18.92	1.60	3,048	2.11	10	350
DWB0343L				3,810	2.63	10	350
DWB1003S	1	25.27	1.60	3,048	2.90	10	250
DWB1003L				3,810	3.61	10	250
DWB1143S	1-1/4	31.62	1.60	3,048	3.69	7	210
DWB1143L				3,810	4.59	7	210
DWB1123S	1-1/2	37.96	1.80	3,048	5.00	5	150
DWB1123L				3,810	6.23	5	150
DWB2003S	2	50.66	2.00	3,048	7.49	3	90
DWB2003L				3,810	9.32	3	90

BS4568

Threaded conduit – Medium/Heavy protection (Class 3)

BS4568: Part 1: 1970

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWB0203	20	19.85	1.60	3,750	2.72	10	350
DWB0253	25	24.80	1.60	3,750	3.48	10	250
DWB0323	32	31.80	1.60	3,750	4.54	7	210

Heavy protection (Class 4)

BS4568: Part 1: 1970

Item No.	Size (inch)	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DWB0204	20	19.85	1.60	3,750	2.92	10	350
DWB0254	25	24.80	1.60	3,750	3.71	10	250
DWB0324	32	31.80	1.60	3,750	4.84	7	210

WHITE CONDUIT

JIS

Plain conduit (Threadless)

JIS C 8305

Item No.	Size	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DW819T	E19	19.1	1.20	3,660	1.94	10	400
DW825T	E25	25.4	1.20	3,660	2.62	10	250
DW831T	E31	31.8	1.40	3,660	3.84	7	175
DW839T	E39	38.1	1.40	3,660	4.64	5	125
DW851T	E51	50.8	1.40	3,660	6.24	3	75
DW863T	E63	63.5	1.60	3,660	8.94	—	50
DW875T	E75	76.2	1.80	3,660	12.09	—	40

Thin wall conduit (Threaded)

JIS C 8305

Item No.	Size	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DW119T	C19	19.1	1.60	3,660	2.53	10	400
DW125T	C25	25.4	1.60	3,660	3.44	10	250
DW131T	C31	31.8	1.60	3,660	4.36	7	175
DW139T	C39	38.1	1.60	3,660	5.27	5	125
DW151T	C51	50.8	1.60	3,660	7.11	3	75
DW163T	C63	63.5	2.00	3,660	11.10	—	50
DW175T	C75	76.2	2.00	3,660	13.40	—	40

Thick wall conduit (Threaded)

JIS C 8305

Item No.	Size	Outside Diameter (mm)	Nominal Wall Thickness (mm)	Length (mm)	Nominal Weight (kg/pc)	Primary Bundle (pcs)	Master Bundle (pcs)
DW216T	G16	21.0	2.30	3,660	3.88	10	250
DW222T	G22	26.5	2.30	3,660	5.02	10	175
DW228T	G28	33.3	2.50	3,660	6.95	7	125
DW236T	G36	41.9	2.50	3,660	8.89	5	75
DW242T	G42	47.8	2.50	3,660	10.22	3	75
DW254T	G54	59.6	2.80	3,660	14.35	—	50
DW270T	G70	75.2	2.80	3,660	18.30	—	40
DW282T	G82	87.9	2.80	3,660	21.51	—	30
DW392T	G92	100.7	3.50	3,660	30.71	—	20
DW394T	G104	113.4	3.50	3,660	34.72	—	20

For your amenity and energy saving.
FULL-2WAY REMOTE LIGHTING CONTROL SYSTEM



Simple, Efficient Lighting Control That Matches Your Needs

ECOLOGY

Energy-saving while
 Creating an Efficient
 Lighting Environment

AMENITY

User-friendly

SIMPLE

Simple Design
 and Labor-saving
 Installation

CONVENIENCE


Minimal Design,
 Minimum Maintenance

FLEXIBILITY

Reduced Total Cost

Centralized Monitoring and Control

Control and Monitor All Lighting
 from a Central Location



Functional Display of Lightning Status

LED Displays Lightning Status

•ON: Red Light Is lit



•OFF: Green Light Is lit




Timer and Sensor Control


Connectable with Timer or Sensor Control
 Equipments for Further Energy Saving



•Program Timer Unit



•Passive Infrared
 Ceiling Unit




•Daylight Sensor Unit

Group Control

Turn ON All Lights
 in The Sales
 Department

Turn OFF All Lights
 in The Sales
 Department



All Lights ON



All Lights OFF

Pattern Control

9:00 AM

Work Starts



All Lights ON

Noon to
 1:00 PM

Lunch Break



Some Lights ON

2:00 to
 3:00 PM

Natural Light
 Come from
 Outside




All Lights OFF

6:00 PM

Work Finish




Dimmer Control




100%

The bigger the building, the more labor-saving the installation.




Wiring diagram for Full-2way remote control system



Flexible wiring systems for stationary loads. Select from four types according to the capacity you desire, from single-phase 20A to three-phase 100A.

FACTORY LINE SYSTEMS



Flexible power supply from the ceiling.

Ceiling wiring systems capable of providing power for lighting & driving. You can change layout simply by reconnecting plugs to the ducts installed at the ceiling – it allows you to reduce time, labor, and cost significantly without major rewiring.

FLEXIBLE
Easy to add or move plugs; suitable for environments where layouts are changed frequently

SAFETY
No more wire across the floor – it prevents tripping & falling.

NICE VIEW
It not only simplifies the wiring & ceiling, but also provides "three-phase and single-phase", or "single-phase two circuits".

FLEXIBLE

No More Wiring-work After Layout Change



Basic advantages
Simple layout change — just re-connect plugs at different positions. You can reduce labor, time & cost.

Additional advantages

You can add, reduce & relocate power supply easily. Just pull down lever, and turn the plugs to remove or connect.



Factory Line 100 / 60

Factory Line 30

SAFETY


No more tripping over & damaging a cable on the floor.



Basic advantages
Wiring from the ceiling keeps the floor tidy. Plugs with breakers provide safety.

Additional advantages

No need to install breakers with distribution panels — it saves space.



NICE VIEW


It simplifies wiring & appearance. Effective for productivity improvement.



Basic advantages
You can keep ceiling & floor tidy, and appeal to visitors during factory tours.

Additional advantages

One single duct provides three-phase power supply & single-phase power supply — it allows one duct to supply power for machine-driving, conventional sockets and lighting. Factory Line 100/60 simplifies the entire wiring plan.



Wide Lineup

Four types of main duct are available – 100A, 60A, 30A and 20A.
You can combine them to create your own flexible wiring systems for factories.



For Main and Branch Lines

Multi-purpose Factory Flexible wiring System – it provides three-phase & single-phase power supplies at a time.




Factory Line 100



- Three-phase power supply (100A max.)
 - Single-phase power supply (20A max.) with breaker-equipped plug
- Can be used simultaneously



Branching from the 3 wires of the upper level to Factory Line 30. [The rating in () is of Factory Line 60.]





Multi-purpose Factory Flexible wiring System – it provides three-phase & single-phase power supplies at a time.


Factory Line 60




- Three-phase power supply (60A max.)
 - Single-phase power supply (20A max.) with breaker-equipped plug
- Can be used simultaneously



Branching from The Upper Level



Branching from The Lower Level



The plugs of Factory Line 30, and 60 & 100 are NOT exchangeable. — they have different ground connection.



For Branch Lines

Four wire Factory Flexible wiring System – it provides one or the other: three-phase circuit, or two single-phase circuits.

Factory Line 30




- Three-phase power supply, one circuit (30A max.)
- Single-phase power supply, two circuits (30A max.)




Standard Power Supply Take-Off

Receptacle plug (for 100V)



Terminal plug (for 440V)



[Adapter for fluorescent lights are the same.]

Terminal plug (for Three-Phase 440V)



You need a dedicated ground wire. Use 4P type plug, and one conductor in the duct for the ground circuit.



For Small-Scale Branch Lines

Factory Flexible wiring System for small-scale branching – it provides one single-phase power supply circuit.


Factory Line 20














- Single-phase power supply (20A max.)




Factory Line 100/60

	Cat. No.	Length ℓ (mm)	Weight (kg)	Rating
Factory Line 100/60 Main Unit (Cream-Gray Finish: Munsell 5Y7.2/1.4)	Factory Line 100 DGHU2411	1,000	3.3	3P 100A 440V + 2P 20A 300V with Ground
		2,000	6.6	
		3,000	9.9	
	Factory Line 60 DGHU2311	1,000	3.1	3P 60A 440V + 2P 20A 300V with Ground
		2,000	6.1	
		3,000	9.1	


	Cat. No.	Weight (kg)	Rating
Feed-in Cap (Cream-Gray Finish)	DGHU2421	1.1	3P 100A 440V + 2P 20A 300V with Ground
			
Center Feed-in Joiner (Cream-Gray Finish)	DGHU2422	2.4	
			
Joiner (Cream-Gray Finish)	DH2431	0.1	2P 20A 300V with Ground
			
End Cap (Cream-Gray Finish)	DH2423K	0.06	—
			
Hanger (with Bolt)	DH2451	0.18	—
			
Terminal adapter A (Cream-Gray Finish)	DGHU2481	0.35	3P 30A 440V with Ground
			
Terminal adapter B (Cream-Gray Finish)	DH2463	0.08	2P 15A 300V with Ground
			
Locking adapter receptacle (Cream-Gray Finish)	DH2477	0.07	Ground 2P 15A 125V Locking
			
Adapter receptacle (Cream-Gray Finish)	DH2461	0.07	Ground 2P 15A 125V
			
Reel-Type Adapter receptacle (Adapter: Cream-Gray Finish, receptacle: Off-White Finish)	DH24621	0.7	for Twin Ground 2P 15A 125V
	DH24641		for Twin Ground 2P 15A 125V Locking
			
Hanger (with earthquake resistant reinforcement fixture)	DH2452K1	0.03	—
			

Factory Line 30

	Cat. No.	Length ℓ (mm)	Weight (kg)	Rating
Factory Line 30 Main Unit (Cream-Gray Finish: Munsell 5Y7.2/1.4)	DGHU2711	1,000	1.6	4P 30A 440V with Ground
		2,000	3.2	
		3,000	4.8	
				

	Cat. No.	Name/ Type	Weight (kg)	Rating
Feed-in Cap (Cream-Gray Finish)	DGHU2721	—	0.16	4P 30A 440V with Ground
				
Center Feed-in Joiner (Cream-Gray Finish)	DGHU2722	—	0.24	
				
End Cap (Cream-Gray Finish)	DH2723	—	0.01	—
				
Joiner (Cream-Gray Finish)	DGHU2731	—	0.08	4P 30A 440V with Ground
				
Terminal Plug (Cream-Gray Finish)	DGHU2781	2PS	0.08	2P 15A 440V with Ground
	DGHU2782	2PL		3P 15A 440V with Ground
	DGHU2783	3P		
	DGHU2784	4P		4P 15A 440V with Ground
※1				
Adapter Receptacle (Cream-Gray Finish)	DH2773	S	0.05	Ground 2P 15A 125V
	DH2774	L		
※2				
Locking Adapter Receptacle (Cream-Gray Finish)	DH2791	S	0.05	Ground 2P 15A 125V Locking
	DH2792	L		
※2				
Reel-Type Adapter Receptacle (Adapter: Cream-Gray Finish, Receptacle: Off-White Finish)	DH27751	S	0.73	for Twin Ground 2P 15A 125V
	DH27761	L		
	DH27781	S		for Twin Ground 2P 15A 125V Locking
	DH27791	L		
※2				
Hanger (with Bolt)	DH2751	—	0.11	—
				
Hanger (with earthquake resistant reinforcement fixture)	DH2752K1	—	0.03	—
				

Factory Line 20

	Cat. No.	Length ℓ (mm)	Weight (kg)	Rating
Factory Line 20 Main Unit (Cream-Gray Finish: Munsell 5Y7.2/1.4)	DGHU2611	1,000	0.79	2P 20A 250V with Ground
		2,000	1.58	
		3,000	2.37	
				

	Cat. No.	Weight (kg)	Rating
Feed-in Cap (Cream-Gray Finish)	DGHU2621K1	0.11	2P 20A 250V with Ground
			
Center Feed-in Joiner (Cream-Gray Finish)	DGHU2622K1	0.19	
			
End Cap (Cream-Gray Finish)	DH2623	0.006	—
			
Joiner (Cream-Gray Finish)	DGHU2631K1	0.1	2P 20A 250V with Ground
			
Terminal Plug (with Ground) (Cream-Gray Finish)	DGHU2683	0.05	2P 15A 250V with Ground
			
Plug Sockets (with Ground) (Cream-Gray Finish)	DH2670	0.04	Ground 2P 15A 125V
			
Locking Plug Socket (Cream-Gray Finish)	DH2671	0.04	2P 15A 125V with Ground
			
Locking Plug Socket (with Ground) (Cream-Gray Finish)	DH2684	0.04	Ground 2P 15A 125V Locking
			
Reel-Type Plug Socket (with Ground) (Plug: Cream-Gray Finish, Socket: Off-White Finish)	DH26751	0.7	for Twin Ground 2P 15A 125V
	DH26771		for Twin Ground 2P 15A 125V Locking
			
Hanger (with Bolt)	DH2651	0.13	—
			
Hanger (with Bolt)	DH2652	0.03	—
			

※1: 2P/3P/4P 15A 300V with Ground, Power Outlet for The Main Unit.
"L" (for the upper 2P conductors) and "S" (for the lower 2P conductors) plug are available in 2P type.

※2: "L" (for the upper conductors) and "S" (for the lower conductors) plug are available.

Factories

You can get power from optimal location quickly even after layout change.

Factory Line 100



Schools

One single duct can supply power for two circuits at a time — it allows you to connect more devices, and keep the floor clean & tidy.

Factory Line 30



Retail Stores

Supplying power for lighting & sockets at a time. Highly functional Factory Line 30, which offers two single phase circuits at a time, allows the store to have power for lighting and extra sockets. It also fits into modern, lightly equipped ceilings — the simple wiring produces spacious environment in the store.

Factory Line 30



[Others]



Research Institutes & Laboratories

One single duct (Factory Line 30) can provide many small capacity power supplies with different voltages & frequencies — it allows many applications.



Data Centers

Factory Line 100, 60 and 30 can supply power to both 200V & 100V devices at a time on server racks. NO NEED FOR WIRING SPACE ON/UNDER FLOOR due to power supply from the ceiling.




Information about Panasonic Factory Line Systems

is available at:

www2.panasonic.biz/es/densetsu/haikan/ffs/en/

● Specification drawings, operation and installation manuals can also be downloaded.


PHOTOVOLTAIC MODULE HIT®



Designed for higher energy production and long-term reliability, Panasonic HIT® ensures you a true peace of mind and satisfaction in your energy management.

1. 19.4% module efficiency


+25% more power from same area



HIT®: 15pcs x 325W = 4.87kW VS Standard*: 15pcs x 260W = 3.90kW

2. High performance at high temperature

Up to +13% more generation in the day time




Total yield with a peak module temperature of 85°C, compared with a conventional crystalline module.

Measurement: 8 July 2013, Kaizuka City, Japan

3. More generation, higher profit

Helping you reach a higher final profit with your PV system




Standard*: Conventional crystalline module with Pmax 260W

Heterojunction technology




Heterojunction cell

Thin monocrystalline silicon wafer
Ultra-thin amorphous silicon layer



Conventional p-Si solar cell

Polycrystalline Si wafer (p type)



Unique water drainage

N325 (VBHN325SJ47)

Cell efficiency	21.8%
Module efficiency	19.4%
Output/m ²	194W/m ²
Temperature coefficient	0.29%/C

Specification		
Max. Power (Pmax)	[W]	325
Open circuit voltage (Voc)	[V]	69.6
Short circuit current (Isc)	[A]	6.03
Size	Weight	
W1,053×H1,590×D35mm	18.5kg	




N240 (VBHN240SJ25)

Cell efficiency	21.6%
Module efficiency	19.0%
Output/m ²	190W/m ²
Temperature coefficient	0.29%/C

Specification		
Max. Power (Pmax)	[W]	240
Open circuit voltage (Voc)	[V]	52.4
Short circuit current (Isc)	[A]	5.85
Size	Weight	
W798×H1,580×D35mm	15kg	



AUTO DOOR



Automatic Sliding Door



This is the most common automatic doors on the market, often used for offices, meeting rooms, a showroom, lobby, restaurants, hospitals, banks, convention centers, airports and many others more...

Remote controller, back-up battery, electric Locks, sensors and access Controllers can be connected if required.

If you connect with a fire alarm, when fire alarm triggers, the door will remain fully open to make it easier to exit.



Model	PS-75	PS-90	PS-120	PS-150	PS-250
Door weight	≤75kg x 2	≤90kg x 2	≤120kg x 2	≤150kg x 2	≤250kg x 2
Opening speed (Adjustable)	14~32 cm/s	14~32 cm/s	14~40 cm/s	14~34 cm/s	10~50 cm/s
Opening speed (Adjustable)	9~30 cm/s	9~30 cm/s	10~38 cm/s	10~34 cm/s	10~50 cm/s
Manual opening (power failure)	44N (4.5 kgf)	36.3N (3.7 kgf)	61.7N (6.3 kgf)	89.2N (9.1 kgf)	150N (15.3 kgf)
Door width	600 ~ 1,250mm				800 ~ 1,500mm
Door hold time	0 ~ 9 s				0~30s
Voltage	AC 200~250V 50/60 Hz				

Air tight doors, Hermetic doors, X-ray shielding doors

The air tight door can effectively prevent dusts in the air from entering the room and avoid bacterial infection, save air-conditioning energy, prevent wind and dust and reduce noise.

V track-shape arc groove design, squeeze inward and downward when closed, rubbers around fit closely with the door frame to ensure excellent sealing effect.

Apply: Medical Treatment, Pharmaceutical, Sensitization, Foodstuff, Biochemistry, Electronics...



Emergency Automatic Door




In the case of normal, the application of Panasonic emergency door is the same as Panasonic general sliding automatic door, while the former has all the functions of the latter, such as operating parameter adjustment and rebound while meeting resistance, etc.

However, when an emergency (e.g. fire) occurs, the evacuation personnel can push the door leaves (flexible or fixed) outwards to 90°, and coincide flexible door leaf to the fixed door leaf, which will greatly increase the evacuation space and be beneficial to the emergency evacuation.

In other special places, such as factory and exhibition hall, where the large scale equipment will be transported from their entrances, the door leaves of emergency door can be pushed outwards to 90° and moved to the two sides for greater passing width and convenience of goods transportation (See Figure 3).


MODEL	
NESR22422R	One wing – Open to right
NESR22422L	One wing – Open to left
NESR224428	Two wings





Door leaves closing




Push out timely
Figure 1





Door leaves opening



Push out timely
Figure 2



Door leaves opening fully



Push out timely
Figure 3

Revolving Automatic Door



Automatic revolving door is designed with luxurious style, a rotation movement should ensure the flow of people streaming big move. Automatic revolving doors are often installed in offices, commercial centers, luxury hotels...

With the highest safety requirements, automatic revolving doors with 32 sensors, the door will automatically rotate counterclockwise when facing an obstacle.

Diameter (mm)	2400	2600	2800	3000	3200	3400	3600	4200	4800
Two wings						PS-A3400-2E	PS-A3600-2E	PS-A4200-2E	PS-A4800-2E
Three wings	NS-A2400-3	NS-A2600-3	NS-A2800-3	NS-A3000-3	NS-A3200-3	NS-A3400-3	NS-A3600-3	NS-A4200-3	NS-A4800-3
Four wings	NS-A2400-4	NS-A2600-4	NS-A2800-4	NS-A3000-4	NS-A3200-4	NS-A3400-4	NS-A3600-4	NS-A4200-4	NS-A4800-4

DOOR HARDWARE

Accessories



Door handle




Glass door lock




Glass hinges




Glass clamp



Door clamp



Hinges



Flush bolt



Floor hinges

Model	Max Door Width	Max Door Weight
S-80	≤ 900mm	≤ 80kg
S-100	≤ 1100mm	≤ 100kg
S-150	≤ 1200mm	≤ 150kg
S-250	≤ 1250mm	≤ 250kg



Dust-proof



Security door guard



Door Close

Model	CM-1000H	CM-1000HYS
Max Door Width	1000mm	1000mm
Max Load-bearing	70kg	70kg
Max Opening Angle	180°	
Color	White / Silver	
Style	Exposed	Exposed



Door viewer



Door coordinator



Door Close

Model	Non hold-open	Hold-open
		CM-1050F
Max Door Width	1050mm	
Max Load-bearing	75kg	
Max Opening Angle	180°	
Color	Silver	
Style	Exposed	



Door stopper



Door bottom seal




Door Close


Model	Hold-open	
	CM-1100F	CM-1100FS
Max Door Width	1100mm	1100mm
Max Load-bearing	80kg	80kg
Max Opening Angle	180°	
Color	Silver	
Style	Exposed	Exposed



Panic exit device



Lock handle



Door Close

Model	Non hold-open	Hold-open
	CY-950	CY-1250T
Max Door Width	950mm	1250mm
Max Load-bearing	60kg	100kg
Max Opening Angle	120°	
Color	Silver	
Style	Concealed, hold-open	



Lock body



Cylinder

VENTILATING FANS & AIR MOVING EQUIPMENTS


Providing you a breath of fresh air



What are the Indoor Air Quality problems existing in your house?

Recently, many reports show that people are in poorer physical condition. It is because of high living density and usage of building or interior material which emit chemical substances in either new-built or reformed house, causing indoor air quality problems.

There are different symptoms, such as eyes / sore throat, nausea, feeling unwell, skin irritation, headache, dizziness, breathing problem and so on. Furthermore, chemical substances like formaldehyde, can lead to the deterioration of allergic illness.




INDOOR AIR PROBLEMS IN YOUR HOUSE



Mites

There are around 30 types of mites found in a home normally. In general, most mites live without causing any harm to human beings. However, sting mites like Cheyletidae, blood-sucking mites like House Mite, and Dust Mite group which can cause allergen also exist.



Molds



Enlarged Photo of Mold

Mold breeds faster when humidity increases, and nearly everything inside & outside our residence can provide nutrients for it. Not only mold is damaging our home appearance and creating bad smell, it also has bad effects on human body. Furthermore, mold increases during rainy season, and its spores fly around at the end of rainy season.



Termite


Volatile organic compounds (VOC) like Formaldehyde which is generated from building material and/or home furniture. It is easily to cause indoor air pollution.



Formaldehyde (HCHO)

Volatile organic compounds (VOC) like Formaldehyde which is generated from building material and/or home furniture. It is easily to cause indoor air pollution.

Indoor Formaldehyde concentration was measured




IMPROVE INDOOR AIR QUALITY

Ways to improve Indoor Air Quality

The first step to improve indoor air quality should reduce or remove the source of the pollutants. Unfortunately, indoor pollutant is virtually impossible to eliminate completely, creating the need for a second step - ventilation. Ventilation is divided into "Natural Ventilation" and "Mechanical Ventilation".


Natural ventilation is neither consistent nor reliable since it relies heavily on wind and weather conditions. Mechanical ventilation removes stale, moist, polluted air and replaces it with fresh outside air by using a fan.



Two widely used methods in today's building industry are continuous and intermittent ventilation.

Continuous Ventilation


Sometimes referred to as general, central, whole-house or primary ventilation. Continuous ventilation is used to remove stale air and provide fresh air on a slow, continuous basis.



Enhance ventilation in the whole house to replace polluted air with fresh air by ventilation equipment.

Intermittent Ventilation

Sometimes referred to as spot, local or secondary ventilation. Intermittent ventilation is used to capture and remove pollutant quickly at the source. This secondary process exhaust "bad air" from contaminated areas quickly, before it can spread throughout the house.



Enhance ventilation in specific part of a house. (e.g. bathroom, kitchen)

VENTILATION SCHEDULE

The Number of Ventilating Fans Required

(A): Room Size [M³] x (B): Necessary Frequency of Ventilation Per Hour

(C): Air Volume of Ventilating Fan [M³]

Note: Room size (A) is calculated from the following equation:
 (A) = Floor area [sq. m. or sq. ft.] x Room height [m. or ft.]
 If the room height exceeds 4 meters (13 feet), use 4 meters (13 feet) in the calculation regardless of the actual room height.

Values for (B) in above equation are given in the table on the below. These values were empirically found by the research scientists. Value for (C) in the above equation are given in our catalogs.

Ventilation Schedule

I: Type of room		II: Necessary frequency of ventilation per hour				
	I	II		I	II	
Hotel	Dance Hall	8	Photo Studio	Dark Room	10	
	Dining Hall	8		School	Laboratory	6
	Kitchen	15			Cooking Room	15
	Hallway	5			Auditorium	6
	Toilet	5			Gymnasium	8
	Lavatory	10			Toilet	12
	Boiler Room	20			Library	6
	Laundry	15			Classroom	6
Hospital	Waiting Room	10	Theatre		Auditorium	6
	Clinic	6		Hallway	6	
	Ward	6		Smoking Room	12	
	Bathroom	5		Toilet	10	
	Office	6		Projection Booth	20	
	Restaurant	8		Workroom	6	
	Kitchen	15		Telephone Switch Board Room	6	
	Gallery	5		Factory	Painting Room	20
	Toilet	10			Dynamo Room and Substation	20
	Boiler Room	10			Condenser Room	15
	Laundry	15			Office	6
	Operating Room	15			Restaurant & Snack Bar	Restaurant
	Disinfecting Room	12		Kitchen		20
	Room for the Patients Receiving Medical Treatment for the Diseases of Respiratory Organs	10		Office Building	Office	6
	Public Toilet				20	Waiting Room
			Conference Room		12	
Vessel	Passenger Room	6	Display Room		10	
			Toilet		10	
Home	Kitchen	15	Rooms where poisonous or inflammable gas is produced		more than 20	
	Parlor	6				
	Living Room	6				
Library	Reading Room	6				

RECOMMENDED APPLICATION

Panasonic ventilating products can be used in various environment, such as residential house, offices and hotels.

Residence

Ventilating fans installed throughout the home draw indoor pollutants and vent them outside. So, a continuous and balanced ventilation system brings you with fresh air.



Office

Office also needs a good ventilation system to maintain constant and fresh airflow. Panasonic Cabinet Fan definitely provides you with a quiet and comfortable environment.



* Local regulations concerning the installation of ventilation fans should be fulfilled.
 * Installation methods please refer to the operation instruction.

CEILING MOUNT TYPE VENTILATING FAN




General Features (DC Motor Series, Super Quiet Series & Standard Series)

1 Quiet Operation

These fans adopt distinctive design of "Resonance-Noise-Absorption Structure". It can minimize the transmission of noise from the blower to exterior, reduce the operation noise to incredibly low levels and accordingly create a tranquil and silent environment for you.

By the "Double Orifice" Structure, noise is effectively absorbed and reduced between the double orifice and casing.

* except 38 model



2 Long Life

The unique design of new motor, corporated with well-lubricated ball bearing, temperature rise is reduced that can increase the motor life time and prolong the product durability.

3 High Efficiency

Taper blade design effectively controls the air turbulence surrounding the blade. That achieves the strong and smooth ventilating performance, as well as reduces the noise level, by whole of the blade.

Seam-processed casing ensures strength and hermetic sealing. Reverse flow prevention shutter results in further improvement of air tightness.

4 Energy Saving

The advanced casing design, along with the new motor, improves the fan performance effectively. Energy saving is attained by reducing power consumption down to 35%.

5 Easy Installation

Wiring of power cord to product is pre-installed in factory, just connect the cord to power supply for operation (except 38 model).

Cassette type discharge adaptor facilitates installation of the product, as well as duct connecting work.

6 Easy Maintenance

One touch louver allows installation and removal of louver by finger touch.


FV-24JR2 DC Motor Series



- DC motor
- Constant airflow
- Variable air volume
- 15-minute delay timer
- Auto operation by motion sensor
- Resonance-Noise-Absorption Structure
- Taper blade sirocco fan
- Pre-installed power cord


Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Air Volume		Power Consumption [W]	Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]
	[CMH]	[CFM]					
FV-24JR2	160	94	8	31	2.9	240 x 240	Ø100
	120	71	5.2	26			
	80	47	3.6	20			

Note: Values in Consumption and Noise are specified at Static Pressure of 0 Pa.


FV-24JA2 DC Motor Series



- DC motor
- Constant airflow
- Variable air volume
- 15-minute delay timer
- Resonance-Noise-Absorption Structure
- Taper blade sirocco fan
- Pre-installed power cord


Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Air Volume		Power Consumption [W]	Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]
	[CMH]	[CFM]					
FV-24JA2	160	94	8	31	2.9	240 x 240	Ø100
	120	71	5.2	26			
	80	47	3.6	20			


Note: Values in Consumption and Noise are specified at Static Pressure of 0 Pa.

FV-17CU7 Super Quiet Series



Dimension


Unit: mm



- Condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Pre-installed power cord
- Resonance-Noise-Absorption Structure
- High performance taper blade designed sirocco fan

Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]
				[CMH]	[CFM]				
FV-17CU7	50	11	790	85	50	26	1.9	177 x 177	Ø100
	60	11	800	85	50	28			


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-24CU7/ FV-24CD7/ FV-24CH7 Super Quiet Series



Dimension




Unit: mm



- Condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Pre-installed power cord
- Resonance-Noise-Absorption Structure
- High performance taper blade designed sirocco fan

Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]
				[CMH]	[CFM]				
FV-24CU7	50	14	690	140	82	28	2.9	240 x 240	Ø100
	60	16	690	140	82	29			
FV-24CD7	50	17	790	170	100	31	3.0	240 x 240	Ø100
	60	19	805	170	100	33			
FV-24CH7	50	20	870	200	118	35	3.0	240 x 240	Ø100
	60	24	840	190	112	35			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-27CH9 Super Quiet Series



- High-Low speed selectable
- Condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Pre-installed power cord
- Resonance-Noise-Absorption structure
- High performance taper blade designed sirocco fan


Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]	
				[CMH]	[CFM]					
FV-27CH9	50	Hi	28	570	330	194	4.4	270 x 270	ø150	
		Lo	23	480	260	153				30
	60	Hi	33	570	330	194				34
		Lo	26	490	270	159				31

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-32CD9/ FV-32CH9 Super Quiet Series



- High-Low speed selectable
- Condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Pre-installed power cord
- Resonance-Noise-Absorption structure
- High performance taper blade designed sirocco fan



Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]	
				[CMH]	[CFM]					
FV-32CD9	50	Hi	42	590	430	253	5.2	320 x 320	ø150	
		Lo	32	460	300	177				28
	60	Hi	48	580	410	241				36
		Lo	33	450	285	168				28
FV-32CH9	50	Hi	55	710	530	312	5.6	320 x 320	ø150	
		Lo	45	570	400	235				34
	60	Hi	61	695	525	309				41
		Lo	47	540	390	230				33


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-38CD8 / FV-38CH8 Standard Series





Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)




- High-Low speed selectable
- Condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- High performance sirocco fan

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]	Duct Size [mm]
					[CMH]	[CFM]				
FV-38CD8	50	Hi	90	645	640	377	44	9.7	385 x 385	Ø150
		Lo	66	456	430	253	35			
	60	Hi	98	628	630	371	44			
		Lo	66	439	410	241	35			
FV-38CH8	50	Hi	122	790	800	471	50	10.4	385 x 385	Ø150
		Lo	89	540	525	309	40			
	60	Hi	138	760	790	465	49			
		Lo	90	509	500	294	39			


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-20CUT1 Propeller Series



Dimension

Unit: mm




- High air volume
- Easy installation
- Designed for a long service life with continuous daily operation
- Motor equipped with thermal fuse

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation space [mm]
				[CMH]	[CFM]			
FV-20CUT1	50	22.6	1,153	438	258	40.5	1.8	270 x 270
	60	23.9	1,245	436	257	41.4		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

LOW NOISE TYPE CABINET FAN (In-Line Fan)



High Performance

- The newly developed twin flow fan achieves large air volume and high static pressure
- The tapered scroll at fan case can minimize the turbulence induced by uneven wind velocity inside the casing

Low Noise

- Noise absorption material adopted for reduction of noise level

Easy Installation

- Exclusive U-type grooved hanging brackets provide safety installation
- Able to install upside down for different location of inspection panel

Easy Maintenance

- Detachable inspection panel can be removed easily for maintenance

Reliability


- Long life condenser motor with thermal cut-off is adopted

Flexibility

- 2-speed selectable enhances flexibility for various usages (for single phase models only)


Compact Size

- Slim and compact design allows installation at narrow ceiling space




Twin Flow Fan

The newly developed twin flow fan achieves a better airflow inside the fan casing. It is divided into two portions which can generate large air volume and high static pressure respectively.




Embedded Terminal Box

Terminal boxes of new models are embedded into the product frame. Wiring to power supply is covered with metal enclosure that enhances the durability and safety concern.



Tapered Scroll

Wind velocity varies according to the shape of fan casing. The tapered scroll at the fan casing can minimize the turbulence induced by uneven wind velocity inside the casing.



Internal Wind Velocity Distribution – Airflow Analysis


FV-12NS3 / FV-15NS3 Single Phase Series



- Long life condenser motor with thermal cut-off
- Twin flow fan (sirocco fan)
- Fan casing with tapered scroll
- Embedded terminal box
- Noise absorption material adopted
- Compact size

Dimension



Unit: mm



Model No.	A	B	C	D	E	F	G	H	I
FV-12NS3	290	250	291	335	184	92	97	112	51
FV-15NS3	290	250	302	346	206	103	146	163	60

Performance Data

[220V 50Hz/60Hz]



Specification

Model No.	Phase	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]	Impeller Diameter [mm]
						[CMH]	[CFM]				
FV-12NS3	1	50	Hi	18	1,265	180	106	21	5.5	Ø100	128
			Lo	17	1,020	145	85	17			
		60	Hi	23	1,370	190	112	22			
			Lo	19	1,000	145	85	18			
FV-15NS3	1	50	Hi	33	1,270	340	200	25	6.5	Ø150	128
			Lo	29.5	1,100	275	162	22			
		60	Hi	42	1,385	370	218	27			
			Lo	33	1,040	260	153	22			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-18NS3 / FV-18NF3 Single Phase Series



- Long life condenser motor with thermal cut-off
- Twin flow fan (sirocco fan)
- Fan casing with tapered scroll
- Embedded terminal box
- Noise absorption material adopted
- Compact size

Dimension



Unit: mm



Model No.	A	B	C	D	E	F	G	H	I
FV-18NS3	316	276	338	382	232	116	145	163	60
FV-18NF3	376	336	397	441	254	127	195	211	70

Performance Data

[220V 50Hz/60Hz]



Specification

Model No.	Phase	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]	Impeller Diameter [mm]
						[CMH]	[CFM]				
FV-18NS3	1	50	Hi	60	1,250	500	294	29	8.5	Ø150	158
			Lo	55	1,100	405	238	27			
		60	Hi	73	1,260	490	288	30			
			Lo	62.5	990	385	227	26			
FV-18NF3	1	50	Hi	91	1,190	770	453	31	10	Ø200	158
			Lo	80	1,000	620	365	29			
		60	Hi	119	1,245	760	447	32			
			Lo	87	990	580	341	28			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-20NS3 / FV-23NL3 Single Phase Series



- Long life condenser motor with thermal cut-off
- Twin flow fan (sirocco fan)
- Fan casing with tapered scroll
- Embedded terminal box
- Noise absorption material adopted
- Compact size

Dimension



Unit: mm



Model No.	A	B	C	D	E	F	G	H	I
FV-20NS3	416	376	441	485	272	136	195	211	70
FV-23NL3	468	424	469	513	298	149	195	211	70

Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Phase	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]	Impeller Diameter [mm]
						[CMH]	[CFM]				
FV-20NS3	1	50	Hi	120	1,195	920	541	32	14	ø200	178
			Lo	113	1,000	720	424	29			
		60	Hi	159	1,165	860	506	32			
			Lo	128	875	620	365	26			
FV-23NL3	1	50	Hi	230	1,245	1,200	706	40	18	ø200	220
			Lo	170	985	900	530	34			
		60	Hi	310	1,210	1,100	647	40			
			Lo	190	890	800	471	32			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-25NS3 / FV-25NF3 Single Phase Series



- Long life condenser motor with thermal cut-off
- Twin flow fan (sirocco fan)
- Fan casing with tapered scroll
- Embedded terminal box
- Noise absorption material adopted
- Compact size

Dimension



Unit: mm



Model No.	A	B	C	D	E	F	G	H	I
FV-25NS3	494	450	505	549	334	167	240	255	85
FV-25NF3	494	450	505	549	334	167	240	255	85

Performance Data

(220V 50Hz/60Hz)



Specification

Model No.	Phase	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]	Impeller Diameter [mm]
						[CMH]	[CFM]				
FV-25NS3	1	50	Hi	345	1,125	1,700	1,001	41	24	ø250	220
			Lo	265	950	1,380	812	38			
		60	Hi	425	1,100	1,650	971	41			
			Lo	300	890	1,200	706	39			
FV-25NF3	1	50	Hi	390	1,225	1,900	1,118	43	24	ø250	220
			Lo	325	1,070	1,600	942	40			
		60	Hi	520	1,245	1,810	1,065	42			
			Lo	380	1,000	1,400	824	41			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

INDUSTRIAL TYPE VENTILATING FAN



Features of High Pressure Series

1 High Static Pressure, Low Power Consumption


The unique design of wave-shaped blade and bellmouth construction enable better performance in high static pressure and low power consumption.

2 Low Noise Design


The blade's distinctive wave-shaped is developed by application of hydrodynamic analysis. It can deliver a smooth and turbulence free airflow, meaning the performance in big air volume but with less noise.

3 Improved Durability

Pressure is distributed more uniformly over the surface of the blade, making it more durable. A special polyester resin powder coating give a beautiful color and a highly rust-resistant finishing.



Fans with 3-dimensional wave-shaped cross section blade



Surface Velocity Vector Diagram


FV-25GS4/ FV-30GS4/ FV-35GS4 High Pressure Series



- Single Phase
- Reversible by adjusting wiring and blade
- Bellmouth construction with distinctive wave-shaped blade
- Durable powder coating
- High performance motor with thermal cut-off
- Able to be used over an ambient temperature range from -10°C to +50°C
- Possible to install horizontally or vertically
- Optional guard and shutter available

Dimension

Unit: mm



Model No.	A	B	C	D	E	F
FV-25GS4	250	327	298	165	171	10
FV-30GS4	300	378	349	210	200	10
FV-35GS4	350	467	434	250	236	12




Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-25GS4	50	39	1,360	1,150	677	34	4.4
	60	47	1,560	1,250	736	39	
FV-30GS4	50	59	1,360	1,820	1,071	38	6.1
	60	80	1,560	2,080	1,224	42	
FV-35GS4	50	88	1,420	2,560	1,507	44	10.5
	60	127	1,660	2,940	1,730	48	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

Performance Data

(220V 50Hz/60Hz)




FV-40GS4/ FV-45GS4 High Pressure Series



- Single Phase
- Reversible by adjusting wiring and blade
- Bellmouth construction with distinctive wave-shaped blade
- Durable powder coating
- High performance motor with thermal cut-off
- Able to be used over an ambient temperature range from -10°C to +50°C
- Possible to install horizontally or vertically
- Optional guard and shutter available

Dimension

Unit: mm



Model No.	A	B	C	D	E	F	G
FV-40GS4	400	518	485	460	280	274	12
FV-45GS4	450	570	540	-	320	297	12



Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-40GS4	50	161	1,450	3,610	2,125	47	19
	60	210	1,710	4,240	2,496	51	
FV-45GS4	50	227	1,410	5,200	3,061	51	19
	60	325	1,630	5,970	3,514	54	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

Performance Data


(220V 50Hz/60Hz)



FV-50GS4 / FV-60GS4 High Pressure Series



Dimension Unit: mm



Model No.	A	B	C	D	E	F	G
FV-50GS4	500	659	620	560	355	315	15
FV-60GS4	620	760	720	650	400	320	15



- Single Phase
- Reversible by adjusting wiring and blade
- Bellmouth construction with distinctive wave-shaped blade
- Durable powder coating
- High performance motor with thermal cut-off
- Able to be used over an ambient temperature range from -10°C to +50°C
- Possible to install horizontally or vertically
- Optional guard and shutter available

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-50GS4	50	249	960	6,130	3,608	47	22.5
	60	326	1,130	7,100	4,179	51	
FV-60GS4	50	245	970	8,040	4,732	50	34
	60	361	1,150	9,410	5,539	54	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


Performance Data (220V 50Hz/60Hz)



FV-45GT4/ FV-50GT4/ FV-60GT4 High Pressure Series



Dimension Unit: mm



Model No.	A	B	C	D	E	F	G
FV-45GT4	450	570	540	-	320	297	12
FV-50GT4	500	659	620	560	355	304	15
FV-60GT4	620	760	720	650	400	320	15




- Three Phase
- Reversible by adjusting wiring and blade
- Bellmouth construction with distinctive wave-shaped blade
- Durable powder coating
- High performance motor with thermal cut-off
- Able to be used over an ambient temperature range from -10°C to +50°C
- Possible to install horizontally or vertically
- Optional guard and shutter available

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-45GT4	50	220	1,450	5,520	3,249	52	18.5
	60	330	1,690	6,420	3,779	56	
FV-50GT4	50	320	1,400	6,960	4,097	54	28.5
	60	475	1,590	8,010	4,715	58	
FV-60GT4	50	310	940	9,420	5,544	49	34
	60	450	1,070	10,920	6,427	53	

Note: The value in Specification table are representative characteristics value at 380V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

Performance Data (220V 50Hz/60Hz)




FV-30KUT / FV-40KUT Shutter Series



Dimension

Unit: mm





Model No.	A	B	C	D	E	F	G	H	I	J	K
FV-30KUT	420	385	305	116	34	40	141	90	340	10	164
FV-40KUT	510	480	410	133	40	52	141	90	434	10	181

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-30KUT	50	42	1,185	1,220	718	46	4.9
	60	51	1,255	1,270	747	47	
FV-40KUT	50	61	1,175	2,060	1,212	49	6.4
	60	76	1,260	2,190	1,289	51	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

Performance Data (220V 50Hz/60Hz)




- Used in factories, warehouses or other locations in where powerful ventilation is necessary
- Metal large blade assembly for abundant air volume
- Powerful, efficient and durable condenser motor
- Able to be used over an ambient temperature range from -10°C to +50°C

FV-50AET2 Shutter Series




Dimension

Unit: mm



Performance Data (220V 50Hz/60Hz)



- Used in factories, warehouses or other locations in where powerful ventilation is necessary
- Metal large blade assembly for abundant air volume
- Powerful, efficient and durable condenser motor
- Able to be used over an ambient temperature range from -10°C to +50°C

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]		
FV-50AET2	50	108	920	3,630	2,137	54	11.5
	60	130	1,050	4,200	2,472	58	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


WALL MOUNT TYPE VENTILATING FAN



General Features

Advanced Blade Design


New blade design applies advanced aerodynamic principle that minimizes any obstacles against the airflow.



HP (Half-Pitch) Motor & Bearing

Compared with previous models, new models adopt high performance condenser motor and long life bearing that prolong the product durability, from average 30,000 hours life time to 60,000 hours.

They also enable energy saving by reducing power consumption down to average 13%.




FV-10EGK1/ FV-15EGK1 Bathroom Series



Dimension

Unit: mm




- Pipe Hood Series
- Powerful exhaust of moisture and smell
- Compact and stylish design
- Prevent trace caused by rain water
- All accessories are included for most convenience
- Easy installation
- Wall thickness 100-150mm

Model No.	A	B	C	D	E	F	G	H	I
FV-10EGK1	176	170	9.3	177	250	220	107	99	120
FV-15EGK1	230	220	11.5	230	310	270	142	138	165

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-10EGK1	50	5.5	2,706	75	44	33	1.2	Ø 135 ± 5
	60	4.4	2,888	80	47	34		
FV-15EGK1	50	6.2	2,329	160	94	34	1.5	Ø 180 ± 5
	60	8.5	2,647	180	106	38		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions. This specifications are specified with duct sleeve, duct spinner and pipe hood.




FV-10EGS1/ FV-15EGS1 Bathroom Series



Dimension

Unit: mm




- Shutter Series (for Vertical Shaft)
- Powerful exhaust of moisture and smell
- Compact and stylish design
- Back draft shutter
- All accessories are included for most convenience
- Easy installation

Model No.	A	B	C	D	E	F	G
FV-10EGS1	176	170	9.3	177	160	115	40
FV-15EGS1	230	220	11.5	230	160	160	80

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-10EGS1	50	5.5	2,706	75	44	35	0.9	Ø 120 - Ø 125
	60	4.4	2,888	80	47	36		
FV-15EGS1	50	6.2	2,329	150	88	36	1.1	Ø 165 - Ø 170
	60	8.5	2,647	175	103	40		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions. This specifications are specified with duct sleeve.




FV-25AUF1 Filter Series




Dimension

Unit: mm



Performance Data

(220V 50Hz/60Hz)



- Recommend to use in kitchen
- Automatic Shutter
- Perforated aluminum filter with hydrophobic coating
- Large capacity oil cup
- Oil Indicator on oil cup
- High exhaust air volume under actual usage condition (20Pa)

Specification


Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-25AUF1	50	34	1,100	835	491	42	2.8	300 x 300
	60	34	1,060	820	483	42		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-20AU9/ FV-25AU9/ FV-30AU9 Automatic Shutter Series

Dimension

Unit: mm



- HP condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Propeller fan incorporated with advanced blade design (except FV-30AU9)
- Automatic Shutter
- Single Speed

Model No.	A	B	C	D	E	F	G	H
FV-20AU9	200	306	260	302	240	52	90	80
FV-25AU9	250	356	310	352	290	38	90	63
FV-30AU9	300	406	360	402	340	38	90	78

Specification



Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-20AU9	50	20	1,190	546	321	40	2.2	250 x 250
	60	24	1,340	600	353	44		
FV-25AU9	50	27	1,060	835	491	43	2.7	300 x 300
	60	36	1,110	846	498	43		
FV-30AU9	50	31	880	935	550	43	3.1	350 x 350
	60	38	880	915	539	43		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-20AL9/ FV-25AL9/ FV-30AL7 Automatic Shutter Louver Series

Dimension

Unit: mm
FV-20AL9



Model No.	A	B	C	D	E	F	G	H
FV-20AL9	200	306	260	302	240	68	90	80
FV-25AL9	250	356	310	352	290	63	90	63
FV-30AL7	300	406	360	402	340	63	90	78

- HP condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Propeller fan incorporated with advanced blade design (except FV-30AL7)
- Automatic Shutter
- Single Speed

Specification



Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-20AL9	50	20	1,190	546	321	40	2.2	250 x 250
	60	24	1,340	600	353	44		
FV-25AL9	50	27	1,060	835	491	43	2.7	300 x 300
	60	36	1,110	846	498	43		
FV-30AL7	50	31	880	935	550	43	3.1	350 x 350
	60	38	880	915	539	43		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-20RG7/ FV-25RG7/ FV-30RG7 Reversible Series

Dimension

Unit: mm
FV-20RG7



Model No.	A	B	C	D	E	F	G	H
FV-20RG7	200	306	260	302	240	52	90	80
FV-25RG7	250	356	310	352	290	38	90	63
FV-30RG7	300	406	360	402	340	38	90	78

- Reversible
- On-off and reverse operated by pull cord switch
- HP condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Propeller fan incorporated with advanced blade design (except FV-30RG7)
- Shutter operated by pull cord

Specification

Model No.		Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
					[CMH]	[CFM]			
FV-20RG7	Exhaust	50	20	1,260	580	341	36	2.2	250 x 250
		60	24	1,410	630	371	39		
	Intake	50	15	1,150	405	238	46		
		60	17	1,140	355	209	46		
FV-25RG7	Exhaust	50	27	1,090	945	556	38	2.4	300 x 300
		60	31	1,110	950	559	39		
	Intake	50	21	1,010	600	353	45		
		60	23	970	560	330	44		
FV-30RG7	Exhaust	50	31	885	1,165	686	39	2.8	350 x 350
		60	38	800	1,000	589	38		
	Intake	50	24	840	700	412	43		
		60	26	810	680	400	42		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-20RL7/ FV-25RL7/ FV-30RL6 Reversible Louver Series




- Reversible
- On-off and reverse operated by pull cord switch
- HP condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Propeller fan incorporated with advanced blade design (except FV-30RL6)
- Shutter operated by pull cord

Dimension

Unit: mm



Model No.	A	B	C	D	E	F	G	H
FV-20RL7	200	306	260	302	240	68	90	80




Model No.	A	B	C	D	E	F	G	H
FV-25RL7	250	356	310	352	290	63	90	63
FV-30RL6	300	406	360	402	340	63	90	78


Performance Data

(220V 50Hz/ 60Hz)


FV-20RL7



FV-25RL7



FV-30RL6



Specification

Model No.		Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
					[CMH]	[CFM]			
FV-20RL7	Exhaust	50	20	1,240	546	321	39	2.4	250 x 250
		60	24	1,290	570	335	43		
	Intake	50	15	1,190	370	218	46		
		60	17	1,180	340	200	46		
FV-25RL7	Exhaust	50	29	1,100	840	494	43	2.7	300 x 300
		60	33	1,100	835	491	43		
	Intake	50	21	1,035	580	341	45		
		60	23.5	1,035	560	330	44.5		
FV-30RL6	Exhaust	50	31	890	990	583	44	3.1	350 x 350
		60	38	880	945	556	43		
	Intake	50	25	770	600	353	43		
		60	26	770	600	353	44		


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-15AST1 Automatic Shutter Series



Dimension

Unit: mm



- Condenser motor with thermal cut-off
- Lubricated sintered bush for long life operation
- High performance propeller fan adopted
- Automatic shutter with plastic cushions
- Orifice equipped with oil cup

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-15AST1	50	15	1,480	288	170	31	1.4	175 x 175
	60	19	1,560	306	180	34		


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz.
R.P.M. data is for reference only, values may vary subject to different conditions.

FV-10BAT1 Plastic Series



Dimension

Unit: mm



- Condenser motor with thermal cut-off
- Lubricated sintered bush for long life operation
- Highly efficient sirocco fan
- Front louver with blind shutter
- Plastic frame, blade and louver

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-10BAT1	50	15	1,250	85	50	40	1.7	155 x 205
	60	17	1,200	76	45	40		


Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz.
R.P.M. data is for reference only, values may vary subject to different conditions.

WINDOW MOUNT TYPE VENTILATING FAN



1 High performance condenser motor with long life bearing

- Low power consumption (50% down VS previous model)
- Low noise level (6% down VS previous model)
- Long life up to 40,000 hours (1.5 time VS previous model)
- Comply with IPX4 (outside)



"HP motor" and "Bearing" are used

3 Strengthened Shutter Structure




Metallic shutter axis is used as the supporter for movement of shutter that provides a better endurance.


- Durable
- Sustainable to strong wind

2 Advanced Blade Design

- High Air Volume
- Low noise level (6% down VS previous model)



Leading Edge forms no obstacle to airflow that streamlines airflow from every direction




Air Foil Chip is to reduce turbulence at rear edge, and curvature of front edge is improved for smooth airflow that minimizes fan noise as well.

FV-15WU4 / FV-20WU4 Cord-operated Shutter Series



FV-15WU4, FV-20WU4

Dimension Unit: mm



Applicable Glass Thickness = 3mm - 7mm

- HP condenser motor with thermal cut-off
- Well lubricated bearing for long life operation
- Propeller fan incorporated with advanced blade design
- Shutter operated by pull cord
- Metallic shutter axis

Model No.	A	B	C	D	E	F	G	H
FV-15WU4	150	210	97	43	54	37	177	149
FV-20WU4	200	271	98	36	62	36	237	201

Specification

Model No.	Hz	Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Installation Space [mm]
				[CMH]	[CFM]			
FV-15WU4	50	8	1,463	210	124	35	0.9	Ø 186 - Ø188
	60	9	1,393	198	117	34		
FV-20WU4	50	16	1,042	360	212	32	1.1	Ø 247 - Ø250
	60	19	1,024	360	212	31		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

RANGE HOOD



Powerful Airflow





Sirocco Fan

Sirocco Fans are adopted that maintain better performance than turbo fan and keep a low noise level.

A range hood must overcome resistance when pushing air from the inlet, through the duct, to the outside of the building. This resistance is known as static pressure. The amount of static pressure depends on the duct length, type of duct and bending. Longer duct and more bending generate higher static pressure, that result decrease in air volume.

Many installations require long duct and at least one bending. As shown in the figure, duct of 1.5m length and grille are installed (*), static pressure increases to 80Pa. Under this condition (*), air volume of Panasonic rangehood can maintain up to 580 CMH (Point C) while other brands are decreased to 530 CMH (Point D).

These hoods are enclosed casings equipped with blowers to capture odors and oil fumes from cooking areas. Most range hoods are installed over the cooking surface in order to maximize exhaust effectiveness.



Installation of Rangehood with 1.5m duct and grille.

Comparison of Suction Power	Air Volume [CMH]				
	Without duct	5m duct	10m duct	15m duct	1.5m duct grille (*)
FV-70HQD1 (Super)	730	650	610	560	580 (C)
Other Brand	720	610	540	480	530 (D)

Prolonged Off-Timer

The 8-minute prolonged off-timer design absorbs residual oil vapor after cooking (FV-70HQD1 only).


FV-70HQU1 Twin Motor Type




Silver

- Equipped with powerful sirocco fan
- 2-speed selection with 2-motor operating individually
- Rocker switch
- Easy detachable for cleaning
- Slim design with only 120mm body thickness
- Color option: champagne gold, silver or white

Dimension Unit: mm



Performance Data (220V 50Hz/60Hz)



Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]
					[CMH]	[CFM]			
FV-70HQU1	50	High	140	905	730	430	53	17	Ø150
		Low	72	565	400	235			

Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


FV-70HQD1 Twin Motor Type




Champagne gold

- Equipped with powerful sirocco fan
- 3-speed selection with 2-motor operating simultaneously
- Soft touch switch
- LED indicator and delay timer built-in
- Easy detachable for cleaning
- Slim design with only 120mm body thickness
- Color option: champagne gold, silver or white

Dimension Unit: mm



Performance Data (220V 50Hz/60Hz)



Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]
					[CMH]	[CFM]			
FV-70HQD1	50	Super	140	905	730	430	53	17	Ø150
		High	95	665	500	294			
		Low	72	565	400	235			

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

FV-90HQU1 Twin Motor Type




Dark Grey

- Equipped with powerful sirocco fan
- 2-speed selection with 2-motor operating individually
- Rocker switch
- Easy detachable for cleaning
- Slim design with only 115mm body thickness
- Color option: silver or dark grey


Dimension

Unit: mm



Performance Data

[220V 50Hz/60Hz]



Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Volume		Noise [dB(A)]	Weight [kg]	Duct Size [mm]
					[CMH]	[CFM]			
FV-90HQU1	50	Hi	152	993	785	462	52	18	Ø 150
		Lo	75	570	484	285	38		
	60	Hi	127	905	779	459	38		
		Lo	69	594	464	273	41		

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

HAND DRYER



Power Dry hand dryer provides a comfortable and speedy hand drying experience by removing moistures on hands with warm and high velocity airflow. In addition, environment protection and cost saving are achieved by comparing with using paper towel.

New Features of Power Dry

Safe Operation

- Power Dry will stop after 60 seconds of continuous operation
- "Check" indicator will light up when the unit detects overheated

Quick Response Sensor

- Automatic sensor operation, no physical contact is required to activate the unit



Heater ON/OFF Switch

- Heater can be switched off for energy saving in hot season

Full Tank Indicator (FJ-T09A3 only)

- Remind you for cleaning up the water tank when it is full



Easy Installation

- Metallic bracket for wall hanging attached
- Stylish and streamline design fits most interior

Anti-bacteria Material

- The product body is adopted with anti-bacteria material to prevent the growth of bacteria and germs in the warm and humid environment of washroom

Drain Pan (FJ-T09A3 only)



- Drain pan can reduce water dripping on floor to avoid slippery



Super alleru-buster Filter

- The filter is equipped to ensure the air blow to your hand is clean

Quick Drying with 3 way Airflow

Wide Nozzle

Blow off water droplets on the whole palm with wide airflow.

Spot Nozzle


Dry fine water droplets by rubbing hands with spot airflow.



2 kinds of nozzle, wide nozzle and spot nozzle, are equipped at front and rear of drying chamber respectively for efficient drying. The new structure realizes quick drying in only 4-9 seconds.

What is Super alleru-buster?

Super alleru-buster can inhibit up to several types of allergen.



Testing Organization: The Osaka Municipal Technical Research Institute.
Testing Method: to measure the level of reduction in cat's dandruff by Enzyme-linked Immuno Sorbent Assay.

FJ-T10T1, FJ-T09A3, FJ-T09B3



FJ-T10T1



FJ-T09A3
With Drain Pan




FJ-T09B3
Without Drain Pan

- Double-side & quad-row airflow for dual wiping effect
- Conical flask shaped nozzles for strong blow airflow
- Blue LED light reminds elapsed time of drying
- Super alleru-buster filter equipped
- Anti-bacteria material adopted for hand drying section
- Heater On/Off selectable

- Powerful air velocity enables drying time in few seconds
- Automatic operation by infra-red motion sensor
- Super-alleru buster filter equipped
- Anti-bacteria material adopted
- Heater ON/OFF switch for energy saving
- Safety check light function terminate the operation in case overload
- Drain pan and water tray equipped (FJ-T09A3 only)

Dimension

Unit: mm



Specification


Model No.	Power Consumption [W]		Air Velocity [m/min]	Noise [dB(A)]	Drain Pan	Weight [kg]
	Heater ON	Heater OFF				
FJ-T10T1	1,250	800	-	59	Yes	8
FJ-T09A3	1,020	650	90-110	62	Yes	4
FJ-T09B3	1,020	650	90-110	62	No	3.5

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz.

AIR CURTAIN



Air Curtain - Improved Functionality and Workability



Length of unit	900mm (3 feet) FY-12ESN	1200mm (4 feet) FY-12ELN	900mm (3 feet) FY-14ESN	1200mm (4 feet) FY-14ELN
Air velocity chart (m/s) Maximum value at HI speed 50Hz				
Efficient distance	3.5m (12 feet)		4.0m (14 feet)	


FY-12ESN/14ESN Standard Type - 900mm



- Product length = 900mm
- Unique sirocco fan design
- Either wall hanging or suspending from ceiling
- Air deflection vent for adjusting air flow direction
- 2-speed changeover by push button switch
- ABS resin casing provides better weather resistance
- Optional suspending hanger available

Dimension

Unit: mm



Model No.	A	B	C	D	E	F	G	H
FY-12ESN / FY-14ESN	900	50	400	120	63	205	226	250

Specification

Model No.	Hz		Consumption [W]	Air Volume		Current [A]	Outlet Velocity [m/s]	Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]				
FY-12ESN	50	Hi	176	1,050	618	0.82	16.9	55	13
		Lo	155	960	565	0.69	15.8	50	
	60	Hi	202	990	583	0.94	16.1	54	
		Lo	170	940	553	0.75	15.3	49	
FY-14ESN	50	Hi	257	1,340	789	1.14	21.9	62	13
		Lo	218	1,168	687	0.99	19.1	59	
	60	Hi	312	1,303	767	1.43	21.3	61	
		Lo	255	1,083	637	1.16	17.7	57	

Note: The Value In Specification tables are representative characteristic value at 220V, 50/60Hz


FY-12ELN/14ELN Extra Type - 1200mm



- Product length = 1200mm
- Unique sirocco fan design
- Either wall hanging or suspending from ceiling
- Air deflection vent for adjusting air flow direction
- 2-speed changeover by push button switch
- ABS resin casing provides better weather resistance
- Optional suspending hanger available

Dimension

Unit: mm



Model No.	A	B	C	D	E	F	G
FY-12ELN / FY-14ELN	1,200	200	400	120	63	205	226

Specification

Model No.	Hz		Consumption [W]	Air Volume		Current [A]	Outlet Velocity [m/s]	Noise [dB(A)]	Weight [kg]
				[CMH]	[CFM]				
FY-12ELN	50	Hi	224	1,420	836	1.04	17	56	15
		Lo	200	1,320	777	0.9	15.8	51	
	60	Hi	258	1,340	789	1.21	16.2	55	
		Lo	220	1,290	759	1.04	15.4	50	
FY-14ELN	50	Hi	333	1,867	1,099	1.52	22.5	63	15
		Lo	290	1,668	982	1.32	20.1	61	
	60	Hi	423	1,826	1,075	1.93	22	63	
		Lo	339	1,552	913	1.55	18.7	59	

Note: The Value In Specification tables are representative characteristic value at 220V, 50/60Hz

AIR MOVING EQUIPMENT



COMPACT AXIAL FLOW FAN (50Hz)




Single Phase

FY-25DSF2NET
 FY-28DSM2NET
 FY-35DSM2NET
 FY-40DSL2NET
 FY-40DSH2NET
 FY-45DST2NET

Three Phase

FY-40DTL2BET
 FY-40DTH2BET
 FY-45DTT2BET
 FY-45DTH2BET

Performance Data (230V 50Hz)



Specification (50Hz)

	MODEL No.		Consumption [W]	Air Volume		Noise Level [dB]			Wheel Diameter [cm]	Weight [kg]	Duct Size [mm]
				[CMH]	[CFM]	Side of Body	Inlet Side	Outlet Side			
Single-phase	FY-25DSF2NET	Hi	34	600	353	41.0	51.0	50.5	25	4.7	Ø200
		Lo	27	550	324	39.5	49.0	48.5			
	FY-28DSM2NET	Hi	51	1,194	703	44.5	54.5	54.0	28	8.5	Ø250
		Lo	55	1,050	618	42.0	52.0	51.5			
	FY-35DSM2NET	Hi	95	2,016	1,187	45.5	56.5	56.0	35	13.0	Ø300
		Lo	87	1,782	1,049	43.0	54.0	53.5			
FY-40DSL2NET	Hi	204	3,228	1,900	56.0	68.0	67.5	40	20.0	Ø350	
	Lo	194	3,084	1,815	54.0	66.0	65.5				
FY-40DSH2NET	Hi	256	3,504	2,062	55.5	67.5	67.0	40	22.0	Ø350	
	Lo	233	3,444	2,027	53.5	65.5	65.0				
FY-45DST2NET	Hi	428	4,968	2,924	59.5	69.5	69.5	45	37.0	Ø400	
	Lo	398	4,206	2,476	58.0	68.0	68.0				
Three-phase	FY-40DTL2BET	Hi	241	3,396	1,999	56.0	68.0	67.5	40	18.0	Ø350
		Lo	237	3,330	1,960	54.0	66.0	65.5			
	FY-40DTH2BET	Hi	250	3,426	2,016	56.0	68.0	67.5	40	19.0	Ø350
		Lo	220	3,264	1,921	55.0	67.0	66.5			
	FY-45DTT2BET	Hi	421	5,004	2,945	61.0	71.0	71.0	45	36.0	Ø400
Lo		397	4,860	2,860	60.5	70.5	70.5				
FY-45DTH2BET	Hi	511	5,454	3,210	59.0	68.5	68.5	45	37.0	Ø400	
	Lo	482	5,250	3,090	58.5	68.0	68.0				

Note: In above table, the values are tested 230V for Single-phase Models, and 380V for Three-phase Models.

- The values of air volume are measured at 0 static pressure (Pa) by the chamber method.
- The values of Current and Input are in the free load condition.
- The values of noise level are measured at 0 static pressure [Pa] and at the following positions.
 (When ducts are connected on both inlet and outlet side.)
 Side of fan body : 1.5m apart from the fan body [excluding the noise of outlet side]
 Inlet side : 1.5m apart from the inlet of the fan [excluding the noise of outlet side]
 Outlet side : 1.5m angle 45° apart from outlet side [excluding the noise of inlet side]
 Add 2dB to the values above for the noise levels apart from 1.0 m.
- Specifications above indicate the values under the condition of normal temperature [20 degrees Celsius].

Use condition:

- Use in the following conditions
 Handling air and Ambient air : -10 to +40 deg C, relative humidity 85% or less
- Do not use the product in the places such as outdoor [where rain water splashes], where water splashes, steam is always generated, corrosive gas may be generated, or chemicals may be used.
- Do not use the product in the places such as pools or hot springs where the chemicals such as chlorine are used. It has high possibility to cause corrosion in a short term.

MINI SIROCCO FAN (60Hz)



Single Phase


**FY-10CG1 / FY-12CG1 /
FY-14CG1 / FY-16CG1 /
FY-17CG1 / FY-19CG1 /
FY-21CG1**

Three Phase

FY-21CT1

- Long life induction motor with thermal cut-off
- High efficient sirocco fan employed for powerful airflow
- Outlet direction is adjustable to vertical or horizontal position
- Compact size
- 2-speed selectable (except FY-10CG1, FY-12CG1, FY-14CG1)

Performance Data (230V 60Hz)



Specification (60Hz)

	Model No.	Hz	Consumption [W]	R.P.M [min ⁻¹]	Air Volume		Noise [dB (A)]			Weight [kg]	Duct Size [mm]	Impeller Diameter [cm]	
					[CMH]	[CFM]	Casing Side	Suction Side	Discharge Side				
Single Phase	FY-10CG1	60	-	13	970	143	84	32	38	38	3.1	∅100	10
	FY-12CG1	60	-	22	725	242	142	32	38	38	3.6	∅150	12
	FY-14CG1	60	-	40	870	284	167	36	41.5	41.5	3.8	∅150	12
	FY-16CG1	60	Lo	59	1,060	470	277	42.5	49	49	5.3	∅150	15
			Hi	40	805	335	197	36	42.5	42.5			
	FY-17CG1	60	Lo	95	850	722	425	44.5	49	49	8.8	∅200	18
			Hi	79	730	593	349	40	45	45			
	FY-19CG1	60	Lo	143	1,100	931	548	50	55	55	9.4	∅200	18
Hi			127	985	791	466	48	53	53				
FY-21CG1	60	Lo	340	1,430	1,540	906	59	63	63	15	∅200	20	
		Hi	300	1,180	1,230	724	54	58.5	58.5				
Three Phase	FY-21CT1	60	Hi	370	1,485	1,590	936	59.5	63.5	63.5	14.5	∅200	20
		Lo	228	1,030	1,020	600	50	54	54				

Note: In above table, the values are tested 230V for Single-phase Models, and 380V for Three-phase Models

1. Power consumption is expressed as open value.

2. Air volume is measured using the Chamber method (JIS B 8330 or JIS C 9603) at 0 Pa static pressure.

3. Noise: Suction side - Noise at 1.5m at suction side. Casting side - Noise at 1.5m on the side of a machine body. Discharge side - Noise at 1.5m orthogonally at discharge side.

Use condition:

- Don't use it for ventilation at a site generating heat, oily smoke, steam and/or moisture. (Environmental condition : -10 deg C~+40 deg C, relative humidity below 85%)
- Install a door 600x600mm or more for maintenance purpose.
- Install a leak breaker or a motor breaker on the source site. A control panel such as a contact switch relay is required for three phase power source.
- In cold air supply to indoor during winter and at any other occasion susceptible to dew drop, heat insulation is required.
- It is recommended to use a commercially available filter at the suction side to avoid dust and/or oil waste attachment on a blade.
- Install it on a horizontal direction.
- Do not perform parallel operation of more than one unit on a switch, for it may result in motor failure.

ACCESSORIES




PIPE HOOD



With Net (MGX)

Without Net (MCX)



Model No.	A	B	C	D	E
FV-MGX100P	141	79	20	97	48
FV-MGX150P	190	106	23	147	53
FV-MCX100P	141	79	20	97	48
FV-MCX150P	190	106	23	147	53


With Net

FV-MGX100P FV-MGX150P

Without Net

FV-MCX100P FV-MCX150P


- High strength – adopt 0.5mm thickness SUS 304 stainless steel
- Excellent anti-rust capability – hood part coated with metallic silver paint prevent oxidation of material
- Easy installation – 3pcs of spring clip facilitate duct / pipe connection
- 2.5mm x 2.5mm net keep out ingress of small particles and insects from outside (FV-MGX100P & FV-MGX150P)
- It is recommended to use pipe hood with net at intake terminal while without net at exhaust



Specification


Model No.	Diameter of Applicable Pipe [mm]	Material	Dimension of Net [mm]
FV-MGX100P	100	Stainless Steel	2.5 x 2.5
FV-MGX150P	150	Stainless Steel	2.5 x 2.5
FV-MCX100P	100	Stainless Steel	-
FV-MCX150P	150	Stainless Steel	-

VENT CAP



With Net (VGX)

Without Net (VCX)



Model No.	A	B	C	D	E
FV-VGX100P	120	97	145	13	47
FV-VGX150P	169	147	195	18	52
FV-VCX100P	120	97	145	13	47
FV-VCX150P	169	147	195	18	52


With Net

FV-VGX100P FV-VGX150P

Without Net

FV-VCX100P FV-VCX150P


- High strength – adopt 0.5mm thickness SUS 304 stainless steel
- Easy installation – 3pcs of spring clip facilitate duct / pipe connection
- 2.5mm x 2.5mm net keep out ingress of small particles and insects from outside (FV-VGX100P & FV-VGX150P)
- It is recommended to use vent cap with net at intake terminal while without net at exhaust



Specification

Model No.	Diameter of Applicable Pipe [mm]	Material	Dimension of Net [mm]
FV-VGX100P	100	Stainless Steel	2.5 x 2.5
FV-VGX150P	150	Stainless Steel	2.5 x 2.5
FV-VCX100P	100	Stainless Steel	-
FV-VCX150P	150	Stainless Steel	-

ELECTRIC FAN



Safety Features for Ceiling Fan

1 Cut-off Safety Switch


Patents registration in Japan, The United States, China, Malaysia and Vietnam

Problem

In case there is any wear at either the shaft or the bolt, abnormal wobbling of fan will occur as it runs. The wear will be further enlarged if the fan continues to operate, and the part or fastener will break eventually.


Our solution

Cut-off safety switch is equipped to cut off power supply while dangerous wear and tear of the shaft or bolt are detected. As abnormal wobbling occurs, the lever will detach from the switch and the fan will stop. It will prevent further wear to the damaged part. It can minimize the fracture of the part that reduces the possibility of falling of fan.



2 Safety Hook

Patents registration in Japan, The United States, China and Vietnam




Problem

Blade fins may fall off from the fan motor in case fatigue of material occurs.

Our solution

An exclusively designed fall prevention hook is equipped on the back of motor. This mechanism secures against falling of blades caused by damaging wear.

3 Safety Wire



Problem

Fan motor may fall from the pipe rod accidentally whatever any factors, such as wearing of shaft bolt, etc.

Our solution

Safety wire is adopted to secure the fan motor with the ceiling hook that prevents falling of the motor when detaching of the fan motor from the pipe rod occurs.


4 Wobbling Reduction Mechanism

Problem

Improper wobbling cause striking between bolt, motor shaft and pipe that wearing will be formed. Fracture may be happened when the wear of those parts are enlarged.

Our solution

The newly developed anti-wobbling structure can reduce wobbling between bolt, motor shaft and pipe. It can minimize wearing of motor shaft and bolt to prevent falling of fan.




Other Features

1 1/f Yuragi (Natural Breeze) *1/f yuragi*

These fans are equipped with 1/f Yuragi function which is a fluctuated pattern acting a gentle breeze. By this sophisticated formula, in varying air velocity and controlling wind force, these new ceiling fans present you a peaceful and comfortable feeling.

Current function rhythm breeze


Speed notch toggles by 4 seconds regularly.



This regular pattern makes body temperature falling after a period of time. After that, you may feel anxious and uncomfortable when the wind velocity changes.

New function 1/f Yuragi



Speed notch toggles based on Yuragi pattern.




Incorporated with this human-concerned technology, this kind of rhythm maintains your external body temperature by giving you a feeling of natural wind when there is a change of wind velocity.

2 3D Blade (Powerful Airflow)

With the exclusive and unique 3D blade design, it provides a smooth and strong air flow while maintaining operating noise in low level.



3D curve design in the center of blade effectively catch the air.




3 ON Timer

On Timer can be incorporated with air conditioner to realize economy and comfortable operation. It can minimize excessive cold feeling and save power consumption during your sleep.




4 Sleep Mode

The fan is equipped with Sleep Mode, by which fan speed and timer will gradually go down until the fan is off. The function not only creates an optimal sleeping environment, but also enhances energy saving as well.



5 LED Lamp

The embedded LED illumination lamp has 2 selection of color, blue or white. Incorporated with contemporary interior, they can foster a charming atmosphere to the room.




Blue Lamp

White Lamp

6 Direct Current Motor (F-60UFN, F-60TAN, F-60TDN)


Newly developed direct current (DC) motor are adopted in these fans. Power consumption is reduced as compared with alternative current (AC) motor that energy saving is achieved. DC motor has lighter weight compared with conventional AC motor, that allows easy handling for DC ceiling fan.

Direct Current (DC) Motor



Electric power input is required for stator only

Alternative Current (AC) Motor



Electric power input is required for both rotor and stator

7 Auto Mode with ECONAVI Function

F-60TAN is equipped with temperature sensor. Incorporated with ECONAVI function, the innovative Auto Mode function is enhanced. This function controls the fan to generate the most comfortable air velocity to human body subject to the change of room temperature.


The sensor monitors the surrounding temperature change and air velocity will vary automatically in accordance with below table.

Range of Room Temperature	Change of Room Temperature		Change of Speed F-60TAN	
	-1°C	+1°C	-	+
Above 30°C	Blue bar	Red bar	Blue bar	Red bar
30°C - 29°C	Blue bar	Red bar	Blue bar	Red bar
29°C - 24°C	Blue bar	Red bar	Blue bar	Red bar
Below 24°C	Blue bar	Red bar	No Change	

Speed change for ECONAVI is among speed 1 to speed 9

8 Comfort Eco (F-60TAN, F-56PZM)

The figure illustrates the effect of using air conditioner and ceiling fan with 'Auto Mode'. The fan speed is adjusted according to room temperature monitored by the thermal sensor. Room temperature decreases to 28°C over a period, while the sensible temperature could be maintained to 26.7°C, which is said to be most comfortable to human body.




F-60UFN Ceiling Fan - Super Deluxe Series



- Dual function: Fan and Light
- Direct Current (DC) motor adopted
- LED lighting with brightness for daily life
- Selectable light color (White/Daylight/Warm)
- 5-PPG Blade material for durability
- 1/f Yuragi Function
- LCD wireless remote control
- Equipped with safety device
- 1-8 Hours On & Off timer
- 2-8 hours Sleep mode
- Color: Silver

Dimension


Unit: mm




Specification

Model No.	Voltage		Consumption		Air Velocity		Air Delivery		Weight [kg]
	[V]	[Hz]	Fan	Fan+Light	[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-60UFN	220	50	37	59	200	656	235	8,299	6.2

Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.




F-60TAN Ceiling Fan- Super Delux Series



Dimension

Unit: mm



- Direct current (DC) motor adopted
- Auto mode with ECONAVI function by temperature sensor
- 1/f Yuragi function
- 3D blade delivers smooth and strong airflow
- PPG blade material for durability
- LCD wireless remote control
- 9-speed control
- Sleep mode with On time & Off time
- Equipped with safety device
- Blade safety plate and safety wire attached

Specification

Model No.	[V]	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-60TAN	220	Hi	37	228	200	656	235	8,299	5.3
		Lo	3	80	-	-	-	-	
	230	Hi	39	230	205	673	240	8,476	
		Lo	3	80	-	-	-	-	

* Hi - Notch 9 / Lo - Notch 1


Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-56PZM Ceiling Fan - Super Deluxe Series



Dimension

Unit: mm



- Temperature sensor for auto airflow adjustment
- LED illumination lamp equipped
- 1/f Yuragi function
- 3D blade delivers smooth and strong airflow
- PPG blade material for durability
- LCD wireless remote controller
- 5-speed selection
- Sleep mode
- 8-hour off timer
- Equipped with cut-off safety device
- Blade safety plate attached
- Safety wire adopted


Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-56PZM	50	Hi	70	195	175	574	215	7,593	6.4
		Lo	18	87	-	-	-	-	


* Hi-Notch 5 / Lo-Notch 1

Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-60TDN Ceiling Fan- Deluxe Series



Dimension Unit: mm



- Direct current (DC) motor adopted
- 1/f Yuragi function
- 3D blade delivers smooth and strong airflow
- PPG blade material for durability
- LCD wireless remote control
- 9-speed control
- Sleep mode with On timer & Off timer
- Equipped with safety device
- Blade safety plate and safety wire attached

Specification

Model No.	[V]	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-60TDN	220	Hi	37	228	200	656	235	8,299	5.3
		Lo	3	80	-	-	-	-	
	230	Hi	39	230	205	673	240	8,476	
		Lo	3	80	-	-	-	-	


* Hi - Notch 9 / Lo - Notch 1

Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-60WWK Ceiling Fan- Deluxe Series



Dimension Unit: mm



- 1/f Yuragi function
- 3D blade delivers smooth and strong airflow
- PPG blade material for durability
- LCD wireless remote controller
- 7 speed control
- Sleep mode
- 8-hour off timer
- Equipped with cut-off safety device
- Blade safety plate attached
- Safety wire adopted

Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-60WWK	50	Hi	80	183	191	627	220	7,769	8
		Lo	23	83	-	-	-	-	

* Hi-Notch 7 / Lo-Notch 1


Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-56MPG Ceiling Fan - Wireless Remote Control Series



Dimension

Unit: mm



- Wireless remote controller
- 3-speed selection
- 1, 3, 6 hours timer
- Sleep mode
- Thermal fuse prevent overheating or power surge
- Safety wire provided
- Cut-off safety switch equipped
- Fall prevention of blade adopted
- Permanently lubricated ball-bearing assembly
- Color: Gold or Silver

Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-56MPG	50	Hi	59	184	150	492	180	6,357	7
		Lo	17	88	-	-	-	-	
	60	Hi	69	180	150	492	190	6,710	
		Lo	19	88	-	-	-	-	

* Hi-Notch 3 / Lo-Notch 1


Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-56MZG Ceiling Fan - Wireless Remote Control Series



Dimension

Unit: mm



- Wireless remote controller
- 3-speed selection
- 1, 3, 6 hours timer
- Sleep mode
- Thermal fuse prevent overheating or power surge
- Safety wire provided
- Cut-off safety switch equipped
- Fall prevention of blade adopted
- Permanently lubricated ball-bearing assembly
- Color: Gold or Silver

Pipe Type	9 inch	12 inch	16 inch	18 inch	22 inch
Pipe Length	229	305	406	457	559
E	332.5	408.5	509.5	560.5	662.5
F	430.0	506.0	607.0	658.0	760.0

Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-56MZG	50	Hi	59	184	150	492	180	6,357	6.9
		Lo	17	88	-	-	-	-	
	60	Hi	69	180	150	492	190	6,710	
		Lo	19	88	-	-	-	-	

* Hi-Notch 3 / Lo-Notch 1


Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-60MZZ Ceiling Fan - Regulator Control Series



Dimension

Unit: mm



Pipe Type	9 inch	12 inch	16 inch	18 inch	22 inch
Pipe Length	229	305	406	457	559
F	375.7	451.7	552.7	603.7	705.7

Model No.	A	C
F-60MZZ	84.2	ø1,500

- Compact size condenser controlled regulator
- 5-speed selection
- Thermal fuse prevent overheating or power surge
- Safety wire provided
- Cut-off safety switch equipped
- Fall prevention of blade adopted
- Permanently lubricated ball-bearing assembly
- Color: Body - White

Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-60MZZ	50	Hi	66	225	150	492	215	7,593	6.1
		Lo	15	94	-	-	-	-	
	60	Hi	78	234	155	509	225	7,946	
		Lo	16	92	-	-	-	-	

* Hi-Notch 5 / Lo-Notch 1

Note: The value in Specification table are representative characteristics value at 220V, 50Hz. R.P.M. data is for reference only, values may vary subject to different conditions.


F-409Q Cycle Fan



- Oscillation over 360°
- 5-speed and on/off by wired regulator
- Easy angle adjustment
- Metal blade
- Color: Blue or Gold

Adjustment of Circulating Angle

The oscillation angle can be adjusted to 15,30 or 50 degrees.



Specification

Model No.	Hz	*	Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-409Q	50	Hi	46.8 - 57.2	1,080 - 1,320	256	840	79	2,790	4.3
		Lo	22.5 - 27.5	690 - 850	-	-	-	-	
	60	Hi	57.7 - 70.5	1,160 - 1,410	277	909	86	3,037	
		Lo	26.6 - 32.5	710 - 860	-	-	-	-	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-409M Wall Fan - Remote Control Type




Grey

Blue

- Wireless remote controller
- Oscillation control
- Easy angle adjustment
- 3-speed and off electronic switch
- Transparent plastic blade
- Color: Blue or Grey


Adjustment of Circulation Angle “One-touch” adjustment of tilt

The air flow can be adjusted upward or downward by simply moving the guard up or down as shown in the figure. Adjust the angle of the fan only after first confirming that it has stopped rotating.



Double oscillation

To change the direction of the air flow, push the edge of the guard to the desired position.




Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-409M	50	Hi	46.8 - 57.2	1,055 - 1,289	228	748	63	2,225	4.4
		Lo	37.9 - 46.3	688 - 840	-	-	-	-	
	60	Hi	56.1 - 68.5	1,094 - 1,337	237	778	65	2,295	
		Lo	37.9 - 46.3	625 - 763	-	-	-	-	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-409U Wall Fan - Cord Operated Type




Blue

Gold

- Oscillation control
- 3-speed and on/off by pull switch
- Easy angle adjustment
- Blade - Metallic material
- Color: Blue or Gold


Adjustment of Circulation Angle “One-touch” adjustment of tilt

The air flow can be adjusted upward or downward by simply moving the guard up or down as shown in the figure. Adjust the angle of the fan only after first confirming that it has stopped rotating.



Double oscillation

To change the direction of the air flow, push the edge of the guard to the desired position.




Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery		Weight [kg]
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]	
F-409U	50	Hi	42.5 - 51.9	1,097 - 1,341	226	741	63	2,225	4.4
		Lo	33.5 - 40.9	744 - 910	-	-	-	-	
	60	Hi	52.8 - 64.6	1,166 - 1,425	241	791	67	2,366	
		Lo	34.7 - 42.5	676 - 826	-	-	-	-	

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-409K 40cm (16")



- Wireless remote control
- 3-speed and off electronic switch
- Rhythm breeze function
- Height adjustable:
128cm-143cm (50"-56")
- Transparent plastic blade
- Color: Blue or Beige or Red (Vietnam only)

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery	
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]
F-409K	50	Hi	46.8-57.2	1,055-1,289	228	748	63	2,225
		Lo	37.9-46.3	688-840	-	-	-	-
	60	Hi	56.1-68.5	1,094-1,337	237	778	65	2,295
		Lo	37.9-46.3	625-763	-	-	-	-

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-407W 40cm (16")



- 3-speed and off push-button switch
- Attractive twin lamps
- Height adjustable:
134cm-157cm (52^{3/4}-61^{3/4})
- Metal blade
- Color: Blue or Gold

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery	
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]
F-407W	50	Hi	47.9-58.5	1,097-1,341	226	741	63	2,225
		Lo	38.9-47.5	744-910	-	-	-	-
	60	Hi	58.2-71.2	1,166-1,425	241	791	67	2,366
		Lo	40.1-49.1	676-826	-	-	-	-

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

F-308NH/F-307KH 30cm (12")



- 1/f Yuragi function
- 3-speed and electronic ON/OFF switch
- Slim and compact motor design
- 4-hour electronic timer
- Height adjustable: 91cm-105cm (36"-41")
- Wireless remote control
- Transparent plastic blade
- Color: Baby Pink or Pastel Blue



Remote Control



- 1/f Yuragi function
- The attached air filter combines Super alleru-buster, Green Tea Catechin and Anti-bacteria Enzyme functions
- 3-speed and electronic ON/OFF switch
- Wireless remote control
- Height adjustable: 66cm-85cm (26"-33")
- 4-hour electronic timer
- Transparent plastic blade
- Color: Metallic Green or Silver



Remote Control

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity [m/min]	Air Delivery		Weight [kg]
						[m ³ /min]	CFM	
F-308NH	50	Hi	34-42	935-1,140	181	40	1,412	4.8
		Lo	19-25	630-800	-	-	-	

Note: All values in specification table are at 220V

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity [m/min]	Air Delivery		Weight [kg]
						[m ³ /min]	CFM	
F-307KH	50	Hi	44	968-1232	201	51	1,801	4.1
		Lo	25	711-940	-	-	-	

Note: All values in specification table are at 220V

F-400C 40cm (16")



Beige gray

- 3-speed and push-button switch
- Transparent plastic blade
- Color: Ivory or Beige gray

Specification

Model No.	Hz		Consumption [W]	R.P.M. [min ⁻¹]	Air Velocity		Air Delivery	
					[m/min]	[ft/min]	[m ³ /min]	[ft ³ /min]
F-400C	50	Hi	44.0-53.8	1,055-1,289	228	748	63	2,225
		Lo	33.9-41.5	688-840	-	-	-	-
	60	Hi	54.0-66.0	1,094-1,337	237	778	65	2,295
		Lo	35.0-42.8	625-763	-	-	-	-

Note: The value in Specification table are representative characteristics value at 220V, 50/60Hz. R.P.M. data is for reference only, values may vary subject to different conditions.

VENTILATION PRODUCT SPECIFICATION

	Model No.	Phase	Consumption [W]		R.P.M [min ⁻¹]		Air Volume				Noise [dB(A)]		Weight [kg]	Duct Size [mm]	
			50Hz	60Hz	50Hz	60Hz	50Hz		60Hz		50Hz	60Hz			
							[CMH]	[CFM]	[CMH]	[CFM]					
Ceiling Mount Type Ventilating Fan	FV-24JR2	1	8	8	-	-	160	94	160	94	31	31	2.9	Ø100	
	FV-24JA2	1	8	8	-	-	160	94	160	94	31	31	2.9	Ø100	
	FV-17CU7	1	11	11	790	800	85	50	85	50	26	28	1.9	Ø100	
	FV-24CU7	1	14	16	690	690	140	82	140	82	28	29	2.9	Ø100	
	FV-24CD7	1	17	19	790	805	170	100	170	100	31	33	3.0	Ø100	
	FV-24CH7	1	20	24	870	840	200	118	190	112	35	35	3.0	Ø100	
	FV-27CH9	1	Hi	28	33	570	570	330	194	330	194	34	34	4.4	Ø150
		1	Lo	23	26	480	490	260	153	270	159	30	31		
	FV-32CD9	1	Hi	42	48	590	580	430	253	410	241	36	36	5.2	Ø150
		1	Lo	32	33	460	450	300	177	285	168	28	28		
	FV-32CH9	1	Hi	55	61	710	695	530	312	525	309	41	41	5.6	Ø150
		1	Lo	45	47	570	540	400	235	390	230	34	33		
	FV-38CD8	1	Hi	90	98	645	628	640	377	630	371	44	44	9.7	Ø150
		1	Lo	66	66	456	439	430	253	410	241	35	35		
FV-38CH8	1	Hi	122	138	790	760	800	471	790	465	50	49	10.4	Ø150	
	1	Lo	89	90	540	509	525	309	500	294	40	39			
FV-20CUT1	1		22.6	23.9	1,153	1,245	438	258	436	257	40.5	41.4	1.8		
Low Noise Type Cabinet Fan (In-line Fan)	FV-12NS3	1	Hi	18	23	1,265	1,370	180	106	190	112	21	22	5.5	Ø100
		1	Lo	17	19	1,020	1,000	145	85	145	85	17	18		
	FV-15NS3	1	Hi	33	42	1,270	1,385	340	200	370	218	25	27	6.5	Ø150
		1	Lo	29.5	33	1,100	1,040	275	162	260	153	22	22		
	FV-18NS3	1	Hi	60	73	1,250	1,260	500	294	490	288	29	30	8.5	Ø150
		1	Lo	55	62.5	1,100	990	405	238	385	227	27	26		
	FV-18NF3	1	Hi	91	119	1,190	1,245	770	453	760	447	31	32	10.0	Ø200
		1	Lo	80	87	1,000	990	620	365	580	341	29	28		
	FV-20NS3	1	Hi	120	159	1,195	1,165	920	541	860	506	32	32	14.0	Ø200
		1	Lo	113	128	1,000	875	720	424	620	365	29	26		
	FV-23NL3	1	Hi	230	310	1,245	1,210	1,200	706	1,100	647	40	40	18.0	Ø200
		1	Lo	170	190	985	890	900	530	800	471	34	32		
	FV-25NS3	1	Hi	345	425	1,125	1,100	1,700	1,001	1,650	971	41	41	24.0	Ø250
		1	Lo	265	300	950	890	1,380	812	1,200	706	38	39		
	FV-25NF3	1	Hi	390	520	1,225	1,245	1,900	1,118	1,810	1,065	43	42	24.0	Ø250
		1	Lo	325	380	1,070	1,000	1,600	942	1,400	824	40	41		

VENTILATION PRODUCT SPECIFICATION

	Model No.	Phase		Consumption [W]		R.P.M [min ⁻¹]		Air Volume				Noise [dB(A)]		Weight [kg]
				50Hz	60Hz	50Hz	60Hz	50Hz		60Hz		50Hz	60Hz	
								[CMH]	[CFM]	[CMH]	[CFM]			
Industrial Type Ventilating Fan	FV-25GS4	1		39	47	1,360	1,560	1,150	677	1,250	736	34	39	4.4
	FV-30GS4	1		59	80	1,360	1,560	1,820	1,071	2,080	1,224	38	42	6.1
	FV-35GS4	1		88	127	1,420	1,660	2,560	1,507	2,940	1,730	44	48	10.5
	FV-40GS4	1		161	210	1,450	1,710	3,610	2,125	4,240	2,496	47	51	19.0
	FV-45GS4	1		227	325	1,410	1,630	5,200	3,061	5,970	3,514	51	54	19.0
	FV-50GS4	1		249	326	960	1,130	6,130	3,608	7,100	4,179	47	51	22.5
	FV-60GS4	1		245	361	970	1,150	8,040	4,732	9,410	5,539	50	54	34.0
	FV-45GT4	3		220	330	1,450	1,690	5,520	3,249	6,420	3,779	52	56	18.5
	FV-50GT4	3		320	475	1,400	1,590	6,960	4,097	8,010	4,715	54	58	28.5
	FV-60GT4	3		310	450	940	1,070	9,420	5,544	10,920	6,427	49	53	34.0
	FV-30KUT	1		42	51	1,185	1,255	1,220	718	1,270	747	46	47	4.9
	FV-40KUT	1		61	76	1,175	1,260	2,060	1,212	2,190	1,289	49	51	6.4
FV-50AET2	1		108	130	920	1,050	3,630	2,137	4,200	2,472	54	58	11.5	
Wall Mount Ventilating Fan	FV-10EGK1	1		5.5	4.4	2,706	2,888	75	44	80	47	33	34	1.2
	FV-15EGK1	1		6.2	8.5	2,329	2,647	160	94	180	106	34	38	1.5
	FV-10EGS1	1		5.5	4.4	2,706	2,888	75	44	80	47	35	36	0.9
	FV-15EGS1	1		6.2	8.5	2,329	2,647	150	88	175	103	36	40	1.1
	FV-25AUF1	1		34	34	1,100	1,060	835	491	820	483	42	42	2.8
	FV-15AST1	1		15	19	1,480	1,560	288	170	306	180	31	34	1.4
	FV-20AU9	1		20	24	1,250	1,400	580	341	650	383	37.5	41.5	2.0
	FV-25AU9	1		27	31	1,070	1,125	920	541	940	553	39	39	2.4
	FV-30AU9	1		31	38	1,000	1,000	1,200	706	1,140	671	39	38	2.7
	FV-20AL9	1		20	24	1,190	1,340	546	321	600	353	40	44	2.2
	FV-25AL9	1		27	36	1,060	1,110	835	491	846	498	43	43	2.7
	FV-30AL7	1		31	38	880	880	935	550	915	539	43	43	3.1
	FV-20RG7	1	Exhaust	20	24	1,260	1,410	580	341	630	371	36	39	2.2
		1	Intake	15	17	1,150	1,140	405	238	355	209	46	46	
	FV-25RG7	1	Exhaust	27	31	1,090	1,110	945	556	950	559	38	39	2.4
		1	Intake	21	23	1,010	970	600	353	560	330	45	44	
	FV-30RG7	1	Exhaust	31	38	885	800	1,165	686	1,000	589	39	38	2.8
		1	Intake	24	26	840	810	700	412	680	400	43	42	
	FV-20RL7	1	Exhaust	20	24	1,240	1,290	546	321	570	335	39	43	2.4
		1	Intake	15	17	1,190	1,180	370	218	340	200	46	46	
FV-25RL7	1	Exhaust	29	33	1,100	1,100	840	494	835	491	43	43	2.7	
	1	Intake	21	23.5	1,035	1,135	580	341	560	330	45	44.5		
FV-30RL6	1	Exhaust	31	38	890	880	990	583	945	556	44	43	3.1	
	1	Intake	25	26	770	770	600	353	600	353	43	44		
FV-10BAT1	1		15	17	1,250	1,200	85	50	76	45	40	40	1.7	
Window Mount Ventilating Fan	FV-15WU4			8	9	1,463	1,393	210	124	198	117	35	34	0.9
	FV-20WU4			16	19	1,042	1,024	360		360	212	32	31	1.1


INSTALLATION METHOD

Ceiling Mount Type Ventilating Fan - Applicable Models:

FV-17CU7 / FV-24CU7 / FV-24CD7 / FV-24CH7 / FV-27CH9 / FV-32CD9 / FV-32CH9


1A Installation with a wooden keel (for FV-17CU7 / FV-24CU7 / FV-24CD7 and FV-24CH7 only)

1. Build a wooden frame horizontally from the wooden keel. Note that the distance between the top of the fan body and the ceiling should be at least 20mm.



Model No.	A	B
FV-17CU7	177mm	275mm
FV-24CU7 / FV-24CD7 / FV-24CH7	240mm	335mm


2. Firmly secure the fan body with six tapping screws.



Tapping screw


1B Installation with anchor bolts

1. Secure the 1 set of suspension bracket FV-KB021C (optional accessory) with screws.




The screw length should not exceed 8mm.

* 2 sets of accessories are required for FV-32CD9 and FV-32CH9



Model No.	C	D	E
FV-17CU7	226mm	89mm	108mm
FV-24CU7 / FV-24CD7 / FV-24CH7	286mm	131mm	124mm
FV-27CH9	296mm	160mm	158.5mm
FV-32CD9 / FV-32CH9	346mm	200mm	158.5mm


2. Mount the fan body enclosure on the anchor bolts (M8-M10, not supplied).




Suspension bracket

1C Installation of adaptor assembly first

1. First remove the hexagon screw attaching the adaptor assembly to the fan body.



2. Build a wooden frame horizontally from the keel. Note that the distance between the top of the fan body and the ceiling should be at least 20mm.




Model No.	F	G
FV-17CU7	177mm	30-50mm
FV-24CU7 / FV-24CD7 / FV-24CH7	240mm	30-50mm
FV-27CH9	270mm	25-30mm
FV-32CD9 / FV-32CH9	320mm	25-30mm


* Ceiling joist must be subject to static load more than 5 times of the product weight.

Ceiling Mount Type Ventilating Fan - Applicable Models:


- Attach the adaptor assembly to the wooden frame as shown in the figure.



- Insert the fan body in the wooden frame, and connect it to the adaptor assembly.



- Firmly secure the fan body with four tapping screws and a hexagon screw.




2 Power cord connection


Connect the power cord to the power supply line according to the wiring diagram and the local electrical wiring rules of fixed wiring.

Make sure all connections are fastened firmly after wiring is finished.

For FV-17CU7 / FV-24CU7 / FV-24CD7 and FV-24CH7




For FV-27CH9, FV-32CD9 and FV-32CH9




3 Duct connection and ceiling plate installation


- Insert the duct into the adaptor assembly, and tighten it with adhesive tape (not supplied). (Suspend the duct from the ceiling to prevent any external force onto the fan body.)



Slope the duct downward and guide it through the wall to the outside. Be sure to prevent rainwater from falling in the duct from its outlet. (The minimum size of the hole opening on the wall is: $\varnothing 116\text{mm}$ for 17/24 models, $\varnothing 168\text{mm}$ for 27/32 model.)



- Install the ceiling plate. Note that the gap between the flange and the ceiling plate should be 2 to 3mm.




- Install the pipe hood or vent cap (optional accessories) on the outer wall.


	Pipe Hood	Vent Cap
FV-17CU7 / FV-24CU7 / FV-24CD7 / FV-24CH7	FV-MCX100P	FV-VCX100P
FV-27CH9 / FV-32CD9 / FV-32CH9	FV-MCX150P	FV-VCX150P

4 Test run and louver installation

- When the power is turned on, check for malfunctions as follow:
Does the fan rotate correctly?
Does the fan rotate anti-clockwise?
Is there any abnormal sound or vibration?




- Insert the mounting spring into the slots and mount the louver to the fan body. (Please wear gloves during installation.)



Low Noise Type Cabinet Fan (In-line Fan)

Applicable Models - FV-12NS3 / FV-15NS3 / FV-18NS3 / FV-18NF3 / FV-20NS3
FV-23NL3 / FV-25NS3 / FV-25NF3



Notes:


To install the fan with the inspection panel facing down, remove the attached four hanger fittings and re-attach them in the holes on the top and bottom surfaces (use the screws you just removed). The former holes for installing the hanger fitting need to be sealed.

Model No.	A	B	C	D
FV-12NS3	250	335	291	184
FV-15NS3	250	346	302	206
FV-18NS3	276	382	338	232
FV-18NF3	336	441	397	254
FV-20NS3	376	485	441	272
FV-23NL3	424	513	469	298
FV-25NS3	420	549	505	334
FV-25NF3	450	549	505	334

Unit: mm

Wall Mount Type Ventilating Fan


Applicable Models - FV-20AU9 / FV-25AU9 / FV-30AU9 / FV-20AL9 / FV-25AL9 / FV-30AL7
 FV-20RG7 / FV-25RG7 / FV-30RG7 / FV-20RL7 / FV-25RL7 / FV-30RL6



Wiring Diagram

Connect the power cord to the power supply line according to the wiring diagram and the local electrical wiring rules of fixed wiring.

- Make sure all connections are fastened firmly after wiring is finished.
- It is required to use terminal (not included) that complies IEC 60998.




Wall Mount Type Ventilating Fan


Applicable Models - FV-10EGK1 / FV-15EGK1

1 Make a hole on the wall.


Model No.	∅A	B	Wall thickness
FV-10EGK1	135 ± 5mm	more than 125mm	100 ~ 150mm
FV-15EGK1	180 ± 5mm	more than 150mm	




2 Make two holes for the plug bolt.




3 Insert the duct sleeve into the hole and fix with two screws.




4 Caulk around the duct sleeve and insert the fan body and fix it with two screws.




5 Install the louver.




6 Screw the duct spinner and fix from outside wall.




7 Make a hole for the plug bolt.



8 Hang and fix pipe hood.




9 Screw pipe hood to the wall seal with caulking around pipe hood.




Ceiling Fan

Applicable Models - F-60WWK


- 1 Remove the supplied bolt, nut, cotter pin and pulley at the top. Place the pulley onto the ceiling hook.




- 2 Remove the spring washer and safety wire screw from the pipe. Arrange and tie the safety wire as shown.



- 3 Firmly screw the safety wire onto the pipe.




- 4 Connect the wires to the house supply line according to diagram shown. Pull the wires after fixing to ensure the wires are tighten firmly.




The length of the external earthing conductor which should be such that when failure of the system occur, the current-carrying conductors taut before the earthing conductor.


- 5 Before proceed to Step A, remove the screws from the canopy.
 Step A : Take the canopy (2pcs) and press (until "click" sound is heard) it as shown.
 Step B : Fix the screws into the canopy and tighten it.
 Step C : Separate the canopy plate set as shown in picture.
 Step D : Take the canopy plate (2pcs) and clip it as shown.



- 6 Hook the blades on the motor and tighten with the blade screws.



- 7 Fix the decoration cap at the motor.






Ceiling Fan


Applicable Models - Regulator Control Series

A Assemble Pipe To Motor Assembly


1. Pull power cord (from power supply) and insert into the Pipe hole.
2. Insert the Cap to the Motor Shaft, fix the Pipe to Motor Shaft and ensure the Switch Lever is pressing the Switch.
3. Fix the Pipe and Motor Assembly with a) Ellipse Bolt, b) P-R Washer, c) Spring Washer, d) Hexa Nut and e) Bend the Cotter Pin.




4. Remove Safety Wire Screw at shaft. Fix the Safety Wire firmly to the shaft with Safety Wire Screw.



5. Connect the Power Cord to the 3 Pin Terminal.





6. Remove Blade Screw from Motor Assembly. Set Blade towards to the Cover Hook and Pull to lock the Blade Hole. Tighten the Blades firmly with Blade Screws (2 pcs / Blade).




B Installation to Ceiling

1. Cross C Hook of Pulley Set to the Pipe and place the Pulley on Ceiling Hook.
2. Loop the Safety Wire to the Ceiling Hook and screw it to the Pipe with Safety Wire Screw.




C Fix the Canopy

1. Adjust Upper Canopy position and fix Upper Canopy to Pipe firmly with screw.




2. Pull down Lower Canopy until it stop and fix to Pipe firmly by with screw.




D Installation of Speed Regulator

1. Fix the Base of Speed Regulator Box on the wall with screws and connect Live Wire to the Terminal.



2. Set the regulator cover by Insert the 2 holes of regulator cover to the protruding parts of the base and fix with the screw.



HEATER VENTILATING



Panasonic Energy Recovery Ventilators help you with your “comfort” and “energy-saving” plan.

Panasonic Energy Recovery Ventilators can reduce the outside air load because they efficiently recover the heat lost by ventilation during the heat recovery process. This results in energy-saving ventilation and lower running costs for air-conditioning and heating equipment.

Furthermore, by designing our current models with a counter-flow heat-exchange element, we achieved products with slim body shapes and quiet operation that create a comfortable and pleasant air-conditioned environment while saving energy.

Energy-saving ventilation

Energy consumption is dramatically reduced by using a counter-flow heat-exchange element.

The air conditioning load is reduced by approximately 20%, resulting in significant energy savings.

(For details, refer to P.2)

Slim shape

A slim shape saves on installation work.

Compared with the cross-flow configuration, the counter-flow element is more compact and slim.

Structure


The counter-flow heat-exchange element requires no regular cleaning.

Because of the use of an counter-flow element in a plastic frame, the heat-exchange element not only has large air passages that resist clogging, but the element itself has a rugged construction. In addition, a filter with a high dust collection capacity is adopted.

Quiet operation

Low-noise operation results in noticeably quieter units.


All models run at low noise level, and even the largest 1000m³/h-capacity models are only 39.5dB (high notch)




FY-250ZDY8



Dimension



Performance



No.	Parts Name	Qty.
1	Frame	1
2	Adaptor	4
3	Electrical Equipment Box	1
4	Inspection Cover	1
5	Fan	2
6	Motor	2
7	Heat Exchange Element	1
8	Filter	2
9	Damper	1
10	Damper Motor	1
11	Ceiling Suspension Fixture	4

- Counter-flow heat-exchange element used for reduced noise and more compact and slim body shape.
- All maintenance can be performed through a single inspection hole.
- Straight air supply/exhaust system used for easier installation.
- Each unit can be mounted in reverse position.
- Equipped with a Extra-High setting.
- Can incorporate a medium-performance filter (optional, installed at site).

Specifications


Model No.	Power Source	Notch	Hz	Input [W]	Current [A]	Air Volume [m³/h]	External Static Pressure [Pa]	Temperature Exchange Efficiency (%)	Enthalpy Exchange Efficiency (%)	Noise [dB]	Product Weight [kg]	
FY-250ZDY8	220-240V	Extra High	50	Heat Exchange Ventilation	112-128	0.51-0.53	250	105	75	63	70	30.0-31.5
			50	Normal Ventilation	112-128	0.51-0.53	250	105	-	-	-	30.0-31.5
		High	50	Heat Exchange Ventilation	108-123	0.49-0.51	250	95	75	63	70	29.5-30.5
			50	Normal Ventilation	108-123	0.49-0.51	250	95	-	-	-	29.5-30.5
		Low	50	Heat Exchange Ventilation	87-96	0.40-0.41	190	45	77	65	72	23.5-26.5
			50	Normal Ventilation	87-96	0.40-0.41	190	45	-	-	-	23.5-26.5

* This noise of the product is the value which was measured at the acoustic room. Actually, in the established condition, that undergo influence by the echoing of the room and so that become bigger than the display numerical value. The input, current and exchange efficiency are values at the time of mentioned air volume. The noise level shall be measured 1.5m below the center of the unit. The temperature exchange efficiency averages that of when cooling and when heating.


FY-350ZDY8



Dimension



Performance



No.	Parts Name	Qty.
1	Frame	1
2	Adaptor	4
3	Electrical Equipment Box	1
4	Inspection Cover	1
5	Fan	2
6	Motor	2
7	Heat Exchange Element	2
8	Filter	2
9	Damper	1
10	Damper Motor	1
11	Ceiling Suspension Fixture	4

- Counter-flow heat-exchange element used for reduced noise and more compact and slim body shape.
- All maintenance can be performed through a single inspection hole.
- Straight air supply/exhaust system used for easier installation.
- Each unit can be mounted in reverse position.
- Equipped with a Extra-High setting.
- Can incorporate a medium-performance filter (optional, installed at site).

Specifications


Model No.	Power Source	Notch	Hz	Input [W]	Current [A]	Air Volume [m³/h]	External Static Pressure [Pa]	Temperature Exchange Efficiency (%)	Enthalpy Exchange Efficiency (%)	Noise [dB]	Product Weight [kg]	
FY-350ZDY8	220-240V	Extra High	50	Heat Exchange Ventilation	182-190	0.83-0.79	350	140	75	66	69	32.5-33.0
			50	Normal Ventilation	182-190	0.83-0.79	350	140	-	-	-	32.5-33.0
		High	50	Heat Exchange Ventilation	178-185	0.81-0.77	350	60	75	66	69	30.5-31.0
			50	Normal Ventilation	178-185	0.81-0.77	350	60	-	-	-	30.5-31.0
		Low	50	Heat Exchange Ventilation	175-168	0.79-0.70	240	45	78	71	73	22.5-25.5
			50	Normal Ventilation	175-168	0.79-0.70	240	45	-	-	-	22.5-25.5

* This noise of the product is the value which was measured at the acoustic room. Actually, in the established condition, that undergo influence by the echoing of the room and so that become bigger than the display numerical value. The input, current and exchange efficiency are values at the time of mentioned air volume. The noise level shall be measured 1.5m below the center of the unit. The temperature exchange efficiency averages that of when cooling and when heating.


FY-500ZDY8



Dimension



Performance



No.	Parts Name	Qty.
1	Frame	1
2	Adapter	4
3	Electrical Equipment Box	1
4	Inspection Cover	1
5	Fan	2
6	Motor	2
7	Heat Exchange Element	2
8	Filter	2
9	Damper	1
10	Damper Motor	1
11	Ceiling Suspension Fixture	4

- Counter-flow heat-exchange element used for reduced noise and more compact and slim body shape.
- All maintenance can be performed through a single inspection hole.
- Straight air supply/exhaust system used for easier installation.
- Each unit can be mounted in reverse position.
- Equipped with a Extra-High setting.
- Can incorporate a medium-performance filter (optional, installed at site).

Specifications


Model No	Power Source	Notch	Hz	Input [W]	Current [A]	Air Volume [m³/h]	External Static Pressure [Pa]	Temperature Exchange Efficiency (%)	Enthalpy Exchange Efficiency (%)		Noise [dB]	Product Weight [kg]
									Cooling	Heating		
FY-500ZDY8	220-240V	Extra High	50	Heat Exchange Ventilation	263-289	1.20-1.21	500	120	75	62	67	36.5-37.5
				Normal Ventilation	263-289	1.20-1.21	500	120	-	-	-	37.5-38.5
		High	50	Heat Exchange Ventilation	204-225	0.93-0.94	500	60	75	62	67	34.5-35.5
				Normal Ventilation	204-225	0.93-0.94	500	60	-	-	-	37.0-38.0
		Low	50	Heat Exchange Ventilation	165-185	0.75-0.77	440	35	76	64	69	31.0-32.5
				Normal Ventilation	165-185	0.75-0.77	440	35	-	-	-	31.0-32.5

* This noise of the product is the value which was measured at the acoustic room. Actually, in the established condition, that undergo influence by the echoing of the room and so that become bigger than the display numerical value
The input, current and exchange efficiency are values at the time of mentioned air volume
The noise level shall be measured 1.5m below the center of the unit
The temperature exchange efficiency averages that of when cooling and when heating


FY-800ZDY8



Dimension



Performance



No.	Parts Name	Qty.
1	Frame	1
2	Adapter	4
3	Electrical Equipment Box	1
4	Inspection Cover	1
5	Fan	2
6	Motor	2
7	Heat Exchange Element	3
8	Filter	2
9	Damper	1
10	Damper Motor	1
11	Ceiling Suspension Fixture	4

- Counter-flow heat-exchange element used for reduced noise and more compact and slim body shape.
- All maintenance can be performed through a single inspection hole.
- Straight air supply/exhaust system used for easier installation.
- Each unit can be mounted in reverse position.
- Equipped with a Extra-High setting.
- Can incorporate a medium-performance filter (optional, installed at site).

Specifications


Model No	Power Source	Notch	Hz	Input [W]	Current [A]	Air Volume [m³/h]	External Static Pressure [Pa]	Temperature Exchange Efficiency (%)	Enthalpy Exchange Efficiency (%)		Noise [dB]	Product Weight [kg]
									Cooling	Heating		
FY-800ZDY8	220-240V	Extra High	50	Heat Exchange Ventilation	387-418	1.76-1.74	800	140	75	65	71	37.0-37.5
				Normal Ventilation	387-418	1.76-1.74	800	140	-	-	-	37.0-37.5
		High	50	Heat Exchange Ventilation	300-378	1.64-1.58	800	110	75	65	71	36.5-37.0
				Normal Ventilation	300-378	1.64-1.58	800	110	-	-	-	36.5-37.0
		Low	50	Heat Exchange Ventilation	293-295	1.33-1.23	630	55	76	68	74	33.5-34.5
				Normal Ventilation	293-295	1.33-1.23	630	55	-	-	-	33.5-34.5

* This noise of the product is the value which was measured at the acoustic room. Actually, in the established condition, that undergo influence by the echoing of the room and so that become bigger than the display numerical value
The input, current and exchange efficiency are values at the time of mentioned air volume
The noise level shall be measured 1.5m below the center of the unit
The temperature exchange efficiency averages that of when cooling and when heating


FY-01KZDY8A



Dimension



Performance



No.	Parts Name	Qty.
1	Frame	1
2	Adapter	4
3	Electrical Equipment Box	1
4	Inspection Cover	1
5	Fan	2
6	Motor	2
7	Heat Exchange Element	1
8	Filter	2
9	Damper	1
10	Damper Motor	1
11	Ceiling Suspension Fixture	4

- Counter-flow heat-exchange element used for reduced noise and more compact and slim body shape.
- All maintenance can be performed through a single inspection hole.
- Straight air supply/exhaust system used for easier installation.
- Each unit can be mounted in reverse position.
- Equipped with a Extra-High setting.
- Can incorporate a medium-performance filter (optional, installed at site).

Specifications

Model No.	Power Source	Notch	Hz		Input [W]	Current [A]	Air Volume [m³/h]	External Static Pressure [Pa]	Temperature Exchange Efficiency [%]	Enthalpy Exchange Efficiency [%]		Noise [dB]	Product Weight [kg]
										Cooling	Heating		
FY-01KZDY8A	220-240V	Extra High	50	Heat Exchange Ventilation	437-444	1.99-1.93	1,000	105	75	65	71	37.5-38.5	83
				Normal Ventilation	437-444	1.99-1.93	1,000	105	-	-	39.5-40.5		
		High	50	Heat Exchange Ventilation	416-432	1.89-1.80	1,000	80	75	65	71	37.0-37.5	
				Normal Ventilation	416-432	1.89-1.80	1,000	80	-	-	39.0-39.5		
		Low	50	Heat Exchange Ventilation	301-311	1.37-1.29	700	75	79	70	76	33.5-34.5	
				Normal Ventilation	301-311	1.37-1.29	700	75	-	-	35.5-36.5		

* This noise of the product is the value which was measured at the acoustic room. Actually, in the established condition, that undergo influence by the echoing of the room and so that become bigger than the display numerical value
 The input, current and exchange efficiency are values at the time of mentioned air volume
 The noise level shall be measured 1.5m below the center of the unit
 The temperature exchange efficiency averages that of when cooling and when heating

Use conditions


Outdoor air conditions
Temperature range -10°C~40°C
Relative humidity 85% or less
Indoor air conditions
Temperature range -10°C~40°C
Relative humidity 85% or less
Installation requirements
Same as the indoor air conditions
* Indoor air here means air in air-conditioned living rooms. Its use in refrigerators or other places where temperature can fluctuate greatly is prohibited even if a temperature range is acceptable.
Example Indoor air conditions
During cooling period
Temperature 27°C
Relative humidity 50%
During heating period
Temperature 20°C
Relative humidity 40%

Motor Specifications

Type	4 Poles open type induction motor
Rating	Cont.
Insulation Class	class E
Temperature Rise	under 75 K
Surrounding Temperature	-10°C~40°C
Insulation Resistance	over 1MΩ (by DC500V)
Withstand Voltage	AC 1,500V for 1min

Condensation in energy exchange element

As shown in the figure to the right, suppose a high temp absorbing air condition A and a low temp absorbing air condition B are plotted on the air line figure, then a high temp air A is heat-exchanged by the unit and goes out of the saturation curve as shown by Point C. In this case, the unit will be dewed or frosted. To avoid this, you are required to heat a low temp air B up to B' so as to get C' below the saturation curve, before using the unit




Filter


Model	Part No.	No. of Filter
FY-250ZDY8	25ZD80811	2
FY-350ZDY8	35ZD80811	2
FY-500ZDY8	50ZD80811	2
FY-650ZDY8	65ZD80811	2
FY-800ZDY8	65ZD80811	2
FY-01KZDY8A	01KZD80811	2

WIRING DIAGRAM


FY-250ZDY8




FY-350ZDY8 FY-500ZDY8



FY-650ZDY8



FY-800ZDY8 FY-01KZDY8A



AIR PURIFIER



Air Purifier Provide Clean And Fresh Air For You And Your Family

1



Provide your healthy and maintenance your beauty with the unique technology


2



Eco operation mode that runs only as it is necessary

3

HEPA Composite Filter



HEPA Composite Filter not only can remove 0.3um particles, it also consists of 3 kinds of technology, Super alleru-buster, Green tea Catechin and Anti- bacteria enzyme. It can inhabit 17 kinds of virus, bacteria and allergen up to 99%

F-PXL45A

F-PXM55

F-PXF35A


F-PXJ30A



Specification

	Silver			Gold			Grey	Black	Grey			
Applicable area (m ²)	33			41			26			20		
Nanoe Purification												
	High	Medium	Low	High	Medium	Low	High	Medium	Low	High	Medium	Low
Air purifying [Air volume [m ³ /min]	4,5	2,3	1,0	5,3	2,0	0,9	3,5	2,0	1,0	2,8	1,8	0,8
Power consumption	42	13	6,5	49	11	7	20	9	6	30	22	15
Noise [[dB [A]]	52	32	18	52	32	18	44	32	18	44	35	21
Filter Life HEPA Composite Filter (year)	3			10			3			2		
Deodorizing Filter (year)	3			10			3			2		
Filter Replace Indicator/ Filter Life check	●			●			●			●		
Motor type	DC 1-way			DC 1-way			DC 1-way			DC multi-way		
3D Circulation Airflow	●			●			●			●		
Econavi							-			-		
Eco Mode	-			-			-			-		
Turbo mode	-			-			●			●		
Sleep mode (8 hours)	●			●			●			●		
Spot Air Mode	-			●			-			-		
Sensor	Dust / Smell			Dust / Smell			Dust			Dust		
Light Sensor	●			●			-			-		
Clean sign	●			●			●			●		
Child lock	●			●			-			-		
Seamless drive	●			●			●			-		
Dimension	404x516x221			580x300x205			520x300x189			540x311x210		
Weight	5,9			5,8			4,8			4,3		

PUMP



Compact and Energy Efficient

- Pump cover with smooth curve for elegant outlook
- Brass-made casing cover and impeller are resistance to friction and high temperature that allow smoother water stream

Reliable and Safe

- Equipped with Thermal Protector (130°C) enhances security against burning by turning off the pump directly as temperature exceeds the limit
- Double stator protection being resistant to abrasion reduce the danger of short circuit


Durable

- High accurate rotor with anti-rust layer allows operation up to 8,000 hours without stopping
- Stainless aluminum motor body and brass casing cover allow high durability

Structure (For Auto Series) (*)


- Accumulator is a compression space containing Nitrogen Gas which has characteristics of elasticity. The gas content will never deplete that always stay stable and optimum.
- Rubber Bladder is made of Butyl that is stainless and anti-leakage. It functions as water separator with the Nitrogen compression room.
- Automatic Switch equipped with a protector made of fire-retardant material and a Platinum-made Switch that is long-lasting. It functions to break the stream if the water stream is closed.

(*) Except A-130JTX



Auto Series (Shallow Well Type)


With Auto Series water pump, flow of water can be controlled by the automatic switch associated with water tap operation, that provides greater convenience.



Model No.	A-130JTX	A-130JACK	A-130JAK	A-200JAK
Maximum Capacity	30 liters / minute	30 liters / minute	30 liters / minute	45 liters / minute
Capacity at 12m	18 liters / minute	18 liters / minute	18 liters / minute	29 liters / minute
Power Suction	9 meters	9 meters	9 meters	9 meters
Maximum Total Head	25 meters	27 meters	27 meters	27 meters
Motor Power	125 watts	125 watts	125 watts	200 watts
Switch On Pressure	1.1 kgf / cm ²	1.1 kgf / cm ²	1.1 kgf / cm ²	1.1 kgf / cm ²
Switch Off Pressure	1.6 kgf / cm ²	1.8 kgf / cm ²	1.8 kgf / cm ²	1.8 kgf / cm ²
Suction Pipe	3/4 inch (19 mm)	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)
Push pipe	3/4 inch (19 mm)	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)
Size (L x W x H)	∅ 330 x 425 mm	330 x 255 x 340 mm	246 x 225 x 240 mm	257 x 238 x 245 mm
Weight	14.5 kg	8.8 kg	6.9 kg	8.3 kg

Non-Auto Series (Shallow Well Type)

Compact-size and high performance of Non-auto Series allow easy installation and maintenance in different applications.



Model No.	GP-129JXK	GP-200JXK	GP-250JXK	GP-350JA
Maximum Capacity	30 liters / minute	45 liters / minute	50 liters / minute	45 liters / minute
Capacity at 12m	18 liters / minute	29 liters / minute	36 liters / minute	39 liters / minute
Power Suction	9 meters	9 meters	9 meters	9 meters
Maximum Total Head	30 meters	30 meters	38 meters	45 meters
Motor Power	125 watts	200 watts	250 watts	350 watts
Switch On Pressure	-	-	-	-
Switch Off Pressure	-	-	-	-
Suction Pipe	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)
Push pipe	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)	1 inch (25 mm)
Size (L x W x H)	206 x 152 x 212 mm	225 x 182 x 215 mm	233 x 168 x 236 mm	239 x 182 x 250 mm
Weight	5.9 kg	7.5 kg	8 kg	14 kg

ELECTRICAL CONSTRUCTION MATERIALS

WIRING DEVICES

Item No.	Page
EBG	
EBG888	23,27,32,41,53,58
EGG	
EGG331	23,27,32,41,53,58
EGG335	23,27,32,41,53,58
NR	
NR3170W-8	47
NRV3160W	47,60
WA	
WA1215	52
WA1219	52
WA1220	52
WA1229	52
WA1315	52
WA1319	52
WA1320	52
WA1329	52
WA1415	52
WA1419	52
WA1420	52
WA1429	52
WA1515	52
WA1519	52
WA1615	52
WA1619	52
WA3215K	52
WA3219K	52
WA3220	52
WA3229	52
WA3230	52
WA3239	52
WA3315	52
WA3319	52
WA3320	52
WA3329	52
WA3330	52
WA3339	52
WA3415	52
WA3419	52
WA3420K	52
WA3429K	52
WA3430	52
WA3439	52
WA35159	52
WA3519K	52
WA3615	52

WA3619	52
WA3630	52
WA3639	52
WA5215K	50
WA5219K	50
WA5220K	50
WA5229K	50
WA5315K	50
WA5319K	50
WA5320K	50
WA5329K	50
WA5330	50
WA5331	50
WA5338	50
WA5339	50
WA5360	50
WA5369	50
WA5420K	50
WA5429K	50
WA5430	50
WA5439	50
WA5460	50
WA5469	50
WA5520	50
WA5529	50
WBG	
WBG5408699W	46,60
WBG5414699W	46,60
WBG5414699W-SP	46,60
WCH	
WCHG28334	61
WCHG28352	61
WCHG2836	61
WEB	
WEB1051W	42,59
WEB51511-7SW	59
WEB52521-7SW	59
WEB535317	59
WEB5781WK	42,59
WEB7811MA	37
WEB7811MB	37
WEB7811MF	37
WEB7811MH	37
WEB7811MW	34,37
WEB7811MWZ	37
WEB7811MY	37
WEB7811SW	35,37
WEB7812MA	37
WEB7812MB	37
WEB7812MF	37
WEB7812MH	37
WEB7812MW	34,37
WEB7812MWZ	37
WEB7812MY	37
WEB7812SW	35,37

WEB7813MA	37
WEB7813MB	37
WEB7813MF	37
WEB7813MH	37
WEB7813MW	34,37
WEB7813MWZ	37
WEB7813MY	37
WEB7813SW	35,37
WEBP	
WEBP515117MA	36
WEBP515117MB	36
WEBP515117MF	36
WEBP515117MH	36
WEBP515117MW	36
WEBP515117MWZ	36
WEBP515117MY	36
WEBP515117SW	36
WEBP515127MA	36
WEBP515127MB	36
WEBP515127MF	36
WEBP515127MH	36
WEBP515127MW	36
WEBP515127MWZ	36
WEBP515127MY	36
WEBP515127SW	36
WEBP525217MA	36
WEBP525217MB	36
WEBP525217MF	36
WEBP525217MH	36
WEBP525217MW	36
WEBP525217MWZ	36
WEBP525217MY	36
WEBP525217SW	36
WEBP525227MA	36
WEBP525227MB	36
WEBP525227MF	36
WEBP525227MH	36
WEBP525227MW	36
WEBP525227MWZ	36
WEBP525227MY	36
WEBP525227SW	36
WEBP535317MA	36
WEBP535317MB	36
WEBP535317MF	36
WEBP535317MH	36
WEBP535317MW	36
WEBP535317MWZ	36
WEBP535317MY	36
WEBP535317SW	36
WEBP535327MA	36
WEBP535327MB	36
WEBP535327MF	36
WEBP535327MH	36
WEBP535327MW	36
WEBP535327MWZ	36

WEBP535327MY	36
WEBP535327SW	36
WEC	
WEC5542-7	30
WEG	
WEG1001H	32,41
WEG1001SW	26,32,41,58
WEG1090H	32,41
WEG1090SW	26,32,41,58
WEG1181BK-G	22
WEG15829B-G	22
WEG3020B-G	22
WEG3020H	40
WEG3020SW	19,40,56,58
WEG3023H	40
WEG3023SW	19,40,56,58
WEG3032G-031	42
WEG3032GH	40
WEG3032GSW	40
WEG3032GSW (Green)	58
WEG3032R-021	42
WEG3032RH	40
WEG3032RSW	40
WEG3032RSW (Red)	58
WEG3032SW	40
WEG3032SW (White)	58
WEG3032WH	40
WEG5001SWK-031	42
WEG5002SWK-021	42
WEG5003HK	40
WEG5003KSW	40,53,58
WEG5004HK	40
WEG5004KSW	40,53,58
WEG5141	58
WEG5141H	40
WEG5141SW	40
WEG5151-51HK	34,40
WEG5151-51SWK	35,40,58
WEG5151-7H	40
WEG5151-7SW	40,53,58
WEG5152-51HK	40
WEG5152-51KSW	53
WEG5152-51SWK	40,58
WEG5152-7H	40
WEG5152-7SW	40,58
WEG51527SW	53
WEG5341	53,58
WEG5341H	40
WEG5341SW	40
WEG5400-7	40
WEG5400-7SW	58
WEG5401-011SW	42
WEG5401-7SW	35,41,58
WEG5401H-7	41
WEG5511-MH	30

Item No.	Page				
WEG5512-MH	30	WEG68030MWZ	33,43	WEV5001SW	40,53,58
WEG5521-MH	30	WEG68030MY	33,43	WEV5002-7H	40
WEG5522-MH	30	WEG7801	43	WEV5002-7SW	40,53,58
WEG5531-MH	30	WEG7802	43	WEV5002H	40
WEG5532-MH	30	WEG78029	43	WEV5002SW	40,58
WEG5551-MH	30	WEG7803	43	WEV5033-7SW	40
WEG5552-MH	30	WEG7901	43	WEV5511-7SW	31
WEG5561-MH	30	WEG7902	43	WEV5511SW	31,57
WEG5562-MH	30	WEG79029	43	WEV5512-7SW	31
WEG5571-MH	30	WEG7903	43	WEV5512SW	31
WEG5572-MH	30	WEG8881	43	WEV5521-7SW	31
WEG575081	26,58	WEG8981	43	WEV5521SW	31,57
WEG575151H	42	WEGP		WEV5522-7SW	31
WEG575151SW	19,26,42,53,56,58	WEGP1282	31	WEV5522SW	31
WEG575181	26,35,42,53,58	WEGP1282MA	31	WEV5531-7SW	31,35
WEG575181H	34,42	WEGP1282MB	31	WEV5531SW	31,57
WEG57813B-1-G	23	WEGP1282MF	31	WEV5532-7SW	31
WEG57816B-1-G	23	WEGP1282MH	31	WEV5532SW	31
WEG6501-1	43	WEGP1282MW	31	WEV55337SW	30
WEG6502-1	43	WEGP1282MWZ	31	WEV68010SW	33,43
WEG65029-1	43	WEGP1282MY	31	WEV68020SW	33,43
WEG6503-1	43	WEV		WEV680290SW	33,43
WEG6591-1	43	WEV1081-7H	32,34,41	WEV68030SW	33,43
WEG6601-1	43	WEV1081-7SW	19,27,32,35,41,56,58	WEV68910SW	43
WEG6602-1	43	WEV1081H	32,34,41	WEV7061SW	48
WEG66029-1	43	WEV1081SW	19,26,32,41,56,58	WEVH	
WEG6603-1	43	WEV1091H	32,41	WEVH5003	18,53,55
WEG6691-1	43	WEV1091SW	19,26,32,41,56,58	WEVH5004	18,53,55
WEG68010MA	33,43	WEV1181-7H	32,41	WEVH5033-7	18,56
WEG68010MB	33,43	WEV1181-7SW	19,27,32,35,41,56,58	WEVH5151-51	18,55
WEG68010MF	33,43	WEV1181H	32,34,41	WEVH5151-7	18,56
WEG68010MH	33,43	WEV1181SW	19,27,32,41,56,58	WEVH5152-51	18,55
WEG68010MW	33,43	WEV1191H	34	WEVH5152-7	18,56
WEG68010MWZ	33,43	WEV1191SW	58	WEVH5401-011	19,56
WEG68010MY	33,43	WEV1582-7H	32,34,41	WEVH5511	18,53,55
WEG68020MA	33,43	WEV1582-7SW	19,27,32,35,41,56,58	WEVH5511-7	18,53,55
WEG68020MB	33,43	WEV1582H	32,41	WEVH5512	18,53,55
WEG68020MF	33,43	WEV1582SW	19,27,32,41,56,58	WEVH5512-7	18,53,56
WEG68020MH	33,43	WEV1592SW	58	WEVH5521	18,55
WEG68020MW	33,43	WEV2364B	22	WEVH5521-7	18,55
WEG68020MWZ	33,43	WEV2364H	32,34,41	WEVH5522	18,55
WEG68020MY	33,43	WEV2364SW	19,27,32,35,41,56,58	WEVH5522-7	18,56
WEG680290MA	33,43	WEV2488	58	WEVH5531	18,55
WEG680290MB	33,43	WEV24886	58	WEVH5531-7	18,56
WEG680290MF	33,43	WEV24886H	32,34,41,54	WEVH5532	18
WEG680290MH	33,43	WEV24886SW	19,27,32,35,41,54,56	WEVH5532-7	56
WEG680290MW	33,43	WEV2488B	22	WEVH5532-7	18
WEG680290MWZ	33,43	WEV2488H	32,34,41,54	WEVH5542-7	18,56
WEG680290MY	33,43	WEV2488SW	19,27,32,35,41,42,54,56	WEVH68010	19
WEG68030MA	33,43	WEV2501B	22	WEVH68010	55
WEG68030MB	33,43	WEV2501H	32,34,41	WEVH68020	19
WEG68030MF	33,43	WEV2501SW	19,27,32,35,41,42,56,58	WEVH68020	55
WEG68030MH	33,43	WEV5001-7H	40	WEVH680290	19,55
WEG68030MW	33,43	WEV5001-7SW	35,40,53,58	WEVH68030	19
		WEV5001H	40	WEVH68030	55
				WEVH68040	19,55
				WEVH68060	19,55
				WEVH68910	19,55
				WEVH8061	19,55
				WF	
				WF1220BK	51
				WF1220WK	51
				WF1230BK	51
				WF1230WK	51
				WF1315BK	51
				WF1315WK	51
				WF1320BK	51
				WF1320WK	51
				WF1330BK	51
				WF1330WK	51
				WF1415BK	51
				WF1415WK	51
				WF1420BK	51
				WF1420WK	51
				WF1430BK	51
				WF1430WK	51
				WF2215BK	49
				WF2215WK	49
				WF2220BK	49
				WF2220WK	49
				WF2315BK	49
				WF2315WK	49
				WF2320BK	49
				WF2320WK	49
				WF2330B	49
				WF2330W	49
				WF2331B	49
				WF2331W	49
				WF2360B	49
				WF2360W	49
				WF2420BK	49
				WF2420WK	49
				WF2430B	49
				WF2430W	49
				WF2460B	49
				WF2460W	49
				WF2520B	49
				WF2520W	49
				WF3012WK	51
				WF3314	50
				WF3315B	50
				WF3315W	50
				WF3324	50
				WF3334	50
				WF3424	50
				WF3434	50
				WF3524	50
				WF3630B	51
				WF3630W	51
				WF4212	52

PRODUCT NUMBER INDEX

Item No.	Page				
WF4215	52	WF6420	50	WK2330W	49
WF4220	52	WF6420W	50	WK2331B	49
WF4230	52	WF6430	50	WK2331W	49
WF4315	52	WF6430W	50	WK2420K	49
WF4320	52	WF7002	51	WK2430	49
WF4330	52	WF7002W	51	WK2520B	49
WF4415	52	WF7004	52	WK2520W	49
WF4420	52	WF7005K	52	WK3630	51
WF4430	52	WF7011	51	WK36301B	51
WF4430	52	WF7011W	51	WK36301W	51
WF4630	52	WF7013	52	WK3730B	51
WF5015W	51	WF7215K	52	WK3730W	51
WF5115B	51	WF7220	52	WK6315	49
WF5115W	51	WF7230	52	WK6320	49
WF5215	51	WF7315	52	WK6330	49
WF52153B	51	WF7320	52	WK6331	49
WF52153W	51	WF7330	52	WK6420	49
WF5215W	51	WF7415	52	WK6430	49
WF5220	51	WF7420K	52	WK6520	49
WF52201	51	WF7430	52	WKG	
WF5220W	51	WF75159	52	WKG1091-250	47
WF5230	51	WF7615	52	WKG1092-250	47,60
WF5230W	51	WF7630	52	WN	
WF5315	51	WF8215K	50	WN1001-7KW	60
WF5315W	51	WF8220K	50	WN1090-7K-W	60
WF5320	51	WF8315K	50	WN1101-7W	60
WF5320W	51	WF8320K	50	WN3020W	47,60
WF5330	51	WF8330	50	WN3023W	47,60
WF5330W	51	WF8331	50	WN5241W-801	46,59
WF5415	51	WF8360	50	WN6501K-8	48
WF5415W	51	WF8420K	50	WN6502K-8	48
WF5420	51	WF8430	50	WN6503K-8	48
WF5420W	51	WF8460	50	WN6504K-8	48
WF5430	51	WF8520	50	WN6506K-8	48
WF5430W	51	WH		WN7501-8	48
WF5630	51	WH4007	52	WN7502-8	48
WF56301B	51	WK		WN7503-8	48
WF56301W	51	WK1091-250	60	WN7504-8	48
WF5630W	51	WK1220B	51	WN7506-8	48
WF5730B	51	WK1220W	51	WN7591-8	48
WF5730W	51	WK1230	51	WN7601-8	48
WF6215	50	WK1315	51	WN7602-8	48
WF62153B	50	WK1320	51	WN7603-8	48
WF62153W	50	WK1330	51	WN7604-8	48
WF6215W	50	WK1415	51	WN7606-8	48
WF6220	50	WK1420	51	WN7691-8	48
WF6220W	50	WK1430	51	WN7801K-8	48
WF6315	50	WK2215	49	WN7802K-8	48
WF6315W	50	WK2215W	49	WN7803K-8	48
WF6320	50	WK2220K	49	WN7821K-8	48
WF6320W	50	WK2315K	49	WN7901K-8	48
WF6330	50	WK2315W	49	WN7902K-8	48
WF6330W	50	WK2320K	49	WN7903K-8	48
WF6331B	50	WK2320W	49	WN7921K-8	48
WF6331W	50	WK2330	49	WNG	
				WNG15923-7W	47,60
				WNG5003-7W	59
				WNG5003W-7	46,53
				WNG5004-7W	59
				WNG5004W-7	46,53
				WNG5021W-7	46,59
				WNG5051W-751	46,53,59
				WNG5052W-751	46,53,59
				WNG5061-701W	46,59
				WNG5343W-761	46,59
				WNG5401W-7K	46,59
				WNGP	
				WNGP575152W	46,60
				WNGP575253	53
				WNGP575283	53
				WNGP575283W	46,60
				WNH	
				WNH5611-801	46,60
				WNTG	
				WNTG15649W	47,60
				WNV	
				WNV1001-7K-W	47
				WNV1081-7W	47,60
				WNV1090-7K-W	47
				WNV1091-7W	47,60
				WNV1101-7W	47
				WNV5001-7W	46,53,59
				WNV5002-7W	46,53,59
				WSG	
				WSG3001	47,60
				WTAG	
				WTAG6101SW	26,27
				WTAG6102SW	27
				WTAG6803SW	27
				WTAG7152	57
				WTAG7152CDSW	26
				WTAG7152CHSW	26
				WTAG7152CLSW	26
				WTAG7252CDSW	26
				WTAG7252CHSW	26
				WTAG7252CLSW	26
				WTAG7352CDSW	26
				WTAG7352CHSW	26
				WTAG7352CLSW	26
				WTC	
				WTC5631WK-8	27,57
				WTEG	
				WTEG6503S-1-G	23
				WTEG6506S-1-G	23
				WTEG6506S-G	23
				WTEGP	
				WTEGP51552S-1-G	22,57
				WTEGP52562S-1-G	22
				WTEGP53572S-1-G	22
				WTEGP54562S-1-G	22,57

Item No.	Page
WTEGP55582S-1-G	22,57
WTEGP56572S-1-G	22,57
WTFB	
WTFB6503S-1-G	23
WTFBP	
WTFBP51552S-1-G	23
WTFBP52562S-1-G	23
WTFBP53572S-1-G	23
WTKG	
WTKG2310	67
WTKG2311	67
WTKG2411	67
WTKG2911	67
WTNG	
WTNG4101W	27,57
WTNG4102W	27,57
WZV	
WZV1201W	47,60
WZV7061W	48
WZV7841W	48
WZV7842W	48
WZV7843W	48
WZV7844W	48
WZV7846W	48
FLOOR OUTLET	
DU	
DU5102HTC-1	63
DU5103HTK-1	64
DU59833LT9-1	62
DU59835LT9-1	62
DU5983LT9-1	62
DU5990LT9-1	62
DU5993LT9-1	62
DU61223HTC-1	64
DU61233HTC-1	64
DU61233HTK-1	64
DU61235HTK-1	64
DU61355HTK-1	64
DU61466HTK-1	64
DU6935LT9-1	62
DU6966LT9-1	62
DU6993LT9-1	62
DU6995LT9-1	62
DU7199HTC-1	64
DU8100HTC-1	63
DU8102HTC-1	63
DU81835HTK-1	64
DU8183HTK-1-1	64
DU81931HTK-1	64
DU8199HTK-1	64
DUF	

DUF1200LTK-1	63
DUF1260LTK-1	62
DUF1270LTK-1	62
DUF2214LTK-1	63
DUF2229LTK-1	63
DUF2259LTK-1	63
DUF3221LTK-1	62
DUF3234LTK-1	63
DUF5200LT-1	63
DUMF	
DUMF3200LT-1	63

SMOKE DETECTOR	
SH28455911	68

DOOR PHONE	
VL-MVN511	69
VL-MW251	70
VL-SVN511VN	69
VL-SW251VN	70
VL-V522L	69,70
VL-V554	69
VL-V555	69
VL-V590	69
VL-W605	70

AUTOMATIC TIME SWITCH	
TB118NE7	73
TB178NE5	73
TB2118E7	74
TB2128E7	74
TB271018E7	74
TB272018E7	74
TB35809NE5	73
TB358NE5	73
TB36809NE5	73
TB38809NE7	73
TB388NE7	73
TB39809NE7	73
TB438NE7	74
TB5560187N	74
TB5630187N	74
TB621018A7	74
TB622018A7	74

BREAKER	
BBD	

BBD1061CNV	75
BBD1061DNV	75
BBD108011C	75
BBD108011D	75
BBD110011C	75
BBD110011D	75
BBD1101CNV	75
BBD1101DNV	75
BBD112511C	75
BBD1161CNV	75
BBD1161DNV	75
BBD1201CNV	75
BBD1201DNV	75
BBD1251CNV	75
BBD1251DNV	75
BBD1321CNV	75
BBD1321DNV	75
BBD1401CNV	75
BBD1401DNV	75
BBD1501CNV	75
BBD1501DNV	75
BBD1631CNV	75
BBD1631DNV	75
BBD2062CNV	75
BBD2062DNV	75
BBD208021C	75
BBD208021D	75
BBD210021C	75
BBD210021D	75
BBD2102CNV	75
BBD2102DNV	75
BBD212521C	75
BBD2162CNV	75
BBD2162DNV	75
BBD2202CNV	75
BBD2202DNV	75
BBD2252CNV	75
BBD2252DNV	75
BBD2322CNV	75
BBD2322DNV	75
BBD2402CNV	75
BBD2402DNV	75
BBD2502CNV	75
BBD2502DNV	75
BBD2632CNV	75
BBD2632DNV	75
BBD3063CNV	75
BBD3063DNV	75
BBD308031C	75
BBD308031D	75
BBD310031C	75
BBD310031D	75
BBD3103CNV	75
BBD3103DNV	75
BBD312531C	75

BBD3163CNV	75
BBD3163DNV	75
BBD3203CNV	75
BBD3203DNV	75
BBD3253CNV	75
BBD3253DNV	75
BBD3323CNV	75
BBD3323DNV	75
BBD3403CNV	75
BBD3403DNV	75
BBD3503CNV	75
BBD3503DNV	75
BBD3633CNV	75
BBD3633DNV	75
BBD4064CNV	75
BBD4064DNV	75
BBD408041C	75
BBD408041D	75
BBD410041C	75
BBD410041D	75
BBD4104CNV	75
BBD4104DNV	75
BBD412541C	75
BBD4164CNV	75
BBD4164DNV	75
BBD4204CNV	75
BBD4204DNV	75
BBD4254CNV	75
BBD4254DNV	75
BBD4324CNV	75
BBD4324DNV	75
BBD4404CNV	75
BBD4404DNV	75
BBD4504CNV	75
BBD4504DNV	75
BBD4634CNV	75
BBD4634DNV	75
BBDE	
BBDE20631CNV	75
BBDE20631DNV	75
BBDE20641CNV	75
BBDE20641DNV	75
BBDE20651CNV	75
BBDE20651DNV	75
BBDE21031CNV	75
BBDE21031DNV	75
BBDE21041CNV	75
BBDE21041DNV	75
BBDE21051CNV	75
BBDE21051DNV	75
BBDE21631CNV	75
BBDE21631DNV	75
BBDE21641CNV	75
BBDE21641DNV	75
BBDE21651CNV	75

PRODUCT NUMBER INDEX

Item No.	Page				
BBDE21651DNV	75	BBW2201SKY	79	BBW3200KY	80
BBDE22031CNV	75	BBW2201Y	79	BBW3201SKY	79
BBDE22031DNV	75	BBW2202Y	79	BBW3201Y	79
BBDE22041CNV	75	BBW2203KY	79	BBW3202Y	79
BBDE22041DNV	75	BBW220CKY	79	BBW3203KY	79
BBDE22051CNV	75	BBW220Y	79	BBW320CKY	79
BBDE22051DNV	75	BBW2225KY	80	BBW320Y	79
BBDE22531CNV	75	BBW22501KY	80	BBW3225KY	80
BBDE22531DNV	75	BBW2250KY	80	BBW32501KY	80
BBDE22541CNV	75	BBW23001KY	80	BBW3250KY	80
BBDE22541DNV	75	BBW2301SKY	79	BBW33001KY	80
BBDE22551CNV	75	BBW2301Y	79	BBW3301SKY	79
BBDE22551DNV	75	BBW2302Y	79	BBW3301Y	79
BBDE23231CNV	75	BBW2303KY	79	BBW3302Y	79
BBDE23231DNV	75	BBW230CKY	79	BBW3303KY	79
BBDE23241CNV	75	BBW230Y	79	BBW330CKY	79
BBDE23241DNV	75	BBW232Y	79	BBW330Y	79
BBDE23251CNV	75	BBW2350KY	80	BBW332Y	79
BBDE23251DNV	75	BBW23CKY	79	BBW3350KY	80
BBDE24031CNV	75	BBW23Y	79	BBW33CKY	79
BBDE24031DNV	75	BBW2400KY	80	BBW33Y	79
BBDE24041CNV	75	BBW2401Y	79	BBW3400KY	80
BBDE24041DNV	75	BBW2402KY	79	BBW3401Y	79
BBDE24051CNV	75	BBW240SKY	79	BBW3402KY	79
BBDE24051DNV	75	BBW240Y	79	BBW340SKY	79
BBDE25031CNV	75	BBW2501SKY	79	BBW340Y	79
BBDE25031DNV	75	BBW2501Y	79	BBW3501SKY	79
BBDE25041CNV	75	BBW2502KY	79	BBW3501Y	79
BBDE25041DNV	75	BBW250SKY	79	BBW3502KY	79
BBDE25051CNV	75	BBW250Y	79	BBW350SKY	79
BBDE25051DNV	75	BBW251SKY	79	BBW350Y	79
BBDE26331CNV	75	BBW252Y	79	BBW351SKY	79
BBDE26331DNV	75	BBW25CKY	79	BBW352Y	79
BBDE26341CNV	75	BBW25Y	79	BBW35CKY	79
BBDE26341DNV	75	BBW2601KY	79	BBW35Y	79
BBDE26351CNV	75	BBW2601SKY	79	BBW3601KY	79
BBDE26351DNV	75	BBW260SKY	79	BBW3601SKY	79
		BBW260Y	79	BBW360SKY	79
		BBW275KY	79	BBW360Y	79
		BBW275SKY	79	BBW375KY	79
		BBW3100KY	79	BBW375SKY	79
		BBW3100SKY	79		
		BBW3101SKY	79	BJJ	
		BBW3102Y	79	BJJ215228	78
		BBW310CKY	79	BJJ215328	78
		BBW310Y	79	BJJ220228	78
		BBW31251KY	80	BJJ220328	78
		BBW3125SKY	80	BJJ230228	78
		BBW31501KY	80	BJJ230308	78
		BBW3150SKY	80	BJJ230328	78
		BBW3151SKY	79		
		BBW3152Y	79	BJS	
		BBW315CKY	79	BJS1512S	77
		BBW315Y	79	BJS1522S	77
		BBW3175KY	80	BJS1532S	77
		BBW3175KY	80	BJS2012S	77
				BJS2022S	77
				BJS2032S	77
				BJS3012S	77
				BJS3020NA2	77
				BJS3022S	77
				BJS3030NA2	77
				BJS3032S	77
				BKW	
				BKW210 CKY	81
				BKW210 KY	81
				BKW210 Y	81
				BKW2100 SKY	81
				BKW2125 SKY	81
				BKW215 1CKY	82
				BKW215 1SKY	82
				BKW215 CKY	81
				BKW215 Y	81,82
				BKW2150 SKY	81
				BKW220 1CKY	82
				BKW220 1SKY	82
				BKW220 1Y	81
				BKW220 CKY	81
				BKW220 Y	81,82
				BKW23 Y	81
				BKW230 1Y	81
				BKW230 CKY	81,82
				BKW230 SKY	82
				BKW230 Y	81,82
				BKW240 CKY	82
				BKW240 SKY	82
				BKW240 Y	81,82
				BKW25 CKY	81
				BKW25 Y	81
				BKW250 CKY	82
				BKW250 SKY	82
				BKW250 Y	81,82
				BKW260 1KY	81
				BKW260 1SKY	81
				BKW260 SY	82
				BKW260 Y	82
				BKW275 KY	81
				BKW275 SKY	81
				BKW310 CKY	81
				BKW310 KY	81
				BKW310 Y	81
				BKW3100 SKY	81
				BKW3125 1KY	82
				BKW3125 SKY	81
				BKW315 1CKY	82
				BKW315 1SKY	82
				BKW315 CKY	81
				BKW315 Y	81,82
				BKW3150 1KY	82
				BKW3150 SKY	81
				BKW3175 KY	82
				BKW320 1CKY	82

Item No.	Page
BKW320 1SKY	82
BKW320 1Y	81
BKW320 CKY	81
BKW320 Y	81,82
BKW3200 KY	82
BKW3225 KY	82
BKW3250 1KY	82
BKW3250 KY	82
BKW33 Y	81
BKW330 1Y	81
BKW330 CKY	81,82
BKW330 SKY	82
BKW330 Y	81,82
BKW3330 1KY	82
BKW3350 KY	82
BKW340 2SKY	81
BKW340 CKY	82
BKW340 SKY	82
BKW340 Y	81,82
BKW3400 KY	82
BKW35 CKY	81
BKW35 Y	81
BKW350 2SKY	81
BKW350 CKY	82
BKW350 SKY	82
BKW350 Y	81,82
BKW360 1KY	81
BKW360 1SKY	81
BKW360 SY	82
BKW360 Y	82
BKW375 KY	81
BKW375 SKY	81
BS	
BS11106TV	78
BS1110TV	78
BS1111TV	78
BS1112TV	78
BS1113TV	78
BS1114TV	78

CONDUIT PIPE

DME	
DME012	89
DME034	89
DME100	89
DW	
DW119T	90
DW125T	90
DW131T	90
DW139T	90
DW151T	90
DW163T	90

DW175T	90
DW216T	90
DW222T	90
DW228T	90
DW236T	90
DW242T	90
DW254T	90
DW270T	90
DW282T	90
DW392T	90
DW394T	90
DW819T	90
DW825T	90
DW831T	90
DW839T	90
DW851T	90
DW863T	90
DW875T	90
DWB	
DWB0203	89
DWB0204	89
DWB0253	89
DWB0254	89
DWB0323	89
DWB0324	89
DWB0343L	89
DWB0343S	89
DWB1003L	89
DWB1003S	89
DWB1123L	89
DWB1123S	89
DWB1143L	89
DWB1143S	89
DWB2003L	89
DWB2003S	89
DWE	
DWE012Y	88
DWE034Y	88
DWE100Y	88
DWE112Y	88
DWE114Y	88
DWE200Y	88
DWE212Y	88
DWE300Y	88
DWE312Y	88
DWE400Y	88
DWM	
DWM012Y	88
DWM034Y	88
DWM100Y	88
DWM112Y	88
DWM114Y	88
DWM200Y	88
DWM212Y	88
DWM300Y	88

DWM312Y	88
DWM400Y	88
DWR	
DWR012Y/ZY	88
DWR034Y/ZY	88
DWR100Y/ZY	88
DWR112Y/ZY	88
DWR114Y/ZY	88
DWR200Y/ZY	88
DWR212ZY	88
DWR300ZY	88
DWR400ZY	88
DWR500ZY	88
DWR600ZY	88

FACTORY LINE SYSTEMS

DGHU	
DGHU2311	95
DGHU2312	95
DGHU2313	95
DGHU2411	95
DGHU2412	95
DGHU2413	95
DGHU2421	95
DGHU2422	95
DGHU2481	95
DGHU2611	95
DGHU2612	95
DGHU2613	95
DGHU2621K1	95
DGHU2622K1	95
DGHU2631K1	95
DGHU2683	95
DGHU2711	95
DGHU2712	95
DGHU2713	95
DGHU2721	95
DGHU2722	95
DGHU2731	95
DGHU2781	95
DGHU2782	95
DGHU2783	95
DGHU2784	95
DH	
DH2423K	95
DH2431	95
DH2451	95
DH2452K1	95
DH2461	95
DH24621	95
DH2463	95
DH24641	95
DH2477	95

DH2623	95
DH2651	95
DH2652	95
DH2670	95
DH2671	95
DH26751	95
DH26771	95
DH2684	95
DH2723	95
DH2751	95
DH2752K1	95
DH2773	95
DH2774	95
DH27751	95
DH27761	95
DH27781	95
DH27791	95
DH2791	95
DH2792	95

VENTILATING FANS & AIR MOVING EQUIPMENTS

VENTILATING FAN

Item No.	Page
FV-10BAT1	124,148
FV-10EGK1	124,148,153
FV-10EGS1	120,148
FV-12NS3	113,147,151
FV-15AST1	124,148
FV-15EGK1	120,148,153
FV-15EGS1	120,148
FV-15NS3	113,147,151
FV-15WU4	125,148
FV-17CU7	109,147,149
FV-18NF3	113,147,151
FV-18NS3	113,147,151
FV-20AL9	122,148,152
FV-20AU9	121,148,152
FV-20CUT1	111,147
FV-20NS3	111,147,151
FV-20RG7	122,148,152
FV-20RL7	123,148,152
FV-20WU4	125,148
FV-23NL3	114,147,151
FV-24CD7	109,147,149
FV-24CH7	109,147,149
FV-24CU7	109,147,149
FV-24JA2	108,147
FV-24JR2	108,147
FV-25AL9	122,148,152
FV-25AU9	121,148,152
FV-25AUF1	121,148
FV-25GS4	116,148
FV-25NF3	114,147,151
FV-25NS3	114,147,151
FV-25RG7	122,148,152
FV-25RL7	123,148,152
FV-27CH9	110,147,149
FV-30AL7	122,148,152
FV-30AU9	121,148,152
FV-30GS4	116,148
FV-30KUT	118,148
FV-30RG7	122,148,152
FV-30RL6	123,148,152
FV-32CD9	110,147,149
FV-32CH9	110,147,149
FV-35GS4	116,148
FV-38CD8	111,147

FV-38CH8	111,147
FV-40GS4	116,148
FV-40KUT	118,148
FV-45GS4	116,148
FV-45GT4	117,148
FV-50AET2	118,148
FV-50GS4	117,148
FV-50GT4	117,148
FV-60GS4	117,148
FV-60GT4	117,148
FV-70HQD1	126

RANGE HOOD

FV-70HQD1	127
FV-70HQU1	127
FV-90HQU1	128

HAND DRYER

FJ-T09A3	130
FJ-T09B3	130
FJ-T10T1	130

AIR CURTAIN

FY-12ELN	132
FY-12ESN	132
FY-14ELN	132
FY-14ESN	132

AIR MOVING EQUIPMENT

FY-10CG1	134
FY-12CG1	134
FY-14CG1	134
FY-16CG1	134
FY-17CG1	134
FY-19CG1	134
FY-21CG1	134
FY-21CT1	134
FY-25DSF2NET	133
FY-28DSM2NET	133
FY-35DSM2NET	133
FY-40DSH2NET	133
FY-40DSL2NET	133
FY-40DTH2BET	133
FY-40DTL2BET	133
FY-45DST2NET	133
FY-45DTH2BET	133
FY-45DTT2BET	133

ACCESSORIES

FV-MCX100P	135
FV-MCX150P	135
FV-MGX100P	135
FV-MGX150P	135
FV-VCX100P	135
FV-VCX150P	135
FV-VGX100P	135
FV-VGX150P	135

ELECTRIC FAN

F-307KH	146
F-308NH	146
F-400C	146
F-407W	145
F-409K	145
F-409M	144
F-409Q	143
F-409U	144
F-56MPG	142
F-56MZG	142
F-56PZM	140
F-60MZZ	143
F-60TAN	140
F-60TDN	141
F-60UFN	139
F-60WWK	141,154

HEATER VENTILATING

FY-01KZDY8A	159
FY-01AZDY8A	160
FY-250ZDY8	157,160
FY-350ZDY8	157,160
FY-500ZDY8	158,160
FY-650ZDY8	160
FY-800ZDY8	158,160

AIR PURIFIER

F-PXF35A	161
F-PXJ30A	161
F-PXL45A	161
F-PXM55	161

PUMP

A

A-130JACK	163
A-130JAK	163
A-130JTX	163
A-200JAK	163
GP	
GP-129JXX	163
GP-200JXX	163
GP-250JXX	163
GP-350JA	163

A series of horizontal dashed lines for writing notes, spanning the width of the page.

NOTE

A series of horizontal dashed lines for writing notes.

A series of horizontal dashed lines for writing notes, spanning the width of the page.

NOTE

A series of horizontal dashed lines for writing notes.

A series of horizontal dashed lines for writing notes.