

Toad Edge® 2.1.6

## **User Guide**



# Copyright

## **Copyright 2020 Quest Software Inc. ALL RIGHTS RESERVED.**

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of Quest Software Inc.

The information in this document is provided in connection with Quest Software products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Quest Software products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, QUEST SOFTWARE ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL QUEST SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF QUEST SOFTWARE HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Quest Software makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Quest Software does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

Quest Software Inc.  
Attn: LEGAL Dept  
4 Polaris Way  
Aliso Viejo, CA 92656

Refer to our Web site ([www.quest.com](http://www.quest.com)) for regional and international office information.

## **Patents**

Quest Software is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at [www.quest.com/legal](http://www.quest.com/legal).

## **Trademarks**

Toad, Toad Edge, Quest, and the Quest logo are trademarks and registered trademarks of Quest Software Inc. in the U.S.A. and other countries. For a complete list of Quest Software trademarks, please visit our website at [www.quest.com/legal](http://www.quest.com/legal). Microsoft, Windows, Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Oracle is a trademark or registered trademark of Oracle and/or its affiliates in the United States and other countries. MySQL is a registered trademark of MySQL AB in the United States, the European Union and other countries. macOS™ and OS X® are trademarks of Apple Inc., registered in the U.S. and other countries. This product includes software developed by the Apache Software Foundation (<http://www.apache.org>). All other trademarks, servicemarks, registered trademarks, and registered servicemarks are the property of their respective owners.

# Contents

<b>Copyright</b> .....	<b>2</b>
<b>Contents</b> .....	<b>3</b>
<b>About Toad Edge®</b> .....	<b>6</b>
Features .....	6
<b>About Quest</b> .....	<b>7</b>
New features of Toad Edge .....	7
General features .....	7
Connection dialog enhancements .....	7
Worksheet enhancements .....	7
Support for DBMS output .....	7
Database features .....	8
Support for PostgreSQL 12 .....	8
Support for PostgreSQL 11 .....	8
Support for EDB Postgres Advanced Server 11 .....	8
MySQL 8 timezone improvements .....	8
Enhancements .....	8
Getting started with Toad Edge .....	8
Contents of installation package .....	8
Additional resources .....	9
<b>Commercial features</b> .....	<b>10</b>
<b>Technical support resources</b> .....	<b>19</b>
<b>About product improvement program</b> .....	<b>20</b>
<b>Additional Resources</b> .....	<b>21</b>
<b>Connections View</b> .....	<b>22</b>
<b>Error View</b> .....	<b>26</b>
<b>Object Detail and Describe Object</b> .....	<b>27</b>
<b>Object Explorer</b> .....	<b>29</b>

<b>Object Search</b> .....	<b>31</b>
<b>Outline View</b> .....	<b>32</b>
<b>Quick Doc View</b> .....	<b>34</b>
<b>Run Routines</b> .....	<b>36</b>
<b>SQL Monitor</b> .....	<b>37</b>
<b>SQL Recall</b> .....	<b>38</b>
<b>Session Browser</b> .....	<b>39</b>
<b>Snapshots View</b> .....	<b>40</b>
<b>Text Search</b> .....	<b>41</b>
<b>Worksheet</b> .....	<b>43</b>
<b>Result</b> .....	<b>45</b>
Multiple Result Set .....	46
<b>Keyboard Shortcuts</b> .....	<b>49</b>
<b>AutoCommit</b> .....	<b>53</b>
<b>Bind Variables</b> .....	<b>54</b>
<b>Content Assist</b> .....	<b>55</b>
<b>Copy Table</b> .....	<b>57</b>
<b>Repository</b> .....	<b>58</b>
<b>Data Export</b> .....	<b>60</b>
<b>Data Import</b> .....	<b>62</b>
<b>JSON support and JSON Editor</b> .....	<b>63</b>
<b>Management of BLOBs</b> .....	<b>66</b>
<b>Running Stored Procedures and Functions</b> .....	<b>67</b>
<b>Snapshots</b> .....	<b>68</b>
<b>Templates</b> .....	<b>69</b>
<b>About User Privileges</b> .....	<b>70</b>

<b>User and Object Privilege Views</b> .....	<b>71</b>
<b>Wildcard Patterns and Proxy Privileges</b> .....	<b>73</b>
<b>About Schema Compare</b> .....	<b>75</b>
<b>Overview Grid</b> .....	<b>76</b>
<b>Comparison Area</b> .....	<b>79</b>
About Continuous Integration and Delivery in Toad Edge® .....	80
Creating build steps - Jenkins .....	81
Creating build steps - other systems .....	82
Continuous Integration and Delivery Wizard .....	84
Toad Edge® command line interface .....	87
<b>Preferences</b> .....	<b>89</b>
General .....	89
Connection Parameters .....	90
Database .....	90
Data .....	91
Templates .....	93
Export .....	93
Folder Paths .....	94
Appearance .....	94
Feedback .....	94
<b>Third party components</b> .....	<b>95</b>

# About Toad Edge®

Toad Edge® is a next-generation tool for today's complex database environments

Toad Edge® is a flexible Java based toolset for the development and management of open source relational databases. It is built to reduce the learning curve for developers and DBAs working in next-generation database environments.

## Features

Toad Edge® allows you to:

- Connect to your databases on premise or in cloud
- View, explore and edit database structure, database objects and properties
- Manage database objects, easily add, edit or drop objects in **Object Explorer**
- Manage data stored in your database, add, edit or remove records
- Write complex SQL code comfortably in **Worksheet**
- Monitor running SQL queries in progress
- Compare and synchronize databases using powerful **Schema Compare**
- Obtain detailed information about your databases
- Edit JSON script in an advanced **Editor**
- Take database **Snapshots** and much more

# About Quest

## We are more than just a name

We are on a quest to make your information technology work harder for you. That is why we build community-driven software solutions that help you spend less time on IT administration and more time on business innovation. We help you modernize your data center, get you to the cloud quicker and provide the expertise, security and accessibility you need to grow your data-driven business. Combined with Quest's invitation to the global community to be a part of its innovation, and our firm commitment to ensuring customer satisfaction, we continue to deliver solutions that have a real impact on our customers today and leave a legacy we are proud of. We are challenging the status quo by transforming into a new software company. And as your partner, we work tirelessly to make sure your information technology is designed for you and by you. This is our mission, and we are in this together. Welcome to a new Quest. You are invited to Join the Innovation.

## Our brand, our vision. Together.

Our logo reflects our story: innovation, community and support. An important part of this story begins with the letter Q. It is a perfect circle, representing our commitment to technological precision and strength. The space in the Q itself symbolizes our need to add the missing piece — you — to the community, to the new Quest.

For sales or other inquiries, visit [www.quest.com/contact](http://www.quest.com/contact).

## New features of Toad Edge

In Toad Edge® 2.1 the following new features were implemented:

### General features

#### Connection dialog enhancements

- **Connections** has been improved

#### Worksheet enhancements

- Fix misspelled words using spell check when writing in **Worksheet**
- Responsiveness and accuracy of automatic suggestions have been improved
- Toad now highlights more letters in suggestions to help you find the object you are looking for
- Press Tab to indent selected paragraphs of text

#### Support for DBMS output

- Toad Edge now supports DBMS message output for Postgres and EDB Postgres connections

# Database features

## Support for PostgreSQL 12

- Toad Edge now supports PostgreSQL 12

## Support for PostgreSQL 11

- You now can run stored procedures

## Support for EDB Postgres Advanced Server 11

- Toad Edge now supports connecting to EDB 11

## MySQL 8 timezone improvements

- Your timezone is now preset in 'Server Time Zone' field when you create a new connection
- Difference of client and server timezones is now recorded in MySQL log

# Enhancements

The following is a list of enhancements implemented in Toad Edge 2.1.6

- UI enhancements in menus and options
- Minor enhancements of connection process for MySQL 8.0

# Getting started with Toad Edge

## Contents of installation package

The Toad Edge release package contains the following:

- Installation file of Toad Edge (MSI or PKG)
- Product Documentation, including:
  - Release Notes
  - Installation Guide
  - User Guide

**i** | **NOTE:** Toad Edge® is distributed with the latest Advanced Server JDBC Connector 4.2, MySQL Connector/J 5.1.46, and PostgreSQL JDBC 42.2.2 .



### ***Installation Instructions***

- See **System requirements** before installation to avoid any possible issues during installation or later when using Toad Edge
- Launch Toad Edge installation file and follow the instructions in the installation wizard

### ***How to Install Java Cryptography Extension***

- Download the latest JCE files:
  - local\_policy.jar
  - US\_export\_policy.jar
- and use them to replace the files in Toad Edge security folder
  - (...)Quest Software\Toad Edge\bin\jre\lib\security\

## **Additional resources**

Additional information is available from the following:

---

Toad World [Community Site](#)


Toad Edge Toad World Community.

---




## MySQL event editor

- While you can see Events in Freeware version of Toad Edge, you will be also able to edit these objects directly in **Object Detail**
- **New Object Wizard** will also help you to create new Events with ease



## Advanced user privilege management


- One of the most valuable features for database administrators is the ability to grant and revoke various user privileges at server, user or even object level



## SQL Worksheet/Editor

### Advanced Content Assist


- Content Assist is present in the Freeware version. However, upgrading allows you to configure its function



The screenshot shows the 'Content Assist / Autocompletion' configuration window. It includes several sections: 'Enable content assist' and 'Activate automatically' are both checked. The 'Delay in milliseconds' is set to 200. The 'Content Assist trigger characters' field contains a colon (:). Under 'Sorting and Filtering', 'Sort proposals by dependencies and relevance' is selected. Under 'Alias Handling', 'Generate and insert aliases (select m.title from movies m)' is selected.

### Editable result grid

- Easily select any data that fits your requirements and modify its value right in the result grid



The screenshot shows a table with 4 columns: ID, Identification, Type, and Name. The table contains 5 rows of data. The last row, with ID 2,839 and Name 'Sishen Airport', is highlighted and has a text cursor in the 'Name' cell, indicating it is editable. Below the table is a toolbar with a dropdown menu set to 'Result is Editable', navigation arrows, a page number '2762', and icons for delete, save, and refresh.

ID	Identification	Type	Name
2,835	FASC	medium_airport	Secunda Airport
2,836	FASD	medium_airport	Saldanha /Vredenburg Airport
2,837	FASI	small_airport	Springs Airfield
2,838	FASK	small_airport	Swartkop Air Force Base
2,839	FASS	medium_airport	Sishen Airport

## Export


### Export to CSV

- Export your entire table, selected rows or even query results to the universally used CSV format file

ID	Identification	Type	Name	Latitude	Longitude	Elevation	Continent	ISO country	Iso Region
56	AYGA	medium_airport	Goroka Airport	6	145	5 323	OC	PG	PG-EHG
63	AYMH	medium_airport	Mount Hagen Kagamuga Airport					PG	PG-WHM
63	AYMH	medium_airport	Mount Hagen Kagamuga Airport					PG	PG-WHM
148	SDAM	small_airport	Amarais Airport					BR	BR-SP
152	SDBP	small_airport	Fazenda Pontal Airport					BR	BR-GO
156	SDCO	small_airport	Sorocaba Airport					BR	BR-SP
255	SBAV	closed	Usina Porto Primavera Airport					BR	BR-SP
612	CAA8	small_airport	Invermere Airport					CA	CA-BC
612	CAA8	small_airport	Invermere Airport					CA	CA-BC
614	CAD4	small_airport	Trail Airport					CA	CA-BC
615	CAD5	small_airport	Merritt Airport					CA	CA-BC
621	CAH4	small_airport	Valemount Airport					CA	CA-BC
623	CAJ3	small_airport	Creston Valley Regional Airport - Art Sut					CA	CA-BC
624	CAJ4	small_airport	Anahim Lake Airport					CA	CA-BC
625	CAJ7	small_airport	Cayley A J Flying Ranch Airport					CA	CA-BC
629	CAL3	small_airport	Douglas Lake Airport					CA	CA-BC


## Schema Compare

- This powerful tool makes database difference resolution significantly easier. You can:
  - Compare two different Schemas/Databases, even across two different database connections of the same platform and version
  - View all SQL code differences between two objects
  - Compare two objects with the same name based on their timestamps
  - Generate an HTML report detailing each and every difference found
  - Generate and deploy change scripts to automatically resolve the differences



## Snapshots


- By taking a snapshot of your database, you will be able to store its structure as a JSON file and use it as a backup or as a reference for Schema Compare



## Versioning/Collaboration

### Repository


- This feature brings databases and version control systems together
- Map your database to a file system and Toad Edge will transfer your database metadata to a folder structure populated with JSON files representing individual objects, referred to as a repository
- Then, use any version control system to manage the repository



## Automation

### Continuous Integration/Continuous Delivery


- Enhance your workflow by utilizing Toad Edge CI/CD features to perform periodic tasks with no manual input
- Toad Edge is able to generate scripts and JAR files, which can be used by your automation server (such as Jenkins or TeamCity)



## Other application features


### Code snippets and templates

- Create many code templates and then reuse them by invoking a specific custom keyword. This ability saves you a significant amount of effort in the long run



### Session Browser

- This view displays all current database sessions and is updated continuously. Observe all connected users and the states of their sessions while also being able to terminate any of them, assuming you possess the appropriate privileges



ID	User	Host	DB	Command	Time	State	Thread ID	Type
23	JohnDoe	localhost		Query	0	Sending data	43	BACKGROUND
22	root	localhost		Sleep	36		42	BACKGROUND
24	root	localhost		Sleep	5		44	BACKGROUND

## Feature comparison matrix

Feature	Commercial	Freeware
SQL Worksheet/Editor		



Feature	Commercial	Freeware
Advanced Content Assist	✓	✗
Syntax check	✓	✓
Code formatting	✓	✓
Multiple statement execution	✓	✓
Execution from/to position	✓	✓
<b>Data editor</b>		
Table lookup via foreign keys	✓	✓
Basic data filters	✓	✓
Data type specific data editors	✓	✓
Editable result grid	✓	✗
<b>Export and import</b>		
Export to CSV	✓	✓
Export to SQL	✓	✗
Export to HTML	✓	✗
Export to XML	✓	✗
Import from SQL	✓	✗
Import from CSV	✓	✓
<b>Schema Compare</b>		
Schema/Database comparison	✓	✗
Advanced SQL difference recognition	✓	✗
Detailed SQL comparison settings	✓	✗
Timestamp comparison	✓	✗

Feature	Commercial	Freeware
Detailed Schema Compare reports	✓	✗
Generation of change scripts	✓	✗
<b>Snapshots</b>		
Snapshot creation	✓	✗
Snapshot comparison	✓	✗
<b>Versioning/Collaboration</b>		
Repository (MySQL only)	✓	✗
Continuous Integration/Continuous Delivery support	✓	✗
Native plugin solution for Jenkins	✓	✗
<b>Other application features</b>		
Object search	✓	✓
Code snippets/templates	✓	✗
Session browser	✓	✗
Support for JSON data types	✓	✓
JSON structure visualization	✓	✗
JSON in-place data editor	✓	✗
MySQL Events editor	✓	✗
Advanced user privilege management	✓	✗

# Technical support resources

Technical support is available to Quest customers with a valid maintenance contract and customers who have trial versions. You can access the Quest Support Portal at <https://support.quest.com>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to-videos
- Engage in community discussions
- Chat with support engineers online
- View services to assist you with your product

# About product improvement program

To prioritize enhancements in future releases, Toad Edge® collects data about the use of its different features, and periodically, this data is communicated back to us. Initially, this usage data includes an IP address. Upon its receipt at a temporary server in the U.S.A., the IP address is removed, and then the anonymous data is aggregated before it is sent to our servers in California. Our product team analyses the aggregated data to understand our user community's preferences and common practices. This analysis influences our future releases. Click [here](#) for more information on the data we collect and on our privacy policy.

- No personal information is collected
- You can stop participating at any time

## ***To initiate participation in Product Improvement Program***

Select **View | Preferences | Feedback | Product Improvement Program** and select **Yes, I want to participate**

## ***To cancel participation in Product Improvement Program***

Select **View | Preferences | Feedback | Product Improvement Program** and select **No, thank you**

# Additional Resources

---

Toad World [Community Site](#)

Toad Edge Toad World Community.

---

# Connections View


All of your existing connections can be found in this view. You can edit or delete them as well as add new ones.

## ***To create a new connection***


1. Click **New Connection** or click **Connect** in application toolbar and select **New Connection**
2. Select your **Database Platform**
3. Fill in the **Connection Settings**. You can **Test Connection** before you actually create it to see whether Toad Edge is able to connect to your database successfully
4. Optionally, check **Custom connection string** and edit it
5. Adjust your new **Connection Details**, such as name, color, and Autocommit

6. Optionally, enter your secure connection details:


- In **SSL Authentication** click Enable SSL and enter paths or click browse to set your Certificate authority file, Certification file and Key file







- In **SSH Authentication** click Enable SSH and set your SSH connection details. Optionally, enable **Certificate Authorization** and enter the path to your certificate and your passphrase



7. Click **Finish** to save the connection



Button	Option	Description
	Link with Editor	If enabled, bringing a window ( <a href="#">Worksheet</a> , <a href="#">Object Detail</a> and <a href="#">Describe Object...</a> ) into focus will highlight the window in Connections View and selecting the window in Connections view will bring it into focus
	New Connection	Displays a dialog where you can create a new connection as described above
	Connect Selected	Connects the selected connection
	Disconnect Selected	Disconnects the selected connection

## To create like connection

- Right-click any connection in **Connections** and select **Copy Connection** to use its settings to create a similar database connection

## Connection properties

Existing connections, connection drivers and performance settings can be configured in this dialog.

### *To configure a connection*

- Right-click any connection in **Connections** and select **Properties**



Tab	Description
Connection Settings	This tab contains connection settings identical to those that are set when a connection is created
Connection Details	<p>You can set the following options here:</p> <ul style="list-style-type: none"> <li>• Connection name - Add a custom name for your connection</li> <li>• Connection color - Select a color for your connection</li> <li>• Description - Add a custom description</li> <li>• <a href="#">AutoCommit</a> - Check to enable Autocommit feature for the connection</li> <li>• Restore previous work after login - Automatically restores the previous Toad Edge session</li> </ul>
SSL Authentication	Enable SSL and enter paths or click browse to set your Certificate authority file, Certification file and Key file
SSH Authentication	Enable SSH and set your SSH connection details. Optionally, enable <b>Certificate Authorization</b> and enter the path to your certificate and your passphrase
Driver Settings	You can choose which available JDBC driver should be used by the connection. <b>Add</b> a new driver, <b>Remove</b> a selected driver. Click <b>Suggest</b> to let Toad Edge decide which driver is the most appropriate for you
Performance	This tab contains settings which determine the performance of the connection by loading objects in <b>Object Explorer</b> in a specific way. Click <b>Auto Configure</b> to let Toad Edge decide for you

# Error View

This view provides you with information about issues encountered during the execution of SQL statements.

- Click the error description to highlight the statement that caused the problem while working with [Worksheet](#)



# Object Detail and Describe Object


**Object Detail** and **Describe Object** are the primary ways to view and modify objects in your database (especially data in [Data tab](#)). They are nearly identical except for one key difference:

- **Object Detail** is opened to view any database object of any connection
- **Describe Object** is opened for each connection to view all database objects of the connection

## To view an object in Object Detail window

- In **Object Explorer**, double-click the object you would like to view
- Note how each object is displayed in its own **Object Detail** window



## To view objects in Describe Object window

1. In **Object Explorer** toolbar, enable the  **Open Objects in Common Detail Window** option
2. Left-click any object in **Object Explorer** that you would like to view
  - Note how all objects of a connection are displayed in one **Describe Object** window


The tabs displayed in **Object Detail** and **Describe Object** depend on the specific type of an object you are trying to view. For example, if you open a table, you will see additional tabs such as Columns, Indexes and Constraints.

## Data tab

One of the most useful features of both **Object Detail** and **Describe Object** is this tab where you can view, filter and edit data in your tables and views without the need of writing complicated SQL queries.













**TIP:** While working with records in a child table, you can quickly move to the linked record in the parent table by pressing **CTRL** () and clicking on the record value in its foreign key column. The values change into hyperlinks when you hold **CTRL** (.




comment_id	movie_comment	customer_id	movie_id
9	What a movie!	<a href="#">23</a>	1




The screenshot shows the 'Describe Object' window for the 'world\_energy\_use' table. The 'Data' tab is selected, displaying a table with the following data:

id	Country	Year	Population	GDP_PPP	GDP_USD	Energy_use
1	Sao Tome & Principee	2006	158,806	404	139	44
2	Uruguay	2006	3,330,217	43,900	18,075	3,183
3	Bangladeshs	2007	146,457,067	316,125	68,810	26,626

Button	Option	Description
	Refresh Query	Refreshes the data currently visible in the grid
	Cancel Query	Cancels loading of the data in grid. Useful in cases where your tables/views have millions of rows and you have disabled the <a href="#">Use fetch limit</a> option
	Insert Row	Creates a new record in the table, simply fill in the values for all columns
	Delete Rows	Deletes the selected row(s)
	Apply Changes	Saves the value that is currently being edited
	Discard Changes	Restores the original data in the value that is currently being edited
	Commit Transaction	Commits the changes you have made to the table. See <a href="#">AutoCommit</a> for more information
	Rollback Transaction	Rolls back the changes you have made to the table. See <a href="#">AutoCommit</a> for more information
	Resize Columns to Data	Resizes columns so they fit the values they contain
	Sort Columns Alphabetically	If enabled, the columns are ordered alphabetically
	Select Visible Columns	Opens a dialog where you can select which columns you would like to display or hide
	Sort Data	Opens a dialog where you can sort the records by one or more column values in ascending or descending order

Where:   Filter  

Filters the currently shown data. Use the same notation as you would in the WHERE clause in a query. In case of multiple conditions, put "and" between them

**i** **TIP:** The light bulb icon  suggests that there is an available history of your Where conditions. Press **CTRL (⌘) + ARROW DOWN** while typing in the field to view it.

# Object Explorer

Object Explorer allows you to comfortably navigate your databases and view their objects. The contents of the explorer change depending on the currently selected connection in [Connections View](#). There are various options available in the context menu depending on the type of object you select.


**i** | Note: To quickly find a specific object in any database of a connection, use the [Object Search](#) function (**CTRL (⌘) + SHIFT + D**)

## Default database (MySQL/MariaDB)








You can set any of your MySQL or MariaDB databases as **default**. This means that scripts in [Worksheet](#) will be executed on the selected database by default if you do not specify another database.

### To set a default database

- In Object Explorer, right-click any database and select **Set Database as Default**



## Object Explorer toolbar

Button	Option	Description
	Link with Editor	If enabled, bringing a window ( <a href="#">Worksheet</a> , <a href="#">Object Detail</a> and <a href="#">Describe Object...</a> ) into focus will highlight the window in <a href="#">Connections View</a> and selecting the window in <a href="#">Connections view</a> will bring it into focus
	Define Visible Categories	Opens a dialog where you can set which categories / object types should be shown or hidden
	Open Objects in Common Detail Window	If enabled, allows you to use the <b>Describe Object</b> window. See <a href="#">Object Detail and Describe Object</a> for more information
	Refresh	Refreshes the status of the selected object / object type / database
	Rename Selected Object	Opens a dialog where you can change the name of the selected object
	Drop Selected Objects	Deletes the selected object(s) from the database
	New *object*	Creates a new specific object depending on the object type you are currently viewing

**Button**   **Option**

**Description**

---

Filter:  Filter 

Filters the objects in Object Explorer according to the input. It is possible to use wildcards (? and \*) and regular expressions as well as filter by multiple comma separated values

# Object Search


This tool allows you to search for any database object of the currently selected connection in [Connections View](#).

## To search for object(s)

1. Open Object Search window by clicking the **Object Search** button in the application toolbar or by pressing **CTRL (⌘) + SHIFT + D**
2. From the **Databases** section, select databases that should be searched
3. In the **Object types** section, check the object types that should be included in the search
4. Start writing the object name. The search results will be displayed as you write

You can use any of the following in your search query:

- **Simple text** - Toad Edge will look for the literal text string, the search is case insensitive
  - For example, "air" will match "airport\_frequencies", but not "test\_airport"
- **Wildcard characters** - where a question mark (?) represents any one character and an asterisk (\*) any number of any characters
  - For example, "?cc\*s" will match "ACCESS\_TIME" as well as "accounts", but not "accident\_data"
- **Multiple values** - use multiple search patterns, separated by commas (,)
  - For example, "test, customer" will match both "test\_function" and "customer\_id"
- **Regular expressions** - enclosed in square brackets ([regex])
  - For example, "[^[cd]u+]" will match "DURATION" or "customer\_id", but not "concurrent\_connections"



# Outline View


The contents of the View change depending on what are you doing in Toad Edge. Its functionality can be divided into several modes:

- [Code outline](#)
- [Database object outline](#)
- [JSON outline](#)
- [Schema Compare settings](#)

**i** **TIP:** In all modes except for **Schema Compare**, you can click on any item in the **Outline** to navigate to the object quickly in the other UI element. For example, clicking on a specific constraint in database object outline mode switches **Object Detail/Describe Object** to **Constraints** tab and highlights the selected constraint.


## Code outline

When editing procedures, functions, etc., **Outline** displays the code structure, including variables.



## Database object outline


In this mode, **Outline** displays important details of database objects displayed in [Object Detail and Describe Object](#).



## JSON outline

This mode is triggered by opening a JSON column value in [JSON support and JSON Editor](#). In this case, the complete structure of the current JSON value, including nested values, is shown.





## Schema Compare settings

When in **Schema Compare**, **Outline** displays comparison settings which determine what is considered a difference and what should be ignored.

### Column Matching

You can match columns based on:

- Position
- Identical names
- Similar names

### Difference Fragmentation

This slider further determines the precision of difference finding. The further it goes left, the smaller and more precise the differences are, such as specific values or words. The further it goes right, the looser and more flexible the differences are, such as entire statements or blocks of code.

Slider position	Difference precision
	<pre>ELSEIF (bonus &lt;= 1000 AND bonus &gt;= 1000)</pre>
	<pre>ELSEIF (bonus &lt;= 1000 AND bonus &gt;= 1000)</pre>

# Quick Doc View

**Quick Doc** displays brief, relevant information about the currently selected objects.

**Quick Doc** has two modes:

- **Object Explorer mode**
- **Comparison mode**


## Object Explorer mode

This mode is used most of the time. As you select various objects in [Object Explorer](#), **Quick Doc** displays basic information about them.




## Comparison mode

This mode is triggered when you work with [Overview Grid](#) as part of [About Schema Compare](#) or [Repository](#). It displays specific differences between two objects in a row that is currently selected in the grid. The view becomes very useful in cases where there are many differences.



## Quick Doc view toolbar


Button	Option	Description
	Link with Selection	If enabled, <b>Quick Doc</b> automatically displays information every time you select an object in <b>Object Explorer</b> or a record in the <b>Overview Grid</b>







Open Declaration (Object Explorer mode only) Opens the currently described object in [Object Detail and Describe Object](#)

# Run Routines

The results of all executed routines (procedures and functions) are shown in this view. You can rerun routines using the same arguments or view past results.




Button	Option	Description
	Run	Runs the routine using the argument values entered in the grid
	Select Connection	If you executed a routine with the same name from multiple connections, you can specify the connection from which the routine should be executed using this drop down menu
	Show Results	Displays the results of routines you executed in the past
	Remove Execution Result	Removes the current routine result from the view


# SQL Monitor






**SQL Monitor** displays all internal/user executed SQL queries as well as their execution time. Any queries that fail during the execution are commented out in the monitor and the error description is attached.

**i** | **NOTE:** Internal queries refer to queries automatically performed by Toad Edge during certain actions (e.g. viewing table data in **Object Detail**)

**SQL Monitor** is disabled by default and you will have to enable it by clicking the  **Enable/Disable Output**


button in order to monitor queries.



Button	Option	Description
	Enable/Disable Output	Enables/disables SQL query monitoring
	Clear Console	Deletes the contents of the view
	Export Script	Exports the contents of the view to a SQL file
	Scroll Lock	If enabled, your current position in the monitor is not changed even as new information is being displayed. Otherwise, the position changes to display the newest information
	View Menu	This menu allows you to enable/disable monitoring of internal/user queries

# SQL Recall

**SQL Recall** displays the last 100 executed SQL statements. The statements are grouped by connection and can be filtered and pinned. You can view the entire statement simply by selecting in the view. Double-clicking a statement will cause it to be pasted into the currently active [Worksheet](#).



Button	Option	Description
--------	--------	-------------



	Filter	Filters the statements according to the input. It is possible to use wildcards (? and *) and regular expressions as well as filter by multiple comma separated values
--	--------	---

- |  |                       |  |
|--|-----------------------|--|
|  | Expand All            | Expands all connections to display their statements  |
|  | Collapse All          | Collapses all connections, hiding all statements   |
|  | Copy                  | Copies the currently selected statement to clipboard. You can copy multiple statements at once |
|  | Hide Unpinned Entries | Hides statements that are not pinned   |
|  | Pin Entry             | Pins the selected statement(s) so they can be filtered using the option above                  |
|  | Delete All            | Deletes all statements from the view   |
|  | Delete                | Deletes the selected statement(s) from the view  |


# Session Browser


The **Session Browser** displays database sessions and their state. The information is continuously updated and all changing values are highlighted. The sessions can be filtered and inactive sessions can be hidden. If the current user has sufficient privileges, it is also possible to terminate sessions.







## To start monitoring sessions

- Select a database connection from the  **Select Connection** dropdown menu
- The refresh period can be configured in the  **View Menu** dropdown menu

## To terminate a session


- Select session that you want to terminate and then click the  **Kill Selected Session** button









Toolbar button	Name	Description
	Refresh	Manual update of the status of all sessions
	Select Connection	Select a connection here in order to monitor its sessions
	Hide Inactive Sessions	Hides sessions that are currently not being active (e.g. sessions that are asleep)
	Resize Columns to Data	Resizes columns so they fit the values they contain
	Kill Selected Session	Terminates the selected session
	View Menu	Allows you to change the monitoring refresh period

# Snapshots View

This view displays all taken [Snapshots](#), grouped by connection and database. From here you can filter, export/import and also delete snapshots.



Button	Option	Description
	Import Snapshot	When a database is selected, you can import a snapshot from file (.json). This snapshot will be then listed under the database in the view
	Export Snapshot	Exports the selected snapshot as a JSON file
	Compare Snapshot with Active Database	Compares the selected snapshot with the database that is currently marked as <b>Default</b> in <a href="#">Object Explorer</a> . Note that the currently selected connection in <a href="#">Connections View</a> must have a default database for this option to be available
	Compare with Each Other	When you select two snapshots, you can compare them with each other using this option
	Generate Script	Generates a create script based on the selected snapshot. The script can be generated to clipboard, a worksheet or to a file
	Delete Snapshot	Removes the selected snapshot from the view and deletes the snapshot file



# Text Search

Not to be confused with [Object Search](#), **Text Search** allows you to find specific strings in database scripts of certain object types such as (platform dependent):

- Aggregates
- Procedures
- Functions
- Events
- Packages
- Triggers
- User types
- Views and materialized views

## **To search for specific text in object scripts**


1. Select **Database Menu | Text Search** or by pressing *CTRL + H*
2. Enter the text you want to look for into the **Containing text** field
3. The other field, **Object name patterns**, allows you to search only in objects that match the given pattern
  - For example, `"*energy*"` will cause the application to only search for text in objects whose names contain "energy"
4. Select the **Databases** that you want to search in as well as the **Object types**
5. Once finished, click **Search**. The results will be shown in **Text Search**










**i** **NOTE:** You can use standard wildcard characters in both fields mentioned above. Use question mark (?) to match one character, asterisk (\*) to match multiple characters and back slash (/) to escape literal characters.

You can also use multiple search patterns in the **Object name patterns** field as long as you separate them with commas.

## **Text Search**

The results of Text Search are displayed in this window. By double-clicking any match, you can open the respective object in **Object Detail** and highlight the match.



Button	Option	Description
	Show Next Match	Jumps to the next match, automatically displaying it in Object Detail
	Show Previous Match	Jumps to the previous match, automatically displaying it in Object Detail
	Remove Selected Matches	Removes the selected matches from the view
	Remove All Matches	Removes all matches from the view
	Expand All	Expands all objects and their matches
	Collapse All	Collapses all matches to their respective objects
	Refresh the Current Search Again	Performs the current search again
	Cancel Current Search	Cancels the currently undergoing search
	Show Previous Searches	Contains a history of past searches that you can perform again

# Worksheet














Worksheet is one of the most basic tools in Toad Edge. It is used to interact with a database using SQL scripts and queries. Coupled with additional features such as [Content Assist](#) and [Outline View](#), you can create and modify queries in a fast and efficient manner.

**i** | **NOTE:** If you do not specify a database, the scripts and queries will be executed on the [Default database \(MySQL/MariaDB\)](#)

## To open a Worksheet

- Click the **Worksheet** button on main toolbar to open a blank Worksheet

## Worksheet toolbar


Button	Option	Description
	Execute All Statements	Executes all statements in the query
	Execute From Current Position	Executes all statements from the current cursor position in the query
	Execute to Current Position	Executes all statements up to the current cursor position in the query
	Execute SQL Statement	Executes the statement where the cursor is currently placed. Can be used to execute multiple selected statements at once
	Execute Explain All	Displays explain plan cost of all queries
	Execute Explain From	Displays explain plan cost of all queries from the current one up to the end
	Execute Explain To	Displays explain plan cost of all queries from the beginning up to the current one
	Execute Current	Displays explain plan cost of the current SQL query
	Cancel Query	Stops the query that is currently being executed
	Commit Transaction	Commits the changes included in the current transaction. See <a href="#">AutoCommit</a> for more information
	Rollback Transaction	Cancels the changes included in the current transaction. See <a href="#">AutoCommit</a> for more information
	Select Connection	Allows you to select a connection using which the query should be executed
	Show Result Set	Displays <b>Result Set</b> either in <b>Vertical Layout</b> or <b>Horizontal Layout</b>


## Worksheet context menu options

Option	Description
Revert	Restores the last saved state of the Worksheet
Open	Opens the selected object in <b>Object Detail</b> . Note that this option only works when you place the cursor in or select a highlighted object name, i.e. an object that already exists in the database
Make Code Statement	Generates Java code which recreates the selected query as a StringBuilder object. The code is copied to clipboard
Strip Code Statement	When selecting Java code which contains a SQL query, this option will strip away the Java code and keep the SQL code. The code is copied to clipboard
Formatting	Provides options to switch the selected text to uppercase/lowercase or to enclose it in text/object quotes
Quick Outline	Displays the basic structure of a Worksheet if it contains multiple queries
Toggle Comment	Comments out the selected lines

## Hint Window

When you hover over a database object name, **Hint Window** is displayed to provide you with quick information about the object. Hover over the bottom bar of the window to see additional options.



Button	Option	Description
	Open Declaration	Opens the object in <b>Object Detail</b>
	Show Script	Displays the object SQL code in a new Worksheet


# Result

When you execute a SELECT statement in Worksheet, the result is displayed in the Result. The rows and cell values here can be conveniently exported to multiple formats and you can even edit the cell values in-place.

**i** | **NOTE:** Currently, the Result is only displayed if you execute a SELECT statement alone and not as a part of a query.

## To switch Result to editable mode

- Select the **Result is Editable** option in the drop down menu in the bottom-left corner of the Result






**i** | **NOTE:** The SELECT statement must satisfy several conditions in order for the Result to be editable. Specifically, the statement must not contain:

- Aggregation functions (count, max, sum...)
- Set operators (join, union...)
- Nested SELECT statements

Additionally, the Result is not editable when selecting from a view or when the selection does not include at least one identification key column (e.g. primary key).

## To navigate and manipulate results

Button	Option	Description
	Go to Beginning	Goes to the first page of the Result Set
	Go to Previous Page	Goes to the previous page of the Result Set
	Selected Row	Displays the number of the currently selected row
	Go to Next Page	Goes to the next page of the Result Set
	Go to End	Goes to the last page of the Result Set

	Drop Selected Rows	Deletes the selected rows
	Apply Changes	After editing a value, applies the changes
	Restore Original Values	After editing a value, cancels the changes

### Result context menu options


Option	Description
Define in Editor	Edits the selected cell value in a type-specific editor
Set Null	Sets the selected cell value to null
Export BLOB to file	(BLOB columns only) Exports the binary object of the selected cell as a file
Import BLOB from file	(BLOB columns only) Imports a file as a binary object and places it into the selected cell
Export Selection	Exports the currently selected rows as SQL code or to a CSV/HTML/XML file
Export Query Result	Exports the entire result as SQL code or comma separated values

## Multiple Result Set


Toad Edge supports working with more than one result sets. Type your **SELECT** queries into **Worksheet** and click **Execute All Statements**. Result sets from all queries will be displayed in a new **Result** view, where you can easily switch between results, display them side-by-side, edit and export them

### To work with multiple results


- Left-click a result to select it
- Hold Shift/Ctrl + left-click multiple results to select them



- Click **SQL** button to highlight a specific statement in **Worksheet**
- Right-click a statement in **Result** and click copy to copy the statement and later paste it into **Worksheet**




- Only a certain number of results will be fetched on execution. Scroll down to reveal more results when one result is selected. Set the number of fetched rows in **View | Preferences | Data | Use fetch limit**
- When more result sets are selected, click **Fetch More Rows** or **Fetch All Rows** to load more data



### To export results

- Click **Export Selected Statements Data to CSV/SQL** to export some of the result sets
- Click **Export All Statements Data to CSV/SQL** to export all of the result sets



- Configure destination and format options in the next step:

Feature	Description
Export As	<p>Select the desired option:</p> <ul style="list-style-type: none"> <li>• SQL - INSERT statements - exports the data as INSERT SQL statements into the selected destination</li> <li>• SQL - MERGE statements - exports the data as MERGE SQL statements into the selected destination</li> <li>• CSV - exports the data as comma separated values into the selected destination</li> </ul>
Line Terminator	<p>Select from:</p> <ul style="list-style-type: none"> <li>• Environment default</li> <li>• Mac/Unix</li> <li>• Windows</li> <li>• Mac OS Classic</li> </ul>
Destination for exported data	<p>Exported data are displayed in:</p> <ul style="list-style-type: none"> <li>• Worksheet - Toad Edge exports the data into a new instance of <b>Worksheet</b></li> <li>• Clipboard - Exports data into system clipboard</li> <li>• Single file - Click browse button to select the name for the exported file and its location. All result sets will be saved in one file.</li> <li>• Separate files - Click browse button to select the name for the exported file and its location. Files will named automatically.</li> </ul>
Compress file in ZIP format	Available for exporting as files.
Open directory after finishing the export	Opens the destination directory after a successful export.
Format exported queries	Check to export data in an easier-to-read format with indentations and extra lines.



# Keyboard Shortcuts

This topic lists shortcuts that you can use when working Toad Edge.

## General shortcuts

Option	Shortcut
Open SQL <a href="#">Worksheet</a>	CTRL (⌘) + N
Close	CTRL (⌘) + W
Close All	CTRL (⌘) + SHIFT + W
Save	CTRL (⌘) + S
Print	CTRL (⌘) + P
Undo	CTRL (⌘) + Z
Redo	CTRL (⌘) + Y
Cut	CTRL (⌘) + X
Copy	CTRL (⌘) + C
Paste	CTRL (⌘) + V
Delete	DELETE
Select All	CTRL (⌘) + A
<a href="#">Object Search</a>	CTRL (⌘) + SHIFT + D
Text Search	CTRL (⌘) + H
Enable / Disable <a href="#">AutoCommit</a>	CTRL (⌘) + ALT (OPT) + A
Manage Connections	CTRL (⌘) + ALT (OPT) + C
New Connection	CTRL (⌘) + ALT (OPT) + N
Disconnect	CTRL (⌘) + ALT (OPT) + I
Reconnect	CTRL (⌘) + ALT (OPT) + R
Preferences	ALT (OPT) + P
Maximize Window	CTRL (⌘) + M
Reset Application Layout	ALT (OPT) + SHIFT + L
Help	F1
Open Tab Dropdown Menu	CTRL (⌘) + E
Next Tab	CTRL (⌘) + F6
Previous Tab	CTRL (⌘) + SHIFT + F6

## New object shortcuts

Option	Shortcut
Database	ALT (OPT) + SHIFT + D
Event	ALT (OPT) + SHIFT + E
Function	ALT (OPT) + SHIFT + F
Procedure	ALT (OPT) + SHIFT + P
Role	ALT (OPT) + SHIFT + O
Schema	ALT (OPT) + SHIFT + H
Sequence	ALT (OPT) + SHIFT + Q
Table	ALT (OPT) + SHIFT + T
Trigger	ALT (OPT) + SHIFT + R
Trigger Function	ALT (OPT) + SHIFT + G
Type	ALT (OPT) + SHIFT + Y
User	ALT (OPT) + SHIFT + U
View	ALT (OPT) + SHIFT + V

## Worksheet shortcuts

Use these shortcuts while working with [Worksheet](#). Some of these shortcuts also work in **Source** of procedures and functions opened in **Object Detail**.

Option	Shortcut
Find and Replace	CTRL (⌘) + F
Find Next	CTRL (⌘) + K
Find Previous	CTRL (⌘) + SHIFT + K
Format Code	CTRL (⌘) + SHIFT + F
Open (cursor located in an existing object name)	F3
Rename/refactor (cursor located in an existing object name or alias)	F2
Add Object Quotation Marks	CTRL (⌘) + SHIFT + Q
Add Text Quotation Marks	CTRL (⌘) + ALT (OPT) + SHIFT + Q
To Upper Case	CTRL (⌘) + SHIFT + X
To Lower Case	CTRL (⌘) + SHIFT + Y
Execute All Statements	CTRL (⌘) + SHIFT + ENTER
Execute Selected	CTRL (⌘) + ENTER
Execute To Current Position	CTRL (⌘) + SHIFT + UP ARROW

Option	Shortcut
Execute From Current Position	CTRL (⌘) + SHIFT + DOWN ARROW
Toggle Comment	CTRL (⌘) + /
Content Assist	CTRL + SPACE
Surround with Parentheses	CTRL (⌘) + ALT (OPT) + 1
Surround with Brackets	CTRL (⌘) + ALT (OPT) + 2
Surround with Braces	CTRL (⌘) + ALT (OPT) + 3
Delete Line	CTRL (⌘) + D
Go to Line	CTRL (⌘) + L
Scroll Line Up	CTRL (⌘) + UP ARROW
Scroll Line Down	CTRL (⌘) + DOWN ARROW
Additional context menu	CTRL (⌘) + F10
Move Line Up	ALT (OPT) + UP ARROW
Move Line Down	ALT (OPT) + DOWN ARROW
Object Information (cursor located in an existing object name)	F6

## Object Detail | Data, Editable Result set

Option	Shortcut
Insert Row	SHIFT + INSERT
Delete Selected Row	SHIFT + DELETE
Apply Changes	SHIFT + ENTER
Discard Changes	ESC
Edit Value	ENTER
Open Value in Editor	CTRL (⌘) + E
Insert Null	DELETE
Restore Original Values	ESC
Lock/Unlock values for editing (Result set)	CTRL (⌘) + SHIFT + E

## Object Detail | Source (procedures and functions)

Option	Shortcut
Refresh	F5
Execute SQL Statement	SHIFT + ENTER
Run	CTRL (⌘) + R

## Connections

Option	Shortcut
Copy Connection	CTRL (⌘) + C
Reconnect	F5
Properties	F2

## Search

Option	Shortcut
Next Match	CTRL (⌘) + .
Previous Match	CTRL (⌘) + ,
Remove Selected Matches	DELETE

# AutoCommit

When you turn on AutoCommit for your connection, all SQL statements will form transactions on their own and will be committed immediately unless an error is returned.

## To enable/disable AutoCommit in Worksheet/Object Detail

- Double-click the **AutoCommit** button in the bottom application bar





## To enable/disable AutoCommit in Connections

- Right-click a connection in **Connections** and select **Properties** | Connection Details **Enable AutoCommit**
- The last option is to go to **Database menu** and select **Enable/Disable AutoCommit**

When you disable AutoCommit, you will have to commit or rollback your transactions manually. Whenever you execute a DML statement in **Worksheet** or make any modification using **Object Detail**, the changes will be applied only in your session. They will not be applied in the database unless you commit them.

There are two buttons that can be used to manually control the process:

- **Commit Transaction**  - the changes you have made will be committed and applied in the database
- **Rollback Transaction**  - the changes you have made will be discarded and the database will not be modified


**i** | **NOTE:** These buttons are disabled when AutoCommit is enabled.

# Bind Variables

Toad Edge provides a way to reuse queries by using variables instead of specific values. These variables can be given value each time you execute a query.

## To bind and use variables

1. Open a new **Worksheet** and start writing your query. Use a single or double question mark ("?" or "??") to bind variables
2. Execute the query
3. **Bind Variables** dialog appears. You can give each variable a value and then finish executing the query



# Content Assist


To make writing scripts and editing JSON data easier, Toad Edge offers a convenient tool - Content Assist (also known as Intellisense). This utility automatically suggests keywords or templates you might want to use when you are working with [Worksheet](#) or [JSON support and JSON Editor](#) on page 63

Content Assist can be displayed in two ways:

- Type any Content Assist trigger character and wait a set delay (configurable in Preferences | [Content Assist / Autocompletion](#) on page 91)
- Manually by pressing *CTRL (⌘) + SPACE*


## Content Assist - SQL

In this environment, Content Assist suggests various relevant SQL keywords depending on the context of your query. It also suggests default or custom [Templates](#).



## Content Assist - JSON

Once you open JSON Editor, you can invoke Content Assist to utilize JSON templates. Instead of worrying about closing brackets and quoting keys properly, you can simply insert the key-value structure and just fill in the values.






# Copy Table

The Copy Table tool is convenient for when you need to copy an entire table with all its contents to the same or a different database.

**i** | **NOTE:** You can only copy tables between databases of the same connection.

## To copy a table:

- In **Object Explorer**, right-click the table you want to copy and select **Copy Table...**
- In the first dialog of **Copy Table wizard**, select the destination **Database** and enter the copied **Table name**
- In the last dialog, you can select which table columns should be copied




# Repository

Version control systems (VCS) are not a part of database systems by default. However, Toad Edge® offers a way to apply version control to a database by mapping it to a file system as a folder structure where each object is represented by a JSON file. The resulting structure is referred to as a "repository". It can be tracked with any VCS and it can be also synchronized with any other database of the same platform and version using **Schema Compare. Repository** is available for MySQL and MariaDB.


## To map a database to a file system

1. Right-click a database in **Object Explorer** and select **Repository | Map Database**
2. Enter the path to the destination folder where the database folder structure should be created

Your database is now mapped to the file system. The path to the folder structure is displayed next to the database icon in **Object Explorer**.








Object Explorer also displays the synchronization status of all objects in the database.



The following table lists all possible states indicated by the object decorators and the action suggested once you synchronize database and repository:

Decorator	Cause	Suggested action	Description
	A new object was added to database that is not present in repository	 Change target	You added a new object to your database. Toad Edge assumes you want to add the object to your repository as well
	An object was deleted from repository, but it still exists in database	 Change source	You deleted an object in your repository. Toad Edge assumes you want to delete the object from your database as well
	An object was probably modified in database / repository	None	You modified an object in your database / repository. These changes have been detected by Toad Edge but they have not been confirmed yet. To confirm and resolve them, <b>Synchronize</b> the database and the repository
	An object was confirmed to be		You modified an object in your database / repository and synchronized them afterwards. Toad Edge assumes that when

	modified in database / repository	Change source / target	you modify an object on one side you will want to modify on the other side as well.
	An object was possibly modified in both database and repository	None	You modified an object in both your database and your repository. These changes have been detected by Toad Edge but they have not been confirmed yet. To confirm and resolve them, <b>Synchronize</b> the database and the repository
	An object was confirmed to be modified in both database and repository	 Change both	You modified an object in your database / repository and synchronized them afterwards. Toad Edge assumes that when you modify an object on both sides, you will want to decide which specific changes should be applied in the source and the target
	An object has not been added to repository yet, its state is unknown	 Change target	You mapped your database to a file system (repository), but you have not synchronized them yet. <b>Synchronize</b> the database and the repository in order to copy the objects from your database to the repository

### **To remove mapping of a database to a file system**

1. Right-click a database in **Object Explorer** and select **Repository | Remove Mapping**
2. Confirm the removal. Optionally, you can check the **Also delete file on disk** checkbox to delete the remaining files in the file system

### **To synchronize a mapped database with a repository**

- Right-click a database that is mapped to a file system in **Object Explorer** and select **Repository | Synchronize**

The process of synchronization of a database and a repository is very similar to **Schema Compare**. See [About Schema Compare](#) to learn more about the synchronization process.



**i** **NOTE:** When synchronizing a database and a repository, it is currently not possible to use the **Change both** resolution action to resolve specific differences.

# Data Export

Toad Edge allows you to export various data from [Object Explorer](#), [Object Detail](#) and [Describe Object and Result Set](#).

## Exporting data from Object Explorer

There are two kinds of exports available in **Object Explorer**:

- **Export Script**  - exports the SQL create script for any object
- **Export Data**  - exports table records

You can export data in SQL (INSERT/MERGE ) or CSV format.

### *To export script of an object in Object Explorer*



1. Right-click an object and select **Export Script**
2. Select **Destination** and configure **Script Options**

### *To export table data in Object Explorer*

1. Right-click a table and select **Export Data**
2. In the first dialog of the wizard, you can **Add** other tables to the export. If your table is linked to other tables by a relationship, you can also **Add Children/Parent** tables
3. In the next dialog, select the export **format** and its **Destination**
4. The next dialog presents you with a grid where you can exclude specific data type columns from the export
5. If you want to exclude specific columns rather than column data types, you can do so in the following dialog
6. The last dialog contains a couple more **SQL Settings**. Once you are done with the configuration, click **Finish**

## Exporting data from Object Detail and Result Set

There are two kinds of exports available in **Object Detail | Data tab** and **Result Set**:

- **Export Grid Selection**  - exports the rows that you have selected in grid
- **Export Query Result**  - exports the entire contents of the grid


You can export data in CSV and SQL (INSERT/MERGE statements) format. Grid selection can be additionally exported in HTML and XML format.

### ***To export data from Object Detail or Result Set***


1. Open a table or a view in **Object Detail | Data tab** or execute a query to display the **Result Set**
2. Right-click anywhere in the grid and select **Export Grid Selection** or **Export Query Result**
3. If exporting to XML/HTML, simply choose the destination path and **Save** the export
4. If exporting to CSV/SQL, select the **format** of the export and its **Destination**
5. In the last dialog, configure the final **SQL/CSV Settings** to your liking and click **Finish**


# Data Import

Importing data is the fastest way to populate your tables. Toad Edge offers data import from SQL (INSERT or MERGE statements) or CSV files. You can even import data from ZIP archives that contain these files.

 Note: CSV file import currently allows importing data only into one table at a time.

## To import data into a table:

1. In **Object Explorer**, right-click the table you want to import data into and choose **Import Data...** 
2. In the **Import Data wizard**, choose the import file format, the **Source** path and encoding. The encoding field is editable in case encoding is not detected correctly
3. The final dialog depends on whether you import a SQL or a CSV file:
  - SQL file - you can configure additional **SQL Format Settings**, for example, you may want to remove the database name from the code or open it in [Worksheet](#)
  - CSV file - you can configure various **CSV Format Settings** such as delimiters, date and time formats...
4. Once you are done with the final configuration, click **Finish**




# JSON support and JSON Editor

With Toad Edge you can view JSON columns structure clearly in multiple places and you can also edit specific JSON values using an editor with support of Content Assist, Quick Fixes, and other features that support native JSON (JavaScript Object Notation) data types.


## To view JSON column values

1. In **Object Explorer**, locate your database/schema and then the table that contains a JSON data type column
2. Expand the table node, the columns node and then finally the node of the specific JSON column




## To view detailed structure of JSON values

1. Double-click any table in **Object Explorer** with a JSON data type column to open it in **Object Detail**
2. In **Object Detail**, switch to the **Data** tab
3. Right-click a value and select **Define in Editor** to open the value in **JSON Editor**
4. The structure of the specific JSON value is then displayed in **Outline View**




## JSON Editor





### To edit values in JSON Editor

1. Double-click any table in **Object Explorer** with a JSON data type column to open it in **Object Detail**
2. In **Object Detail**, switch to the **Data** tab
3. Open a JSON value in **JSON Editor** by either:
  - Right-clicking the value and selecting **Define in Editor**
  - Double-clicking the value and clicking the edit icon 



JSON Editor has two especially notable features:

- **Content Assist** (*CTRL* ( $\#$ ) + *SPACE*) - suggests JSON templates (see [Templates](#) for more information)
- **Quick Fix** - offers simple solutions to syntax errors, use them by right-clicking an underlined part of the JSON value and selecting a fix



Toolbar button	Name	Description
	Brackets Highlighting	Toggles brackets highlighting. Corresponding starting/ending brackets are highlighted in the same color
	Brackets Content Highlighting	Toggles brackets content highlighting. Bracket values of the same depth are highlighted in the same color
	Vertical Layout	Switches the editor into vertical layout
	Horizontal Layout	Switches the editor into horizontal layout



<b>Toolbar button</b>	<b>Name</b>	<b>Description</b>
	Apply	Applies changes made to a value
	Cancel	Discards changes made to a value

# Management of BLOBs

There are several tools that can be used to work with BLOBs (Binary large objects). You can open them in application of your choice and you can also import/export BLOB values directly in **Object Detail**.

## **To view the contents of a BLOB value**

1. Open a table with BLOB values in **Object Detail** and switch to the **Data tab**
2. Double-click any BLOB value to open it in its associated application

**i** | **NOTE:** The application in which the BLOB value will be opened depends on current settings. See [BLOB Viewers](#)

## **To export BLOB values**

1. Open a table with BLOB values in **Object Detail** and switch to the **Data tab**
2. Right-click any BLOB value and select **Export BLOB to File**
3. Choose the destination for the file and click **Save**

## **To import BLOB values**

1. Open a table with BLOB values in **Object Detail** and switch to the **Data tab**
2. Right-click any BLOB value and select **Import BLOB from File**
3. Select the file that you would like to import as a BLOB value and click **Open**

**i** | **NOTE:** The imported file must not exceed the maximum size of the destination BLOB column type. The maximum size of a BLOB column value of each type is:


- TINYBLOB - 255 bytes
- BLOB - 64 KB
- MEDIUMBLOB - 16 MB
- LONGBLOB - 4GB

# Running Stored Procedures and Functions


Procedures and functions stored in your database can be executed right from the **Object Explorer**. Once the procedure/function is executed, you can display the results in the **Run Routines** window. See [Run Routines](#) for more information.

## To run a stored procedure

- Right-click a procedure/function and select **Run**



- If your procedure or function accepts parameters, you will be able to enter them before execution in the **Set Input Parameters** window




# Snapshots

In Toad Edge, snapshots are a way of storing database structure (without data) as a readable JSON file. This file can be subsequently used as a create script source or as a **Schema Compare** source/target in **Continuous Integration and Delivery (CI/CD)**.

There is also another type of snapshot - **baseline snapshot**. It is nearly identical to regular snapshot except it can be used in CI/CD in the **Compare database with baseline** build step. This build step will return an error if the database is different from the baseline snapshot. See [Continuous Integration and Delivery Wizard](#) for more information.

## To take a snapshot of a database

1. In **Object Explorer**, right-click any database and select **Take Snapshot**
2. Change the snapshot name if you wish. Then click **OK**



Snapshots are stored in the Toad Edge folder structure. You can access the snapshot files in [Snapshots View](#).

# Templates

Templates are script snippets that can be reused in various editors. In Toad Edge, templates can be defined in three contexts:


- **SQL** - usable in [Worksheet](#) while working with all databases
- **JSON** - usable in [JSON support and JSON Editor](#)
- *Database specific* - usable in [Worksheet](#) while working with the specific database

## To configure templates

1. Go to **Preferences (View menu | Preferences** or press *ALT + P*)
2. Switch to the **Templates** tab. Here you can add/edit/remove templates

**i** **TIP:** You can use variables in the code of your templates by typing `${variableName}`. If you need to enter a literal dollar symbol, enter two dollar characters in sequence `$$`.

When a template is used, its variables can be quickly set to specific values. You can also jump between the variables by pressing *TAB* and *SHIFT + TAB*.






# About User Privileges

Toad Edge provides a number of options related to user privileges and how to grant/revoke them. As a general overview, user privileges are granted/revoked on three levels.

- **Server** (global level)
- **Database/Schema**
- **Database objects** (tables, views, routines - procedures and functions)

These levels also represent a hierarchy where privileges on higher level are inherited at lower levels by default. User privileges can be of several types:

- **Inherited** (  ) - the privilege has been granted on higher level and it is not possible to revoke it on the current level
  - Example: User has been granted the CREATE privilege on the server level. It appears as inherited on the database/object levels and cannot be revoked there. It can be granted again on lower levels although this is unnecessary
- **Granted & Inherited** (  ) - this privilege has been granted on higher level and also on the current level
  - Example: User has been granted the SELECT privilege on the server level and then again on the database level. It appears as granted & inherited on the database level
- **Granted** (  ) - the privilege has been granted on the current level and can be revoked
  - Example: User has been granted the UPDATE privilege on the object level. It appears as granted on the object level, and it can be revoked
- **Revoked** (blank value) - the privilege has not been granted on any level
  - Example: User has been revoked the EXECUTE privilege on the database level. It appears as revoked on the object level. It also appears as revoked on the server level as if it were granted on the server level, it could not be revoked on the database level in the first place

The following table describes how privileges set on higher levels affect privileges on the other levels:

Higher level	Current level	Lower level
Granted	Inherited (granted)	Inherited (granted)
Revoked	Inherited (revoked)	Inherited (revoked)
Revoked	Granted	Inherited (granted)
Granted	Granted & Inherited	Inherited (granted)

# User and Object Privilege Views

Toad Edge allows you to examine currently configured privileges from two views:

- **User** - displays objects and the privileges the user has to the objects
- **Object** - displays users and the privileges the users have to the object





## To examine privileges of a user

1. In **Object Explorer**, expand the **Users** node and double-click the user whose privileges you would like to review
2. Switch to the **Privileges** tab




## To examine privileges of an object



1. In **Object Explorer**, locate the object you would like to review (server/database/database object)
2. Double-click the object to open it in **Object Detail**
3. Switch to the **Privileges** tab

## User Detail | Privileges tab

Button	Option	Description
	Modify Privileges	Opens a dialog where you can grant/revoke privileges to each individual object
	Add Wildcard Pattern Privileges	Opens a dialog where you can configure <a href="#">Wildcard patterns privileges</a>
	Add Proxy User Privileges	Opens a dialog where you can set up <a href="#">Proxy user privileges</a>
	Revoke Privileges	Revokes the selected privilege for the selected object

## Object Detail | Privileges tab

Button	Option	Description
	Modify Privileges	Opens a dialog where you can grant/revoke privileges of any user to the object
	Open Script in Worksheet	Opens the privilege configuration script of the selected user to the object in <b>Worksheet</b>
	Open Script Generation Settings	Allows you to enable/disable inclusion of inherited privileges in the generated privilege script. When disabled, only granted or granted & inherited privileges will be included

Button	Option	Description
	Open User Detail	Opens the <b>User Detail</b> of the selected user
	Filter Unprivileged	Hides users that have not been granted any privileges




# Wildcard Patterns and Proxy Privileges


**i** | **NOTE:** Privileges that are set using these methods are NOT visible in the **Privileges tab** in **User Detail** and **Object Detail**.

## Wildcard patterns privileges

Wildcard pattern privileges offer a way to grant privileges for multiple databases at once. The condition is that the database names must match a specific wildcard.

### To set wildcard pattern privileges for databases

1. Locate the user whose privileges you would like to modify in **Object Explorer** and double-click it
2. Switch to the **Privileges tab**
3. Click the **Add Wildcard Pattern Privileges**  button
4. In the first dialog of the wizard, specify the wildcard pattern. The percent (%) sign represents one or more characters and the underscore (\_) sign represents a single character. If you need to use a literal % or \_, escape them using a back slash (\)
5. In the next dialog, select the privileges that you would like to grant and **Finish** the wizard



**i** | **NOTE:** Setting database privileges using wildcards has a side effect. You are not able to revoke privileges to a particular database from the set of databases that match the wildcard. Consider the following example.


A user has been granted the SELECT privilege to all databases which match the "test\\_%" wildcard. There are three such databases - test\_tables, test\_views and test\_routines. In this situation, you are not able to revoke the privilege for any one of the three databases, such as test\_tables.


## Proxy user privileges

Using proxies, users are able to use privileges of other users. In this operation, there are two sides:

- **Proxy** - the user that uses the privileges of some other user
- **Proxied** - the user whose privileges will be available to the original user

### To add proxy user privileges

1. Locate the user whose privileges you would like to modify in **Object Explorer** and double-click it
2. Switch to the **Privileges tab**
3. Click the **Add Proxy User Privileges**  button
4. In the wizard, specify the **Proxied** and the **Proxy** users and click **Finish**



# About Schema Compare

With Toad Edge, you can compare database objects of two databases/schemas. Based on the result, you can generate an HTML report or change scripts for both the source and the target to deploy changes immediately.

**i** | **NOTE:** Although possible, it is not recommended to compare two databases of different database versions (e.g. MySQL 5.6 and MySQL 5.7).

## **To quickly compare two databases/schemas**

- Select any two databases in **Object Explorer**, right-click and select **Compare Schemas**

## **To configure comparison settings before performing Schema Compare**

1. Click the **Compare** button on main toolbar and select **New**
2. Specify the Source and Target schemas and select the desired **Object Types** and **Comparison Rules**
3. Click **Compare**




This comparison process may take a while depending on the number of objects in both databases. Once it is completed, you can see all the differences between the source and the target and perform various actions.

**Schema Compare** consists of three parts:

- **Overview Grid** - Displays differences between databases. The differences can be resolved and marked as read/unread, important or excluded
- **Comparison Area** - Shows the specific differences in SQL code between the source/target database objects
- **Outline View** - Contains settings that determine which types of differences should be considered or ignored

# Overview Grid

The main purpose of the grid is to resolve differences between database objects as a part of **Schema Compare**. You can also use other tools to filter the differences or mark them via context menu as:

- **Read/Unread**  - signifies whether you have already reviewed the difference or not
- **Important**  - simply marks the difference as important, has no influence on the result of the comparison
- **Excluded**  - the difference is ignored and removed from the grid unless you enable the **Show Excluded Items** option


There are two main types of differences:


- **Only in source/target** - objects that are found only in one of the two compared databases
- **Different** - objects that are linked (same name or linked by user) but their SQL code is different

In case you want to compare an unlinked object in source with an unlinked object in target, you will have to map them.

## **To map an unlinked object to any other unlinked object**

1. In the grid, find an object that is not linked yet by looking in the **Only in source/target** nodes
2. Notice the [map] text in the other database column. It is a drop down menu from which you can select the object that should be mapped to your original object







3. After selecting the object, the two objects are now linked. You can unlink them again by clicking the unlink icon 

Once you link objects as you wish, you can go through the differences and decide on how to resolve them.








## **To resolve differences between two database objects**








1. In the Overview Grid, locate any row that marks a difference between two objects
2. Click on the arrow in the cell between the object names to specify how the difference is going to be resolved.

The following table lists all possible resolution actions and their meanings:

Action	Action description	Resolution description
	Change target	The generated change script will change target so it matches source
	Change source	The generated change script will change source so it matches target
	Change both	<b>(Different objects only)</b> All differences between the two objects are marked as ignored. You can go through the specific differences one by one and resolve them in the <a href="#">Comparison Area</a>
	Ignore	The differences between the two objects are ignored and not included in the generated change script

## Overview Grid Toolbar

UI Element	Option	Description
	Recompare All	Compares the source and the target again
	Save As	Saves the comparison as a .compare file that can be loaded and displayed at any time
	Previous Unread Change	Switches to the previous difference marked as unread ( ● )
	Next Unread Change	Switches to the next difference marked as unread ( ● )
	Export Report	Exports an HTML report detailing the detected differences
	Generate Script for Source	Generates a change script for the source schema/database according to the resolution actions you have set. The script can be generated to clipboard, a worksheet or a file
	Generate Script for Target	Generates a change script for the target schema/database according to the resolution actions you have set. The script can be generated to clipboard, a worksheet or a file

UI Element	Option	Description
	Update Objects in Database	( <a href="#">Repository</a> only) Updates objects in database according to the resolution actions you have set. The drop down menu allows you to only generate a change script instead. The script can be generated to clipboard, a worksheet or a file
	Overwrite Files on File system	( <a href="#">Repository</a> only) Updates objects in file system repository according to the resolution actions you have set. The drop down menu allows you to only generate a change script instead. The script can be generated to clipboard, a worksheet or a file
	Filter by Action	Displays only the differences that you have resolved by the selected action(s)
Group by: <input type="text" value="Object Type and Status"/>	Group by	Groups the differences by the selected criteria
Filter: <input type="text" value="type filter text"/> 	Filter	Filters the differences according to the input. It is possible to use wildcards (? and *) and regular expressions as well as filter by multiple comma separated values
	Show/Hide Excluded Items	Shows/Hides differences marked as <b>Excluded</b>
	Hide Empty Nodes	Hides object type nodes with no detected differences
	Export Settings	Exports the Schema Compare settings and <b>Detailed Settings</b> which can be configured in the <a href="#">Outline View</a>

# Comparison Area

This part of Schema Compare displays specific differences between the SQL code of two given database objects. It also allows you to export the SQL code of any of the two objects in various ways and you can also deploy changes based on the actions that you have used to resolve the differences.


Comparison Area has the following tabs:

- **Script Definition** - displays the SQL code of both objects and the differences between them
- **Change Script** - displays the change script SQL code that will be generated in order to resolve the differences

In the Script Definition tab, differences can be resolved one by one with different actions.

## To resolve differences between two objects in Script Definition

1. In [Overview Grid](#), select a row with two different objects
2. You should now see the specific differences displayed in the **Comparison Area | Script Definition** tab
3. Select a specific difference by simply clicking on it. A border should appear to signal that the difference is currently selected
4. Right-click and select the action that you would like to use to resolve the difference




Once you resolve all the differences, you will probably want to deploy the changes. This can be done in two scopes:




- **Deploy changes of all objects** - in this case, you generate and execute a change script for all objects that are resolved/not excluded in the [Overview Grid](#)
- **Deploy changes of a single object** - this method uses the Change Script tab

## To deploy changes of a single object

1. Resolve all differences as described in the walkthrough above
2. When you are done, switch to the **Change Script** tab

3. You should see a generated change script that is based on the resolution actions you have used. To deploy the changes, simply click the **Deploy** button . If you just want to generate the script rather than deploy it immediately, use one of the three buttons to the right of the Deploy button

## Comparison Area Toolbar

Button	Option	Description
	Deploy	Executes the generated change script in the source/target to address the differences
	Export/Copy/Open SQL Worksheet	Exports the generated change script for source/target to a file/clipboard/Worksheet
	Set Action	Resolves <b>all</b> differences between the two objects using the selected action

# About Continuous Integration and Delivery in Toad Edge®

Toad Edge aims to simplify **Continuous Integration** and **Continuous Delivery** (CI and CD) processes by providing build steps that can be used in your CI/CD systems (Jenkins, TeamCity and others).

CI/CD process can be comprised of multiple build steps. Consider this illustrative workflow where changes made in development database are deployed to staging database:

1. Compare the staging database with a baseline to check for unintended changes made since the last deployment
2. Compare the development database with the staging database
3. Generate HTML reports
4. Generate change SQL script
5. Create a snapshot of the staging database as a backup
6. Deploy the change script to the staging database
7. Create a new baseline snapshot of the staging database

To create a build step in your CI/CD system, several files are required:

- Batch file or shell script (generated by Toad Edge)
- Connection information in XML format (generated by Toad Edge)
- Toad Edge JAR file with additional libraries (available for download [here](#))



**NOTE:** Some build steps may require additional files. List of build step requirements can be found in [Continuous Integration and Delivery Wizard](#) topic

In general, each build step can be broken down into three stages:



1. Your CI/CD system executes the batch/shell script generated by Toad Edge
2. The script launches Toad Edge JAR with specific arguments to perform the desired operation
3. If there are no errors, the build step is successfully finished

The way to create build steps depends on whether you are using [Jenkins](#) or [a different CI/CD system](#).

## Creating build steps - Jenkins

**i** **IMPORTANT:** To execute build steps correctly, Toad Edge requires a 64-bit installation of Java Development Kit (JDK), however, 32-bit Java is usually used by default. It is therefore necessary to create a JAVA\_HOME system variable pointing at 64-bit JDK directory. Please do the following steps to perform the configuration:

1. Right-click **This PC** and select **Properties | Advanced System Settings | Environment Variables**
2. Click **New** in System Variables
3. In the Variable Name field, enter JAVA\_HOME
4. In the Variable Value field, enter your JDK installation path, e.g. C:\Progra~1\Java\jdk1.8.0\_65

Creating build steps in Jenkins is easier than in other CI/CD systems since Toad Edge provides its CI/CD functionality in the form of a Jenkins plugin. This topic explains how to install the plugin and use it to create build steps.


The Toad Edge Jenkins plugin can be downloaded [here](#).

### ***To install and configure Toad Edge plugin in Jenkins***

1. In Jenkins, go to home page and select **Manage Jenkins** from the left menu
2. Select **Manage Plugins**
3. Switch to the **Available** tab and type Toad Edge into the **Filter** box
4. Check the checkbox next to the Toad Edge plugin name and then select **Install without restart** or **Download now and install after restart**
5. Once the plugin is installed, download Toad Edge JAR file with additional libraries in zip archive from [here](#)

You will now need to configure the plugin:

1. In Jenkins, go to home page, then select **Manage Jenkins** from left menu
2. Select **Configure System**
3. Scroll down until you see **Toad Edge for Jenkins**. Fill in the path to the Toad Edge zip archive that contains the JAR file and a library folder



Toad Edge for Jenkins

Toad Edge Libraries folder:

4. **Save** or **Apply** the changes


With the plugin installed and configured, you can start creating new build steps. In this example, we are going to create a new **Generate create SQL script** build step. We assume that a project has already been created in Jenkins.

### **To create a new build step (Generate create script) in Jenkins**

1. In Jenkins, click on your project, and select **Configure** from the left menu.
2. On the configuration page, scroll down to the **Build** section
3. Click **Add build step** and then select **Toad Edge: Generate Create Script**
4. Enter the path in **Input file/folder** field. The input can be:
  - Connection XML file

**NOTE:** Connection XML files can be obtained by exporting a build step in **CI/CD Wizard**.

- Repository folder structure
  - Snapshot file
5. In the **Output file**, enter the destination folder and the file name for the generated create script



6. **Save** or **Apply** the changes.
7. Build the Project and you should see the generated create script file in the destination folder

## Creating build steps - other systems

In case you are not using Jenkins, you can still take advantage of Toad Edge CI/CD build steps as long as your system is able to execute batch files/shell scripts.

This example illustrates how to create a **Create Snapshot** build step and use it in **TeamCity**.


### **To create a new build step in TeamCity using Toad Edge CI/CD Wizard**

1. In Toad Edge, click the **CI/CD** (Continuous Integration and Delivery) button on main toolbar to open the **CI/CD Wizard**

2. Select **Create Snapshot** from the available builds
3. Configure the path to **toadedge.jar** (obtained from [here](#)). The exported batch/shell script will use this path to look for the jar file, so enter the path relative to the path of the script (**Export Path** in the last dialog).
  - We choose to set **Export Path** to *N:\TeamCity\working\_directory*
  - The toadedge.jar file will be located in *N:\TeamCity\working\_directory\jars*
  - Therefore, the toadedge.jar file path will be *.jars* (relative) or *N:\TeamCity\working\_directory\jars* (absolute)
4. In the next dialog, select the **Connection** and **Database** that you would like to take a snapshot of
  - The connection is exported as an XML file. If we choose to place it in a different folder than the exported script, we have to modify the **Connection File Name** path in the same way as in step 3
5. You can also change the **Output** file name and path (relative to the **Export Path**)
6. In the final dialog, configure the **Export Path** first. This is the destination folder for the exported script and other files
7. Now change the **Command File Name** if you wish. The suffix of the file name determines whether the file will be a batch file (.bat) or a shell script (.sh)
  - Since we are running TeamCity on Windows, it is better to use batch script format. On Linux, shell script would be a better choice

The rest of the configuration is done in TeamCity. This guide assumes that you have already created a **Project** and a **Build Configuration**.

1. In TeamCity web UI, locate your **Project** and a **Build Configuration** to which you would like to add a new build step
2. Open the Build Configuration and select **Build Steps** from the left menu
3. Click the **Add build step** button
4. From the **Runner type** dropdown menu, select **Command Line**
5. The fields that you now need to configure are:
  - **Working directory** (you might need to click **Show advanced settings**) - this is the directory where TeamCity will look for and execute the batch/shell script (in our case, same as **Export Path** in **CI/CD Wizard**)
  - **Run** - select **Executable with parameters**
  - **Command executable** - enter the name of the script here (with or without the suffix)



Working directory: ⓘ	N:\TeamCity\working_directory ⓘ <small>Optional, set if differs from the checkout directory.</small>
Run:	Executable with parameters ▼
Command executable: *	create_snapshot_tech ⓘ

6. Once you are done with the configuration, **Save** the changes

7. Run the Build Configuration to see if everything is configured correctly. If the build step is executed successfully, you should see the newly generated snapshot in the script folder

# Continuous Integration and Delivery Wizard

The CI/CD Wizard guides you through the process of creating and customizing various build steps. It saves you the hassle of having to manually write a script with appropriate arguments to use with the [Toad Edge® command line interface](#).

The generated script can be viewed at any time in the wizard by clicking the **Command Preview** button.

```

Bash Command:
java -jar N:\TeamCity\working_directory\jars/toadedge.jar
-compare
-in_source ./root@localhost.xml
-in_target ./root@localhost.xml
-settings ./compare_settings.json
-out ./compare_result
  
```

The following table lists all currently available build steps and files/configuration required to export them.

Build Step	Requirements	Description
Empty database	<ul style="list-style-type: none"> <li>Database connection file (XML)</li> </ul>	Executes a query that drops all objects in the selected database
Create snapshot	<ul style="list-style-type: none"> <li>Database connection (XML file)</li> </ul>	Stores the structure (not data) of the selected database as a JSON file. The <a href="#">Snapshots</a> can be used as a backup
Create baseline	<ul style="list-style-type: none"> <li>Database connection (XML file)</li> </ul>	Stores the structure (not data) of the selected database as a JSON file. This

Build Step	Requirements	Description
		snapshot can be used as a backup or as a baseline for the <b>Compare            database            with            baseline</b> build step
Generate create SQL script	One of the following: <ul style="list-style-type: none"> <li>• Database connection (XML file)</li> <li>• Repository (folder structure)</li> <li>• Snapshot (JSON file)</li> </ul>	Generates a create SQL script from a repository, saved snapshot or a database. The script can be used to recreate the structure of the source (not data)
Generate change SQL script	<ul style="list-style-type: none"> <li>• Schema Compare result (folder with JSON files)</li> </ul>	Generates a change SQL script to deploy changes to the Schema Compare target based on differences found in the previously executed <b>Compare            database            schemas</b> build step
Compare database schemas	<ul style="list-style-type: none"> <li>• Recent Schema Compare</li> <li>• Saved Schema Compare (.compare file)</li> </ul> Or two of the following:	Compares two different schemas

Build Step	Requirements	Description
	<ul style="list-style-type: none"> <li>• Database connection (XML file)</li> <li>• Repository (folder structure)</li> <li>• Snapshot (JSON file)</li> </ul>	(from databases, repositories or snapshots). The results are stored in a folder that can be used as an input for other build steps
Compare database with baseline	<p>One of the following:</p> <ul style="list-style-type: none"> <li>• Database connection (XML file)</li> <li>• Repository (folder structure)</li> <li>• Snapshot (JSON file)</li> </ul> <p>And also a baseline snapshot (JSON file)</p>	Compares the given database with the given baseline snapshot. In case any differences are found, an error is raised and the build step will fail
Deploy SQL script	<ul style="list-style-type: none"> <li>• Database connection (XML file)</li> <li>• Input SQL file</li> </ul>	Executes any SQL script on a selected database
Generate HTML comparison report	<ul style="list-style-type: none"> <li>• Schema Compare result (folder with JSON files)</li> </ul>	Generates an HTML report based on the results of the previously executed <b>Compare database schemas</b> build step

# Toad Edge® command line interface

**i** **IMPORTANT:** To execute build steps correctly, Toad Edge requires a 64-bit installation of Java Development Kit (JDK), however, 32-bit Java is usually used by default. It is therefore necessary to create a JAVA\_HOME system variable pointing at 64-bit JDK directory. Please do the following steps to perform the configuration:

1. Right-click **This PC** and select **Properties | Advanced System Settings | Environment Variables**
2. Click **New** in System Variables
3. In the Variable Name field, enter JAVA\_HOME
4. In the Variable Value field, enter your JDK installation path, e.g. C:\Progra~1\Java\jdk1.8.0\_65

The core Continuous Integration and Delivery (CI/CD) functionality in Toad Edge is provided by its command line interface (CLI). Although the best way to use it is to use the **CI/CD Wizard**, you can also work with it manually.

## **To use Toad Edge CLI manually**

1. Download a zip archive containing Toad Edge JAR file and other libraries from [here](#)
2. Extract the archive
3. Launch the command line utility (Windows) or the terminal (Linux) and navigate to the folder with the JAR file
4. Execute the JAR file with Java command and additional arguments

Every usable command begins with **java -jar toadedge.jar** followed by the operation you want to perform and additional arguments.

The available operation arguments correspond to the build steps available in the **CI/CD Wizard**:

- -compare
- -report
- -sql\_change
- -sql\_create
- -deploy
- -snapshot
- -baseline

The operation argument has to be followed by other arguments specifying input, output, settings, etc. To learn which arguments you need to use to perform a specific operation, add the **-help** argument at the end of your command.

```

C:\Users\lknapek\Documents\TE CLI>java -jar toadedge.jar -compare -help
usage: java -jar toadedge.jar -compare [-fail_on_diff] -in_source <arg>
      -in_target <arg> [-jdbc_driver <arg>] [-lib <arg>] -out <arg>
      [-settings <arg>] [-workspace <arg>]
  -compare                Run compare
  -fail_on_diff           If this parameter is used then the compare will end
                          with error status if there are any changes between
                          source and target
  -in_source <arg>       Input target
  -in_target <arg>       Input source
  -jdbc_driver <arg>     Jdbc driver path
  -lib <arg>             Path to library folder
  -out <arg>             Output
  -settings <arg>       Settings file
  -workspace <arg>      Application workspace

```

Once you supply all the necessary arguments, you can start performing CI/CD actions without having to launch Toad Edge itself.

```

C:\Users\lknapek\Documents\TE CLI>"C:\Program Files\Java\jdk1.8.0_102\bin\java.exe" -jar toadedge.jar -snapshot -in root@localhost.xml -out my_db_snapshot.json
2017-06-23 13:50:22.699 INFO [CIService] Loading model
2017-06-23 13:50:24.117 INFO [CIService] Writing snapshot to file: C:\Users\lknapek\Documents\TE CLI\my_db_snapshot.json
2017-06-23 13:50:25.440 INFO [CIService] Snapshot/baseline taken successfully

```



# Preferences

Many aspects of Toad Edge and its behavior can be configured in the Preferences.

## To open Preferences

- On Windows: Select **View | Preferences** or press ALT + P
- On macOS: Select **Toad Edge | Preferences** or press  $\text{⌘} + P$  or  $\text{⌘} + ,$

The settings are divided into several categories:

- [General](#)
- [Database](#)
- [Worksheet](#)
- [Data](#)
- [Templates](#)
- [Export](#)
- [Folder Paths](#)
- [Appearance](#)
- [Feedback](#)

## General

### Startup Options

Option	Description
Restore active connections	If enabled, database connections that were active before exiting the application will be reconnected again on startup
Verify drivers existence on application start	If enabled, automatically check whether the drivers listed in the <b>Database</b> tab actually exist
Play Toad wave on application start	By default, Toad Edge plays a toad sound when it is launched. Uncheck this box to disable the sound

### Dialogs and Wizards

Option	Description
Use quotation marks in SQL output	This option concerns mostly new database object wizards. If enabled, names of database objects created via these wizards will be quoted if necessary (e.g. when the name uses both uppercase and lowercase letters or if it contains special characters)
Show warning when connecting to unsupported database	In Toad Edge you might be able to connect to databases that are not fully supported and some features might be missing. Check to display a warning message when you are connecting to a database that is not supported.

## User Interface

Option	Description
Number of connections in application toolbar	Determines the number of connections that appear in the <b>Connect</b> button drop down menu in the application toolbar. If you have more connections than the number set here, they will be shown in the order in which they were last used or modified
Show database object count in Object Explorer	If enabled, the number of objects of each type is shown next to the object node in the <b>Object Explorer</b>
Format script on load	This option automatically formats SQL scripts in <b>Object Detail   Script tab</b> and also whenever you export a script to <b>Worksheet</b>
Confirm before closing Toad Edge	If enabled, a prompt is displayed when you attempt to close the application

## Connection Parameters

Option	Description
Maximum number of sessions	Enter the maximum number of concurrent sessions per connection. Enter a value from 1 to 99. With AutoCommit turned off only one session is open.

## Database

Option	Description
<i>platform</i>	Each tab lists available drivers for each of the database platforms

## Timeout Settings

Option	Description
Database connection timeout in seconds	Sets the timeout for database connections. If Toad Edge is unable to establish connection to a database within the timeout period, the connection will fail automatically
Query execution timeout in seconds	Sets the timeout for query execution. If the database is unable to execute a query within the timeout period, it will fail automatically

## Worksheet

### SQL Worksheet

Option	Description
Enable Syntax Highlighting	Highlights SQL keywords, database objects and aliases by default

Enable Syntax Check	By default, checks the syntax of SQL code in <a href="#">Worksheet</a> and underlines errors
Hide results when typing	If enabled, automatically hides <a href="#">Result</a> when you start typing in <a href="#">Worksheet</a>
Vertical layout of result set	If enabled, vertical layout of Result Set is used by default. Otherwise, horizontal layout is used
Show line numbers	Shows/hides line numbers in <a href="#">Worksheet</a>
Show range indicator	If enabled, highlights SQL statement line ranges (e.g. lines 9-13) in the vertical bar on the left side of the <a href="#">Worksheet</a>

## Content Assist / Autocompletion

Option	Description
Enable Content Assist	Enables/disables <b>Content Assist</b> entirely
Activate automatically	By default, <b>Content Assist</b> is automatically activated when you type a specific character and wait for a set amount of time. You can disable this option and instead activate the tool manually by pressing ( <i>CTRL</i> ( $\#$ ) + <i>SPACE</i> )
Delay in milliseconds	This determines the delay between typing a <b>Content Assist</b> trigger character and the suggestion popup appearing
Content Assist trigger characters	Specifies which characters can be used to activate <b>Content Assist</b> . Once you type any of them and wait for a set amount of time, the suggestion popup will appear
Sorting and Filtering	Determines how the suggestions will be sorted
Alias Handling	Enables/disables the use of aliases when using <b>Content Assist</b> to autocomplete your queries

## Data

### Data Grid Options

Option	Description
Display {null} for NULL values	If enabled, NULL values are represented by the {null} string. Otherwise, blank cells are shown instead
Show tooltips over results	By default, tooltips are displayed when you hover over data values that have been truncated due to the small column width
Show web links preview	You can enable this option to view website previews when you hover over data values that contain a website address

Use fetch limit	The fetch limit determines how many rows should be fetched from a table at once. If you disable this option, Toad Edge will fetch all rows at once. This might hinder Toad Edge performance depending on the size of the tables fetched
Number of fetched rows	If the fetch limit is enabled, this option determines how many rows should be fetched from a table. Once you scroll past the fetched rows, another set of rows is fetched

## Data Manipulation

Option	Description
Confirm any DROP, REVOKE and TRUNCATE actions	If enabled, you will be prompted before performing some actions using Toad Edge such as dropping objects, truncating tables or revoking permissions. Note that you will not receive a prompt when you try to perform the above actions using a SQL query in <b>Worksheet</b>
Confirm record deletion	If enabled, you will be prompted every time you try to delete rows from a table in <b>Object Detail</b>
Trim leading spaces when editing string data	Removes spaces in front of the string values you insert into your table when you edit its values directly (in <b>Object Detail</b> or <b>Result Set</b> )
Trim trailing spaces when editing string data	Removes trailing spaces in the string values you insert into your table when you edit its values directly (in <b>Object Detail</b> or <b>Result Set</b> )

## Date and Time Data Format

Option	Description
Date format	Determines the format of Date and Datetime types
Time format	Determines the format of Time and Datetime types

## Numeric Data Format

Option	Description
Decimal symbols	Sets the symbol used to separate integers and decimals in number data types
Digit grouping symbol	Sets the symbol used to separate thousands in number data types
No. of digits after decimal	Determines how many decimal digits are shown for Decimal type values. The actual maximum number of decimals is always limited by the scale of the specific decimal type column

## JSON Data Settings

Option	Description
Number of records used	Values in JSON data type column can have a varying number of different columns. Toad Edge analyzes the first X number of records and generates the column structure in <b>Object</b>

for JSON schema recognition	<a href="#">Explorer</a> based on the columns of these records. The number of analyzed records can be changed here. See <a href="#">JSON support and JSON Editor</a> for more information
Max number of keys in the same level	Determines how many key of the same depth level will be displayed in JSON column structure in <b>Object Explorer</b>
Max number of levels	Determines how many nested levels will be displays in JSON column structure in <b>Object Explorer</b>
Load keys on demand	If enabled, the records used to model JSON column structure in <b>Object Explorer</b> will be loaded only when you expand the JSON column node

## BLOB Viewers

Option	Description
File Viewers	<p>In this section you can configure which viewer should be used to open BLOBs (binary large objects) of specific formats:</p> <ul style="list-style-type: none"> <li>• Default - if possible, BLOBs are opened in an internal Eclipse editor. If not, default system application is used instead</li> <li>• System - BLOBs are opened in default system application associated with the specific file format</li> <li>• Text - BLOBs are opened in a plain text editor</li> </ul>

## Templates

This section allows you to define and customize your own code templates. See [Templates](#) for more information.

## Export

Option	Description
Open file after execution	Determines whether exported XML and HTML files should be automatically opened after the export is completed

## XML

Option	Description
Encoding	Sets the default encoding for exported XML files

## Naming

Option	Description
Name of the root tag	Determines the name of the tag that should be used in XML to indicate the start and the end of the entire row/record section
Name of the row tag	Determines the name of the tag that should be used in XML to indicate the start and the end of a single row/record

## Options

Option	Description
Trim string values	Removes leading and trailing spaced from exported string values if enabled
Include null fields	If enabled, null values are listed in exported XML files as {null}
Indent size	Determines the indentation size of tags in exported XML files
CDATA export selection	Here you can configure which data type values should be enclosed in character data (CDATA) tag

## HTML

Option	Description
CSS Style	You can choose the CSS style applied to exported HTML files here

## Folder Paths

Option	Description
Document path	This path is used as a default for many file related operations in Toad Edge such as exporting/importing and saving/loading files
Repository mapping mask	The default file path used when creating a repository. See <a href="#">Repository</a> for more information

## Appearance

This sections contains settings related to colors and fonts used in the application. For example, you can change syntax highlighting colors, Worksheet fonts or background colors of certain UI elements.

## Feedback

Option	Description
Error Reporting	Toad Edge can detect unexpected termination and then send an anonymous error log to the application developers. The specific settings can be configure here

# Third party components

This product contains the following third-party components. For third-party license information, go to <https://www.quest.com/legal/license-agreements.aspx>. Source code for components marked with an asterisk (\*) is available at <https://opensource.quest.com>.

**Table 1: List of Third-Party Contributions**

Component	License or Acknowledgement
[ini4j] 0.5.2	Apache License 2.0
A Base64 encoder/decoder 1.0	The MIT License (MIT) Copyright ©2012, 2013 Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
accessors-smart 1.1	Copyright 2011 JSON-SMART authors Apache License 2.0
aopalliance 2.4.0	Public Domain
Apache Commons Cli 1.4	Copyright © 2000-2014 The Apache Software Foundation. All Rights Reserved. Apache License 2.0
Apache Commons IO 1.3.2	Copyright © 2002-2014 The Apache Software Foundation. All Rights Reserved.

Component	License or Acknowledgement
Apache Commons Pool 2.3	<p>Apache License 2.0</p> <p>Copyright ©2001–2014 The Apache Software Foundation. All rights reserved.</p> <p>Apache License 2.0</p>
Apache Commons Validator 1.5.1	<p>Copyright ©2002-2017 The Apache Software Foundation. All Rights Reserved.</p> <p>Apache License 2.0</p>
Apache Log4J 1.2.15	<p>Copyright © 1999-2012 Apache Software Foundation.</p> <p>Apache License 2.0</p>
ASM 5.0.4	<p>Copyright ©2000-2011 INRIA, France Telecom All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3. Neither the name of the copyright holders nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.</p>



Component	License or Acknowledgement
Bean Validation API 1.1.0.Final	Copyright 2007-2013 Red Hat Inc. All rights reserved. NOTICE The Specification is protected by copyright and the information described therein may be protected by one or more U.S. patents, foreign patents, or pending applications. Except as provided under the following license, no part of the Specification may be reproduced in any form by any means without the prior written authorization of Red Hat Inc. and its licensors, if any. Any use of the Specification and the information describe Apache License 2.0
Bouncy Castle 149	Copyright ©2000 - 2019 The Legion of the Bouncy Castle Inc. ( <a href="https://www.bouncycastle.org">https://www.bouncycastle.org</a> ) Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Bouncy Castle TLS/JSSE APIs 1.0.9	Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
BouncyCastle FIPS 1.0.2	THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
BouncyCastle PKIX FIPS 1.0.3	THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Easy Rules Core 3.2.1	Copyright ©2018 Mahmoud Ben Hassine (mahmoud.benhassine@icloud.com) 1.0 MIT License
*Eclipse RCP 4.7.3	Copyright ©2017 The Eclipse Foundation. All Rights Reserved.

<b>Component</b>	<b>License or Acknowledgement</b>
	Eclipse Public License - 1.0
Esri Geometry API 1.2.1	Copyright 2013-2017 Esri Apache License 2.0
FasterXML Jackson 2.7.0	Copyright ©2009 FasterXML, LLC Apache License 2.0
guava-libraries 19.0.0	Copyright ©2017 The Guava Authors Apache License 2.0
Guess Encoding 1.4	Copyright 2002-2007 Guillaume Laforge Apache License 2.0
HK2 2.4.0	Copyright ©2009-2017 Oracle Corporation. All Rights Reserved. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)
Java API for JSON Processing 1.0.4	Copyright ©2013 Oracle Corporation. All Rights Reserved. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)
Java API for RESTful Services 2.0.1	Copyright ©2014, Oracle Corporation and/or its affiliates. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)
Java JSON 1.0	Copyright ©2002 JSON.org Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies

Component	License or Acknowledgement
Java Native Access (JNA) 4.1	<p>or substantial portions of the Software. The Software shall be used for Good, not Evil. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.</p> <p>Copyright (c) 2007 Timothy Wall, All Rights Reserved</p> <p>This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.</p> <p>This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.</p> <p>Apache License 2.0</p>
Javassist 3.21.0	<p>Copyright (C) 1999- by Shigeru Chiba, All rights reserved.</p> <p>Mozilla Public License (MPL) 1.1</p>
javax.annotation 1.2	<p>©2017, Oracle Corporation and/or its affiliates. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p>
javax.inject 2.4.0	<p>©2017, Oracle Corporation and/or its affiliates. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p>
javax.persistence 1.0	<p>©2017, Oracle Corporation and/or its affiliates.</p>

Component	License or Acknowledgement
javax.servlet 3.0.1	<p>COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p> <p>©2017, Oracle Corporation and/or its affiliates. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p>
JAXB 2.2.7	<p>Copyright ©2013-2017 COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p>
JDBC EnterpriseDB 4.2	<p>Copyright 1997 PostgreSQL Global Development Group All rights reserved. BSD 2-clause "Simplified" License - PostgreSQL 1.0</p>
JDBC PostgreSQL 42.2.2	<p>Copyright (c)1997, PostgreSQL Global Development Group All rights reserved.</p> <p>Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:</p> <ol style="list-style-type: none"> <li>1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.</li> <li>2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.</li> </ol> <p>THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR</p>

Component	License or Acknowledgement
Jersey RESTful Web Services in Java 2.22.2	<p>PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.</p> <p>Copyright ©2010-2017 Oracle Corporation. All Rights Reserved.</p> <p>COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)</p>
JSch 0.1.54	<p>Copyright 1998-2016 JCraft, Inc. All rights reserved.</p> <p>All rights reserved.</p> <p>Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:</p> <ol style="list-style-type: none"> <li>1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.</li> <li>2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.</li> <li>3. The names of the authors may not be used to endorse or promote products derived from this software without specific prior written permission.</li> </ol> <p>THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL JCRAFT, INC. OR ANY CONTRIBUTORS TO THIS SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT,</p>

Component	License or Acknowledgement
	<p>INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.</p>
json-path 2.2.0	<p>Copyright 2011 the original author or authors. Apache License 2.0</p>
json-smart 2.2.1	<p>Copyright 2011 the original author or authors. Apache License 2.0</p>
Log4J 1.2.17	<p>Apache License 2.0 This product includes software developed by the Apache Software Foundation (<a href="http://www.apache.org">http://www.apache.org</a>)</p>
Metrics Core Library 3.0	<p>©Copyright 2010-2014, Coda Hale, Yammer Inc. Apache License 2.0</p>
Nebula Widgets 1.3.0	<p>Copyright ©2017 The Eclipse Foundation. All Rights Reserved. Eclipse Public License - 1.0</p>
Netty 4.0.36	<p>Copyright ©2017 The Netty project Apache License 2.0</p>
Open JDK 11.0	<p>Copyright © 2019 Oracle Corporation and/or its affiliates GNU General Public License, version 2, with the Classpath Exception Upon a receipt of a written request to <a href="mailto:legal@quest.com">legal@quest.com</a>, Quest Software Inc. will ship to ship a copy of the source code on a CD for a nominal fee.</p>

Component	License or Acknowledgement
opencsv 2.3	Copyright ©2017. All rights reserved. Apache License 2.0
org.osgi.core 4.2.0	Copyright (c) OSGi Alliance (2000, 2009). All Rights Reserved. Apache License 2.0
OSGI Resource Locator 1.0.1	Copyright © 2005-2015 Oracle Corporation and/or its affiliates. COMMON DEVELOPMENT AND DISTRIBUTION LICENSE Version 1.1 (CDDL-1.1)
proxy-vole 20131209	<p>Bernd Rosstauscher (proxyvole@rosstauscher.de) Copyright 2013 The BSD 3-Clause License</p> <p>Copyright (c) Bernd Rosstauscher (proxyvole@rosstauscher.de) Copyright 2013 All rights reserved.</p> <p>Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.</p> <p>Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.</p> <p>The name of Bernd Rosstauscher may not be used to endorse or promote products derived from this software without specific prior written permission.</p> <p>THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED</p>

Component	License or Acknowledgement
slf4j - Simple Logging Facade for Java 1.7.21	<p>TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.</p> <p>Copyright ©2004-2017 QOS.ch All rights reserved. MIT 1.0</p>
Univocity Parsers 2.8.1	<p>© Copyright 2019 univocity. Apache License 2.0</p>
xpp3 1.1.4c	<p>Copyright 2002 Extreme! Lab, Indiana University. All rights reserved. Indiana University Extreme! Lab Software License 1.1.1 This product includes software developed by the Indiana University Extreme! Lab (<a href="http://www.extreme.indiana.edu/">http://www.extreme.indiana.edu/</a>).</p>
Xstream 1.4.11.1	<p>Copyright ©2003-2006, Joe Walnes Copyright ©2006-2015 XStream Committers All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:</p> <ol style="list-style-type: none"> <li>1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.</li> <li>2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.</li> <li>3. Neither the name of XStream nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.</li> </ol>



**Component****License or Acknowledgement**

---

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.