



FAST A-SERIES APPLICATOR

The all-new FAST A-Series Applicator features an innovative toolbar design for an industry-leading transport width of 11 ft. 10 in. — that is 3 ft. narrower than any other 60-ft. toolbar design on the market! This design increases safety, eases operator stress, and helps decrease operator liability while on the road.

The A-Series Applicator utilizes many previous FAST toolbar design concepts, which have been proven to exceed the demands of your operation with our Flex-Hinge™ design, Wide-Stance Cast Parallel Links, Hydraulic Wing Kick™ and Active Hydraulic Downforce.

The A-Series model offers both 1,800 and 2,600-gal. tank capacities with a larger sump, enhanced weight distribution and lower profile to significantly increase operator visibility from the cab. This applicator will also accommodate row/coulter spacing from 10-40 in.



STANDARD FEATURES

- 1,800 or 2,600-gal. Tank Design – Low center of gravity and large, trough-sloped sump.
- Active Hydraulic Downforce – Adjustable downforce provides superior ground penetration and consistent application.
- Hydraulic Wing Kick™ – The outer toolbar raises for headland turns to minimize crop damage and maximize yields.
- Ace 205-304F Hydraulic Pump and Over-Speed Protection – The hydraulic flow limiter provides over-speed protection, adding to pump longevity.
- Overall Quality Manufacturing – The FAST commitment to quality presents itself in the details of our products. With our castings, DOM's and greaseable pins in higher wear pivot points, and the Magni treatment of every nut, bolt and hardware piece, we build machines to last.

FAST Cast AP Coulter

Our ingenious cast design features unmatched durability and mounting flexibility for a smooth coulter ride through the field with minimal deflection for a more consistent nitrogen placement.



Hydraulic Folding Gauge Wheels (Optional)

FAST also offers an optional folding gauge wheel that ties into the hydraulic fold circuit. This premium add-on will help reduce liability on the road with its reduced transport width.

A SERIES SPECS

| | Tank Size | Toolbar Widths | Transport Width | Transport Height | Empty Weight | Hitch Pin To Axle | Std Tires | Engine HP Required | Coulter Spacing Capability |
|---|-------------|----------------|-----------------|------------------|--------------|-------------------|--------------------|--------------------|----------------------------|
| A18 | 1,800 | 60' or 66' | 11' 10" | 12' 0" | 18,250 lbs | 15' 10" | 380/90R46" Singles | 200+ | 10" through 40" |
| A26 | 2,600 | 60' or 66' | 11' 10" | 12' 0" | 19,250 lbs | 15' 10" | 380/90R46" Duals | 200+ | 10" through 40" |
| A18/26 (w/o Folding Gauge Wheels) | 1,850/2,600 | 60' or 66' | 14' 2" | 12' 7" | See Above | 15' 10" | See Above | 200+ | 10" through 40" |

CONTACT FAST

WINDOM, MN

4130 Commerce Blvd, Windom, MN 56101
 toll free 800-772-9279 | p 507-427-3861 | f 507-427-3030

GILMAN, IL

1340 S Crescent, PO Box 236, Gilman, IL 60938
 toll free 800-872-8894 | p 815-265-7125 | f 815-265-7130