



FT77D-B7109

Service Engineer's Manual



PREFACE

Copyright

This publication, including all photographs, illustrations, and software, is protected under international copyright laws, with all rights reserved. Neither this manual, nor any material contained herein, may be reproduced without written consent of manufacturer.

Copyright 2017 MITAC COMPUTING TECHNOLOGY CORPORATION. All rights reserved. TYAN[®] is a registered trademark of MITAC COMPUTING TECHNOLOGY CORPORATION.

Version 1.0a

Disclaimer

Information contained in this document is furnished by MITAC COMPUTING TECHNOLOGY CORPORATION and has been reviewed for accuracy and reliability prior to printing. MITAC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TYAN[®] products including liability or warranties relating to fitness for a particular purpose or merchantability. MITAC retains the right to make changes to produce descriptions and/or specifications at any time, without notice. In no event will MITAC be held liable for any direct or indirect, incidental or consequential damage, loss of use, loss of data or other malady resulting from errors or inaccuracies of information contained in this document.

Trademark Recognition

All registered and unregistered trademarks and company names contained in this manual are property of their respective owners including, but not limited to the following.

TYAN[®] is a trademark of MITAC COMPUTING TECHNOLOGY CORPORATION.

Intel[®] is a trademark of Intel[®] Corporation.

AMI[®], AMIBIOS[®] and combinations thereof are trademarks of AMI Technologies.

Microsoft[®], Windows[®] are trademarks of Microsoft Corporation.

IBM[®], PC[®], AT[®] and PS/2[®] are trademarks of IBM Corporation.

Winbond[®] is a trademark of Winbond Electronics Corporation.

● FCC Declaration



Notice for the USA

Compliance Information Statement (Declaration of Conformity Procedure) DoC FCC Part 15: This device complies with part 15 of the FCC Rules.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Notice for Canada

This Class A digital apparatus complies with Canadian ICES-003. Cet appareil numérique de la Classe A est conforme à la norme NMB-003 du Canada.

● Notice for Europe (CE Mark)



This product is in conformity with the Council Directive 2014/30/EU.

Warning

This equipment is compliant with Class A of CISPR 32. In a residential environment this equipment may cause radio interference.

CAUTION

Lithium battery included with this board. Do not puncture, mutilate, or dispose of battery in fire. There will be danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type recommended by manufacturer. Dispose of used battery according to manufacturer instructions and in accordance with your local regulations.

● VCCI-A

この装置は、クラス A 情報技術装置です。この装置を家庭環境で使用すると電波妨害を引き起こすことがあります。この場合には使用者が適切な対策を講ずるよう要求されることがあります。

● Safety: EN/IEC 60950-1

This equipment is compliant with CB/LVD of Safety: EN/IEC 60950-1.

About this Manual

This manual is intended for trained service technician/personnel with hardware knowledge of personal computers.

It is aimed to provide you with instructions on installing your TYAN FT77D-B7109.

How this guide is organized

This guide contains the following parts:

Chapter 1: Overview

This chapter provides an introduction to the TYAN FT77D-B7109 barebones and standard parts list, describes the external components, gives an overview of the product from different angles.

Chapter 2: Setting Up

This chapter covers procedures on installing the processors, memory modules, hard drivers and other optional parts.

Chapter 3: Replacing the Pre-installed Components

This chapter covers the removal and replacement procedures for pre-installed components.

Chapter 4: Motherboard Information

This chapter lists the hardware setup procedures that you need to abide by when installing system components. It includes description of the jumpers and connectors on the motherboard.

Chapter 5: BIOS Setup

This chapter tells how to change system settings through the BIOS setup menu. Detailed descriptions of the BIOS parameters are also provided.

Chapter 6: Diagnostics

This chapter introduces some BIOS codes and technical terms to provide better service for the customers.

Appendix:

This chapter provides the cable connection table, the FRU parts list for reference of system setup, and technical support in case a problem arises with your system.

Safety and Compliance Information

Before installing and using TYAN FT77D-B7109, take note of the following precautions:

- Read all instructions carefully.
- Do not place the unit on an unstable surface, cart, or stand.
- Do not block the slots and opening on the unit, which are provided for ventilation.
- Only use the power source indicated on the marking label. If you are not sure, contact the power company.
- The unit uses a three-wire ground cable, which is equipped with a third pin to ground the unit and prevent electric shock. Do not defeat the purpose of this pin. If your outlet does not support this kind of plug, contact your electrician to replace your obsolete outlet.
- Do not place anything on the power cord. Place the power cord where it will not be in the way of foot traffic.
- Follow all warnings and cautions in this manual and on the unit case.
- Do not push objects in the ventilation slots as they may touch high voltage components and result in shock and damage to the components.
- When replacing parts, ensure that you use parts specified by the manufacturer.
- When service or repairs have been done, perform routine safety checks to verify that the system is operating correctly.
- Avoid using the system near water, in direct sunlight, or near a heating device.
- Cover the unit when not in use.

Safety Information

Retain and follow all product safety and operating instructions provided with your equipment. In the event of a conflict between the instructions in this guide and the instructions in equipment documentation, follow the guidelines in the equipment documentation.

Observe all warnings on the product and in the operating instructions. To reduce the risk of bodily injury, electric shock, fire and damage to the equipment, observe all precautions included in this guide.

You must become familiar with the safety information in this guide before you install, operate, or service TYAN products.

Symbols on Equipment

	Caution. This symbol indicates a potential hazard. The potential for injury exists if cautions are not observed. Consult equipment documentation for specific details.
	Caution. Slide-mounted equipment is not to be used as a shelf or a work space.
	Warning. This symbol indicates the presence of hazardous energy circuits or electric shock hazards. Refer all servicing to qualified personnel.
	Warning. This symbol indicates the presence of a hot surface or hot component. If this surface is contacted, the potential for injury exists. To reduce risk of injury from a hot component, allow the surface to cool before touching.

General Precautions

- Follow all caution and warning instructions marked on the equipment and explained in the accompanying equipment documentation.

Machine Room Environment

- This device is for use only in a machine room or IT room.
- Make sure that the area in which you install the system is properly ventilated and climate-controlled.

- Ensure that the voltage and frequency of your power source match the voltage and frequency inscribed on the electrical rating label of the equipment.
- Do not install the system in or near a plenum, air duct, radiator, or heat register.
- Never use the product in a wet location.

Equipment Chassis

- Do not block or cover the openings to the system.
- Never push objects of any kind through openings in the equipment. Dangerous voltages might be present.
- Conductive foreign objects can produce a short circuit and cause fire, electric shock, or damage to your equipment.
- Lift equipment using both hands and with your knees bent.

Equipment Racks

To avoid injury or damage to the equipment:

- Observe local occupational health and safety requirements and guidelines for manual materials handling.
- Do not attempt to move a rack by yourself; a minimum of two people are needed to move a rack.
- Do not attempt to move a fully loaded rack. Remove equipment from the rack before moving it.
- Do not attempt to move a rack on an incline that is greater than 10 degrees from the horizontal.
- Make sure the rack is properly secured to the floor or ceiling.
- Make sure the stabilizing feet are attached to the rack if it is a single-rack installation.
- Make sure racks are coupled together if it is a multiple-rack installation.
- Make sure the rack is level and stable before installing an appliance in the rack.
- Make sure the leveling jacks are extended to the floor.

- Make sure the full weight of the rack rests on the leveling jacks.
- Always load the rack from the bottom up. Load the heaviest component in the rack first.
- Make sure the rack is level and stable before pulling a component out of the rack.
- Make sure only one component is extended at a time. A rack might become unstable if more than one component is extended.

To avoid damage to the equipment:

- The rack width and depth must allow for proper serviceability and cable management.
- Ensure that there is adequate airflow in the rack. Improper installation or restricted airflow can damage the equipment.
- The rack cannot have solid or restricted airflow doors. You must use a mesh door on the front and back of the rack or remove the doors to ensure adequate air flow to the system.
- If you install the Model in a rack, do not place equipment on top of the unit. It will cause restricted airflow and might cause damage to the equipment.
- Make sure the product is properly matted with the rails. Products that are improperly matted with the rails might be unstable.
- Verify that the AC power supply branch circuit that provides power to the rack is not overloaded. This will reduce the risk of personal injury, fire, or damage to the equipment. The total rack load should not exceed 80 percent of the branch circuit rating. Consult the electrical authority having jurisdiction over your facility wiring and installation requirements.

Equipment Power Cords

- Use only the power cords and power supply units provided with your system. The system might have one or more power cords.
- Plug the power cord into a grounded (earthed) electrical outlet that is easily accessible at all times.
- In all European electrical environments, you must ground the Green/Yellow tab on the power cord. If you do not ground the Green/Yellow tab, it can cause an electrical shock due to high leakage currents.
- Do not place objects on AC power cords or cables. Arrange them so that no

one might accidentally step on or trip over them.

- Do not pull on a cord or cable. When unplugging from the electrical outlet, grasp the cord by the plug.
- To reduce the risk of electrical shock, disconnect all power cords before servicing the appliance.



Equipment Batteries

- The system battery contains lithium manganese dioxide. If the battery pack is not handled properly, there is risk of fire and burns.
- Do not disassemble, crush, puncture, short external contacts, or dispose of the battery in fire or water.
- Do not expose the battery to temperatures higher than 60°C (140°F).
- The system battery is not replaceable. If the battery is replaced by an incorrect type, there is danger of explosion. Replace the battery only with a spare designated for your product.
- Do not attempt to recharge the battery.
- Dispose of used batteries according to the instructions of the manufacturer. Do not dispose of batteries with the general household waste. To forward them to recycling or proper disposal, use the public collection system or return them to TYAN, your authorized TYAN partner, or their agents.

Equipment Modifications

- Do not make mechanical modifications to the system. TYAN is not responsible for the regulatory compliance of TYAN equipment that has been modified.

Equipment Repairs and Servicing

- The installation of internal options and routine maintenance and service of this product should be performed by trained service technician/personnel who are knowledgeable about the procedures, precautions, and hazards associated with equipment containing hazardous energy levels.

- Do not exceed the level of repair specified in the procedures in the product documentation. Improper repairs can create a safety hazard.
- Allow the product to cool before removing covers and touching internal components.
- Remove all watches, rings, or loose jewelry when working before removing covers and touching internal components.
- Do not use conductive tools that could bridge live parts.
- Use gloves when you remove or replace system components; they can become hot to the touch.
- If the product sustains damage requiring service, disconnect the product from the AC electrical outlet and refer servicing to an authorized service provider. Examples of damage requiring service include:
 - The power cord, extension cord, or plug has been damaged.
 - Liquid has been spilled on the product or an object has fallen into the product.
 - The product has been exposed to rain or water.
 - The product has been dropped or damaged.
 - The product does not operate normally when you follow the operating instructions.

Table of Contents

Chapter 1: Overview	17
1.1 About the TYAN FT77D-B7109	17
1.2 Product Models	18
1.3 GPU limited support list for FT77D-B7109	18
1.4 Features	19
1.5 Standard Parts List	31
1.5.1 Box Contents	31
1.5.2 Accessories	31
1.6 About the Product	32
1.6.1 System Front View	32
1.6.2 System Rear View	34
1.6.3 LED Definitions	36
1.6.4 System Top View	38
Chapter 2: Setting Up	39
2.0.1 Before you Begin	39
2.0.2 Work Area	39
2.0.3 Tools	39
2.0.4 Precautions	40
2.1 Installing Motherboard Components	41
2.1.1 Removing the Chassis Cover	41
2.1.2 Installing the CPU and Heat sink	43
2.1.3 Installing the Memory	46
2.1.4 Installing Expansion Cards	50
2.1.5 Installing the Mezzanine Card	53
2.1.6 Installing Hard Drives	55
2.2 Rack Mounting	56
2.2.1 Installing the Server in a Rack	56
2.2.2 Installing the inner Rails to the Chassis	57
2.2.3 Installing the Outer Rails to the Rack	59
2.2.4 Rack mounting the Server	60
Chapter 3: Replacing Pre-Installed Components	63
3.1 Introduction	63
3.2 Disassembly Flowchart	63
3.3 Removing the Cover	64
3.4 Replacing the Power Supply	64
3.5 Replacing the Front Panel Board	65
3.5.1 Front Panel Board Features	67
3.6 Replacing the Fan Board	68
3.6.1 Fan Board Features	70

3.7	Replacing the HDD Backplane Board	71
3.7.1	HDD BP Board Features	75
3.8	Replacing Power Distribution Board	76
3.8.1	Power Distribution Board Features	77
3.9	Replacing the Riser Card	78
3.9.1	Riser card Feature	80
3.10	Replace the Power Backplane Board	81
3.10.1	Power Backplane Board Features	82
3.11	Replacing the Motherboard	83
Chapter 4:	Motherboard Information	87
4.1	Board Image	88
4.2	Block Diagram	89
4.3	Motherboard Mechanical Drawing	90
4.4	Board Parts, Jumpers and Connectors	91
4.5	Thermal Interface Material	98
4.6	Tips on Installing Motherboard in Chassis	99
4.7	Installing the Memory	101
4.8	Mainboard LED Definition	107
4.9	Finishing Up	110
Chapter 5:	BIOS Setup	111
5.1	About the BIOS	111
5.1.1	Setup Basics	111
5.1.2	Getting Help	112
5.1.3	In Case of Problems	112
5.1.4	Setup Variations	112
5.2	Main Menu	113
5.3	Advanced Menu	115
5.3.1	iSCSI Configuration	117
5.3.2	Intel® Virtual RAID on CPU	123
5.3.3	Trusted Computing	131
5.3.4	ACPI Settings	132
5.3.5	OnBoard Device Configuration	133
5.3.6	Hardware Health Configuration	134
5.3.7	PCIe Slot Configuration	136
5.3.8	AST2500 Super IO Configuration	137
5.3.9	S5 RTC Wake Settings	139
5.3.10	Serial Port Console Redirection	140
5.3.11	Option ROM Dispatch Policy	146
5.3.12	PCI Subsystem Settings	148
5.3.13	Network Stack Configuration	149
5.3.14	CSM Configuration	151
5.3.15	USB Configuration	153

5.4	Platform Configuration	155
5.4.1	PCH Configuration.....	156
5.4.2	Miscellaneous Configuration	167
5.4.3	Server ME Configuration	168
5.5	Socket Configuration	169
5.5.1	Processor Configuration	170
5.5.2	Common RefCode Configuration	172
5.5.3	UPI Configuration	174
5.5.4	Memory Configuration	177
5.5.5	IIO Configuration	181
5.5.6	Advanced Power Management Configuration.....	196
5.6	Server Management	201
5.6.1	System Event Log	203
5.6.2	BMC Network Configuration	204
5.7	Security.....	205
5.7.1	Secure Boot.....	206
5.8	Boot	210
5.8.1	Delete Boot Option	212
5.9	Save & Exit	213
Chapter 6:	Diagnostics	215
6.1	Flash Utility	215
6.2	AMIBIOS Post Code (Aptio)	216
Appendix I:	How to recover UEFI BIOS	225
Appendix II:	Cable Connection Tables	227
Appendix III:	Fan and Temp Sensors	231
Appendix IV:	FRU Parts Table.....	237
Appendix V:	Technical Support	239

NOTE

Chapter 1: Overview

1.1 About the TYAN FT77D-B7109

Congratulations on your purchase of the TYAN[®] FT77D-B7109, a highly optimized 4U rack-mountable barebone system. The FT77D-B7109 is designed to support dual Intel[®] Xeon[®] Scalable Processor Families and up to 768GB RDIMM / 1536GB LRDIMM / 3072GB RDIMM 3DS / LRDIMM 3DS, providing a rich feature set and incredible performance. Leveraging advanced technology from Intel[®], the FT77D-B7109 server system is capable of offering scalable 32 and 64-bit computing, high bandwidth memory design, and lightning-fast PCI-E bus implementation. The FT77D-B7109 not only empowers your company in nowadays IT demand but also offers a smooth path for future application usage.

TYAN[®] also offers the FT77D-B7109 in a version that can support up to fourteen (14) internal hot-swappable 2.5" SATA HDD/SSD or NVMe SSD with Intel[®] RSTe 5.0 support. The FT77D-B7109 uses TYAN's latest chassis featuring a robust structure and a solid mechanical enclosure. All of this provides FT77D-B7109 the power and flexibility to meet the needs of nowadays server application.



1.2 Product Models

The system board within the Tyan Barebone is defined by the following models:

- **B7109F77DV10E4HR-2T-N**: Intel-based platform
- **B7109F77DV14HR-2T-NF**: Intel-based platform
- **B7109F77DV14HR-2T-N**: Intel-based platform

Model	SKU	Internal HDD Bays	Fabric CPU support
FT77D-B7109	B7109F77DV10E4HR-2T-N	(10) SATA + (4) NVMe SSD bays	-
FT77D-B7109	B7109F77DV14HR-2T-NF	(14) SATA	support
FT77D-B7109	B7109F77DV14HR-2T-N	(14) SATA	-

1.3 GPU limited support list for FT77D-B7109

GPU Card (when 8 slots fully populated)	Configure
NVIDIA Tesla V100/16GB	Need to remove HDD6~HDD13 at 33° C
NVIDIA Tesla P100/16GB	Need to remove HDD6~HDD13 at 35° C
NVIDIA Tesla P100/12GB	Need to remove HDD6~HDD13 at 35° C

1.4 Features

TYAN FT77D-B7109 (B7109F77DV10E4HR-2T-N)

System	Form Factor	4U Rackmount
	Chassis Model	FT77D
	Dimension (D x W x H)	30.31" x 17.24" x 6.93" (770 x 438 x 176mm)
	Motherboard	S7109GM2NR-2T
	Gross Weight	45 kg (99.5 lbs)
	Net weight	26 kg (57.5 lbs)
Front Panel	Buttons	(1) RST, (1) ID, (1) NMI, (1) PWR w/ LED
	LEDs	(1) HDD, (1) ID, (3) LAN, (1) IPMI/Warning
	I/O Ports	(2) USB 3.0 port
External Drive Bay	Type / Q'ty	2.5" Hot-Swap SSD/HDD + NVMe, (10) + (4)
	HDD backplanesupport	SAS 12Gb/s, SATA 6Gb/s, NVMe
	Supported HDD Interface	(10) SATA 6Gb/s + (4) NVMe
System Cooling Configuration	FAN	(6) 12cm fans
Power Supply	Type	RPSU
	Input Range	AC 100-127V/12.9A, AC 200-240V/9.5A
	Frequency	47 - 63 Hz
	Output Watts	Max 2,000 Watts for 100-127V AC input, Max 3,200Watts for 200-240V AC input
	Efficiency	PFC, 80 plus Platinum
	Redundancy	2+1 NOTE: When use 100V-127V AC

		input, the system does not support redundant PSU operation if the total system load exceeds 20A (2000 Watts)
Processor	Socket Type / Q'ty	LGA3647/ (2)
	Supported CPU Series	Intel Xeon Scalable Processor Family
	Thermal Design Power (TDP) wattage	Max up to 205W
	System Bus	Up to 10.4/9.6 GT/s with Intel UltraPath Interconnect (UPI) support
Chipset	PCH	Intel C621
	Switch IC	(4) PLX PEX8747
Memory	Supported DIMM Qty	(12)+(12) DIMM slots
	DIMM Type / Speed	DDR4 RDIMM/RDIMM 3DS/ LRDIMM/LRDIMM 3DS 2666
	Capacity	Up to 768GB RDIMM/ 1,536GB LRDIMM/ 2,048GB RDIMM 3DS/ LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
	Memory channel	6 Channels per CPU
	Memory voltage	1.2V
Expansion Slots	PCI-E	(8) PCI-E Gen3 x16 slots, (2) PCI-E Gen3 x8 slots (one for Tyan OCP riser card only)
	Pre-install TYAN Riser Card	M2215-L8-1F
	Pre-install TYAN Mezz Card	M2093 w/ (2) PCI-E x8 SFF-8611 OCuLink connectors for (4) NVMe ports
LAN	Port Q'ty	(2) 10GbE ports, (1) PHY
	Controller	Intel X550-AT2
	PHY	Realtek RTL8211E

Storage	SATA	Connector	(2) Mini-SAS HD (8-ports)
		Controller	Intel C621
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
	sSATA	Connector	(2) SATA-III, (1) Mini-SAS HD (4-ports)
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
Graphic	Connector type		D-Sub 15-pin
	Resolution		Up to 1920x1200
	Chipset		Aspeed AST2500
I/O Ports	USB		(2) USB3.0 ports (at front)
	COM		(1) DB-9 COM port (at front)
	VGA		(1) D-Sub 15-pin port (at front)
	RJ-45		(2) 10GbE ports, (1) PHY dedicated for IPMI
TPM (Optional)	TPM Support		Please refer to our TPM supported list.
System Monitoring	Chipset		Aspeed AST2500
	Temperature		Monitors temperature for CPU & memory & system environment
	Voltage		Monitors voltage for CPU, memory, chipset & power supply
	LED		Over temperature warning indicator, Fan & PSU fail LED indicator
	Others		Watchdog timer support
Server	Onboard Chipset		Onboard Aspeed AST2500

Management	AST2500 iKVM Feature	IPMI 2.0 compliant baseboard management controller (BMC), Supports storage over IP and remote platform-flash, USB 2.0 virtual hub
	AST2500 IPMI Feature	24-bit high quality video compression, 10/100/1000 Mb/s MAC interface
BIOS	Brand / ROM size	AMI, 32MB
	Feature	Hardware Monitor, SMBIOS 3.0/PnP/Wake on LAN, Boot from USB device/PXE via LAN/Storage, User Configurable FAN PWM Duty Cycle, Console Redirection, ACPI sleeping states S4,S5, ACPI 6.1
Operating System	OS supported list	Please refer to our AVL support lists.
Regulation	FCC (DoC)	Class A
	CE (DoC)	Class A
	VCCI	Class A
	CB/LVD	Yes
	RCM	Class A
Operating Environment	Operating Temp.	10° C ~ 35° C (50° F~ 95° F)
	Non-operating Temp.	- 40° C ~ 70° C (-40° F ~ 158° F)
	In/Non-operating Humidity	90%, non-condensing at 35° C
RoHS	RoHS 6/6 Compliant	Yes
Package Contains	Manual	(1) Web User's manual, (1) Quick Installation Guide
	Installation CD	(1) TYAN installation CD
	Barebone	(1) FT77D-B7109 w/NV Tesla-aware FW Barebone

FT77D-B7109 (B7109F77DV14HR-2T-NF)

System	Form Factor	4U Rackmount
	Chassis Model	FT77D
	Dimension (D x W x H)	30.31" x 17.24" x 6.93" (770 x 438 x 176mm)
	Motherboard	S7109GM2NR-2T
	Gross Weight	45 kg (99.5 lbs)
	Net weight	26 kg (57.5 lbs)
Front Panel	Buttons	(1) RST, (1) ID, (1) NMI, (1) PWR w/ LED
	LEDs	(1) HDD, (1) ID, (3) LAN, (1) IPMI/Warning
	I/O Ports	(2) USB 3.0 port
External Drive Bay	Type / Q'ty	2.5" Hot-Swap SSD/HDD/ (14)
	HDD backplanesupport	SAS 12Gb/s, SATA 6Gb/s
	Supported HDD Interface	(14) SATA 6Gb/s
System Cooling Configuration	FAN	(6) 12cm fans
Power Supply	Type	RPSU
	Input Range	AC 100-127V/12.9A, AC 200-240V/9.5A
	Frequency	47 - 63 Hz
	Output Watts	Max 2000 Watts for 100-127V AC input, Max 3,200Watts for 200-240V AC input
	Efficiency	PFC, 80 plus Platinum

	Redundancy	2+1 NOTE: When use 100V-127V AC input, the system does not support redundant PSU operation if the total system load exceeds 20A (2000 Watts)
Processor	Socket Type / Q'ty	LGA3647/ (2), *Socket-F support
	Supported CPU Series	Intel Xeon Scalable Processor Family
	Thermal Design Power (TDP) wattage	Max up to 205W
	System Bus	Up to 10.4/9.6 GT/s with Intel UltraPath Interconnect (UPI) support
Chipset	PCH	Intel C621
	Switch IC	(4) PLX PEX8747
Memory	Supported DIMM Qty	(12)+(12) DIMM slots
	DIMM Type / Speed	DDR4 RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 2666
	Capacity	Up to 768GB RDIMM/ 1,536GB LRDIMM/ 3,072GB RDIMM 3DS/ LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
	Memory channel	6 Channels per CPU
	Memory voltage	1.2V
Expansion Slots	PCI-E	(9) PCI-E Gen3 x16 slots, (2) PCI-E Gen3 x8 slots (one for Tyan OCP riser card only)
	Pre-install TYAN Riser Card	M2215-L8-1F
LAN	Port Q'ty	(2) 10GbE ports, (1) PHY
	Controller	Intel X550-AT2
	PHY	Realtek RTL8211E

Storage	SATA	Connector	(2) Mini-SAS HD (8-ports)
		Controller	Intel C621
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
	sSATA	Connector	(2) SATA-III, (1) Mini-SAS HD (4-ports)
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
Graphic	Connector type		D-Sub 15-pin
	Resolution		Up to 1920x1200
	Chipset		Aspeed AST2500
I/O Ports	USB		(2) USB3.0 ports (at front)
	COM		(1) DB-9 COM port (at front)
	VGA		(1) D-Sub 15-pin port (at front)
	RJ-45		(2) 10GbE ports, (1) PHY dedicated for IPMI
TPM (Optional)	TPM Support		Please refer to our TPM supported list.
System Monitoring	Chipset		Aspeed AST2500
	Temperature		Monitors temperature for CPU & memory & system environment
	Voltage		Monitors voltage for CPU, memory, chipset & power supply
	LED		Over temperature warning indicator, Fan & PSU fail LED indicator
	Others		Watchdog timer support
Server Management	Onboard Chipset		Onboard Aspeed AST2500

	AST2500 iKVM Feature	IPMI 2.0 compliant baseboard management controller (BMC), Supports storage over IP and remote platform-flash, USB 2.0 virtual hub
	AST2500 IPMI Feature	24-bit high quality video compression, 10/100/1000 Mb/s MAC interface
BIOS	Brand / ROM size	AMI, 32MB
	Feature	Hardware Monitor, SMBIOS 3.0/PnP/Wake on LAN, Boot from USB device/PXE via LAN/Storage, User Configurable FAN PWM Duty Cycle, Console Redirection, ACPI sleeping states S4,S5, ACPI 6.1
Operating System	OS supported list	Please refer to our AVL support lists.
Regulation	FCC (DoC)	Class A
	CE (DoC)	Class A
	VCCI	Class A
	CB/LVD	Yes
	RCM	Class A
Operating Environment	Operating Temp.	10° C ~ 35° C (50° F~ 95° F)
	Non-operating Temp.	- 40° C ~ 70° C (-40° F ~ 158° F)
	In/Non-operating Humidity	90%, non-condensing at 35° C
RoHS	RoHS 6/6 Compliant	Yes
Package Contains	Manual	(1) Web User's manual, (1) Quick Installation Guide
	Installation CD	(1) TYAN installation CD
	Barebone	(1) FT77D-B7109 w/NV Tesla-aware FW Barebone

TYAN FT77D-B7109 (B7109F77DV14HR-2T-N)

System	Form Factor	4U Rackmount
	Chassis Model	FT77D
	Dimension (D x W x H)	30.31" x 17.24" x 6.93" (770 x 438 x 176mm)
	Motherboard	S7109GM2NR-2T
	Gross Weight	45 kg (99.5 lbs)
	Net weight	26 kg (57.5 lbs)
Front Panel	Buttons	(1) RST, (1) ID, (1) NMI, (1) PWR w/ LED
	LEDs	(1) HDD, (1) ID, (3) LAN, (1) IPMI/Warning
	I/O Ports	(2) USB 3.0 port
External Drive Bay	Type / Q'ty	2.5" Hot-Swap SSD/HDD/ (14)
	HDD backplanesupport	SAS 12Gb/s, SATA 6Gb/s
	Supported HDD Interface	(14) SATA 6Gb/s
System Cooling Configuration	FAN	(6) 12cm fans
Power Supply	Type	RPSU
	Input Range	AC 100-127V/12.9A, AC 200-240V/9.5A
	Frequency	47 - 63 Hz
	Output Watts	Max 2,000 Watts for 100-127V AC input, Max 3,200Watts for 200-240V AC input
	Efficiency	PFC, 80 plus Platinum

	Redundancy	2+1 NOTE: When use 100V-127V AC input, the system does not support redundant PSU operation if the total system load exceeds 20A (2000 Watts)
Processor	Socket Type / Q'ty	LGA3647/ (2)
	Supported CPU Series	Intel Xeon Scalable Processor Family
	Thermal Design Power (TDP) wattage	Max up to 205W
	System Bus	Up to 10.4/9.6 GT/s with Intel UltraPath Interconnect (UPI) support
Chipset	PCH	Intel C621
	Switch IC	(4) PLX PEX8747
Memory	Supported DIMM Qty	(12)+(12) DIMM slots
	DIMM Type / Speed	DDR4 RDIMM/RDIMM 3DS/ LRDIMM/LRDIMM 3DS 2666
	Capacity	Up to 768GB RDIMM/ 1,536GB LRDIMM/ 3,072GB RDIMM 3DS/ LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
	Memory channel	6 Channels per CPU
	Memory voltage	1.2V
Expansion Slots	PCI-E	(9) PCI-E Gen3 x16 slots, (2) PCI-E Gen3 x8 slots (one for Tyan OCP riser card only)
	Pre-install TYAN Riser Card	M2215-L8-1F
LAN	Port Q'ty	(2) 10GbE ports, (1) PHY
	Controller	Intel X550-AT2
	PHY	Realtek RTL8211E

Storage	SATA	Connector	(2) Mini-SAS HD (8-ports)
		Controller	Intel C621
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
	sSATA	Connector	(2) SATA-III, (1) Mini-SAS HD (4-ports)
		Speed	6.0 Gb/s
		RAID	RAID 0/1/10/5 (Intel RSTe)
Graphic	Connector type		D-Sub 15-pin
	Resolution		Up to 1920x1200
	Chipset		Aspeed AST2500
I/O Ports	USB		(2) USB3.0 ports (at front)
	COM		(1) DB-9 COM port (at front)
	VGA		(1) D-Sub 15-pin port (at front)
	RJ-45		(2) 10GbE ports, (1) PHY dedicated for IPMI
TPM (Optional)	TPM Support		Please refer to our TPM supported list.
System Monitoring	Chipset		Aspeed AST2500
	Temperature		Monitors temperature for CPU & memory & system environment
	Voltage		Monitors voltage for CPU, memory, chipset & power supply
	LED		Over temperature warning indicator, Fan & PSU fail LED indicator
	Others		Watchdog timer support
Server	Onboard Chipset		Onboard Aspeed AST2500

Management	AST2500 iKVM Feature	IPMI 2.0 compliant baseboard management controller (BMC), Supports storage over IP and remote platform-flash, USB 2.0 virtual hub
	AST2500 IPMI Feature	24-bit high quality video compression, 10/100/1000 Mb/s MAC interface
BIOS	Brand / ROM size	AMI, 32MB
	Feature	Hardware Monitor, SMBIOS 3.0/PnP/Wake on LAN, Boot from USB device/PXE via LAN/Storage, User Configurable FAN PWM Duty Cycle, Console Redirection, ACPI sleeping states S4,S5, ACPI 6.1
Operating System	OS supported list	Please refer to our AVL support lists.
Regulation	FCC (DoC)	Class A
	CE (DoC)	Class A
	VCCI	Class A
	CB/LVD	Yes
	RCM	Class A
Operating Environment	Operating Temp.	10° C ~ 35° C (50° F~ 95° F)
	Non-operating Temp.	- 40° C ~ 70° C (-40° F ~ 158° F)
	In/Non-operating Humidity	90%, non-condensing at 35° C
RoHS	RoHS 6/6 Compliant	Yes
Package Contains	Manual	(1) Web User's manual, (1) Quick Installation Guide
	Installation CD	(1) TYAN installation CD
	Barebone	(1) FT77D-B7109 w/NV Tesla-aware FW Barebone

1.5 Standard Parts List

This section describes FT77D-B7109 package contents and accessories. Open the box carefully and ensure that all components are present and undamaged. The product should arrive packaged as illustrated below.

1.5.1 Box Contents

FT77D-B7109 Chassis Kit

- (1) 4U chassis
- (2+1) 3,200W (80+ Platinum) w/ PFC redundant power supply
- (6) 120X120X38MM Fan (pre-installed)
- (1) S7109 Motherboard (pre-installed)
- (1) M1284F77D-BP12E-14 HDD Backplane Board (pre-installed)
- (1) M1713F77C-FPB Front Panel Board (pre-installed)
- (1) M7059F77C-D-PDB Power Distribution Board (pre-installed)
- (1) M7109F77D-D-PBP Power Backplane Board (pre-installed)
- (1) M1809F77A-FB Fan Board (pre-installed)
- (1) M2215-L8-1F riser card (pre-installed)
- (1) M2093 riser card (pre-installed) --- only for B7109F77DV10E4HR-2T-N

1.5.2 Accessories

If any items are missing or appear damaged, contact your retailer or browse to TYAN's website for service: <http://www.tyan.com>



FT77D-B7109 Accessory Kit

- (1) Rail kit + (1) Rail screw kit
- (1) Card Guide kit
- (1) Screw Pack
- (2) CPU heatsink
- (3) US power cord
- (3) EU power cord
- (1) Mounting ears
- (16) 2*3P GPU power cable
- (8) 2*4P GPU power cable
- (8) GPU card Holder Bracket (only for GPU card bundle SKU) w/ screw
- (8) 2*4P GPU power cable for K80 GPU
- (1) Air duct
- (2) CPU clip
- (2) Fabric CPU clip (only for Fabric CPU bundle SKU)
- (1) Tyan Drive CD
- (1) Addendum for China Use Only

1.6 About the Product

The following views show you the product.

1.6.1 System Front View



M1713F77C-FPB and Front I/O Ports

1. USB3.0 Ports
2. ID Button
3. NMI Button
4. Reset Button
5. LAN1 LED
6. LAN2 LED
7. LAN3 LED (no function)
8. Power Button with LED
9. ID LED
10. HDD Activity LED
11. IPMI/Warning LED
12. Serial Port
13. VGA Port

M1713F77C-FPB Front Panel LED Control Board


Switch and LED Indication

Item	Status	LED Color	Behavior	Note
5. LAN1	Access	Green	Blinking	
	Link	Green	Solid On	
	Off Link	Green	Off	
6. LAN2	Access	Green	Blinking	
	Link	Green	Solid On	
	Off Link	Green	Off	
7. LAN3	NA	NA	NA	No Function
8. Power	Power On	Green	Solid On	
	Power Off	Green	Off	
9. ID	Located	Blue	Solid On	
	Free	Blue	Off	
10. HDD Activity	Access	Green	Blinking	
11. IPMI / Warning	Normal	Amber	Off	BMC & HWM system alert event (*) N+1 Redundant PSU Indication
	Alert	Amber	Solid On	


*Warning LED Indication for 2+1 PSU Redundancy System

Status	System Warning LED
All PSU present and plug AC cord when system power on	Off
One of PSU AC lose	Amber solid on
One of PSU not present	Amber solid on

1.6.2 System Rear View




B7109F77DV14HR-2T-N / B7109F77DV14HR-2T-NF	
No.	Description
1	PSU2
2	PSU1
3	PSU0
4	Mezzanine Card Slot
5	ID LED Button
6	LAN3 (IPMI)
7	LAN2
8	LAN1
9	PCIE Slots
NOTE: 1. With every two out of three PSUs can boot up the FT77D-B7109. 2. The FT77D-B7109 can support the redundant power under the condition when the voltage is 100~127V and the output power is less than 2000W, or the voltage is 200~240V and the output power is less than 3200W.	



B7109F77DV10E4HR-2T-N	
No.	Description
1	PSU2
2	PSU1
3	PSU0
4	Mezzanine Card Slot
5	ID LED Button
6	LAN3 (IPMI)
7	LAN2
8	LAN1
9	PCIE Slots
10	PCIE Slot (M2093 pre-installed for NVMe SKU)
NOTE: 1. With every two out of three PSUs can boot up the FT77D-B7109. 2. The FT77D-B7109 can support the redundant power under the condition when the voltage is 100~127V and the output power is less than 2000W, or the voltage is 200~240V and the output power is less than 3200W.	

1.6.3 LED Definitions

10Gbps LAN Port LAN Indication

10Gbps LAN Link/Activity LED Scheme			
		Left LED (Link/Activity) LED Color: Green	Right LED (Speed) LED Color: Yellow
No Link		OFF	OFF
100 Mbps	Link	Green Solid On	Green Solid On
	Active	Green Blinking	Green Solid On
1000 Mbps (1Gbps)	Link	Green Solid On	Yellow Solid On
	Active	Green Blinking	Yellow Solid On
10 Gbps	Link	Yellow Solid On	Yellow Solid On
	Active	Yellow Blinking	Yellow Solid On


1Gbps LAN Port LAN Indication

1Gbps LAN Link/Activity LED Scheme			
		Left LED (Link/Activity) LED Color: Green	Right LED (Speed) LED Color: Amber
No Link		OFF	OFF
10 Mbps	Link	Green Solid On	OFF
	Active	Green Blinking	OFF
100 Mbps	Link	Green Solid On	Green Solid On
	Active	Green Blinking	Green Solid On
1000 Mbps (1Gbps)	Link	Green Solid On	Amber Solid On
	Active	Green Blinking	Amber Solid On

NOTE: “Left” and “Right” are viewed from the rear panel.

NOTE:

1. LAN1/LAN2: Intel X550
2. LAN3: Realtek RTL8211E for IPMI




PSU LED Definitions

Power Supply Condition	Dual-color	
	Green LED	Amber LED
No AC power to all power supplies	OFF	OFF
Power supply critical event causing a shutdown; failure, OCP, OVP, Fan Fail, OTP, UVP	OFF	ON
Power supply warning events where the power supply continues to operate; but triggered high Temperature, high Voltage, high Current, and low fan rpm critical limit.	OFF	1Hz Blinking Amber
AC present only 12VSB on (PS off) or PS in Smart Redundant state	1Hz Blinking Green	OFF
Output ON and OK	ON	OFF
AC cord unplugged	OFF	ON

Warning: All PSUs have to be AC-ON at the same time before you power on the system.

1.6.4 System Top View



HDD Configurations

1. (14) SATA (#1~#14)
2. (10) SATA (#1~#2, #7~#14) + (4) NVMe (#3~#6)

No.	Description
1~14	(14) 2.5" HDDs/SSDs (HDD0 ~ HDD13) w/ M1284F77D-BP12E-14 HDD BP Board pre-installed
15	M1713F77C-FPB Front Panel Board
16	System Fans
17	CPU0
18	CPU1
19	M7059F77C-D-PDB Power Distribution Board
20	M7109F77D-D-PBP Power Backplane Board
21	(2+1) Redundant Power Supply
22	M2093 Riser Card (pre-installed for NVME SKU)
NOTE: The system is pre-installed with S7109 motherboard.	

Chapter 2: Setting Up

2.0.1 Before you Begin

This chapter explains how to install the CPUs, CPU heatsinks, memory modules, and hard drives. Instructions on inserting add on cards are also given.

2.0.2 Work Area

Make sure you have a stable, clean working environment. Dust and dirt can get into components and cause malfunctions. Use containers to keep small components separated. Putting all small components in separate containers prevents them from becoming lost. Adequate lighting and proper tools can prevent you from accidentally damaging the internal components.

2.0.3 Tools

The following procedures require only a few tools, including the following:

- A cross head (Phillips) screwdriver
- A grounding strap or an anti-static pad
- A T30 Security Torx screwdriver

Most of the electrical and mechanical connections can be disconnected using your fingers. It is recommended that you do not use needle-nosed pliers to remove connectors as these can damage the soft metal or plastic parts of the connectors.



Caution!

1. To avoid damaging the motherboard and associated components, use torque force within the range **5~7 kgf/cm (4.35 ~ 6.09 lb/in)** on each mounting screw for motherboard installation.
2. Do not apply power to the board if it has been damaged.

2.0.4 Precautions

Components and electronic circuit boards can be damaged by discharges of static electricity. Working on a system that is connected to a power supply can be extremely dangerous. Follow the guidelines below to avoid damage to FT77D-B7109 or injury to yourself.

- Ground yourself properly before removing the top cover of the system. Unplug the power from the power supply and then touch a safely grounded object to release static charge (i.e. power supply case). If available, wear a grounded wrist strap. Alternatively, discharge any static electricity by touching the bare metal chassis of the unit case, or the bare metal body of any other grounded appliance.
- Avoid touching motherboard components, IC chips, connectors, memory modules, and leads.
- The motherboard is pre-installed in the system. When removing the motherboard, always place it on a grounded anti-static surface until you are ready to reinstall it.
- Hold electronic circuit boards by the edges only. Do not touch the components on the board unless it is necessary to do so. Do not flex or stress circuit boards.
- Leave all components inside the static-proof packaging that they ship with until they are ready for installation.
- After replacing optional devices, make sure all screws, springs, or other small parts are in place and are not left loose inside the case. Metallic parts or metal flakes can cause electrical shorts.


2.1 Installing Motherboard Components

This section describes how to install components on to the motherboard, including CPUs, memory modules and Add-on cards.


2.1.1 Removing the Chassis Cover

Follow these instructions to remove FT77D-B7109 chassis cover.

1. Loosen 2 thumb screws and 2 screws on the rear top cover.



2. Slide to lift up the rear top cover.



3. Unscrew the front top cover.




4. Release the latch to lift up the front top cover from the chassis.




2.1.2 Installing the CPU and Heat sink

Follow the steps below on installing CPUs and CPU heatsinks.

1. Align and install the processor on the carrier.




2. Carefully flip the heatsink. Then install the carrier assembly on the bottom of the heatsink and make sure the gold is located in the correct direction.






3. Locate the CPU socket's gold arrow. Always start with CPU0 first. Remove the CPU Socket protection cap.



NOTE: A new heatsink comes with pre-applied thermal grease.

Once the heatsink has been removed from the processor, you need to clean the processor and heatsink using an alcohol solvent. Then apply new thermal grease before reinstalling the heatsink.

4. Carefully flip the heatsink. Align the heatsink with the CPU socket by the guide pins and make sure the gold arrow is located in the correct direction. Then place the heatsink onto the top of the CPU socket.




5. To secure the heatsink, use a T30 Security Torx to tighten the screws in a sequential order (1→2→3→4).

NOTE: When disassembling the heatsink, loosen the screws in reverse order (4→3→2→1).

6. Repeat the procedures described earlier to install the second processor and heatsink.

7. Place the CPU air duct back and screw it to the chassis.



2.1.3 Installing the Memory


Follow these instructions to install the memory modules onto the motherboard.

1. Press the memory slot locking levers in the direction of the arrows as shown in the following illustration.



2. Align the memory module with the slot. When inserted properly, the memory slot locking levers lock automatically onto the indentations at the ends of the module.





Dual CPU Installed (CPU0 and CPU1)	Quantity of memory installed											
	2	4	6	8	10	12	14	16	18	20	22	24
CPU0_DIMM_A0	√	√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_A1							√	√	√	√	√	√
CPU0_DIMM_B0		√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_B1								√	√	√	√	√
CPU0_DIMM_C0			√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_C1									√	√	√	√
CPU0_DIMM_D0				√	√	√	√	√	√	√	√	√
CPU0_DIMM_D1										√	√	√
CPU0_DIMM_E0					√	√	√	√	√	√	√	√
CPU0_DIMM_E1											√	√
CPU0_DIMM_F0						√	√	√	√	√	√	√
CPU0_DIMM_F1												√
CPU1_DIMM_A0	√	√	√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_A1							√	√	√	√	√	√
CPU1_DIMM_B0		√	√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_B1								√	√	√	√	√
CPU1_DIMM_C0			√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_C1									√	√	√	√
CPU1_DIMM_D0				√	√	√	√	√	√	√	√	√
CPU1_DIMM_D1										√	√	√
CPU1_DIMM_E0					√	√	√	√	√	√	√	√
CPU1_DIMM_E1											√	√
CPU1_DIMM_F0						√	√	√	√	√	√	√
CPU1_DIMM_F1												√

NOTE:

1. ✓ indicates a populated DIMM slot.
2. Use paired memory installation for max performance.
3. Populate the same DIMM type in each channel, specifically
 - Use the same DIMM size
 - Use the same # of ranks per DIMM
4. Dual-rank DIMMs are recommended over single-rank DIMMs.
5. Un-buffered DIMM can offer slightly better performance than registered DIMM if populating only a single DIMM per channel.
6. Always install with CPU0 Socket and DIMM_0 Slot first, following the alphabetical order.

2.1.4 Installing Expansion Cards

Only the PCI-E Gen3 x16 slots can support **GPU (Graphic Processing Unit)** cards. Follow these instructions to install the PCIE cards.

Using GPU Bracket



1. Locate the PCI-E Gen.3 x16 slot on the motherboard. Unscrew to take out the dummy brackets.



2. Screw the GPU bracket to the GPU card and connect the GPU PWR cable.



3. Insert the GPU card into the PCIE Gen. 3 slot and screw the GPU card to the chassis. Connect the GPU PWR cable to the Power Distribution Board.



Using Card Guide

1. Insert the card guide onto the power distribution board bracket.




2. Insert the full-length, full-height PCIE card into the PCIE Gen3 x16 slot and screw it firmly to the chassis.




2.1.5 Installing the Mezzanine Card

Follow these instructions to install the Mezzanine Card.


1. Unscrew the dummy bracket.



2. Pull the dummy bracket to slide it out.



3. Insert a Mezzanine card associated with tray into the slot and screw it to the chassis.



2.1.6 Installing Hard Drives

The FT77D-B7109 supports fourteen 2.5" HDD/SSD. Follow these instructions to install a hard drive.

1. Pull the HDD tray out from the chassis.



2. Remove 4 screws to detach the HDD tray bracket.



3. Place a HDD/SSD into the drive tray. Use four screws to secure the HDD/SSD.



4. Reinsert the HDD tray into the HDD cage.



2.2 Rack Mounting

After installing the necessary components, FT77D-B7109 can be mounted in a rack using the supplied rack mounting kit.

Rack mounting kit

Rail with Bracket x 2

Mounting Ears x 2

Screw Sack x 2

NOTE: The users have to prepare two screws and two nuts on their own for rack mounting.

2.2.1 Installing the Server in a Rack

Follow these instructions to mount the FT77D-B7109 into an industry standard 19" rack.



Note:

Before mounting FT77D-B7109 in a rack, ensure that all internal components have been installed and that the unit has been fully tested.

2.2.2 Installing the inner Rails to the Chassis

1. Screw the mounting ear to each side of FT77D-B7109 as shown using 4 screws from the supplied screws kit.



2. Press the latch key to draw out the inner rails from sliding rails.



3. Secure inner rails to both sides of the chassis. Be sure the mounting holes are correctly matched.



4. Secure the screws to both sides of the chassis.



2.2.3 Installing the Outer Rails to the Rack

1. Please note to prepare two nuts and two screws before you start the work.



2. Secure the outer rails to the rack.



2.2.4 Rack mounting the Server

1. Lift the chassis and then insert the inner slide rails into the outer rails.




2. Push the chassis in.



3. Screw the mounting ears of chassis to the rack.



4. Press the latch keys on both sides simultaneously to pull the system out.



NOTE


Chapter 3: Replacing Pre-Installed Components

3.1 Introduction

This chapter explains how to replace the pre-installed components, including the [S7109](#) Motherboard, [M1713F77C-FPB](#) Front Panel Board, [M1809F77A-FB](#) Fan Board, [M2215-L8-1F](#) Riser Card, [M1284F77D-BP12E-14](#) HDD Backplane Board, [M7109F77D-D-PBP](#) Power Backplane Board, [M7059F77C-D-PDB](#) Power Distribution Board, System Fan and Power Supply etc.

3.2 Disassembly Flowchart

The following flowchart outlines the disassembly procedure.



3.3 Removing the Cover

Follow Chapter **2.1.1** to remove the cover of FT77D-B7109.

3.4 Replacing the Power Supply

To replace the power supply follow these instructions.

1. Press the tab as shown to pull out the power.



2. Free the power from the power cage.



3. Replace a new single power and reinsert it into the power cage following the above steps in reverse.

3.5 Replacing the Front Panel Board

Follow these instructions to replace the [M1713F77C-FPB](#) Front Panel Board.


1. Disconnect the USB3.0 and Front Panel Cable.



2. Unscrew to remove the front panel board module.




3. Loosen three screws to take out the front panel board. Remove the ID Button cap, LED sponge and LED Lens to reinstall in the new Front Panel Board.



4. Follow the steps described earlier in reverse order to reinstall the front panel board module.

3.5.1 Front Panel Board Features



M1713F77C-FPB Front Panel Board	
Specifications	● SSI 24-pin front panel I/O connector to MB ● (1) 20-pin front panel USB3.0 connector to MB ● BTN: PWR BTN w/LED, Reset BTN, ID BTN, NMI BTN ● LED: PWR LED (green), Warning LED (amber), ID LED (blue), HDD LED (green), LAN active LED (green) ● I/O: (2) Type-A USB3.0 Connector ● Temperature sensor inlet build-in

3.6 Replacing the Fan Board

Follow these instructions to replace the [M1809F77A-FB](#) Fan Board.

1. Remove all Fan modules.




2. Unscrew the fan cage.




3. Lift up the fan cage.




4. Disconnect all cables from the Fan Board.



5. Unscrew to replace with a new Fan Board. Follow the steps in reverse order to reinstall the Fan Board.



3.6.1 Fan Board Features



M1809F77A-FB Fan Board	
Specifications	Support (6) 120x38 mm system FAN (4) 4-pin B4P RA PWR Connector (run DC+12V) (6) 4-pin Hot-swap FAN Connector (1) 20-pin barebone system FAN connector to MB

FAN Sequence

Front Side (facing HDD)		
FAN4	FAN5	FAN6
FAN1	FAN2	FAN3

Rear Side (facing Mainboard)

3.7 Replacing the HDD Backplane Board

Follow these instructions to replace the [M1284F77D-BP12E-14](#) HDD Backplane Board.

1. Remove the screws on both sides of the chassis.



2. Remove all HDD trays from the HDD cage.



3. Refer to Section **3.5 Replacing the Front Panel Board** to take out the Front Panel Board Tray.



4. Unscrew the Front COM and VGA Ports.



5. Disconnect the COM and VGA cables.



6. Unscrew to release the HDD Cage.



7. Lift up the HDD cage from the chassis



8. Disconnect all cables connected to the HDD BP Board.


NVME SKU (R)




SATA SKU (R)



NVME & SATA SKU (L)




9. Unscrew the HDD BP Board from the chassis.



10. Take out the HDD BP Board to replace with a new one. Follow the procedures described earlier in reverse order to reinstall the HDD BP Board and HDD cage.

3.7.1 HDD BP Board Features



M1284F77D-BP12E-14 HDD Backplane Board	
Specifications	Support 14 hot-swappable 2.5" HDD/SSD or NVMe SSD, speed up to 12Gb/s Onboard HDD LED indication for HDD status (Active/Status) (3) B4P HDD PWR Connector (2) 7-pin SATA Connector (3) Mini-SAS HD Connector (2) SFF-8611 OCUlink connectors


HDD/SSD sequence

Port #	0	1	2	3	4	5	6	7	8	9	10	11	12	13
	sSATA4	sSATA5	sSATA0~3				SATA0~7							

3.8 Replacing Power Distribution Board

Follow these instructions to replace the **M7059F77C-D-PDB** Power Distribution Board.

1. Disconnect the PWR cable. Unscrew the **M7059F77C-D-PDB** Power Distribution Board.




2. Remove the power distribution board for replacement.



3. Follow the steps described earlier in reverse order to reinstall the power distribution board into the chassis.

3.8.1 Power Distribution Board Features



M7059F77C-D-PDB Power Distribution Board	
Specifications	(1) 24S+6P RA Connector to M7109F77D-D-PBP (1) ATX 8-pin PWR Connector to Fan Board (16) ATX 8-pin PWR Connector to GPU card

J3~J18: 2x4pin ATX Power Connector for GPU, the max current is 35A

Signal	Pin	Pin	Signal
GND	1	5	+12V
GND	2	6	+12V
GND	3	7	+12V
GND	4	8	+12V

3.9 Replacing the Riser Card

Follow these instructions to replace the [M2215-L8-1F](#) Riser Card.

1. Pull out all power supply units and unscrew the Mezz card module. Unscrew the power supply cage.



2. Unscrew the power supply cage.



3. Lift up the power supply cage.



4. Loosen the screws to lift up the bracket.



5. Unscrew to replace a new riser card.



6. Follow the steps described earlier in reverse order to reinstall the riser card bracket.

3.9.1 Riser card Feature



M2215-L8-1F Riser Card	
Form Factor	W31.85 x L94 (mm), 4-layer PCB
Specification	(1) PCI-E Gen3 x8 Slot for non-standard add-on card


3.10 Replace the Power Backplane Board

Follow these instructions to replace the **M7109F77D-D-PBP** Power Backplane Board.

1. Unscrew the Power Backplane Board Tray.



2. Lift up the PBP Board Tray.




3. Unscrew the M7109F77D-D-PBP from the bracket and replace with a new one.




4. Follow the steps described earlier in reverse order to reinstall the power backplane board.

3.10.1 Power Backplane Board Features

Front View



Rear View




M7109F77D-D-PBP Power Backplane Board	
Specifications	(3) Power supply Connector for DPS-1600CB A (1) 24S+6P RA Connector to MB (1) 24S+6P Connector to M7059F77C-D-PDB (1) ATX 8-pin PWR Connector


3.11 Replacing the Motherboard

After removing all of the aforementioned cables and components, follow these instructions to remove the motherboard from the chassis.

1. Loosen the screws securing the PDB Bracket to the chassis.



2. Unscrew the OCP Riser Card Bracket.




3. Refer to Section **3.9 Replacing the Riser Card** and **3.10 Replacing the Power Backplane Board** to remove the Power Supply Cage and the PBP Tray.


4. (SATA SKU) Disconnect all cables.



5. (NVME SKU) Disconnect all cables.



6. Unscrew the motherboard to lift it up for replacement.



NOTE

Chapter 4: Motherboard Information

You are now ready to install your motherboard.

How to install our products right... the first time

The first thing you should do is read this user's manual. It contains important information that will make configuration and setup much easier. Here are some precautions you should take when installing your motherboard:

- (1) Ground yourself properly before removing your motherboard from the antistatic bag. Unplug the power from your computer power supply and then touch a safely grounded object to release static charge (i.e. power supply case). For the safest conditions, MITAC recommends wearing a static safety wrist strap.
- (2) Hold the motherboard by its edges and do not touch the bottom of the board, or flex the board in any way.
- (3) Avoid touching the motherboard components, IC chips, connectors, memory modules, and leads.
- (4) Place the motherboard on a grounded antistatic surface or on the antistatic bag that the board was shipped in.
- (5) Inspect the board for damage.


The following pages include details on how to install your motherboard into your chassis, as well as installing the processor, memory, disk drives and cables.



Caution!

1. To avoid damaging the motherboard and associated components, use torque force within the range **5~7 kgf/cm (4.35 ~ 6.09 lb/in)** on each mounting screw for motherboard installation.
2. Do not apply power to the board if it has been damaged.

4.1 Board Image




S7109


This picture is representative of the latest board revision available at the time of publishing. The board you receive may not look exactly like the above picture.

4.2


Block Diagram



4.3 Motherboard Mechanical Drawing



4.4 Board Parts, Jumpers and Connectors



This diagram is representative of the latest board revision available at the time of publishing. The board you receive may not look exactly like the above diagram. The DIMM slot numbers shown above can be used as a reference when reviewing the DIMM population guidelines shown later in the manual. For the latest board revision, please visit our web site at <http://www.tyan.com>.

Jumpers & Connectors

Connectors	
1. ID LED Button / ID LED (IDLED_BTN1)	22. 4-pin HDD Backplane Power Connector (D4P_PW3)
2. RJ45 LAN Port (LAN3) (IPMI)	23. CPU1 PWR OK LED (P1_PG_LED1)
3. RJ45 LAN Port (LAN2)	24. 4-pin Fan Connector (CPU1_FAN)
4. RJ45 LAN Port (LAN1)	25. CPU0 PWR OK LED (P0_PG_LED1)
5. BMC Heartbeat LED (BMC_LED1)	26. 4-pin Fan Connector (CPU0_FAN)
6. BIOS Socket (BIOS_SOCKET1)	27. 7-pin Vertical SATA3.0 Connector (SATA) (PCH_SSATA_5)
7. TYAN Module Header (DBG_HD1)	28. 7-pin Vertical SATA3.0 Connector (SATA) (PCH_SSATA_4)
8. Reset Button (RST_BTN1)	29. 4-pin HDD Backplane Power Connector (D4P_PW1)
9. Power Button (PWR_BTN1)	30. PSU12V Power Connector (J45)
10. Platform RESET OK LED (SYS_RST_LED1)	31. PCH AUX PWR OK LED (PCH_PWOK_LED1)
11. ATX PWR OK LED (ATX_PG_LED1)	32. Onboard HDD Active LED (HDD_LED1)
12. FAN Header for BP FAN Board (J29)	33. AST2500 (BMC1)
13. Vertical Type-A USB3.0 Connector (USB1)	34. Onboard BMC IPMI alert LED (IPMI_LED1)
14. IPMB Pin Header (IPMB_HD1)	35. BMC Socket (BMC_SOCKET1)
15. PCH sSATA SGPIO Header for HDD Backplane (SSATA_SGPIO1)	36. CPU Error LED (ERR_LED1)
16. Battery Socket (CR1)	37. CATERR LED (CAT_LED1)
17. VGA Header (FPIO_VGA1)	38. USB3.0 Header (USB3)
18. Front Panel Header (FPIO_1)	39. Mini SAS HD Connector (SATA/SAS signals) (PCH_SSATA_03)
19. COM1 Header (COM1)	40. Mini SAS HD Connector (SATA/SAS signals) (PCH_SSATA_47)
20. Intel VROC Key Header (J47)	41. Mini SAS HD Connector (SATA/SAS signals) (PCH_SSATA_03)
21. 4-pin HDD Backplane Power Connector (D4P_PW2)	
Jumpers	
a ME Recovery Mode Jumper (J38)	d/e LPC Mode Header (J37/J41)
b/c BMC CONSOLE PORT5 Jumper (J34/J36)	f Clear CMOS Header (J44)

Slots	
A PCI-E 3.0x16 slot (J3)	B/C/D/E/F/G/H/I PCI-E3.0x16 slot (x16 link:S7109GM2NR-2T) (x8 link:S7109GM2NR-8X-2T) (J8/J9/J10/J11/J12/J13/J14/J15)
R PCI-E 3.0x8 slot (open-end type, J25)	J/K/L/M/N/O/P/Q PCI-E 3.0x8 slot (x8 link, open-end type, only for S7109GM2NR-8X-2T) (J16/J17/J18/J19/J20/J21/J22/J23)
S PCI-E 3.0x8 slot (open-end type) (J48, only for Tyan riser card)	

Jumper Legend

	OPEN - Jumper OFF	Without jumper cover
	CLOSED - Jumper ON	With jumper cover

J41/J43/J73/J74/J75/J76: 4-Pin FAN Connector

	Pin	1	2	3	4
	Signal	GND	VCC	Tachometer	PWM
	Use this header to connect the cooling fan to your motherboard to keep the system stable and reliable. J41: CPU0_FAN J43: CPU1_FAN J73: SYS_FAN_4 J74: SYS_FAN_3 J75: SYS_FAN_2 J76: SYS_FAN_1				

J5: IDLED Switch Header

 PIN1	Pin	1	2
	Signal	FP IDLED Switch	FP IDLED Switch (GND)


J38: Chassis Intrusion Header

 PIN1 open	Pin	1	2
	Signal	Intrusion Switch	Intrusion Switch (GND)
 PIN1 Short (Default)	Open: Use this header to trigger the system chassis intrusion alarm. Short: Use this header to disable the system chassis intrusion alarm.		

J60: Front Panel Header

Signal	Pin	Pin	Signal
PWRLED+	1	2	FP Power(3.3V standby)
KEY	3	4	ID_LED+
PWRLED-(GND)	5	6	ID_LED-(GND)
HD_LED+	7	8	Fault LED1-
HD_LED-	9	10	Fault LED2-
Power Switch+	11	12	LAN1_ACTIVE_LED+
Power Switch-(GND)	13	14	LAN1_ACTIVE_LED-
Reset Switch+	15	16	SMB_DATA
Reset Switch-(GND)	17	18	SMB_CLK
ID Switch+	19	20	INTRUDER#
TEMP Sensor	21	22	LAN2_ACTIVE_LED+
NMI Switch#	23	24	LAN2_ACTIVE_LED -

J39: USB Front Panel Header (blue)

	Signal	Pin	Pin	Signal
	USB 5V Power	1	2	USB 5V Power
	USB Data-	3	4	USB Data-
	USB Data+	5	6	USB Data+
	GND	7	8	GND
	KEY	9	10	NC



J35: Front Fan Connector (Reserved for Barebone Fan Board)

	Signal	Pin	Pin	Signal
	Tachometer input1	1	2	Tachometer input6
	Tachometer input2	3	4	Tachometer input7
	Tachometer input3	5	6	Tachometer input8
	Tachometer input4	7	8	Tachometer input9
	Tachometer input5	9	10	Tachometer input10
	GND	11	12	KEY
	PWM output2	13	14	PWM output1
	Tachometer input11	15	16	SMB DATA
	Tachometer input12	17	18	SMB CLK
	3.3V Standby	19	20	PWM output3

J31: IPMB Connector

	Signal	Pin	Pin	Signal
	SMB_SDA2	1	2	GND
	SMB_SCL2	3	4	NC

JP5: Clear CMOS Jumper

 PIN1 Normal (Default)	You can reset the CMOS settings by using this jumper. This can be useful if you have forgotten your system/setup password, or need to clear the system BIOS setting.
 PIN1 Clear CMOS	1. Power off system and disconnect power connectors from the motherboard. 2. Remove the jumper from Pin_1 and Pin_2 (Default setting). 3. Move the jumper cap to close Pin_2 and Pin_3 for several seconds to Clear CMOS. 4. Put jumper cap back to Pin_1 and Pin_2 (Default setting). 5. Reconnect power connectors to the motherboard and power on system.


LED1 / SW1: ID LED and ID LED Button

	Pin	Signal	
	+	P3V3_AUX	
	-	ID_SW_L	
	State	Color	Description
	On	Blue	System identified
	Off	Off	System not identified
NOTE: The ID LED can be activated remotely using IPMI. Please visit the TYAN Web Site at http://www.tyan.com to download the latest IPMI Configuration Guide for more details.			

J58/J59: Vertical Type-A USB Connector

	Pin	1	2	3	4
	Signal	USB 5V Power	USB Data-	USB Data+	GND

J56/J57: SATA2.0 Connector

	1	GND	Connects to the Serial ATA ready drives via the Serial ATA cable. J56: SATA4 J57: SATA5
	2	SATA TX DP	
	3	SATA TX DN	
	4	GND	
	5	SATA RX DN	
	6	SATA RX DP	
	7	GND	

J26: SATA SGPIO Header for BB HD Board

	Signal	Pin	Pin	Signal
	3.3V Standby	1	2	SMB SCL
	GND	3	4	SMB SDA
	KEY	5	6	BP HDD FAULT

J18: Flash Security Override Header

	Pin	1	2
	Signal	Signal Input	GND

PW1: 4-pin HDD Power Connector

	Pin	1	2	3	4
	Signal	+12V	GND	GND	+5V


JP6: BIOS Recovery Mode Jumper

	Pin 1-2 Closed: Normal (Default)
	Pin 2-3 Closed: Recovery CMOS

JP7: ME Firmware Update Jumper


	Pin 1-2 Closed: Open (Default)
	Pin 2-3 Closed: ME Force Update

4.5 Thermal Interface Material



There are two types of thermal interface materials designed for use with the processors.

The most common material comes as a small pad attached to the heat sink at the time of purchase. There should be a protective cover over the material. Take care not to touch this material. Simply remove the protective cover and place the heat sink on the processor.




The second type of interface material is usually packaged separately. It is commonly referred to as 'thermal compound'. Simply apply a thin layer on to the CPU lid (applying too much will actually reduce the cooling).

NOTE: Always check with the manufacturer of the heat sink & processor to ensure that the thermal interface material is compatible with the processor and meets the manufacturer's warranty requirements.

4.6 Tips on Installing Motherboard in Chassis

Before installing your motherboard, make sure your chassis has the necessary motherboard support studs installed. These studs are usually metal and are gold in color. Usually, the chassis manufacturer will pre-install the support studs. If you are unsure of stud placement, simply lay the motherboard inside the chassis and align the screw holes of the motherboard to the studs inside the case. If there are any studs missing, you will know right away since the motherboard will not be able to be securely installed.










NOTE: Be especially careful to look for extra stand-offs. If there are any stand-offs present that are not aligned with a mounting hole on the motherboard, it will likely short components on the back of the motherboard when installed. This will cause malfunction and/or damage to your motherboard.

Some chassis include plastic studs instead of metal. Although the plastic studs are usable, MITAC recommends using metal studs with screws that will fasten the motherboard more securely in place.

Below is a chart detailing what the most common motherboard studs look like and how they should be installed.

Mounting the Motherboard

Type	Solutions for installing	
		
		
		

4.7 Installing the Memory

Before installing memory, ensure that the memory you have is compatible with the motherboard and processor. Check the TYAN Web site at <http://www.tyan.com> for details of the type of memory recommended for your motherboard.


- This platform supports (12)+(12) DDR4 RDIMM/RDIMM 3DS/LRDIMM/LRDIMM3DS 2666
- Up to 768GB RDIMM/ 1,536GB LRDIMM/ 3,072GB RDIMM 3DS/LRDIMM 3DS are supported
- 1.2V DDR4 DIMMs are supported
- All installed memory will automatically be detected. No jumpers or settings need to be changed for memory detection.
- All memory must be of the same type and density. **Different memory types can NOT be mixed and matched on the same motherboard.**

Recommended Memory Population Table

Single CPU Installed (CPU0 only)	Quantity of memory installed											
	1	2	3	4	5	6	7	8	9	10	11	12
CPU0_DIMM_A0	√	√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_A1							√	√	√	√	√	√
CPU0_DIMM_B0		√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_B1								√	√	√	√	√
CPU0_DIMM_C0			√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_C1									√	√	√	√
CPU0_DIMM_D0				√	√	√	√	√	√	√	√	√
CPU0_DIMM_D1										√	√	√
CPU0_DIMM_E0					√	√	√	√	√	√	√	√
CPU0_DIMM_E1											√	√
CPU0_DIMM_F0						√	√	√	√	√	√	√
CPU0_DIMM_F1												√
CPU1_DIMM_A0												
CPU1_DIMM_A1												
CPU1_DIMM_B0												
CPU1_DIMM_B1												
CPU1_DIMM_C0												
CPU1_DIMM_C1												
CPU1_DIMM_D0												
CPU1_DIMM_D1												
CPU1_DIMM_E0												
CPU1_DIMM_E1												
CPU1_DIMM_F0												
CPU1_DIMM_F1												

NOTE:

1. ✓ indicates a populated DIMM slot.
2. Use paired memory installation for max performance.
3. Populate the same DIMM type in each channel, specifically
 - Use the same DIMM size
 - Use the same # of ranks per DIMM
4. Dual-rank DIMMs are recommended over single-rank DIMMs.
5. Un-buffered DIMM can offer slightly better performance than registered DIMM if populating only a single DIMM per channel.
6. Always install with CPU0 Socket and DIMM_0 Slot first, following the alphabetical order.




Dual CPU Installed (CPU0 and CPU1)	Quantity of memory installed											
	2	4	6	8	10	12	14	16	18	20	22	24
CPU0_DIMM_A0	√	√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_A1							√	√	√	√	√	√
CPU0_DIMM_B0		√	√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_B1								√	√	√	√	√
CPU0_DIMM_C0			√	√	√	√	√	√	√	√	√	√
CPU0_DIMM_C1									√	√	√	√
CPU0_DIMM_D0				√	√	√	√	√	√	√	√	√
CPU0_DIMM_D1										√	√	√
CPU0_DIMM_E0					√	√	√	√	√	√	√	√
CPU0_DIMM_E1											√	√
CPU0_DIMM_F0						√	√	√	√	√	√	√
CPU0_DIMM_F1												√
CPU1_DIMM_A0	√	√	√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_A1							√	√	√	√	√	√
CPU1_DIMM_B0		√	√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_B1								√	√	√	√	√
CPU1_DIMM_C0			√	√	√	√	√	√	√	√	√	√
CPU1_DIMM_C1									√	√	√	√
CPU1_DIMM_D0				√	√	√	√	√	√	√	√	√
CPU1_DIMM_D1										√	√	√
CPU1_DIMM_E0					√	√	√	√	√	√	√	√
CPU1_DIMM_E1											√	√
CPU1_DIMM_F0						√	√	√	√	√	√	√
CPU1_DIMM_F1												√

NOTE:

1. ✓ indicates a populated DIMM slot.
2. Use paired memory installation for max performance.
3. Populate the same DIMM type in each channel, specifically
 - Use the same DIMM size
 - Use the same # of ranks per DIMM
4. Dual-rank DIMMs are recommended over single-rank DIMMs.
5. Un-buffered DIMM can offer slightly better performance than registered DIMM if populating only a single DIMM per channel.
6. Always install with CPU0 Socket and DIMM_0 Slot first, following the alphabetical order.

4.8 Mainboard LED Definition



BMC_LED1	BMC Heart Beat LED	Pin	Signal	
		+	+3V_AUX	
		-	GND	
		State	Description	
		OFF	OFF	The LED shuts off when the BMC controller cannot be detected or properly initiated.
PCH_PWOK_LED1	PCH PWOK LED	Blinking	Green	The LED blinks per second to indicate that the BMC controller is working normally
		Pin	Signal	
		+	+3V_AUX	
		-	GND	
		State	Description	
CAT_LED1	CAT Error LED	OFF	OFF	The LED shuts off when the power of PCH is abnormal.
		ON	Amber	The amber LED lights up when the power of PCH is normal.
		Pin	Signal	
		+	+3V	
		-	GND	
IDLED_BTN1	Rear ID LED	State	Description	
		OFF	OFF	The LED shuts off when System is running normally.
		ON	Red	The LED lighted up when the system has experienced a fatal or catastrophic error and can not continue to operate.
		Pin	Signal	
		+	+ 3V_AUX	
P0_PG_LED1	CPU0 PWOK LED	-	GND	
		State	Description	
		OFF	OFF	OFF
		ON	Green	ON
		Pin	Signal	
		+	+3V	
		-	GND	
		State	Description	
		OFF	OFF	The LED shuts off when the power of CPU0 is abnormal.
		ON	Green	The LED lights up when the power of CPU0 is normally.

P1_PG_LED1	CPU1 PWOK LED	Pin	Signal	
		+	+ 3V	
		-	GND	
		State	Description	
		OFF	OFF	The LED shuts off when the power of CPU1 is abnormal.
ATX_PG_LED1	PSU PWROK LED	ON	Green	The LED lights up when the power of CPU1 is normally.
		Pin	Signal	
		+	+ 3V	
		-	GND	
		State	Description	
		OFF	OFF	The LED shuts off when the PSU is normal.
		ON	Green	The LED lights up when the PSU is abnormally.

4.9 Finishing Up

Congratulations on making it this far! You have finished setting up the hardware aspect of your computer. Before closing up your chassis, make sure that all cables and wires are connected properly, especially SATA cables and most importantly, jumpers. You may have difficulty powering on your system if the motherboard jumpers are not set correctly.

In the rare circumstance that you have experienced difficulty, you can find help by asking your vendor for assistance. If they are not available for assistance, please find setup information and documentation online at our website or by calling your vendor's support line.

Chapter 5: BIOS Setup

5.1 About the BIOS

The BIOS is the basic input/output system, the firmware on the motherboard that enables your hardware to interface with your software. The BIOS determines what a computer can do without accessing programs from a disk. The BIOS contains all the code required to control the keyboard, display screen, disk drives, serial communications, and a number of miscellaneous functions. This chapter describes the various BIOS settings that can be used to configure your system.

The BIOS section of this manual is subject to change without notice and is provided for reference purposes only. The settings and configurations of the BIOS are current at the time of print and are subject to change, and therefore may not match exactly what is displayed on screen.

This section describes the BIOS setup program. The setup program lets you modify basic configuration settings. The settings are then stored in a dedicated, battery-backed memory (called NVRAM) that retains the information even when the power is turned off.

To start the BIOS setup utility:

1. Turn on or reboot your system.
2. Press **** or **<F2>** during POST (**Del** on remote console) to start the BIOS setup utility.

5.1.1 Setup Basics

The table below shows how to navigate in the setup program using the keyboard.

Key	Function
Left/Right Arrow Keys	Change from one menu to the next
Up/Down Arrow Keys	Move between selections
Enter	Open highlighted section
PgUp/PgDn Keys	Change pages
+/-	Change options
ESC	Exit

5.1.2 Getting Help

Pressing [**F1**] will display a small help window that describes the appropriate keys to use and the possible selections for the highlighted item. To exit the Help Window, press [**ESC**] or the [**Enter**] key again.

5.1.3 In Case of Problems

If you have trouble booting your computer after making and saving the changes with the BIOS setup program, you can restart the computer by holding the power button down until the computer shuts off (usually within 4 seconds); resetting by pressing CTRL-ALT-DEL; or clearing the CMOS.

The best advice is to only alter settings that you thoroughly understand. In particular, do not change settings in the Chipset section unless you are absolutely sure of what you are doing. The Chipset defaults have been carefully chosen either by MITAC or your system manufacturer for best performance and reliability. Even a seemingly small change to the Chipset setup options may cause the system to become unstable or unusable.

5.1.4 Setup Variations

Not all systems have the same BIOS setup layout or options. While the basic look and function of the BIOS setup remains more or less the same for most systems, the appearance of your Setup screen may differ from the charts shown in this section. Each system design and chipset combination requires a custom configuration. In addition, the final appearance of the Setup program depends on the system designer. Your system designer may decide that certain items should not be available for user configuration, and remove them from the BIOS setup program.

NOTE: The following pages provide the details of BIOS menu. Please be noticed that the BIOS menu are continually changing due to the BIOS updating. The BIOS menu provided are the most updated ones when this manual is written. Please visit TYAN's website at <http://www.tyan.com> for the information of BIOS updating.

5.2 Main Menu

In this section, you can alter general features such as the date and time.

Note that the options listed below are for options that can directly be changed within the Main Setup screen.



BIOS Information

It displays BIOS related information.

Memory Information

This displays the total memory size.

System Language

Choose the system default language.

English

System Date

Set the Date. Use Tab to switch between Date elements. Default Ranges:

Year: 2005-2099

Months: 1-12


Days: dependent on month

System Time

Set the Time. Use Tab to switch between Time elements.

5.3 Advanced Menu

This section facilitates configuring advanced BIOS options for your system.



iSCSI Configuration

Configure the iSCSI parameters.

Intel® Virtual RAID on CPU

This formset allows the user to manage Intel® Virtual RAID on CPU.

Trusted Computing

Trusted Computing Settings.

ACPI Settings

System ACPI Parameters.

OnBoard Device Configuration

OnBoard Device and Function Configuration.

Hardware Health Configuration

Hardware Health Configuration.

PCIe Slot Configuration

Onboard PCIe Slot Configuration.

AST2500 Super IO Configuration

System Super IO Chip Parameters.

S5 RTC Wake Settings

Enable system to wake from S5 using RTC alarm.

Serial Port Console Redirection

Serial Port Console Redirection.

Option ROM Dispatch Policy

Option ROM Dispatch Policy.

PCI Subsystem Settings

PCI, PCI-X and PCI Express Settings.

Network Stack Configuration

Network Stack Settings.


CSM Configuration

CSM configuration: Enable/Disable, Option ROM execution settings, etc.

USB Configuration

USB Configuration Parameters.

5.3.1 iSCSI Configuration



Please follow the instructions to initiate the iSCSI function.

Step 1.

Select **Advanced** → **CSM Configuration** → **Network** → [UEFI].

Step 2.

Select **Advanced** → **Network Stack Configuration** → **Network Stack** → [Enabled]

Step 3.

Save changes and reboot.

iSCSI Initiator Name

The worldwide unique name of iSCSI Initiator. Only IQN format is accepted.

Enter [iqn.xxx]. xxx ranges from 4 to 223.

5.3.1.1 Add an Attempt



Read only.

NOTE: Only LAN1 supports iSCSI function.

5.3.1.1.1 MAC 34:12:78:56:00:00

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.

Advanced

iSCSI Attempt Name	1	The human name defined for this attempt. Maximum length is upto 96 characters
iSCSI Mode	[Disabled]	
Internet Protocol	[IP4]	
Connection Retry Count	0	
Connection Establishing Timeout	1000	
Configure ISID	560000	
Enable DHCP	[Disabled]	
Initiator IP Address	0.0.0.0	←+: Select Screen
Initiator Subnet Mask	0.0.0.0	↑↓: Select Item
Gateway	0.0.0.0	Enter: Select
		+/-: Change Opt.
Target Name		F1: General Help
Target IP Address	0.0.0.0	F2: Previous Values
Target Port	3260	F3: Optimized Defaults
Boot LUN	0	F4: Save & Exit
		ESC: Exit
Authentication Type	[None]	
Save Changes		

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

iSCSI Mode

Disabled, Enabled, Enabled for MPIO.

Disabled / Enabled / Enabled for MPIO

Internet Protocol

Initiator IP address is system assigned in IP6 mode. In Autoconfigure mode, iSCSI driver will attempt to connect iSCSI target via IPv4 stack, if failed then attempt IPv6 stack.

IP4 / IP6 / Autoconfigure

Connection Retry Count

The minimum value is 0 and the maximum is 16. 0 means no retry.

Connection Establishing Timeout

The timeout value in milliseconds. The minimum value is 100 milliseconds and the maximum is 20 seconds.

Configure ISID

OUI-format ISID in 6 bytes, default value is derived from MAC address. Only last 3 bytes are configurable. Example: update 0ABBCCDDEEFF to 0ABBCCF07901 by input F07901.

Enable DHCP

Enable DHCP.

Disabled / Enabled

Initiator IP Address

Enter IP address in dotted-decimal notation.

Initiator Subnet Mask

Enter IP address in dotted-decimal notation.

Gateway

Enter IP address in dotted-decimal notation.

Target Name

The worldwide unique name of the target. Only iqn. format is accepted.

iqn. xxx

Target IP Address

Enter IP address in dotted-decimal notation.

Target Port

Target Port.

Boot LUN

Hexadecimal representation of the LU number. Examples are:

4752-3A4F-6b7e-3F99, 6734-9-156f-127, 4186-9.

Authentication Type


Authentication method: CHAP, Kerberos, or None.

CHAP / **None**

Save Changes

Must reboot system manually for changes to take place.

5.3.1.2 Delete Attempts



Attempt 1

MAC: 34:12:78:56:00:00, PFA: Bus 1/ Dev 0 / Func 0, iSCSI mode: Disabled, IP version: IP4.

Disabled / Enabled


Commit Changes and Exit

Commit Changes and Exit.

Discard Changes and Exit

Discard Changes and Exit.

5.3.1.3 Change Attempt Order



Change Attempt Order

Change the order of Attempts using +/- keys. Use arrow keys to select the attempt then press +/- to move the attempt up/down in the attempt order list.

Attempt 1 / Attempt #


Commit Changes and Exit

Commit Changes and Exit.

Discard Changes and Exit

Discard Changes and Exit.

5.3.2 Intel® Virtual RAID on CPU



Please follow the instructions to initiate the Intel Virtual RAID on CPU function.

Step 1.

Select **Socket Configuration** → **I/O Configuration** → **Intel® VMD technology** → **Intel® VMD for Volume Management Device on Socket 0** (for CPU0) / **Socket 1** (for CPU1) → **Intel® VMD for Volume Management Device for PStack0** (Slot 1~4) / **PStack1** (Slot 5~8) / **PStack2** (Slot 9~12)

Step 2.

Suppose the card is installed in CPU0 Slot 3, then **Intel® VMD for Volume Management Device for PStack0** will be set to [Enabled].


Step 3.

Save changes and reboot.

All Intel VMD Controllers

Select to see more information about the Intel VMD Controllers.

5.3.2.1 All Intel VMD Controllers



Create RAID Volume

This page allows you to create a RAID volume.

Non-RAID Physical Disks

Read only.

5.3.2.1.1 Create RAID Volume

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Advanced	
Create RAID Volume Name: Volume0 RAID Level: [RAID0(Stripe)] Enable RAID spanned over VMD Contr [] Select Disks: Port 0, VMD3, INTEL SSDPEDMD400G4 [] Port 1, VMD4, INTEL SSDPE2MD400G4 [] Strip Size: [128KB] Capacity (MB): 0 ► Create Volume Select at least two disks	Enter a unique volume name that has no special characters and is 16 characters or less. ↔: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

Name

Enter a unique volume name that has no special characters and is 16 characters or less.

Volume0

RAID Level

Select RAID Level.

RAID0 (Stripe)

Enable RAID spanned over VMD Controllers

Enter RAID spanned over VMD Controllers.

blank / X

Port 0, VMD0, INTEL SSDPE2MD400G4

X – to Select Disk.

blank / X

Port 1, VMD1, INTEL SSDPEDME400G4

X – to Select Disk.

blank / X

Strip Size

Strip size help.

4KB / 8KB / 16KB / 32KB / 64KB / **128KB**

Capacity (MB)

Capacity in MB. Enter desired volume size. Maximum size=763099.

Create Volume


Create a volume with the settings specified above.

NOTE: For **Create Volume** to be configurable, the following items **Enable RAID spanned over VMD Controllers, Port 0, VMD0, INTEL SSDPE2MD400G4** and **Port 1, VMD1, INTEL SSDPEDME400G4** must be set to [X].

5.3.2.1.1.1 Create Volume

```
You have selected NVMe drives that are connected to multiple VMD controllers.  
Please note that if you continue and create a RAID volume  
with drives from multiple VMD controllers  
that RAID volume will not be bootable in a Windows OS environment.  
Press 'y' to create, 'n' to discard.
```


Press 'y' to create, 'n' to discard.



Volume0, RAID0(Stripe), 708.0GB, Normal


Select to see more information about the RAID volume.

5.3.2.1.1.1.1 Volume0, RAID0(Stripe), 708.0GB, Normal



Read only.

5.3.2.1.1.1.1 Delete




Delete the RAID Volume

Deleting a volume will reset the disks to non-RAID.

Yes / No

5.3.2.1.2 Port 0, VMD0, INTEL SSDPE2MD400G4 SN: xxxx, ...

Port 1, VMD1, INTEL SSDPEDMD400G4 SN: xxxx,



Read only.

5.3.3 Trusted Computing




Security Device Support

Enables or Disables BIOS support for security device. O.S. will not show Security Device. TCG EFI protocol and INT1A interface will not be available.

Enabled / Disabled

5.3.4 ACPI Settings



Enable ACPI Auto Configuration

Enable or disable BIOS ACPI Auto Configuration.


Disabled / Enabled

Enable Hibernation

Enable or disable System ability to Hibernate (OS/S4 Sleep State). This option may not be effective with some OS.

Disabled / **Enabled**

5.3.5 OnBoard Device Configuration



Onboard VGA

Enable/Disable SPEED VGA.
Disabled / **Enabled**

ICC Clock Spread Spectrum

Turn on/off Spread Spectrum Setting of IsCLK.
Disabled / **Enabled**

Onboard Lan X550

Enable/Disable onboard Lan X550.
Disabled / **Enabled**


Chassis Intrusion detect

ENABLED: when a chassis open event is detected, the BIOS will record the event.
Disabled / Enabled

NMI Button

Enable or Disable NMI button.
Disabled / Enabled

5.3.6 Hardware Health Configuration



Auto Fan Control

Auto Fan Control Help.
Disabled / **Enabled**

BMC Alert Beep



Enable/Disable BMC Alert Beep.
On / Off

PMBus Support

PMBus Support.
Enabled / Disabled

5.3.6.1 Sensor Data Register Monitoring

When you enter the **Sensor Data Register Monitoring** submenu, you will see the following dialog window pop out. Please wait 8~10 seconds.



NOTE: SDR can not be modified. Read only.


5.3.7 PCIe Slot Configuration



PCIe Slot J3

Selects PCIe port Bifurcation for selected slot(s).
x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16**

5.3.8 AST2500 Super IO Configuration



Super IO Chip

Read only.

5.3.8.1 Serial Port 1 Configuration

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Advanced	
Serial Port 1 Configuration	Enable or Disable Serial Port (COM)
Serial Port [Enabled]	
Device Settings IO=3F8h; IRQ=4;	
Change Settings [Auto]	
 +/: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	
Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.	

Serial Port

Enable or disable Serial Port (COM).

Enabled / Disabled

Device Settings


Read only.

Change Settings

Select an optimal setting for Super IO Device.

Auto / IO=3F8h; IRQ=4;
/ IO=3F8h, IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;
/ IO=2F8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;
/ IO=3E8h, IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;
/ IO=2E8h, IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;

5.3.9 S5 RTC Wake Settings



Wake system from S5

Enable or disable System wake on alarm event. Select Fixed Time, system will wake on the hr:min:sec specified. Select Dynamic Time, system will wake on the current time + increase minute(s).

Disabled / Fixed Time / Dynamic Time

When Wake system from S5 is set to **[Fixed Time]**

Wake up hour

Select 0-23. For example enter 3 for 3am and 15 for 3pm.

Wake up minute

Select 0-59 for Minute.

Wake up second


Select 0-59 for Second.

When Wake system from S5 is set to **[Dynamic Time]**

Wake up Minute increase

1-5.

5.3.10 Serial Port Console Redirection



COM1 / Serial Port for Out-Of-Band Management/Windows Emergency Services (EMS)

Console Redirection

Console redirection enable or disable.

Disabled / **Enabled**

COM1 / Serial Port for Out-Of-Band Management/Windows Emergency Services (EMS)

Console Redirection Settings

The settings specify how the host computer (which the user is using) will exchange data. Both computers should have the same or compatible settings.

Legacy Console Redirection Settings

Legacy Console redirection settings.

5.3.10.1 Console Redirection Settings

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Advanced	
COM1 Console Redirection Settings	
Terminal Type	[VT100+]
Bits per second	[115200]
Data Bits	[8]
Parity	[None]
Stop Bits	[1]
Flow Control	[None]
VT-UTF8 Combo Key Support	[Enabled]
Recorder Mode	[Disabled]
Resolution 100x31	[Disabled]
Legacy OS Redirection Resolution	[80x24]
Putty KeyPad	[VT100]
Redirection After BIOS POST	[Always Enable]
Emulation: ANSI: Extended ASCII char set. VT100: ASCII char set. VT100+: Extends VT100 to support color, function keys, etc. VT-UTF8: Uses UTF8 encoding to map Unicode chars onto 1 or more bytes.	
↔: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

Terminal Type

Emulation: ANSI: Extended ASCII char set. VT100: ASCII char set.

VT100+: Extends VT100 to support color, function keys, etc.

VT-UTF8: Uses UTF8 encoding to map Unicode chars onto 1 or more bytes.

VT100+ / VT100 / VT-UTF8 / ANSI

Bits per Second

Select serial port transmission speed. The speed must be matched on the other side. Long or noisy lines may require lower speeds.

38400 / 9600 / 19200 / 57600 / **115200**

Data Bits

8 / 7

Parity

A parity bit can be sent with the data bits to detect some transmission errors. Even: parity bit is 0 if the num of 1's in the data bits is even. Odd: parity bit is 0 if the num of 1's in the data bits is odd. Mark: parity bit is always 1. Space: parity bit is always 0. Mark and Space parity do not allow for error detection.

None / Even / Odd / Mark / Space

Stop Bits

Stop bits indicate the end of a serial data packet. (A start bit indicates the beginning). The standard setting is 1 stop bit. Communication with slow devices may require more than 1 stop bit.

1 / 2

Flow Control

Flow Control can prevent data loss from buffer overflow. When sending data, if the receiving buffers are full, a 'stop' signal can be sent to stop the data flow. Once the buffers are empty, a 'start' signal can be sent to restart the flow. Hardware flow control uses two wires to send start/stop signal.

None / Hardware RTS/CTS

VT-UTF8 Combo Key Support

Enable VT-UTF8 Combination Key Support for ANSI/VT100 terminals.

Enabled / Disabled

Recorder Mode

On this mode enabled only text will be sent. This is to capture Terminal data.

Disabled / Enabled

Resolution 100x31

Enable or disable extended terminal resolution.

Disabled / Enabled

Legacy OS Redirection Resolution

On Legacy OS, the number of rows and columns supported redirection.

80x24 / 80x25

Putty KeyPad

Select FunctionKey and KeyPad on Putty.

VT100 / LINUX / XTERMR6 / SCO / ESCN / VT400

Redirection after BIOS POST

The settings specify if BootLoader is selected than Legacy console redirection is disabled before booting to Legacy OS. Default value is Always Enable which means Legacy Console Redirection is enabled for Legacy OS.

Always Enable / BootLoader

5.3.10.2 Legacy Console Redirection Settings




Legacy Serial Redirection Port

Select a COM port to display redirection of Legacy OS and Legacy OPRM Messages.

COM1

5.3.10.3 Serial Port for Out-Of-Band Management/Windows Emergency Services (EMS) Console Redirection Settings



Out-of-Band Mgmt Port

Microsoft Windows Emergency Management Services (EMS) allows for remote management of a Windows Server OS through a serial port.

COM1

Terminal Type

VT-UTF8 is the preferred terminal type for out-of-band management. The next best choice is VT100+ and then VT100. See above, in Console Redirection Settings page, for more Help with Terminal Type/Emulation.

VT-UTF8 / VT100 / VT100+ / ANSI

Bits per Second

Select serial port transmission speed. The speed must be matched on the other side. Long or noisy lines may require lower speeds.

115200 / 9600 / 19200 / 57600

Flow Control


Flow Control can prevent data loss from buffer overflow. When sending data, if the receiving buffers are full, a 'stop' signal can be sent to stop the data flow. Once the buffers are empty, a 'start' signal can be sent to restart the flow. Hardware flow control uses two wires to send start/stop signal.

None / Hardware RTS/CTS / Software Xon/Xoff

Data Bits / Parity / Stop Bits

Read only.

5.3.11 Option ROM Dispatch Policy



OnBoard LAN1 (X550)

Onboard Device has:

UEFI [X]

Legacy [X]

Emabed ROM(s).

VIDx8086; DIDx1563

@ s0/Bx1/Dx0/Fx0.

Enabled / **Disabled**

OnBoard LAN2 (X550)

Onboard Device has:

UEFI [X]

Legacy [X]

Emabed ROM(s).

VIDx8086; DIDx1563

@ s0/Bx1/Dx0/Fx1.

Enabled / **Disabled**

Lan MEZZ Card Empty

Enable or Disable Option ROM execution for selected Slot.

Disabled / **Enabled**

Storage Card Empty

Enable or Disable Option ROM execution for selected Slot.


Disabled / **Enabled**

Slot J3 Empty

Enable or Disable Option ROM execution for selected Slot.

Disabled / **Enabled**

5.3.12 PCI Subsystem Settings



Above 4G Decoding

Enables or Disables 64bit capable Devices to be Decoded in Above 4G Address Space (Only if System Supports 64 bit PCI Decoding).


Enabled / Disabled

SR-IOV Support

If system has SR-IOV capable PCIe Devices, this option Enables or Disables Single Root IO Virtualization Support.

Enabled / Disabled

5.3.13 Network Stack Configuration



NOTE: The BIOS will automatically read the onboard LAN controller.

Network Stack

Enable/Disable UEFI Network Stack.

Enabled / **Disabled**

When Network Stack is set to **[Enabled]**

Ipv4 PXE Support

Enable Ipv4 PXE Boot Support. If disabled IPV\$ PXE boot option will not be created.

Disabled / Enabled

Ipv4 HTTP Support

Enable Ipv4 HTTP Boot Support. If disabled IPV4 HTTP boot option will not be created.

Disabled / Enabled

Ipv6 PXE Support

Enable Ipv6 PXE Boot Support. If disabled IPV6 PXE boot option will not be created.

Disabled / Enabled

Ipv6 HTTP Support

Enable Ipv6 HTTP Boot Support. If disabled IPV6 HTTP boot option will not be created.

Disabled / Enabled

PXE boot wait time

Wait time to press ESC key to abort the PXE boot.


0

Media detect count

Number of times presence of media will be checked.

1

5.3.14 CSM Configuration



CSM Support

Enable/Disable CSM Support.

Enabled / Disabled

Option ROM Messages

Set display mode for Option ROM.

Force BIOS / Keep Current

Network

Controls the execution of UEFI and Legacy PXE OpROM.

Legacy / Do not launch / UEFI

Storage

Controls the execution of UEFI and Legacy Storage OpROM.

Legacy / Do not launch / UEFI

Video

Controls the execution of UEFI and Legacy Video OpROM


Legacy / Do not launch / UEFI

Other PCI Devices

Determines OpROM execution policy for devices other than Network, Storage, or Video.

Legacy / Do not launch / UEFI

5.3.15 USB Configuration



USB Controllers / USB Devices

Read only.

Legacy USB Support

Enable USB legacy support. AUTO option disables legacy support if no USB devices are connected. DISABLE option will keep USB devices available only for EFI applications.

Enabled / Disabled / Auto

XHCI Hand-off

This is a workaround for OSeS without XHCI hand-off support. The XHCI ownership change should be claimed by XHCI driver.

Enabled / Disabled

USB Mass Storage Driver Support

Enable/Disable USB Mass Storage Driver Support.

Enabled / Disabled

Port 60/64 Emulation

Enables I/O Port 60h/64h emulation support. This should be enabled for the complete USB keyboard legacy support for non-USB aware OSes.

Enabled / Disabled

USB transfer time-out

The time-out value for Control, Bulk and Interrupt transfers.

1 sec / 5 sec / 10 sec / **20 sec**

Device reset time-out

USB mass storage device Start Unit command time-out.


10 sec / **20 sec** / 30 sec / 40 sec

Device power-up delay

Maximum time the device will take before it properly reports itself to the Host Controller. 'AUTO' uses default value: for a Root port it is 100 ms, for a Hub port the delay is taken from Hub descriptor.

Auto / Manual

5.4 Platform Configuration




PCH Configuration

Displays and provides option to change the PCH Settings.

Server ME Configuration

Configure Server ME Technology Parameters.

5.4.1 PCH Configuration



PCH Devices

Enable/Disable Intel® IO Controller Hub devices.

PCI Express Configuration

PCI Express Configuration settings.

PCH SATA Configuration

SATA devices and settings.

PCH sSATA Configuration

sSATA devices and settings.

USB Configuration

USB Configuration Settings.

PCH DFX Configuration

PCH DFX Configuration Options.

5.4.1.1 PCH Devices




PCH state after G3

Select S0/S5 for ACPI state after a G3.

Power On / Power Off / **Last State**


5.4.1.2 PCI Express Configuration



PCI Express Root Port 1 ~ Port 20

PCI Express Root Port 1 ~ Port 20 Settings.

5.4.1.2.1 **PCI Express Root Port1 ~ Port20**



PCI Express Root Port 1

Control the PCI Express Root Port.
Disabled / **Enabled**

PCIe ASPM

PCI Express Root port ASPM Setting.
Disabled ASPM / ASPM L1 / ASPM Auto

L1 Substates

PCI Express L1 Substates settings.
Disabled / L1.1 / L1.2 / **L1.1 & L1.2**


PCIe Speed

Configure PCIe Speed.
Auto / Gen1 / Gen2 / Gen3

Max Payload Size

PCIe Max Payload Size Selection.
MPL 128B / MPL 256B

5.4.1.3 PCH SATA Configuration



SATA Controller

Enable or Disable SATA Controller.

Enabled / Disabled

Configure SATA as

Determines how SATA controller(s) operate.

AHCI / RAID

SATA Port 0/1/2/3/4/5/6/7 & Software Preserve

Read Only

Port 0

Enable or Disable SATA Port.

Disabled / **Enabled**

Hot Plug

Designates this port as Hot Pluggable.

Disabled / Enabled

Configure as eSATA

Configures port as External SATA (eSATA).

Disabled / Enabled

Spin Up Device

If enabled for any of ports Staggered Spin Up will be performed and only the drives witch have this option enabled will spin up at boot. Otherwise all drives spin up at boot.


Disabled / Enabled

SATA Device Type

Identify the SATA port is connected to Solid State Drive or Hard disk Drive.

Hard Disk Drive / Solid State Drive

5.4.1.4 PCH sSATA Configuration



sSATA Controller

Enable or Disable SATA Controller.

Enabled / Disabled

Configure sSATA as

Determines how SATA controller(s) operate.

AHCI / RAID

sSATA Port 0/1/2/3/4/5 & Software Preserve

Read Only

Port 0

Enable or Disable SATA Port.

Disabled / **Enabled**

Hot Plug

Designates this port as Hot Pluggable.

Disabled / Enabled

Configure as eSATA

Configures port as External SATA (eSATA).

Disabled / Enabled

Spin Up Device

If enabled for any of ports Staggered Spin Up will be performed and only the drives witch have this option enabled will spin up at boot. Otherwise all drives spin up at boot.


Disabled / Enabled

SATA Device Type

Identify the SATA port is connected to Solid State Drive or Hard disk Drive.

Hard Disk Drive / Solid State Drive

5.4.1.5 USB Configuration




XHCI Idle L1

Enabled XHCI Idle L1. Disabled to workaround USB3 hot plug will fail after 1 hot plug removal. Please put the system to G3 for the new settings to take effect.

Enabled / Disabled

5.4.1.6 PCH DFX Configuration



Enable/Disable ADR

Enable or disable Automatic DIMM Refresh (ADR)

Enabled / Disabled

ADR GPIO

Select between GPIO_B or GPIO_C

GPIO B / GPIO C

Host Partition Reset ADR Enable

Enables/Disables ADR on Host Partition Reset

Enabled / Disabled

Enable/Disable ADR Timer

Held-off for DEBUG PURPOSES ONLY!

Enabled / Held-off

ADR timer expire time

Select proper ADR timer value: 25uS,50uS,100uS or 0.


25 uS / 50 uS / **100 uS** / 0 uS

ADR timer multiplier

Select proper ADR timer multiplier: x1,8,24,40,56,64,72,80,88,96.

x1 / x8 / x24 / x40 / x56 / x64 / x72 / x80 / x88 / x96

5.4.2 Miscellaneous Configuration



Active Video

Select active video type.

Onboard Device / Offboard Device

5.4.3 Server ME Configuration


Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Platform Configuration	
General ME Configuration	
Oper. Firmware Version	0A:4.0.3.206
Backup Firmware Version	N/A
Recovery Firmware Version	0A:4.0.3.206
ME Firmware Status #1	0x000F0245
ME Firmware Status #2	0x88116006
Current State	Operational
Error Code	No Error
Recovery Cause	N/A
PTT Support	[Disabled]
ME Firmware Features	NM

++: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
--

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

Read only.

5.5 Socket Configuration



Processor Configuration

Displays and provides option to change the Processor Settings.

Common RefCode Configuration

Displays the provides option to change the Common RefCode Settings.

UPI Configuration

Displays and provides option to change the UPI Settings.

Memory Configuration

Displays and provides option to change the Memory Settings.


IIO Configuration

Displays and provides option to change the IIO Settings.

Advanced Power Management Configuration

Displays and provides option to change the Power Management Settings.

5.5.1 Processor Configuration



Hyper-Threading [ALL]

Enables Hyper Threading (Software Method) to Enable/Disable Logical Processor threads.

Disabled / **Enabled**

Max CPUID Value Limit

This should be enabled in order to boot legacy OSe that cannot support CPUs with extended CPUID functions.

Disabled / Enabled

Execute Disable Bit

When disabled, forces the XD feature flag to always return 0.

Disabled / **Enabled**

Enable Intel® TXT

Enables Intel® TXT.

Disabled / Enabled

Hardware Prefetcher

MLC Streamer Prefetcher (MSR 1A4h Bit[0]).

Enabled / Disabled

Adjacent Cache Prefetch

MLC Spatial Prefetcher (MSR 1A4h Bit[1]).

Enabled / Disabled

Extended APIC

Enable/Disable extended APIC support.


Disabled / Enabled

AES-NI

Enable/Disable AES-NI support.

Enabled / Disabled

5.5.2 Common RefCode Configuration



MMCFG

Select MMCFG Base.

1G / 1.5G / 1.75G / **2G** / 2.25G / 3G

MMCFG Size

Select MMCFG Size.

64M / 128M / **256M** / 512M / 1G / 2G

MMIO High Base

Select MMIO High Base.

56T / 40T / 24T / 16T / 4T / **3T** / 2T / 1T

MMIO High Granularity Size

Selects the allocation size used to assign mmioh resources. Total mmioh space can be up to 32xgranularity.

Per stack mmioh resource assignments are multiples of the granularity where 1 unit per stack is the default allocation.


1G / 4G / 16G / **64G** / 256G / 1024G

Numa

Enable or Disable Non uniform Memory Access (NUMA).

Disabled / **Enabled**


5.5.3 UPI Configuration



UPI General Configuration

Displays and provides option to change the UPI General Settings.

5.5.3.1 UPI General Configuration



Link Speed Mode

Select the UPI link speed as either the POR speed (Fast) or default speed (Slow).

Slow / **Fast**

Link Frequency Select

Allows for selecting the UPI Link Frequency.

9.6GB/s / 10.4GB/s / **Auto** / Use Per Link Setting

Link L0p Enable

Disabled / Enable / **Auto**

Link L1 Enable

Disabled / Enable / **Auto**

5.5.3.1.1 UPI Status

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.

Socket Configuration

UPI Status

Number of CPU	2
Number of IIO	2
Current UPI Link Speed	Fast
Current UPI Link Frequency	10.4 GT/s
UPI Global MMIO Low Base / Limit	90000000 / FBFFFFFF
UPI Global MMIO High Base / Limit	0000000000000000 / 00...
UPI Pci-e Configuration Base / Siz	80000000 / 10000000

++: Select Screen

↑↓: Select Item

Enter: Select

+/-: Change Opt.

F1: General Help

F2: Previous Values

F3: Optimized Defaults


F4: Save & Exit

ESC: Exit

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

Read only

5.5.4 Memory Configuration



Enforce POR

Enable --- Enforces Plan Of Record restrictions for DDR4 frequency and voltage programming. Disable --- disables this feature. Auto --- Sets it to the MRC default setting; current default is Enable.

Auto / POR / Disable

Memory Frequency

Maximum Memory Frequency Selections in Mhz. Do not select Reserved.


Auto / 2133 / 2400 / 2666

ECC Support

Enable --- Enables DDR ECC Support. Disable --- Disables this feature.

Disabled / **Enabled**

5.5.4.1 Memory Topology



Read only.

5.5.4.2 Memory RAS Configuration

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Socket Configuration	
----- Memory RAS Configuration Setup -----	
Mirror mode	[Disable]
Mirror TAD0	[Disable]
Enable Partial Mirror	[Disable]
Memory Rank Sparing	[Disable]
Correctable Error Threshold	10
SDDC Plus One	[Disable]
Patrol Scrub	[Enable]

Mirror Mode will set entire 1LM/2LM memory in system to be mirrored, consequently reducing the memory capacity by half. Mirror Enable will disable XPT Prefetch

++: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Opt.
F1: General Help
F2: Previous Values
F3: Optimized Defaults
F4: Save & Exit
ESC: Exit

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

Mirror Mode

Mirror Mode will set entire 1LM/2LM memory in system to be mirrored, consequently reducing the memory capacity by half. Mirror Enable will disable XPT Prefetch.

Disabled / Mirror Mode 1LM / Mirror Mode 2LM

Mirror TAD0

Enable Mirror on entire memory for TAD0.

Enabled / **Disabled**

Enable Partial Mirror

Partial mirror mode will enable the required size of memory to be mirrored. If rank sparing is enabled partial mirroring will not take effect. Mirror Enable will disable XPT Prefetch.

Disabled / Enabled

Memory Rack Sparing

Enable/Disable Memory Rank Sparing.

Disabled / Enabled

Correctable Error Threshold

Correctable Error Threshold (1 – 32767) used for sparing, tagging, and leaky bucket.

10

SDDC Plus One

Enable/Disable SDDC Plus One.


Disabled / Enabled

Patrol Scrub

Enable/Disable Patrol Scrub.

Disabled / **Enabled**

5.5.5 I/O Configuration



Intel® VT for Directed I/O (VT-d)

Press <Enter> to bring up the Intel® VT for Directed I/O (VT-d) Configuration menu.

Intel® VMD Technology

Press <Enter> to bring up the Intel® VMD for Volume Management Device Configuration menu.

PCIe Hot Plug

Enable/Disable PCIe Hot Plug globally.

Disabled / **Enabled** / Auto / Manual

PCIe ACPI Hot Plug

Enable/Disable PCIe ACPI Hot Plug globally, or allow per-port control. When Disabled, MSI is generated on HP event. When Enabled, _HPGPE message is generated.


Disabled / Enable / Per-Port

PCIe Access Control Services

Enable/Disable Access Control Services.

Enable / **Disabled**

5.5.5.1 Socket 0 Configuration



IDU0 (IIO PCIe Br1)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16** / Auto

IDU1 (IIO PCIe Br2)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / **x8x8** / x16 / Auto

IDU2 (IIO PCIe Br3)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16** / Auto

Socket 0 PcieBr1D00F0 – Port 1A

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

Socket 0 PcieBr2D00F0 – Port 2A

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

Socket 0 PcieBr2D02F0 – Port 2C

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

Socket 0 PcieBr3D00F0 – Port 3A

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

5.5.5.1.1 Socket 1 PcieBr0D00F0 – Port 1A/2A/3A



PCI-E Port

In auto mode the BIOS will remove the EXP port if there is no device or errors on that device and the device is not HP capable. Disable is used to disable the port and hide its CFG space.

Auto / Disabled / Enabled

Hot Plug Capable

This option specifies if the link is considered Hot Plug capable.

Disabled / Enabled

Surprise Hot Plug Capable

This option specifies if the link is considered Surprise Hot Plug capable.

Disabled / Enabled

PCI-E Port Link

This option disables the link so that the no training occurs but the CFG space is still active.

Enabled / Disabled

Link Speed

Choose Link Speed for this PCIe port.

Auto / Gen 1 (2.5 GT/s) / Gen 2 (5 GT/s) / Gen 3 (8 GT/s)

PCI-E ASPM Support

This option enables/disables the ASPM (L1) support for the downstream devices.

Auto / L1 Only / **Disabled**

L0s Support

When disabled, IIO never puts its transmitter in L0s state.

Disabled / Enabled

Non-Transparent Bridge PCIe Port Definition

[EMBAR1XBASE, EMBAR2XBASE] Configures port as TB, NTB-NTB, or NTB-RP (DON'T SELECT NTB-RP for legacy IIO on A0 Sil).

Transparent Bridge / NTB to NTB / NTB to RP

Hide Port?

User can force to hide this root port from OS.

No / Yes

5.5.5.1.2 Socket 0 PcieBr0D00F0 – Port 2C

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Socket Configuration	
Socket 0 PcieBr2D02F0 - Port 2C	

PCI-E Port	[Auto]
Hot Plug Capable	[Disable]
Surprise Hot Plug Capable	[Disable]
PCI-E Port Link	[Enable]
Link Speed	[Auto]
PCI-E ASPM Support	[Disable]
LOS Support	[Disable]
Hide Port?	[No]
In auto mode the BIOS will remove the EXP port if there is no device or errors on that device and the device is not HP capable. Disable is used to disable the port and hide its CFG space.	
++: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	
Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.	

PCI-E Port

In auto mode the BIOS will remove the EXP port if there is no device or errors on that device and the device is not HP capable. Disable is used to disable the port and hide its CFG space.

Auto / Disabled / Enabled

Hot Plug Capable

This option specifies if the link is considered Hot Plug capable.

Disabled / Enabled

Surprise Hot Plug Capable

This option specifies if the link is considered Surprise Hot Plug capable.

Disabled / Enabled

PCI-E Port Link

This option disables the link so that the no training occurs but the CFG space is still active.

Enabled / Disabled

Link Speed

Choose Link Speed for this PCIe port.

Auto / Gen 1 (2.5 GT/s) / Gen 2 (5 GT/s) / Gen 3 (8 GT/s)

PCI-E ASPM Support

This option enables/disables the ASPM (L1) support for the downstream devices.

Auto / L1 Only / **Disabled**

L0s Support

When disabled, I/O never puts its transmitter in L0s state.


Disabled / Enabled

Hide Port?

User can force to hide this root port from OS.

No / Yes

5.5.5.2 Socket 1 Configuration



IDU0 (II0 PCIe Br1)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16** / Auto

IDU1 (II0 PCIe Br2)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16** / Auto

IDU2 (II0 PCIe Br3)

Selects PCIe port Bifurcation for selected slot(s).

x4x4x4x4 / x4x4x8 / x8x4x4 / x8x8 / **x16** / Auto

Socket 1 PcieBr1D00F0 – Port 1A

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

Socket 1 PcieBr2D00F0 – Port 2A

Settings related to PCI Express Ports


(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

Socket 1 PcieBr3D00F0 – Port 3A

Settings related to PCI Express Ports

(0/1A/1B/1C/1D/2A/2B/2C/2D/3A/3B/3C/3D/4A/5A).

5.5.5.2.1 Socket 1 PcieBr0D00F0 – Port 1A/2A/3A



PCI-E Port

In auto mode the BIOS will remove the EXP port if there is no device or errors on that device and the device is not HP capable. Disable is used to disable the port and hide its CFG space.

Auto / Disabled / Enabled

Hot Plug Capable

This option specifies if the link is considered Hot Plug capable.

Disabled / Enabled

Surprise Hot Plug Capable

This option specifies if the link is considered Surprise Hot Plug capable.

Disabled / Enabled

PCI-E Port Link

This option disables the link so that the no training occurs but the CFG space is still active.

Enabled / Disabled

Link Speed

Choose Link Speed for this PCIe port.

Auto / Gen 1 (2.5 GT/s) / Gen 2 (5 GT/s) / Gen 3 (8 GT/s)

PCI-E ASPM Support

This option enables/disables the ASPM (L1) support for the downstream devices.

Auto / L1 Only / **Disabled**

L0s Support

When disabled, IIO never puts its transmitter in L0s state.

Disabled / Enabled

Non-Transparent Bridge PCIe Port Definition

[EMBAR1XBASE, EMBAR2XBASE] Configures port as TB, NTB-NTB, or NTB-RP (DON'T SELECT NTB-RP for legacy IIO on A0 Sil).


Transparent Bridge / NTB to NTB / NTB to RP

Hide Port?

User can force to hide this root port from OS.

No / Yes

5.5.5.3 Intel® VT for Directed I/O (VT-d)




Intel® VT for Directed I/O (VT-d)


Enable/Disable Intel® Virtualization Technology for Directed I/O (VT-d) by reporting the I/O device assignment to VMM through DMAR ACPI Tables.

Enabled / **Disabled**

5.5.5.4 Intel® VMD Technology



5.5.5.4.1 Intel VMD for Volume Management for Socket 0



Intel® VMD for Volume Management Device for PStack0

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled


Intel® VMD for Volume Management Device for PStack1

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled

Intel® VMD for Volume Management Device for PStack2

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled

5.5.5.4.2 Intel VMD for Volume Management for Socket 1



Intel® VMD for Volume Management Device for PStack0

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled


Intel® VMD for Volume Management Device for PStack1

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled

Intel® VMD for Volume Management Device for PStack2

Enable/Disable Intel® Volume Management Device Technology in this Stack.
Disabled / Enabled

5.5.6 Advanced Power Management Configuration



CPU P State Control

P State Control Configuration Sub Menu, include Turbo, XE and etc.

Hardware PM State Control

Hardware P-State setting


CPU C State Control

CPU C State setting

Package C State Control

Package C State setting

3.5.6.1 CPU P State Control



SpeedStep (Pstates)

Enable/Disable EIST (P-States)

Disabled / **Enabled**

Boot performance mode

Select the performance state that the BIOS will set before OS hand off.

Max Performance / Max Efficient / Set by Intel Node

Energy Efficient Turbo

Energy Efficient Turbo Disable, MSR 0x1FC [19]

Disabled / **Enabled**

Turbo Mode

Enable/Disable processor Turbo Mode (requires EMTTM enabled too).


Disabled / **Enabled**

CPU Flex Ratio Override

Enable/Disable CPU Flex Ratio Programming

Disabled / Enabled

3.5.6.2 Hardware PM State Control Submenu



Hardware P-States

Disable: Hardware choose a P-state based on OS Request (Legacy P-States)

Native Mode: Hardware choose a P-state based on OS guidance

Out of Band Mode: Hardware autonomously choose a P-state (No OS guidance)

Disabled / **Native Mode** / Out of Band Mode / Native Mode with No Legacy Support

3.5.6.3 CPU C State Control

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Socket Configuration	
CPU C State Control	Enable/Disable CPU C6(ACPI C3) report to OS
CPU C6 report [Auto]	
Enhanced Halt State (C1E) [Enabled]	
OS ACPI Cx [ACPI C2]	
↔: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.

CPU C6 report

Enable/Disable CPU C6(ACPI C3) report to OS

Auto / Enable / Disable

Enhanced Halt State (C1E)

Enables the Enhanced C1E state of the CPU, takes effect after reboot

Enabled / Disabled

OS ACPI Cx

Report CC3/CC6 to OS ACPI C2 or ACPI C3

ACPI C2 / ACPI C3

3.5.6.4 Package C State Control


Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Socket Configuration	
Package C State Control	Package C State limit
Package C State [Auto]	
	↔: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.	

Package C State Control

Package C State Limit

C0/C1 state / C2 state / C6 (non Retention) state / C6 (Retention) state / No Limit / **Auto**

5.6 Server Management



FRB-2 Timer

Enable or Disable FRB-2 timer (POST timer).

Disabled / Enabled

FRB-2 Timer timeout

Enter value Between 3 to 6 min for FRB-2 Timer Expiration value.

3 minutes / 4 minutes / 5 minutes / **6 minutes**

FRB-2 Timer Policy

Configure how the system should respond if the FRB-2 Timer expires. Not available if FRB-2 Timer is disabled.

Do Nothing / Reset / Power Down / Power Cycle

OS Watchdog Timer

If enabled, starts a BIOS timer which can only be shut off by Management Software after the OS loads. Helps determine that the OS successfully loaded or follows the OS Boot Watchdog Timer policy.

Enabled / **Disabled**

OS Wtd Timer timeout

Configure the length of the OS Boot Watchdog Timer. Not available if OS Boot Watchdog timer is disabled.

5 minutes / **10 minutes** / 15 minutes / 20 minutes

OS Wtd Timer Policy

Configure how the system should respond if the OS Boot Watchdog Timer expires. Not available if OS Boot Watchdog timer is disabled.

Do Nothing / Reset / Power Down / Power Cycle

BMC Logo

Enable or Disable BMC Logo.

Enabled / Disabled

System Event Log

Press <Enter> to change the SEL event log configuration.

BMC network configuration

Configure BMC network parameters.

5.6.1 System Event Log

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.	
Server Mgmt	
Enabling/Disabling Options	
SEL Components	[Enabled]
Change this to enable or disable all features of System Event Logging during boot.	
Erasing Settings	
Erase SEL	[No]
When SEL is Full	[Do Nothing]
Custom EFI Logging Options	
Log EFI Status Codes	[Error code]
NOTE: All values changed here do not take effect until computer is restarted.	
++: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Version 2.19.1268, Copyright (C) 2017 American Megatrends, Inc.

SEL Components

Change this to enable or disable all features of System Event Logging during boot.

Disabled / **Enabled**

NOTE: When **SEL Components** is set to [Disabled], the following items are read only.

Erase SEL

Choose options for erasing SEL.

No / Yes, on next reset / Yes, on every reset

When SEL is Full

Choose options for reactions to a full SEL.


Do Nothing / Erase Immediately

Log EFI Status Codes

Disable the logging of EFI Status Codes or log only error code or only progress code or both.

Disabled / Both / **Error Code** / Progress Code

5.6.2 BMC Network Configuration



Configuration Address Source

Select the configure LAN channel parameters statically or dynamically (by BIOS or BMC). Unspecified option will not modify any BMC network parameters during BIOS phase.

Unspecified / Static / DynamicBmcDhcp / DynamicBmcNonDhcp

Management Port 2

Enable/Disable BMC Share Nic.


Enabled / **Disabled**

IPv6 Support

Enable or Disable LAN1 IPV6 Support.

Enabled / **Disabled**

5.7 Security



Administrator Password

Set administrator password in the **Create New Password** window. After you key in the password, the **Confirm New Password** window will pop out to ask for confirmation.

User Password


Set user password in the **Create New Password** window. After you key in the password, the **Confirm New Password** window will pop out to ask for confirmation.

Secure Frozen Mode

Disable means Hard Drive on Non-frozen mode. Enable means Hard Drive on Frozen mode.

Disabled / **Enabled**

5.7.1 Secure Boot



Attempt Secure Boot

Secure boot activated when Platform Key (PK) is enrolled, System mode is User/Deployed, and CSM function is disabled.


Disabled / Enabled

Secure Boot Mode

Secure Boot mode selector: Standard/Custom. In Custom mode Secure Boot Variables can be configured without authentication.

Standard / **Custom**

5.7.1.1 Key Management



Provision Factory Default keys

Allow to provision factory default Secure Boot keys when System is in Setup Mode.
Disabled / Enabled

Install Factory Default Keys

Force System to User Mode – install all Factory Default Keys. Press “Yes” to install factory default keys.

Enroll Efi Image

Allow the image to run in Secure Boot mode. Enroll SHA256 has of the binary into Authorized signature Database (db).

Save All Secure Boot Variables

Save NVRAM content of all Secure Boot variables to the files
(EFI_SIGNATURE_LIST data format) in root folder on a target file system device.

Platform Key (PK)

Enroll Factory Defaults or load certificates from a file:

1. Public Key Certificate in:
 - a) EFI_SIGNATURE_LIST

- b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
2. Authenticated EFI Variable
 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New

Key Exchange Keys

Enroll Factory Defaults or load certificates from a file:

1. Public Key Certificate in:
 - a) EFI_SIGNATURE_LIST
 - b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
 2. Authenticated EFI Variable
 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New / Append

Authorized Signatures

Enroll Factory Defaults or load certificates from a file:

1. Public Key Certificate in:
 - a) EFI_SIGNATURE_LIST
 - b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
 2. Authenticated EFI Variable
 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New / Append

Forbidden Signatures

Enroll Factory Defaults or load certificates from a file:

1. Public Key Certificate in:
 - a) EFI_SIGNATURE_LIST
 - b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
 2. Authenticated EFI Variable
 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New / Append

Authorized TimeStamps

Enroll Factory Defaults or load certificates from a file:

1. Public Key Certificate in:

- a) EFI_SIGNATURE_LIST
 - b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
- 2. Authenticated UEFI Variable
 - 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New / Append


OsRecovery Signatures

Enroll Factory Defaults or load certificates from a file:

- 1. Public Key Certificate in:
 - a) EFI_SIGNATURE_LIST
 - b) EFI_CERT_X509 (DER encoded)
 - c) EFI_CERT_RSA2048 (bin)
 - d) EFI_CERT_SHA256, 384, 512 (bin)
 - 2. Authenticated UEFI Variable
 - 3. EFI PE/COFF Image (SHA256)
- Key source: Default, External, Mixed, Test

Set New / Append

5.8 Boot



Setup Prompt Timeout

Number of seconds to wait for setup activation key. 65535 (0xFFFF) means indefinite waiting.

1

Bootup NumLock State

Select the keyboard NumLock state.

Off / On

Quiet Boot

Enable or disable Quiet Boot option.

Disabled / Enabled

Endless Boot

Enable or disable Endless Boot.

Disabled / Enabled

Wait for 'ESC' If Error

Wait for 'ESC' key to be pressed if error occurs.

Disabled / Enabled

Boot Option Priorities

Boot Option #1

Select the first/second boot device.

Device Name / Disabled

5.8.1 Delete Boot Option




Delete Boot Option

Remove an EFI boot option from the boot order.

Select one to delete / UEFI: Built-in EFI Shell

5.9 Save & Exit



Save Changes and Exit

Exit system setup after saving the changes.

Discard Changes and Exit

Exit system setup without saving any changes.

Save Changes and Reset

Reset the system after saving the changes.

Discard Changes and Reset

Reset system setup without saving any changes.

Save Changes

Save changes done so far to any of the setup options.

Discard Changes

Discard changes done so far to any of the setup options.

Restore Defaults

Restore/Load Default values for all the setup options.

Save as User Defaults

Save the changes done so far as User Defaults.

Restore User Defaults

Restore the User Defaults to all the setup options.

Boot Override

Read only.

Chapter 6: Diagnostics

NOTE: if you experience problems with setting up your system, always check the following things in the following order:

Memory, Video, CPU

By checking these items, you will most likely find out what the problem might have been when setting up your system. For more information on troubleshooting, check the TYAN website at <http://www.tyan.com>.

6.1 Flash Utility

Every BIOS file is unique for the motherboard it was designed for. For Flash Utilities, BIOS downloads, and information on how to properly use the Flash Utility with your motherboard, please check the TYAN web site at <http://www.tyan.com>

NOTE: Please be aware that by flashing your BIOS, you agree that in the event of a BIOS flash failure, you must contact your dealer for a replacement BIOS. There are no exceptions. TYAN does not have a policy for replacing BIOS chips directly with end users. In no event will TYAN be held responsible for damages done by the end user.

6.2 AMIBIOS Post Code (Aptio)

The POST code checkpoints are the largest set of checkpoints during the BIOS pre-boot process. The following table describes the type of checkpoints that may occur during the POST portion of the BIOS:

Checkpoint Ranges

Status Code Range	Description
0x01 – 0x0B	SEC execution
0x0C – 0x0F	SEC errors
0x10 – 0x2F	PEI execution up to and including memory detection
0x30 – 0x4F	PEI execution after memory detection
0x50 – 0x5F	PEI errors
0x60 – 0x8F	DXE execution up to BDS
0x90 – 0xCF	BDS execution
0xD0 – 0xDF	DXE errors
0xE0 – 0xE8	S3 Resume (PEI)
0xE9 – 0xEF	S3 Resume errors (PEI)
0xF0 – 0xF8	Recovery (PEI)
0xF9 – 0xFF	Recovery errors (PEI)

Standard Checkpoints

SEC Phase

Status Code	Description
0x00	Not used
Progress Codes	
0x01	Power on. Reset type detection (soft/hard).
0x02	AP initialization before microcode loading
0x03	North Bridge initialization before microcode loading
0x04	South Bridge initialization before microcode loading
0x05	OEM initialization before microcode loading
0x06	Microcode loading
0x07	AP initialization after microcode loading
0x08	North Bridge initialization after microcode loading
0x09	South Bridge initialization after microcode loading

Status Code	Description
0x0A	OEM initialization after microcode loading
0x0B	Cache initialization
SEC Error Codes	
0x0C – 0x0D	Reserved for future AMI SEC error codes
0x0E	Microcode not found
0x0F	Microcode not found

SEC Beep Codes

None

PEI Phase

Status Code	Description
Progress Codes	
0x10	PEI Core is started
0x11	Pre-memory CPU initialization is started
0x12	Pre-memory CPU initialization (CPU module specific)
0x13	Pre-memory CPU initialization (CPU module specific)
0x14	Pre-memory CPU initialization (CPU module specific)
0x15	Pre-memory North Bridge initialization is started
0x16	Pre-Memory North Bridge initialization (North Bridge module specific)
0x17	Pre-memory North Bridge initialization (North Bridge module specific)
0x18	Pre-Memory North Bridge initialization (North Bridge module specific)
0x19	Pre-memory South Bridge initialization is started
0x1A	Pre-Memory South Bridge initialization (South Bridge module specific)
0x1B	Pre-memory South Bridge initialization (South Bridge module specific)
0x1C	Pre-Memory South Bridge initialization (South Bridge module specific)
0x1D – 0x2A	OEM pre-memory initialization codes
0x2B	Memory initialization. Serial Presence Detect (SPD) data reading
0x2C	Memory initialization. Memory presence detection
0x2D	Memory initialization. Programming memory timing information
0x2E	Memory initialization. Configuring memory
0x2F	Memory initialization (other)
0x30	Reserved for ASL (see ASL Status Codes section below)

Status Code	Description
0x31	Memory Installed
0x32	CPU post-memory initialization is started
0x33	CPU post-memory initialization. Cache initialization
0x34	CPU post-memory initialization. Application Processor(s) (AP) initialization
0x35	CPU post-memory initialization. Boot Strap Processor (BSP) selection
0x36	CPU post-memory initialization. System Management Mode(SMM) initialization
0x37	Post-Memory North Bridge initialization is started
0x38	Post-Memory North Bridge initialization (North Bridge module specific)
0x39	Post-Memory North Bridge initialization (North Bridge module specific)
0x3A	Post-Memory North Bridge initialization (North Bridge module specific)
0x3B	Post-Memory South Bridge initialization is started
0x3C	Post-Memory South Bridge initialization (South Bridge module specific)
0x3D	Post-Memory South Bridge initialization (South Bridge module specific)
0x3E	Post-Memory South Bridge initialization (South Bridge module specific)
0x3F – 0x4E	OEM post memory initialization codes
0x4F	DXE IPL is started
PCI Error Codes	
0x50	Memory initialization error. Invalid memory type or incompatible memory speed
0x51	Memory initialization error. SPD reading has failed
0x52	Memory initialization error. Invalid memory size or memory modules do not match
0x53	Memory initialization error. No usable memory detected
0x54	Unspecified memory initialization error
0x55	Memory not installed
0x56	Invalid CPU type or speed
0x57	CPU mismatch
0x58	CPU self test failed or possible CPU cache error
0x59	CPU microcode is not found or microcode update is failed
0x5A	Internal CPU error
0x5B	Reset PPI is not available
0x5C – 0x5F	Reserved for future AMI error codes
S3 Resume Progress Codes	

Status Code	Description
0xE0	S3 Resume is started (S3 Resume PPI is called by the DXE IPL)
0xE1	S3 Boot Script execution
0xE2	Video repost
0xE3	OS S3 wake vector call
0xE4 – 0xE7	Reserved for future AMI progress codes
S3 Resume Error Codes	
0xE8	S3 Resume Failed
0xE9	S3 Resume PPI not Found
0xEA	S3 Resume Boot Script Error
0xEB	S3 OS Wake Error
0xEC – 0xEF	Reserved for future AMI error codes
Recovery Progress Codes	
0xF0	Recovery condition triggered by firmware (Auto recovery)
0xF1	Recovery condition triggered by user (Forced recovery)
0xF2	Recovery process started
0xF3	Recovery firmware image is found
0xF4	Recovery firmware image is loaded
0xF5 – 0xF7	Reserved for future AMI progress codes
Recovery Error Codes	
0xF8	Recovery PPI is not available
0xF9	Recovery capsule is not found
0xFA	Invalid recovery capsule
0xFB – 0xFF	Reserved for future AMI error codes

PEI Beep Codes

# of Beeps	Description
1 (repeatedly)	Memory not installed
1	Memory was installed twice (InstallPEIMemory routine in PEI Core called twice)
2	Recovery started
3	DXE IPL was not found
3	DXE Core Firmware Volume was not found
4	Recovery failed

# of Beeps	Description
4	S3 Resume failed
7	Reset PPI is not available

DXE Phase

Status Code	Description
0x60	DXE Core is started
0x61	NVRAM initialization
0x62	Installation of the South Bridge Runtime Services
0x63	CPU DXE initialization is started
0x64	CPU DXE initialization (CPU module specific)
0x65	CPU DXE initialization (CPU module specific)
0x66	CPU DXE initialization (CPU module specific)
0x67	CPU DXE initialization (CPU module specific)
0x68	PCI host bridge initialization
0x69	North Bridge DXE initialization is started
0x6A	North Bridge DXE SMM initialization is started
0x6B	North Bridge DXE initialization (North Bridge module specific)
0x6C	North Bridge DXE initialization (North Bridge module specific)
0x6D	North Bridge DXE initialization (North Bridge module specific)
0x6E	North Bridge DXE initialization (North Bridge module specific)
0x6F	North Bridge DXE initialization (North Bridge module specific)
0x70	South Bridge DXE initialization is started
0x71	South Bridge DXE SMM initialization is started
0x72	South Bridge devices initialization
0x73	South Bridge DXE initialization (South Bridge module specific)
0x74	South Bridge DXE initialization (South Bridge module specific)
0x75	South Bridge DXE initialization (South Bridge module specific)
0x76	South Bridge DXE initialization (South Bridge module specific)
0x77	South Bridge DXE initialization (South Bridge module specific)
0x78	ACPI module initialization
0x79	CSM initialization
0x7A – 0x7F	Reserved for future AMI DXE codes

Status Code	Description
0x80 – 0x8F	OEM DXE initialization codes
0x90	Boot Device Selection (BDS) phase is started
0x91	Driver connecting is started
0x92	PCI Bus initialization is started
0x93	PCI Bus Hot Plug Controller initialization
0x94	PCI Bus Enumeration
0x95	PCI BUS Request Resources
0x96	PCI Bus Assign Resources
0x97	Console Output devices connect
0x98	Console Input devices connect
0x99	Super IO initialization
0x9A	USB initialization is started
0x9B	USB Reset
0x9C	USB Detect
0x9D	USB Enable
0x9E -0x9F	Reserved for future AMI codes
0xA0	IDE initialization is started
0xA1	IDE Reset
0xA2	IDE Detect
0xA3	IDE Enable
0xA4	SCSI initialization is started
0xA5	SCSI Reset
0xA6	SCSI Detect
0xA7	SCSI Enable
0xA8	Setup Verifying Password
0xA9	Start of Setup
0xAA	Reserved for ASL (see ASL Status Codes section below)
0xAB	Setup Input Wait
0xAC	Reserved for ASL (see ASL Status Codes section below)
0xAD	Ready To Boot event
0xAE	Legacy Boot event
0xAF	Exit Boot Services event

Status Code	Description
0xB0	Runtime Set Virtual Address MAP Begin
0xB1	Runtime Set Virtual Address MAP End
0xB2	Legacy Option ROM initialization
0xB3	System Reset
0xB4	USB hot plug
0xB5	PCI bus hot plug
0xB6	Clean-up of NVRAM
0xB7	Configuration Reset (reset of NVRAM settings)
0xB8 – 0xBF	Reserved for future AMI codes
0xC0 – 0xCF	OEM BDS initialization codes
DXE Error Codes	
0xD0	CPU initialization error
0xD1	North Bridge initialization error
0xD2	South Bridge initialization error
0xD3	Some of the Architectural Protocols are not available
0xD4	PCI resource allocation error. Out of Resources
0xD5	No Space for Legacy Option ROM
0xD6	No Console Output Devices are found
0xD7	No Console Input Devices are found
0xD8	Invalid password
0xD9	Error loading Boot Option (LoadImage returned error)
0xDA	Boot Option is failed (StartImage returned error)
0xDB	Flash update is failed
0xDC	Reset protocol is not available

DXE Beep Codes

# of Beeps	Description
1	Invalid password
4	Some of the Architectural Protocols are not available
5	No Console Output Devices are found
5	No Console Input Devices are found
6	Flash update is failed

# of Beeps	Description
7	Reset protocol is not available
8	Platform PCI resource requirements cannot be met

ACPI/ASL Checkpoints

Status Code	Description
0x01	System is entering S1 sleep state
0x02	System is entering S2 sleep state
0x03	System is entering S3 sleep state
0x04	System is entering S4 sleep state
0x05	System is entering S5 sleep state
0x10	System is waking up from the S1 sleep state
0x20	System is waking up from the S2 sleep state
0x30	System is waking up from the S3 sleep state
0x40	System is waking up from the S4 sleep state
0xAC	System has transitioned into ACPI mode. Interrupt controller is in PIC mode.
0xAA	System has transitioned into ACPI mode. Interrupt controller is in APIC mode.

NOTE

Appendix I: How to recover UEFI BIOS

Important Notes:

The emergency UEFI BIOS Recovery process is only used to rescue a system with a failed or corrupted BIOS image that fails to boot to an OS. It is not intended to be used as a general purpose BIOS flashing procedure and should not be used as such. Please do not shutdown or reset the system while the BIOS recovery process is underway or there is risk of damage to the UEFI recovery bootloader that would prevent the recovery process itself from working. In no event shall Tyan be liable for direct, indirect, incidental, special or consequential damages arising from the BIOS update or recovery.

The BIOS Recovery file is named xxxx.cap, where the 'xxxx' portion is the motherboard model number. Examples: 5630.cap, 7106.cap, 7109.cap, etc. Please make sure that you are using the correct BIOS Recovery file from Tyan's web site.

BIOS Recovery Process

1. Place the recovery BIOS file (xxxx.cap) in the root directory of a USB disk.
2. Ensure that the system is powered off.
3. Insert the USB disk to any USB port on the motherboard or chassis.
4. Power the system on while pressing "Ctrl" and "Home" simultaneously on the keyboard. Continue to hold these keys down until the following Tyan screen is displayed on the monitor:



5. The system will boot to BIOS setup. A new menu item will appear at the far right of the screen. Scroll to the 'Recovery' tab, move the cursor to "Proceed with flash update" and press the "Enter" key on the keyboard to start the BIOS recovery process.

```
Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.
Main Advanced Platform Configuration Socket Configuration Recovery >
-----
Please select blocks you want to update
Reset NVRAM [Enabled]
Boot Block Update [Enabled]

> Proceed with flash update

Select this to start
flash update

-----
|>=: Select Screen
|^v: Select Item
|Enter: Select
|+/-: Change Opt.
|F1: General Help
|F2: Previous Values
|F3: Optomized Defaults
|F4: Save & Exit
|ESC: Exit
|
-----
DXE-USB hot plug2.19.1268. Copyright (C) 2017 American Megatrends, Inc. B4
```

6. **IMPORTANT:** Do not power off or reboot the server during the BIOS recovery process. This can damage the BIOS recovery bootloader and prevent it from loading a subsequent time.

7. Wait for the BIOS recovery procedure to complete. Completion is signified with the message "Flash update completed. Press any key to reset the system" displayed on screen.

8. Remove the USB disk and reboot.

If your system does not have video output or the POST code halts at "FF" on the right-lower portion of the screen, please contact Tyan representatives for RMA service.

Appendix II: Cable Connection Tables

1. Fan Ctrl Cable

M1809F77A FAN board to S7109 MB		
Fan board	Connect to	S7109 M/B
J8	→	FAN_HDR1

2. Fan PWR Cable

M1809F77A FAN board to M7059F77 PDB board		
Fan board	Connect to	PDB board
J7	→	J2
J9	→	
J10	→	
J11	→	

3. FP Ctrl & USB Cable

M1713 FP board to S7109 MB		
M1713 FP board	Connect to	S7109 M/B
J3_SSI_FP (FP Cable)	→	FPIO_1
J1_USB_IN (USB Cable)	→	USB3

4. VGA & COM port Cable

Front BKT to S7109 MB		
Front BKT	Connect to	S7109 M/B
VGA Cable	→	FPIO_VGA1
COM port Cable	→	COM1

5. B4P PWR & Mini-SAS HD & SATA & SGPIO Cable

(For B7109F77DV10E4HR-2T-N)

M1284F77D HDD BP to S7109 MB		
HDD BP	Connect to	S7109 M/B
SATA10~13 (Mini-SAS HD Cable-1)	→	PCH_SATA_4 7
SATA6~9 (Mini-SAS HD Cable-2)	→	PCH_SATA_0 3
SATA0 (SATA Cable-1)	→	PCH_SSATA_4
SATA1 (SATA Cable-2)	→	PCH_SSATA_5
PW1(B4P PWR Cable-1)	→	M/B D4P_PW2
PW2(B4P PWR Cable-2)	→	M/B D4P_PW1
PW3(B4P PWR Cable-3)	→	M/B D4P_PW3
SGPIO1 (SGPIO Cable)	→	SSATA_SGPIO1

6. B4P PWR & Mini-SAS HD & SATA Cable

(For B7109F77DV14HR-2T-N)

M1284F77D HDD BP to S7109 MB		
HDD BP	Connect to	S7109 M/B
SATA10~13 (Mini-SAS HD Cable-1)	→	PCH_SATA_4 7
SATA6~9 (Mini-SAS HD Cable-2)	→	PCH_SATA_0 3
SATA2~5 (Mini-SAS HD Cable-3)	→	PCH_SSATA_0 3
SATA0 (SATA Cable-1)	→	PCH_SSATA_4
SATA1 (SATA Cable-2)	→	PCH_SSATA_5
PW1(B4P PWR Cable-1)	→	M/B D4P_PW2
PW2(B4P PWR Cable-2)	→	M/B D4P_PW1
PW3(B4P PWR Cable-3)	→	M/B D4P_PW3

7. Oculink Cable

(For B7109F77DV10E4HR-2T-N)

M1284F77D HDD BP to M2093		
HDD BP	Connect to	M2093
NVME01 (Oculink Cable-1)	→	J1
NVME23 (Oculink Cable-2)	→	J2

8. 2x3P & 2x4P GPU PWR Cable

M7059F77 PDB to GPU Card		
PDB	Connect to	GPU Card
J17 or J18	→	GPU1
J15 or J16	→	GPU2
J13 or J14	→	GPU3
J11 or J12	→	GPU4
J9 or J10	→	GPU5
J7 or J8	→	GPU6
J5 or J6	→	GPU7
J3 or J4	→	GPU8


NOTE: Please note the thermal design power (TDP) of GPU must be less than 300W or OCP (over current protect) will occur.

NOTE

Appendix III: Fan and Temp Sensors

This section aims to help readers identify the locations of some specific FAN and Temp Sensors on the motherboard. A table of BIOS Temp sensor name explanation is also included for readers' reference.

Figure 1: Sensor Location



NOTE: The red spot indicates the sensor.

Fan and Temp Sensor Location:

1. Fan Sensor: It is located in the **third** pin of the fan connector, which detects the fan speed (rpm)
2. Temp Sensor: refer to Figure 1: Sensor Location. They detect the system temperature around.



BIOS Temp Sensor Name Explanation:

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.				
Advanced				
PC Health Status				
ID#	NAME	READING	UNIT	STATUS
01	P0_DTS_Temp	: 71	°C	OK
02	P0_PECI_Value	: -28		OK
03	P1_DTS_Temp	: 76	°C	OK
04	P1_PECI_Value	: -23		OK
4C	SYS_Air_Inlet	: N/A	°C	OK
4D	MB_Air_Inlet	: 31	°C	OK
4E	SYS_Air_Outlet	: 41	°C	OK
4F	LAN_X550_Temp	: 61	°C	OK
09	PCH_Temp	: 44	°C	OK
46	P0_MOSFET	: 39	°C	OK
47	P1_MOSFET	: 41	°C	OK
48	P0_DIMM_MOSFET_1	: 40	°C	OK
49	P0_DIMM_MOSFET_2	: 45	°C	OK
4A	P1_DIMM_MOSFET_1	: 46	°C	OK
4B	P1_DIMM_MOSFET_2	: 50	°C	OK
0A	P0_MC0_DIM_CH_A	: N/A	°C	OK
0B	P0_MC0_DIM_CH_B	: N/A	°C	OK
0C	P0_MC0_DIM_CH_C	: N/A	°C	OK
0D	P0_MC1_DIM_CH_D	: N/A	°C	OK
0E	P0_MC1_DIM_CH_E	: N/A	°C	OK
0F	P0_MC1_DIM_CH_F	: 32	°C	OK
10	P1_MC0_DIM_CH_A	: N/A	°C	OK
Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.				

←+: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Opt.
F1: General Help
F2: Previous Values
F3: Optimized Defaults
F4: Save & Exit
ESC: Exit

Aptio Setup Utility - Copyright (C) 2017 American Megatrends, Inc.				
Advanced				
11	P1_MC0_DIM_CH_B	: N/A	°C	OK
12	P1_MC0_DIM_CH_C	: 31	°C	OK
13	P1_MC1_DIM_CH_D	: N/A	°C	OK
14	P1_MC1_DIM_CH_E	: N/A	°C	OK
15	P1_MC1_DIM_CH_F	: N/A	°C	OK
30	GPU0_Core0_Temp	: N/A	°C	OK
31	GPU0_Core1_Temp	: N/A	°C	OK
32	GPU1_Core0_Temp	: N/A	°C	OK
33	GPU1_Core1_Temp	: N/A	°C	OK
34	GPU2_Core0_Temp	: N/A	°C	OK
35	GPU2_Core1_Temp	: N/A	°C	OK
36	GPU3_Core0_Temp	: N/A	°C	OK
37	GPU3_Core1_Temp	: N/A	°C	OK
38	GPU4_Core0_Temp	: N/A	°C	OK
39	GPU4_Core1_Temp	: N/A	°C	OK
3A	GPU5_Core0_Temp	: N/A	°C	OK
3B	GPU5_Core1_Temp	: N/A	°C	OK
3C	GPU6_Core0_Temp	: N/A	°C	OK
3D	GPU6_Core1_Temp	: N/A	°C	OK
3E	GPU7_Core0_Temp	: N/A	°C	OK
3F	GPU7_Core1_Temp	: N/A	°C	OK
62	SYS_FAN_1	: N/A	RPM	OK
63	SYS_FAN_2	: N/A	RPM	OK
64	SYS_FAN_3	: N/A	RPM	OK
65	SYS_FAN_4	: N/A	RPM	OK
Version 2.19.1268. Copyright (C) 2017 American Megatrends, Inc.				

←+: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Opt.
F1: General Help
F2: Previous Values
F3: Optimized Defaults
F4: Save & Exit
ESC: Exit



BIOS Temp Sensor	Name Explanation
P0_DTS_Temp	Temperature of the CPU0 Digital Temperature Sensor
P0_PECI_Value	Temperature of the CPU0 Platform Environment Control Interface
P1_DTS_Temp	Temperature of the CPU1 Digital Temperature Sensor
P1_PECI_Value	Temperature of the CPU1 Platform Environment Control Interface
SYS_Air_Inlet	Sensor located on the Front Panel Board
MB_Air_Inlet	Temperature of the M/B Air Inlet Area
SYS_Air_Outlet	Temperature of the System Air Outlet Area
LAN_X550_Temp.	Temperature of the LAN X550 Chip
PCH_Temp	Temperature of the PCH
P0_MOSFET_Temp	The Max Temperature of CPU0 MOSFET
P1_MOSFET_Temp	The Max Temperature of CPU1 MOSFET
P0_DIMM_MOSFET_1	The Max Temperature of P0 DIMM Area1 MOSFET
P0_DIMM_MOSFET_2	The Max Temperature of P0 DIMM Area2 MOSFET
P1_DIMM_MOSFET_1	The Max Temperature of P1 DIMM Area1 MOSFET
P1_DIMM_MOSFET_2	The Max Temperature of P1 DIMM Area2 MOSFET
P0_DIMM_CH_A_Max	The Max Temperature of CPU0 DIMM A Slot
P0_DIMM_CH_B_Max	The Max Temperature of CPU0 DIMM B Slot
P0_DIMM_CH_C_Max	The Max Temperature of CPU0 DIMM C Slot
P0_DIMM_CH_D_Max	The Max Temperature of CPU0 DIMM D Slot
P0_DIMM_CH_E_Max	The Max Temperature of CPU0 DIMM E Slot
P0_DIMM_CH_F_Max	The Max Temperature of CPU0 DIMM F Slot
P1_DIMM_CH_A_Max	The Max Temperature of CPU1 DIMM A Slot
P1_DIMM_CH_B_Max	The Max Temperature of CPU1 DIMM B Slot
P1_DIMM_CH_C_Max	The Max Temperature of CPU1 DIMM C Slot
P1_DIMM_CH_D_Max	The Max Temperature of CPU1 DIMM D Slot
P1_DIMM_CH_E_Max	The Max Temperature of CPU1 DIMM E Slot
P1_DIMM_CH_F_Max	The Max Temperature of CPU1 DIMM F Slot
GPU0_Core0_Temp	Temperature of GPU0 Core0 Slot
GPU0_Core1_Temp	Temperature of GPU0 Core1 Slot
GPU1_Core0_Temp	Temperature of GPU1 Core0 Slot
GPU1_Core1_Temp	Temperature of GPU1 Core1 Slot
GPU2_Core0_Temp	Temperature of GPU2 Core0 Slot
GPU2_Core1_Temp	Temperature of GPU2 Core1 Slot
GPU3_Core0_Temp	Temperature of GPU3 Core0 Slot
GPU3_Core1_Temp	Temperature of GPU3 Core1 Slot
GPU4_Core0_Temp	Temperature of GPU4 Core0 Slot
GPU4_Core1_Temp	Temperature of GPU4 Core1 Slot

GPU5_Core0_Temp	Temperature of GPU5 Core0 Slot
GPU5_Core1_Temp	Temperature of GPU5 Core1 Slot
GPU6_Core0_Temp	Temperature of GPU6 Core0 Slot
GPU6_Core1_Temp	Temperature of GPU6 Core1 Slot
GPU7_Core0_Temp	Temperature of GPU7 Core0 Slot
GPU7_Core1_Temp	Temperature of GPU7 Core1 Slot
SYS_FAN_1	Fan speed of SYS_FAN_1
SYS_FAN_2	Fan speed of SYS_FAN_2
SYS_FAN_3	Fan speed of SYS_FAN_3
SYS_FAN_4	Fan speed of SYS_FAN_4
SYS_FAN_5	Fan speed of SYS_FAN_5
SYS_FAN_6	Fan speed of SYS_FAN_6

NOTE

Appendix IV: FRU Parts Table

FT77D-B7109 FRU Parts				
Item	Model Number	Part Number	Picture	Description
PCBA	M2215-L8-1F	411T56800021		M2215-L8-1F for FT77D
PCBA	M5539-2E	411T55200017		
PCBA	M2093	411T57200025		
PCBA	M1284F77D-BP12E-14 FRU-RC-0550	411T56800058		
Cable	FRU-CS-0750	422T57000005		SGPIO Cable
Cable	FRU-CS-0740	422T56800007		80-80 pin Oculink cable
Cable	FRU-CS-0830	422T56800001		Mini-SAS to 80 pin OcuLink cable
Cable	FRU-CS-0620	422T38700001		SATA cable
Cable	FRU-CS-0330	332810000514		A/C Power Cord, L=1800mm, US type
Cable	CCBL-0300	332810000281		A/C Power Cord, L=1830mm, EU type
Cable	CCBL-146H	422T86600003		PCIe 6-pin, For GPU
Cable	CCBL-146I	422T86600004		PCIe 8-pin, For GPU
Cable	CCBL-1086	422T97000006		CPU 8-pin, For GPU
Cable	FRU-CS-0630	422T53400011		MINI-SAS CABLE, 1000mm
Cable	FRU-CS-0270	422T53400006		MINI-SAS CABLE, 800mm
Cable	FRU-CS-0640	422T55600004		MINI-SAS CABLE, 600mm

Power Supply	FRU-PS-0020	471100000246		Delta, DPS-1600CB A, (00F), 1600W
FAN	FRU-TS-0040	5412T4760009		120*120*38MM w/ holding bracket
Rack Mounting Kit	FRU-AS-0050	452T52800001		Slide Rail Kit
Mounting Ear Kit	FRU-SO-0130	452T57700001		MOUNTING EAR KIT WITH Right and left EAR
CPU Heatsink	FRU-TH-0220	343T56600001		647-2U-NARROW-PASSIVE HEATSINK, 1A0-D042800991, 108.0X78.0X64.0MM, SCREW
GPU bracket	FRU-SO-0050	5412T5060005		For Intel Xeon Phi brackets(w/screws)
Air duct	FRU-TA-0060	343T56800003		
Mezz card	M7059F77A-FDR-2 FRU-RC-0011	5412T5680006		PCBA w/ associate tray
	M7059F77A-X540 FRU-RC-0031	5412T5680008		PCBA w/ associate tray
	M7059F77A-I350 FRU-RC-0041	5412T5680007		PCBA w/ associate tray
	M7077-B810-2F FRU-RC-0520	5412T5680009		PCBA w/ associate tray

Appendix V: Technical Support

If a problem arises with your system, you should first turn to your dealer for direct support. Your system has most likely been configured or designed by them and they should have the best idea of what hardware and software your system contains. Hence, they should be of the most assistance for you. Furthermore, if you purchased your system from a dealer near you, take the system to them directly to have it serviced instead of attempting to do so yourself (which can have expensive consequence).

If these options are not available for you then MITAC COMPUTING TECHNOLOGY CORPORATION can help. Besides designing innovative and quality products for over a decade, MITAC has continuously offered customers service beyond their expectations. TYAN's website (<http://www.tyan.com>) provides easy-to-access resources such as in-depth Linux Online Support sections with downloadable Linux drivers and comprehensive compatibility reports for chassis, memory and much more. With all these convenient resources just a few keystrokes away, users can easily find their latest software and operating system components to keep their systems running as powerful and productive as possible. MITAC also ranks high for its commitment to fast and friendly customer support through email. By offering plenty of options for users, MITAC serves multiple market segments with the industry's most competitive services to support them.

Please feel free to contact us directly for this service at tech-support@tyan.com

Help Resources:

1. See the beep codes section of this manual.
2. See the TYAN's website for FAQ's, bulletins, driver updates, and other information: <http://www.tyan.com>
3. Contact your dealer for help before calling TYAN.

Returning Merchandise for Service

During the warranty period, contact your distributor or system vendor FIRST for any product problems. This warranty only covers normal customer use and does not cover damages incurred during shipping or failure due to the alteration, misuse, abuse, or improper maintenance of products.



NOTE:

A receipt or copy of your invoice marked with the date of purchase is required before any warranty service can be rendered. You may obtain service by calling the manufacturer for a Return Merchandise Authorization (RMA) number. The RMA number should be prominently displayed on the outside of the shipping carton and the package should be mailed prepaid.

TYAN will pay to have the board shipped back to you.

TYAN® FT77D-B7109 Service Engineer's Manual V1.0a

Document No.: D2381-100