

Isco 2102 Wireless Module

Remote data retrieval eliminates repeated manhole entry

The 2102 Wireless Module reduces the need for confined space entry in sewer flow studies by providing remote data retrieval from monitoring instruments. Simply clip the 2102 onto one or more 2100 Series flow modules to form a complete, integrated system for acquiring and communicating open channel flow data.

The 2102 uses spread-spectrum digital radio for direct, reliable, two-way communication between down-hole equipment and a laptop computer in your vehicle.

You can retrieve data from the safety and comfort of your vehicle by simply returning to within range of the monitoring site and interrogating the instruments via a 2102 connected to your laptop computer (running Flowlink software). A single worker can safely and easily perform monitoring tasks that may otherwise require a hazardous entry crew of three or more.

The 2102 can also be interfaced with Isco 6700 Samplers, 4200 Series Flowmeters, and 4100 Series Flow Loggers, providing great versatility for labor saving “drive-up data retrieval” in I&I, CSO, SSO, stormwater, and other projects. The 2102 also avoids the monthly expense of using cellular phones and the hassles of conventional radio technology.

Standard Features

- ◆ “Plug and Play” setup – no special engineering or interfacing needed.
- ◆ Rugged NEMA 4x, 6P (IP68) case.
- ◆ When using the standard internal antenna, all equipment can be hidden in the manhole.
- ◆ Low power consumption, allowing a typical 50-day battery life using two 6-Volt alkaline batteries.



The 2102 wireless module stacks with 2100 Series flow modules and 2191 Battery Modules to provide a compact, integrated system for collecting and retrieving sewer flow data without repeated manhole entry.

Applications

- ◆ Efficient and reliable drive-up data retrieval and site service in I&I and other collection system studies.
- ◆ Above-ground applications requiring line-of-sight communication from remote monitoring sites to base station.



There's no need to get out of the vehicle into bad weather or busy traffic when retrieving data with the 2102 base module.

Specifications

2102 Wireless Communication Module	
Size (H x W x D)	2.2 x 11.3 x 7.5 in (5.4 x 28.7 x 19.1 cm)
Weight	2.0 lbs (0.9 kg)
Enclosure (self-certified)	NEMA 4X, 6P (IP68)
Material	High-impact polystyrene
Carrier Detect Cycle	4 minutes
Average Connect Time	2 minutes
Power	10 to 16.6V DC <1 mA standby, 300 mA maximum 5 mA average at 4 minute power cycle
Typical Battery Life	50 days (with 2 alkaline batteries)
Operating temperature	0° to 140°F (-18° to 60°C)
Storage temperature	-40° to 140°F (-40° to 60°C)
Software	Serial Connection to IBM PC or compatible computer with Isco Flowlink Software (version 4.11 or above)
2191 Battery Module	
Size (H x W x D)	6.0 x 9.6 x 7.6 in (15.2 x 24.4 x 19.3 cm)
Weight (w/o batteries)	3.2 lbs (1.4 kg)
Enclosure (self-certified)	NEMA 4X, 6P (IP68)
Material	High-impact polystyrene
Batteries	Two 6V alkaline lantern or lead-acid lantern
Alkaline Capacity	25 A/hrs
Lead-Acid Capacity	5 A/hrs

Spread Spectrum Radio	
Frequency	902 to 928 MHz
Transmitter	
Output Power	1 Watt
Typical Range line of sight from inside manhole	0.5 miles (0.8 km) 100 ft (30 m)
Modulation, GFSK	120 kBs – 170 kBs
Occupied bandwidth	230 kHz
Receiver	
Sensitivity	-108dBm at 10-6 raw BER (bit error rate)
Selectivity	40 dB at fc ± 230 kHz 60 dB at fc ± 460 kHz
Data Transmission	
Error Detection	32 Bit CRC, resend on error
Data Encryption	Substitution, dynamic key
Link Throughput	115 kBaud
FCC Identifier	KNY-205-108213
DOC (Canada) Identifier	2329 102 336A

Ordering Information

Note: 2102 Modules are available for use in the USA and Canada ONLY.

Description	Part Number
2102 Wireless Remote Module Stacks on 2100 monitoring system to provide two-way communication with 2102 base module (sold separately). Includes manual.	68-2000-003
2102 Wireless Base Module Connects to computer running Flowlink software for communication with 2102 remote modules. Includes power adapters for 12V DC vehicle cigarette lighter, and 120V. Requires Flowlink software and computer connect cable, sold separately. Includes manual.	68-2000-002
Computer connect cable Connects 2102 module to PC with 9-pin connector.	60-2004-046



Contact the factory for 2102 external antenna options. Above: 2102 with captive connector for external antenna of any type. Below: 2102 with directional antenna.



4700 Superior Street
Lincoln NE 68504 USA
Tel: (402) 464-0231
USA and Canada: (800) 228-4373
Fax: (402) 465-3022
E-Mail: iscoinfo@teledyne.com
Internet: www.teledyneisco.com