

NITECORE®
www.nitecore.com

SYSMAX Ind.

SYSMAX Industry Co.,Ltd.
Rm 2601-06, Central Tower, No.5 Xiancun Road, Tianhe District,
Guangzhou, 510623, Guangdong, China
Tel: +86 20 83862000 Fax: +86 20 83882723
E-mail: info@nitecore.com

NITECORE®

2018

KEEP INNOVATING

NITECORE®

**PRODUCT
CATALOGUE**
UPDATED IN JAN. 2018






PHOTO CREDITS

Tactical Two
Lee McGrath
José Miguel Martínez
Alexander Morris
Sirio Sechi
Darren White

KEEP INNOVATING

CONTENTS

Scenarios	2
About NITECORE	4
Patent	6
Awards	8
Knowledge	10
Lighting	18
— Tiny Monster Series	20
— Precise Series	24
— Smart Ring Tactical Series	28
— Chameleon Series	32
— Rechargeable Series	36
— Multitask Hybrid Series	38
— Multi-Task Series	42
— Explorer Series	46
— T Series	50
— NU Series	54
— Headlamp Series	58
— Lantern Series	62
— Explosion-Proof Series	66
— Diving Light Series	70
— Bike Light Series	71
— Concept Series	72
— GEM Series	74
— Hunting Kits	75
Charger	76
Accessory	86
Specifications	94

WHEN THERE IS DARKNESS THERE IS A NITECORE LIGHT

NITECORE LED lights have become standard equipments for military and law enforcement in various countries, whilst being favored by outdoor enthusiasts, which are ideal for outdoor adventures, law enforcement, trail running, industrial lighting and more.



Hiking/Trekking

Generally, lights for hiking not only require high output but also light weight, long duration and reliability. For team leaders, high output and far-reaching spotlights help to see the path ahead, and a red caution light helps team members to find you.

Recommended models : NU10, NU30, HA20, HA40



Running

For long distance running, runners may prefer a lightweight headlamp with flood light and long runtime. High output and red caution light are required when necessary. For those who enjoy leisurely urban night running, a portable and high performance headlamp ensures their safety in running.

Recommended models : NU05, NU20/NU20 CRI, NU25, NU30



Camping

For camping, a lightweight and portable lantern with a loop or magnetic base may be the most convenient to set hands free. Besides high output, it also requires soft beam with high colour rendering index, long duration and more.

Recommended models : LA10/LA10 CRI, LR10/LR10 PANDA, LA30, LR30



Climbing

Considering the harsh environment on high altitude, a headlamp with high intensity, long runtime and grand throw is essential. For freezing environments, low temperature resistance is required to maintain stable performance of lights. Hands-free and lightweight products are more popular.

Recommended models : HC30, HC33, HA40, HC60, HC65, HC70



Caving

Due to the dangerous and low-light environment in cave, high output lights are required for caving. Since there is water in cave and the temperature is low, low temperature resistance and waterproofness are necessary. Ruggedness are also paramount.

Recommended models : HC30, HC33, HC65, HC70, EF1, EH1



Search & Rescue

For search and rescue, a lighting tool should preferably have blinding lumens, superb beam distance as well as long runtime. Qualities like portability, ruggedness and light weight are also a plus.

Recommended models : TM28, TM38, MH23, TM26GT, EA81, R40, EC4SW, HC33, HC70



Tactical

As a simple and intuitive UI is most important in tactical lights, Strobe Ready™ definitely meets the need. Besides, it requires high output and tactical defense function. Using with bezel, tactical ring, gun mount and remote switch to enhance the tactical function overall.

Recommended models : SRT7GT, SRT9, P20UV, P20, CI6, MT1U, P10GT, P05, MH12GT



Law Enforcement

For law enforcement applications, the lighting tools should have high output, long runtime and direct access to strobe. This kind of lighting tool should be highly reliable in resisting dust, water and shocks, and should be tough enough to confront contingencies.

Recommended models : MH27, TM03, P20UV, MH20GT, R25, R40, SRT7GT



Hunting

A hunting light should have high output with optimal beam distance to ensure long range visibility. Light weight, compatibility with shotguns, ability to absorb recoil are also required. Colored outputs are preferred to preserve users' night adapted vision, or to not startle the preys.

Recommended models : P30, MH25GT, P16TAC, CR6, CG6, MH40GT, MT40GT



Industrial workplace

Rechargeable lights are usually welcomed by industrial workers due to better cost performance. Hands-free capability, portability, an intuitive user interface are required to ensure convenience. For hazardous industries like mining or oil extraction, explosion-proof lights are mandatory.

Recommended models : EF1, EH1, EH1S, HC30, TM26GT, TM38



EDC

EDC(everyday carry) is designed to be carried with you everyday, thus it must be ultra-compact, lightweight, and always works when you need it. It does not require multiple choices of brightness level, whilst sufficient runtime and easy operation are necessary.

Recommended models : TINI, TIP2017/TIP SS, P05/P05PINK, P10GT, P12GT, MT2A, EC11, EA11, EC20, SRT3, Concept 1



Cycling

Lighting with capability to illuminate blind spot ahead or under foot is essential to ensure safety in cycling. Features like multiple modes for different riding conditions, easy to operate, install or remove, flexible charging options, compatibility with handlebars of various sizes also add up to a great bike light. A rear caution light is also necessary for maximum attention and safety.

Recommended models : BR35, NU05, BM02, P12GT



Fishing

Hands-free capability is paramount. Colored outputs are inconspicuous, especially blue light. Blue light will not alarm underwater wildlife, and is able to attract some fishes, activate fluorescence of the float, which is why it is well received by fisherman or fishing enthusiasts.

Recommended models : SRT7GT, SRT9, CB6



Diving

A flashlight for diving needs to be totally waterproof and reliable, with high output, sufficient duration and flexibility. It is better to have a lanyard in case of loss. Red output is a plus for it serves as a supplementary lighting underwater.

Recommended models : DL10



Photography

Full area coverage uniform lighting with color rendering capability is best for photography. Multiple output choices allowing for adjusting lighting according to ambient environment are also required. Portability, compatibility with tripods and colored outputs are a plus.

Recommended models : GP3, GP3CRI, LR30, EC4SW, TM28

ABOUT NITECORE

Since its inception in 2007, NITECORE has long been on top of the hierarchy in the LED lighting and battery charger markets backed by the tremendous innovation competences it masters. NITECORE's products are some of the most sought after in America, Europe, Middle East and Oceania totaling over 100 countries.

NITECORE has a R&D team commanding excellent critical thinking competency and ideas generation, which forms the backbone of the company that harvested various invention patents, iF Design Award, Red Dot Design Award, Good Design Award and ISPO Award.

Operating in full compliance with ISO9001, NITECORE's factories have set the most exacting production and testing standards to ensure quality and performance. All products are certified by CE, RoHS, FCC, CEC, REACH, KC or C-TICK. All batteries and chargers are globally insured by Ping An Insurance Group.

2004

LR7 - One of the first high-intensity LED flashlights made in China

2005

Luxeon - The first branded Chinese 3W LED flashlight.

2006

One of the first flashlights that adopts a HA-III finish.

2007

MK2 - The first AA-based flashlight that features an integrated MCU.

2008

ND1 - The world's first AA-based flashlight that features Infinitely Variable Brightness.

2009

D10 - The world's first flashlight that features Smart PD (Piston Drive) System.

2010

IFE1 - The first flashlight that features Magnetic Sensor IBS System.

2011

TM11 - The world's smallest and lightest 2000-lumen flashlight.

2012

EA4 - 4xAA Compact Searchlight

2013

SRT7 - The world's first line of flashlights that features third generation SSR (smart selector ring) technology

2014

CR6 - The only one flashlight available with white light and powerful 3000mW red LEDs

2015

EC4S - ISPO Award WINNER of 2015/2016

2016

reddot award 2016 winner

MH27 - The first USB rechargeable, tri-colored tactical flashlight to win Red Dot Award: Product Design

2017

GOOD DESIGN
ISPO AWARD

LA10/LA10 CRI - The world's first magnetic lipstick-shaped mini lantern wins iF DESIGN AWARD, GOOD DESIGN AWARD and ISPO Award

2018

Concept 2 GEM8UV

PATENT ➤➤➤


With advanced technologies and technical personnel, NITECORE has been keeping innovating for over the years and has harvested over one hundred invention patents and utility model patents.



THE INDUSTRY'S FIRST FLASHLIGHT UTILIZING INDUCTIVE CHARGING TECHNOLOGY




INNOVATIVE STROBE READY™ SYSTEM



INNOVATIVE ACTIVE DIMMING TECHNOLOGY (ADT)

INNOVATIVE MULTIMETER FUNCTIONALITY



INNOVATIVE INTEGRATED DUAL PICATINNY RAIL CONNECTORS




INNOVATIVE MULTI-OUTPUT FLASHLIGHT SERIES



THE FIRST HEADLAMP FEATURING A MAGNETIC SLIDING SWITCH AND INFINITELY VARIABLE BRIGHTNESS



INNOVATIVE UNIQUE INTEGRATED TECHNOLOGY (UIT)



INNOVATIVE TWO STAGE SWITCH

INNOVATIVE FIXABLE/360° ROTATABLE FLASHLIGHT HOLSTER



ALL-IN-ONE HIGHLY COMPATIBLE AND INTELLIGENT CHARGER SERIES



INNOVATIVE 360° ROTATABLE SPHERICAL AXIS DESIGN



PRODUCT AWARDS >>>

Established in 2007, NITECORE has long been at the forefront of technological advancement in portable illumination. Through its tremendous research and development capacity, the brand has harvested numerous global awards including the industrial design "Oscar" iF Design Award, Red Dot Design Award, Good Design Award and ISPO Award. NITECORE products are internationally recognised in over 100 countries.

 **LA10 CRI**

 **R25**

 **EC4S**

Good Design Award

ISPO Award

iF Design Award

85 Lumens

 **CR6**

800 Lumens

iF Design Award 2017

 **MH27**

1000 Lumens

2016 Red Dot Award: Product Design

 **Concept 1**

2150 Lumens

ISPO AWARD WINNER

 **NU05**

440 Lumens

ISPO Award Gold Winner

 **NU05**

35 Lumens

Headlamp Mate

China Good Design Award

 **EA41**

1800 Lumens

MH27UV/TIP2017CRI
2017
www.everydaycarry.com
Everyday Carry Reader's Choice



SRT9/LA10/LA10CRI
2017
www.everydaycarry.com
Everyday Carry Staff Picks



MT1U
2017
www.vergleich.org
BEST UV Flashlight of 2017



BP20
2017
Winner of Small Backpacks
of TACTICAL GEAR Magazin



TIP
2017
www.vergleich.org
BEST MINI Flashlight of 2017



SC2
2016
www.vaping360.com
Best Two Bay Charger for Vaping



D4
2016
www.vapinginsider.com
Best Vape Battery Charger



TUBE
2015
www.everydaycarry.com
The best flashlight for EDC



HC30
2015
www.nightphotographyworkshop.com
The Best Headlamp for Night Photography



SRT7
2014
China outdoor gears: Top Pick



EA41
2014
China outdoor gears:
Best in class



TM26
2014
Xingshi Cup industrial design:
Best appearance design



SRT7
2013
Bushcraft and survival skills magazine:
Best in test



HC50
2013
China outdoor gears:
Best in class annual award



WHAT IS AN LED ? ➤➤➤

LED is an acronym for Light Emitting Diode – a special type of semiconductor that was initially used to replace standard lamps in early electronic equipment, later progressing to consumer electronics in the form of VCR and calculator displays. With the advance of technology, LED can be used as a light source with a general life expectancy of 50,000 hours or even 100,000 hours. In addition, LED features the advantages of energy saving and environmental protection, small size and long lifespan, and can be applied in harsh environments.

LEDs' advantages:

Energy Conservative

LEDs convert approximately 20% of their input power into light energy, whilst traditional incandescent bulbs generally only convert about 2% of their input power into light. As a result LED technology offers excellent energy efficiency, making it a cost effective and environmentally-friendly solution for modern light-emitting devices.

Longevity

Conventional incandescent technology is based on electron's travel through a tungsten filament, causing the filament to generate temperatures up to 2,500 degree Celsius, with light energy merely a byproduct of this process. Due to this inherently inefficient mechanism, incandescent bulbs rapidly deteriorate and burn out after about 1,000 hours of use. LEDs, on the other hand, operate on an entirely different principle. While they do require specialized components to achieve maximum brightness, a working lifespan up to 50,000 hours is possible, with a gradual fading of brightness rather than instant burn-out.


Durability

Due to the absence of a delicate filament and thin glass bulb, LEDs can withstand shock and vibration far stronger than incandescent lamps, making them ideal for rugged and demanding applications.



Quick Activation

An incandescent bulb generally takes about 100-300 milliseconds to illuminate once activated, while an LED needs only a few nanoseconds, giving it a significant advantage in highly demanding applications.



NITECORE's Proprietary LED Technology...


NITECORE's highly efficient, ultra reliable proprietary LED drive circuit plays a crucial role in efficiently transferring battery power to the LED. As a result, all NITECORE products have exceptional output and long runtimes in comparison to competing products. While the majority of LED-based flashlight/personal lighting products on the market today suffer from continuously declining output, NITECORE products are able to maintain constant high output until battery exhaustion.



ADVANCED CIRCUITRY >>>

NITECORE's proprietary regulation circuit is an essential component in every NITECORE flashlight. The circuit's unique power source management system delivers constant current to the LED regardless of battery condition/chemistry, resulting in continuous, unwavering light output for end users. The circuit's efficiency and reliability is further enhanced by carefully engineered electronic components such as gold or silver plated contact points. Moreover, every NITECORE flashlight features an integrated microcontroller unit which works in tandem with the regulation circuit to offer an intuitive and versatile user-interface.

An LED drive/regulation circuit is crucial in improving the efficiency of the 'power to light' conversion process, allowing for longer runtimes and more stable operation using various battery chemistries. NITECORE's highly reliable and compact drive circuit is the reason why NITECORE flashlights run longer and shine brighter than the competition.




Lens and Reflectors

With many years of experience in flashlight optical design, NITECORE's custom-engineered high-efficiency alloy reflectors ensure every flashlight emit a balanced beam profile of both flood and throw with minimal loss of light. All NITECORE reflectors are protected by AR-coated, anti-scratch mineral glass lenses.




Precision Digital Optics Technology

PDOT utilizes digital simulation and precise point-to-point curved reflecting methods to optimize reflector performance. This ensures a more consistent, uniform and far-reaching beams capable of illuminating targets at distance.




COLOR RENDERING INDEX(CRI) >>>

The Color Rendering Index (CRI) is a scale from 0 to 100 percent indicating how a light source makes the color of an object appear to human eyes, and how well subtle variations in color shades are revealed. Light sources with a high CRI are more likely to reveal the original colors of the object, thus becoming more desirable in the market since they can reduce eye strain and give a vibrant view.



CRI Value 90



CRI Value 70

NITECORE lights with high CRI: LA10CRI, LA30, LR10, LR30, TM03CRI, TIPCRI, NU20CRI, NU30



NEUTRAL WHITE >>>

LED color temperatures can be divided into white light (about 6500K), neutral white (about 4000K) and warm white (about 3000K). Neutral white lighting strikes the perfect balance: it has high CRI ability and reduces eye strain, making it extremely easy for the users to see every detail of the object. Neutral white's relatively low color temperature and long wavelength allow it to further penetrate rainy and foggy weather, and its high luminous efficiency also saves battery power. That's why harsh outdoor situations require neutral white lights.

NITECORE neutral white lights: HC30W, MH12W, MH20W, EH1W, EH1SW, EC4SW, EA81W, EA41W



UTRAVIOLET LIGHT >>>

A UV light is a lamp that emits ultraviolet beams and not much visible light. UV light has shorter wavelengths than visible light, and is also known as black light. Ultraviolet LED flashlights are useful in many applications, including identifying forged documents, tracing marked bills, leakage/grease inspection, sanitary check, hunting scorpions etc.

NITECORE UV lights: P20UV, CU6, MH27UV, TUBE UV, THUMB LEO, MT1U



DIE-CASTING ➤➤➤

NITECORE is the first manufacturer to incorporate die casting into the making of a flashlight. This manufacturing process gives a flashlight a significant reduction in weight and size, and an increase in solidity and heat dissipation. Die-cast flashlights are extremely lightweight, compact and robust. Take the EC4 as an example, it is 37% smaller and 30% lighter than products of similar functionality and yet has 200% the strength of an ordinary CNC machined rival. By employing new techniques/technologies, NITECORE has always been innovating to offer significant gains in both ruggedness and performance.



BILLET ALUMINUM BODY ➤➤➤

Most of the NITECORE flashlights are constructed from lightweight, high strength aerospace grade aluminum alloy. Additionally, the majority of NITECORE models are CNC machined from a solid aluminum bar. This manufacturing process gives NITECORE flashlights their superior impact resistance. Many lights are able to withstand being rolled over by car or dropped from several meters onto a hard surface with no performance loss (not recommended as doing so may void warranty). Compared to other similar tubular aluminum flashlights, NITECORE flashlights offer significant strengths in both rigidity and performance. Furthermore, most of the NITECORE models are treated with a military-spec HAlII hard anodized finish, making the flashlight surface as tough as a diamond, thus protecting it from scratches, abrasions and corrosion.

LIGHTING



TINY MONSTER SERIES

All of our groundbreaking Tiny Monster models have thoroughly changed the way people think about portable lights, and more importantly, what they actually carry and use. Created for search and rescue as well as outdoor adventures, our Tiny Monster series is now employed in countless professional applications where bright lighting is needed.



Outdoor



Search & Rescue



PRECISE SERIES

NITECORE Precise Series flashlights are highly innovative illumination tools purpose-designed for law enforcement, hunting and tactical applications. With incredible user-interface design, these lights allow easy access to all modes and brightness levels. With blazingly bright output in turbo/strobe mode, exceptionally long runtimes in low mode and unique gun-mounting functionality, the Precise series flashlights are the ultimate lighting tools for increased tactical effectiveness.



Law Enforcement



Tactical



Hunting



As a representative of compact tactical flashlights, P12GT is ideal for EDC, searching and tactical applications. P12GT emits a superb beam distance and doubled intensity made possible by the revolutionary SC5 technology on the CREE XP-L HI V3 LED. Its max output is 1000 lumens and beam distance up to 320 meters. The side switch and tactical tail switch allows for all-rounded tactical operation.



Front-facing tactical switch for your precise
momentary/constant illumination



Side switch for your quick selection of various modes and brightness levels



- Compact and streamlined design

- HAlII hard anodizing

Output & Runtime



Law Enforcement



Tactical

Chosen by military and law enforcement personnel in the domestic and overseas

- ◆ Strobe Ready™
- ◆ 3 Modes
- ◆ One-handed Operation

P20

CREE XM-L2 (U2) LED
1×18650 Battery
2×CR123 Batteries

800 Lumens

As an intuitive and precise tactical flashlight with maximum 800 lumens, P20 allows for easy one-handed operation and comes with three modes, including tactical mode, law enforcement mode and general mode. Strobe can be accessed instantly via the Strobe Ready™ switch in any state. The crenulated bezel serves as an effective tool in emergency situations, and it is compatible with multiple tactical accessories, which makes P20 the best choice for tactical and law enforcement applications.



Tactical mode



Law enforcement mode



General mode



STROBE READY™
access Strobe mode in any state

The Strobe Ready™ is designed with the lever principle, providing a maximum ease of use with glove.

For P20/P20UV

**P20UV**

365nm Ultraviolet Light
CREE XM-L2 U2 LED
1×18650 Battery
2×CR123 Batteries

800 Lumens**320** mW

P20 Output & Runtime

FLI STANDARD	HIGH	MID	LOW	STROBE
	800 lumens	290 lumens	40 lumens	800 lumens
	4h30min	9h	26h	—
	210m	126m	47m	—
	1100cd	4000cd	550cd	—
	1.5m (Impact Resistant)			
	IPX8, 2m (Waterproof And Submersible)			

PRECISE SERIES

NEW PRODUCT

**P12GTS** CREE XHP35 HD LED
1×18650 Battery
2×CR123 Batteries**1800** Lumens**223** Meters

NEW PRODUCT

**P16 TAC** CREE XM-L2 (U3) LED
1×18650 Battery
2×CR123 Batteries
1000 Lumens


NITECORE®

NEW PRODUCT

**P10GT** CREE XP-L HI V3 LED
1×18650 Battery
2×CR123 Batteries**900** Lumens**286** Meters**P05/P05 PINK** CREE XM-L2 (U2) LED
1×CR123 Battery
1×RCR123 Battery
460 Lumens**P30** CREE XP-L HI V3 LED
1×18650 Battery
2×CR123 Batteries**1000** Lumens**618** Meters**P36** CREE MT-G2 LED
2×18650 Batteries
4×CR123 Batteries
2000 Lumens**P12** CREE XM-L2 U2 LED
1×18650 Battery
2×CR123 Batteries
1000 Lumens

SMART RING TACTICAL SERIES

NITECORE's new SRT series is the world's first line of flashlights to feature third generation SSR (smart selector ring) technology, offering infinitely variable brightness adjustment and unprecedented ease of use. The SSR interface allows users to select modes and brightness levels by simply rotating a smooth magnetic ring. This industry leading design is both user-friendly and extremely durable, making it ideal for law enforcement and tactical applications. The SRT series is yet another example of NITECORE innovation.



NITECORE®



Outdoor



Law Enforcement



Tactical



NEW PRODUCT

SRT9 CREE XHP50 LED
2×18650 Batteries
4×CR123 Batteries

2150 Lumens

SRT9 is capable of emitting 2150 scorching lumens and throwing 246 meters in Turbo. The 3rd generation smart selector ring technology offers swift access to infinite brightness levels and special modes with a simple twist. SRT9 has a white light and RGB/UV auxiliary lights for various scenarios. The die-cast unibody construction makes it more compact, lightweight and have better heat dissipation to cope with complicated scenarios.

◆ **2150 Lumens**

◆ **4 colored LEDs**

◆ **Die-cast Unibody**

◆ **The 3rd Generation Smart Selector Ring**



FLI STANDARD	TURBO	ULTRALOW	RED	GREEN	BLUE	UV	BEACON	POLICE WARNING SIGNAL	STROBE
	2150 lumens	0.1 lumen	13 lumens	19 lumens	3 lumens	--	2150 lumens	--	2150 lumens
	1h 18650	1h 15min	250h	50h	48h	48h	48h	55h	--
	246m	--	12m	15m	2m	--	--	--	--
	15100cd	--	35cd	55cd	2cd	--	--	--	--
	1.5m (Impact Resistant)								
	IPX8, 2m (Waterproof And Submersible)								

Output & Runtime

SMART RING TACTICAL SERIES

NEW PRODUCT



SRT7GT CREE XP-L HI V3 LED
1×18650 Battery
2×CR123 Batteries

1000 Lumens

- ◆ Grand Throw: 450m
- ◆ 4 Colored LEDs
- ◆ The 3rd Generation Smart Selector Ring

SRT7GT is a high output tactical flashlight with multi-colored LEDs. The CREE XP-L HI V3 LED integrated the groundbreaking SC5 technology, significantly to throw a beam distance up to 450 meters. The third generation Smart Selector Ring offers swift access to various brightness levels and functions, providing an enjoyable control in tactical operation.




Output & Runtime

FLI STANDARD	TURBO	ULTRALOW	RED	GREEN	BLUE	UV	STROBE	BEACON	POLICE WARNING SIGNAL
	1000 lumens	0.1 lumen	13 lumens	19 lumens	3 lumens	--	1000 lumens	1000 lumens	--
	1h 15min	240h	28h	26h	26h	26h	26h	--	32h
	450m	7m	8m	13m	3m	--	--	--	--
	50900cd	13cd	17cd	42cd	2.2cd	--	--	--	--
	1.5m (Impact Resistant)								
	IPX8, 2m (Waterproof And Submersible)								



Defender SRT3 CREE XM-L2 U2 LED
1×RCR123 Battery
1×CR123 Battery
1×AA Battery


550 Lumens



Smart Selector Ring

SRT3 features two colored LEDs





CHAMELEON SERIES

The Chameleon series is yet another unique and innovative offering from NITECORE. Featuring two main LEDs, one white and the other a choice of Red, Green, Blue, Ultraviolet or Infrared, Chameleon flashlights offer incredible versatility for a wide range of applications. Chameleon flashlights also include two smaller secondary LEDs which provide lower output red, green or blue for extended runtimes. Furthermore, a newly-designed double side-switch interface with integrated power indicator light allows one-handed operation while providing easy access to brightness levels and functions, including a unique multi-colored warning / hazard mode which rapidly alternates between red, green and blue. The industry-leading design of the Chameleon series is another proof of NITECORE's capacity for innovation.

NITECORE®

Hunting **Law Enforcement** **Tactical**




CU6 is the first tactical flashlight that combined white light with high-power ultraviolet. In addition to its main LED with 440 lumens, CU6 also has a 365nm ultraviolet LED that projects a powerful 3000mW ultraviolet beam. The UV light can stimulate fluorescent material in the dark environments, making it ideal for fishing and hunting, documents authentication and identifying evidence for crime scene investigations and more.

CHAMELEON SERIES

- ◆ **4 Light Sources**
- ◆ **Dual Side Switches**
- ◆ **Tail Switch**

A powerful 3000mW ultraviolet LED is controlled via a convenient side switch



Ultraviolet Light: Stimulates fluorescent material in the dark environments, making it ideal for authentication of documents and identifying evidence for crime scene investigations.

Output & Runtime

FLI STANDARD	WHITE LIGHT TURBO	WHITE LIGHT HIGH	WHITE LIGHT MID	WHITE LIGHT LOW	WHITE LIGHT LOWER	UV	RED	GREEN	BLUE	POLICE WARNING SIGNAL	STROBE	SOS	BEACON
	440 lumens	280 lumens	160 lumens	25 lumens	1 lumen	--	1.8 lumens	3.8 lumens	0.7 lumen	--	440 lumens	440 lumens	440 lumens
	1×18650	1h45min	3h30min	7h	43h	400h	4h	65h	73h	82h	90h	--	--
		190m	132m	99m	42m	10m	--	--	--	--	--	--	--
	9000cd	4360cd	2450cd	460cd	28cd	--	--	--	--	--	--	--	--
	1.5m (Impact Resistant)												
	IPX8, 2m (Waterproof And Submersible)												

CHAMELEON SERIES



NITECORE®





RECHARGEABLE SERIES

Rechargeable Series are aimed at your ultimate maneuver. The smart charging docks keep your flashlights always fully-powered for any abrupt cases. With power-boosted dedicated Li-ion batteries, all R Series flashlights are capable of emitting blinding blaze in no time, smashing up darkness and violence for your law enforcement and tactical tasks.

Law Enforcement 

Tactical 

Search & Rescue 



RECHARGEABLE SERIES

R25 CREE XP-L HI V3 LED
1×NL188DW Battery
2×CR123 Batteries
800 Lumens

STROBE READY! ULTIMATE ONE-POINT OPERATION

- ◆ Smart Charging Dock
- ◆ Strobe Ready™
- ◆ Dedicated 18650 Li-ion Battery

As a winner of iF Design Award, R25 is your must-have gear for searching, rescuing and tactical applications, with a max output up to 800 lumens and a beam distance up to 321 meters. 3 modes available for different needs. STROBE READY™ button for quick access to Strobe. A dedicated NL188DW 3200mAh Li-ion battery and a smart charging dock included help you to fight at full power level.



Output & Runtime

FLI STANDARD	HIGH(MODE 1,2,3)	MID(MODE 3)	MID (MODE 2)	LOW (MODE 3)	STROBE
	800 lumens	230 lumens	120 lumens	50 lumens	800 lumens
 1×18650	1h	9h	12h	15h	---
	32lm	165m	126m	69m	---
	25800cd	6800cd	4000cd	1200cd	---
	1.5m (Impact Resistant)				
	IPX8, 2m (Waterproof And Submersible)				

INDUCTIVE CHARGING INDUSTRY PINNACLE

R40 CREE XP-L HI V3 LED
1×NL2650DW Battery
1000 Lumens
520 Meters

INDUCTIVE CHARGING 





MH12GT is a rechargeable grand throw flashlight that emits maximum 1000 lumens and beam distance up to 320 meters. The side switch and tail switch are specially designed for tactical and outdoor applications. An included 18650 Li-ion battery with large capacity and long runtime, which is ideal for hunting, law enforcement, searching and more scenarios.

Output & Runtime



MULTI-TASK SERIES

Multi-Task flashlight series is a line of highly versatile and practical illumination tools designed for a multitude of users and environments. The maximum output ranges from MT1A's 180 lumens to MT40GT's 1,000 lumens. A sleek, robust body finely etched with extensive knurling and a perfect finish is a hallmark of this range, but even more important is the highly practical and usable user-interface which makes selecting modes a breeze. NITECORE MT series flashlights are your ultimate lighting tools for various environments.



Search & Rescue **Outdoor**

Hunting **Tactical** **Industrial workplace** **Law Enforcement** **EDC**

S.O.S **Mountain**

MULTI-TASK SERIES

NEW PRODUCT

MT06MD NICHIA 219B LED
2×AAA Batteries

180 Lumens



- ◆ High CRI Output
- ◆ Default Low Mode
- ◆ Photobiologically Safe(RG0)

Designed for Medical Personnel and First Responders

MT06MD is specially designed for medical personnel and first responders, utilizing a high color rendering (CRI≥90) Nichia 219B LED that resembles the nature of sunlight, thus allowing medical personnel and first responders to see every detail of the object while eliminating the potential of blue-light hazard. The default mode protects human eyes from glare. Three brightness levels are selectable based on different needs, making MT06MD an essential tool for doctors and nurses.

Output & Runtime

FLI STANDARD	HIGH	MID	LOW
	180 lumens	45 lumens	4 lumens
	45min	5h15min	35h
	58m	28m	11m
	860cd	194cd	30cd
	1.5m (Impact Resistant)		
	IPX8, 2m (Waterproof And Submersible)		

Beam Distance: 618m

Simple Operation

Multiple Scenarios

MT40GT CREE XP-L HI V3 LED
2×18650 Batteries
4×CR123 Batteries

1000 Lumens



MT40GT is a versatile searchlight with 1000 lumens output and 618 meters beam distance in Turbo. Turbo mode and user-defined mode can be selected by simply twisting the head. Running on two 18650 batteries and compatible with various tactical accessories, making it easy to cope with different scenarios.

Output & Runtime

FLI STANDARD	TURBO	HIGH	MID	LOW	STROBE	SOS
	1000 lumens	500 lumens	250 lumens	90 lumens	1000 lumens	1000 lumens
 2×18650	2h15min	4h15min	9h30min	31h	--	--
	618m	389m	274m	134m	--	--
	95400cd	37800cd	18700cd	4465cd	--	--
	1.5m (Impact Resistant)					
	IPX8, 2m (Waterproof And Submersible)					

EXPLORER SERIES

The NITECORE Explorer series flashlights are designed with outdoor sportsmen in mind. Utilizing a highly tactile user interface with attractive appearance, these ultra-compact lights, ranging from the thumb-sized EC11 to the 8xAA powered searchlight EA81, are ideal for hiking, camping, searching and caving, providing the avid outdoorsmen with unprecedented output performance and ultimate illumination experience.



EXPLORER SERIES



EC4S CREE XHP50 LED
2×18650 Batteries
4×CR123 Batteries
2150 Lumens

- ◆ 2150 Lumens
- ◆ Die-cast Unibody
- ◆ One-handed Operation

As a winner of ISPO Award, EC4S comes with a small size and outstanding performance, utilizing a CREE XHP50 LED to deliver blinding 2150 lumens. Die-cast unibody makes it lightweight, portable and rugged. Dual switch design provides one-handed operation, which is ideal for trekking, hiking, searching and everyday carry.

Extreme RIGIDITY

By injecting molten aluminum under high pressure into mold cavity, the die casting process ensures each EC4S is made with supreme structural integrity and has 200% the strength of an ordinary flashlight that consists of three separate parts.


200% THE STRENGTH



NITECORE EC4S



An ordinary




ISPO
AWARD
ISPO AWARD

Output & Runtime


FLI STANDARD	TURBO	HIGH	MID	LOW	ULTRALOW	STROBE	SOS	LOCATION BEACON
	2150 lumens	1100 lumens	400 lumens	80 lumens	2 lumens	2150 lumens	2150 lumens	2150 lumens
	2×18650	45min	2h15min	6h15min	30h45min	325h	--	--
		280m	177m	113m	41m	4.8m	--	--
		19600cd	7800cd	3200cd	420cd	5.8cd	--	--
						1.5m (Impact Resistant)		
							IPX8, 2m (Waterproof And Submersible)	



EC4GT CREE XP-L HI V3 LED
2×18650 Batteries
4×CR123 Batteries
1000 Lumens
475 Meters



NITECORE®



NEW PRODUCT

EC23 CREE XHP35 HD E2 LED
1×18650 Battery
2×CR123 Batteries

1800 Lumens

EC23 is designed with the concept of "compact in size while powerful in performance". In such a portable and compact size, it can emit a maximum 1800 scorching lumens. The side switch is specially designed for outdoor applications that controls 5 brightness levels and 3 special modes. Running on one 18650 Li-ion battery with runtime up to 330 hours, it is an ideal tool for general use and outdoor application.

EXPLORER SERIES

- ◆ **1800 Lumens**
- ◆ **Compact**
- ◆ **Single Switch UI**



Output & Runtime

FLI STANDARD	TURBO	HIGH	MID	LOW	ULTRALOW	STROBE	SOS	BEACON
	1800 lumens	980 lumens	300 lumens	55 lumen	1 lumen	1800 lumens	1800 lumens	1800 lumens
	30min	1h15min	4h15min	20h	300h	--	--	--
	255m	165m	87m	35m	5m	--	--	--
	16200cd	6800cd	1900cd	300cd	7cd	--	--	--
	1.5m (Impact Resistant)							
	IPX8, 2m (Waterproof And Submersible)							

EXPLORER SERIES

NEW PRODUCT



EC4GTS CREE XHP35 HD LED

2×18650 Batteries

1800 Lumens

400 Meters

NEW PRODUCT



EA42 CREE XHP35 HD LED

4 × AA Ni-MH Batteries

1800 Lumens

NITECORE®



EA81 CREE XHP50 LED

8×AA Batteries

2150 Lumens



EA41 CREE XM-L2 U2 LED

4×AA Batteries

1020 Lumens



EC11 CREE XM-L2 U2 LED

1×CR123 Battery

1×IMR18350 Battery

900 Lumens



EC20 CREE XM-L2 U2 LED

1×18650 Battery

2×CR123 Batteries

960 Lumens



EC21 CREE XP-G2 R5 LED

1×18650 Battery

2×CR123 Batteries

460 Lumens



EA11 CREE XM-L2 U2 LED

1×AA Battery

1×IMR14500 Battery

900 Lumens



T SERIES

NEW PRODUCT **USB CHARGING**

TINI **380 Lumens**

CREE XP-G2 S3 LED
Rechargeable
Li-ion battery

380 Lumens

380 Lumens

Electroplated Silver Edge

Electroplated Light-Permeable Switches

Customized Torx Screws

Multiple Colors Available

NITECORE ®

If you have strict requirements on keychain light, then TINI may be your best choice. It distinguished itself with a minimized body and great performance that emits a max output of 380 lumens. Built-in 280mAh Li-ion battery can be recharged via USB port. Dual switches control 4 brightness levels based on general needs. Onboard FPC heat dissipating system with small thermal resistance allows for maximum heat dissipation surface.

Output & Runtime				
FLI STANDARD	TURBO	HIGH	MID	LOW
☀	380 lumens	145 lumens	38 lumens	1 lumen
⌚	15min	1h	4h	60h
▶	64m	40m	19m	3.9m
●	1020cd	400cd	95cd	3.8cd
✓	1.5m (Impact Resistant)			
⚡	IP54 rating			



STAINLESS STEEL
metallic
keychain light



Multiple Colors Available

TIP SS
360 Lumens
CREE XP-G2 S3 LED
Rechargeable Li-ion battery
USB CHARGING



T SERIES



USB CHARGING

TIP 2017
360 Lumens
CREE XP-G2 S3 LED
Rechargeable Li-ion battery
USB CHARGING



USB CHARGING

TIP CRI 2017
240 Lumens
Nichia 219B LED
Rechargeable Li-ion battery
USB CHARGING

Multiple Colors Available



« « « « « « « « T SERIES » » » » » » » »



NITECORE®



NU SERIES

NITECORE NU series are lightweight, lithium-powered illumination tools featuring uniform 100° wide beams, high output main LEDs, lower output secondary colored LEDs and bodies crafted from durable PC materials. Purpose-designed for hiking, climbing, camping and general outdoor recreation, NITECORE headlamps set new standards in output, functionality, comfort and runtime.

■ Rechargeable ■ Built-in Li-ion battery ■ Lightweight

Cycling Outdoor Search & Rescue Running

NITECORE®



NU25 CREE XP-G2 S3 LED
Rechargeable Li-ion battery

360 Lumens 


Multiple Colors Available 

NU25 is a triple outputs rechargeable headlamp, including 360 lumens main light, an auxiliary red light and an auxiliary high CRI light. Red light protects dark vision and high CRI light reveals the natural color of objects. Built-in a 2.26Wh high capacity Li-ion battery with a max runtime of 160 hours, making it ideal for multiple scenarios.

◆ **Triple Outputs**

◆ **Rechargeable**

◆ **Lightweight**



Output & Runtime

FLI STANDARD	TURBO	HIGH	MID	LOW	AUXILIARY WHITE LIGHT	RED LIGHT (LOW)	RED LIGHT (HIGH)	RED CAUTION LIGHT	SOS	BEACON
	360 lumens	190 lumens	38 lumens	1 lumen	20 lumens	0.9 lumen	13 lumens	13 lumens	360 lumens	360 lumens
	30min	5h	8h	160h	6h15min	68h	7h45min	13h	---	---
	8lm	6lm	27m	3.8m	5.5m	---	4m	---	---	---
	1650cd	950cd	190cd	3.7cd	7.5cd	---	4cd	---	---	---
	1.5m (Impact Resistant)									
	IPX66 Rating									

NU SERIES

NEW PRODUCT

WINNER OF
CHINA GOOD
DESIGN AWARD 2017



 **NU05** 4 high performance LEDs
Rechargeable Li-ion battery

Headlamp Mate

35 Lumens



White light

Red light

Multiple Colors Available



 **NU30** CREE XP-G2 S3 LED
Rechargeable Li-ion battery

400 Lumens



Multiple Colors Available



 **NU10** 5 high performance LEDs
Rechargeable Li-ion battery

160 Lumens



Multiple Colors Available



 **NU20** CREE XP-G2 S3 LED
Rechargeable Li-ion battery

360 Lumens

NU10 CRI High colour rendering capability
Rechargeable Li-ion battery

115 Lumens

 **NU20 CRI** Nichia 219B LED
Rechargeable Li-ion battery

270 Lumens

NITECORE®

HEADLAMP SERIES

It is a series of multipurpose headlamps suits for night running, hiking, caving, outdoor adventure and more. Headlamps of this series are high-performance and extremely lightweight, featuring scorching output, long runtime and great reliability.



Outdoor



Industrial workplace



Search & Rescue



Hiking/Trekking





NEW PRODUCT

HC33 CREE XHP35 HD LED
1×18650 Battery
2×CR123 Batteries

1800 Lumens

MAGNETIC

◆ 1800 Lumens
◆ High Performance
◆ Utility

As a versatile high performance L-shaped headlamp, HC33 is capable of outputting a max 1800 lumens and a beam distance up to 187 meters. It is not only a headlamp but also a L-shaped handheld torch when it is detached from the headband. The HC33 has a flood lighting system which produces a wide beam angle. It is easy and convenient for general use with one switch.

Output & Runtime

FLI STANDARD	TURBO	HIGH	MID	LOW	ULTRALOW	STROBE	SOS	BEACON
	1800 lumens	780 lumens	240 lumens	70 lumens	1 lumen	1800 lumens	1800 lumens	1800 lumens
	30min	1h30min	5h15min	15h	300h	---	---	---
	187m	117m	63m	35m	4m	---	---	---
	8750cd	3400cd	1000cd	300cd	4.5cd	---	---	---
1.5m (Impact Resistant)								
IPX68, 2m (Waterproof And Submersible)								

HEADLAMP SERIES

Specially designed for caving

HC70 CREE XM-L2 U2 LED
2×18650 Batteries

1000 Lumens

NEW PRODUCT



HC30 CREE XM-L2 U2 LED
1×18650 Battery
2×CR123 Batteries

1000 Lumens

NEW PRODUCT



NEW PRODUCT

HC65 CREE XM-L2 U2 LED
1×18650 Battery
2×CR123 Batteries

1000 Lumens

USB CHARGING

◆ Triple Outputs
◆ USB Rechargeable
◆ 1000 Lumens
◆ 1×18650 Li-ion Battery included



HC65 is a triple-output full metal headlamp with a main LED emitting 1000 lumens, an auxiliary red light and a high CRI auxiliary light. It can be recharged via the on-board Micro-USB port. An included 3400mAh Li-ion battery drives it for a maximum runtime of 800 hours, saving the need of frequent battery replacement.

Output & Runtime

FLI STANDARD	TURBO	HIGH	MID	LOW	ULTRALOW	AUXILIARY WHITE LIGHT	RED LIGHT ILLUMINATION	RED CAUTION LIGHT	STROBE	SOS	BEACON
	1000 lumens	550 lumens	280 lumens	80 lumens	1 lumen	26 lumens	11 lumens	11 lumens	1000 lumens	1000 lumens	1000 lumens
	1h	2h45min	4h45min	16h	800h	25h	20h	32h	---	---	---
	110m	78m	56m	29m	3.6m	6.6m	4m	---	---	---	---
	3000cd	1530cd	780cd	210cd	3.3cd	11cd	4.5cd	---	---	---	---
1.5m (Impact Resistant)											
IPX8, 2m (Waterproof And Submersible)											

HC60 CREE XM-L2 U2 LED
1×18650 Battery
2×CR123 Batteries

1000 Lumens

USB CHARGING



HA40 CREE XM-L2 U2 LED
4×AA Batteries

1000 Lumens

NEW PRODUCT



LANTERN SERIES

NITECORE Lantern series products are professionally designed for camping. With a CRI rating ≥ 90 , the lanterns emit a beam that is more close to natural daylight to avoid eye fatigue and reveal subtle details of objects. A single switch controls all brightness levels and modes, ideal for camping, excursion, working at night, night photography, everyday carry and so on.




Outdoor



Photography



Camping





GOOD DESIGN
ISPO AWARD **if DESIGN AWARD 2017**

LA10 CREE XP-G2 S3 LED 1×AA Battery **135** Lumens **MAGNETIC**

LA10CRI Nichia 219B LED 1×AA Battery **85** Lumens **MAGNETIC**

Multiple Colors Available (Red, Black, Blue)

LA10 Output & Runtime

FLI STANDARD	HIGH	MID	LOW
135 lumens	40 lumens	10 lumens	
1h30min	6h	23h	
10m	5.7m	2.8m	
28cd	8cd	2cd	
1.5m (Impact Resistant)			
IPX6 (Waterproof)			

LANTERN SERIES

LR10 PANDA



NEW PRODUCT
USB CHARGING
Multiple Colors Available (Yellow, Black, Green)

LR10 9 high CRI LEDs Rechargeable Li-ion battery **250** Lumens **MAGNETIC**




NEW PRODUCT

Bi-fuel High CRI Camping Lantern

LA30 8 high performance white LEDs and 3 red LEDs Rechargeable Li-ion battery 2×AA Batteries **250** Lumens **MAGNETIC** **USB CHARGING**

LA30 Output & Runtime


Output	HIGH	MID	LOW	RED LIGHT (HIGH)	RED LIGHT (LOW)	RED SOS	RED BEACON
Runtime	Built-in Li-ion Battery	250 lumens	55 lumens	8 lumens	40 lumens	5 lumens	40 lumens
	2×AA	4h	9h15min	56h	7h15min	48h	—
Beam Diameter 35m (MAX)							
Beam Intensity 80cd (MAX)							
Impact Resistance 1.5m							
Waterproof IP66							



Multiple Colors Available (Yellow, Green, Blue)

LR30 6 high performance white LEDs and a red LED 1×18650 Battery / 2×CR123 Batteries **205** Lumens **MAGNETIC**





EXPLOSION-PROOF SERIES

To meet the demand of market, NITECORE has developed explosion-proof series. It is suitable for various flammable and explosive sites and underground operations, serving as portable lighting for electric power industry, metallurgical industry, petroleum industry, railway, fire fighting, factories and mines.

◀◀◀◀◀ EXPLOSION-PROOF SERIES ▶▶▶▶▶



EF1
CREE XM-L2 U3 LED
1x18650 Battery

830 Lumens



ATEX Credential
Ex II 2 G Ex d IIC T6 Gb



PCEC Credential
Ex d IIC T5 Gb



EH1 Credential
Ex ib IIB T5 Gb
SHExC16.0340



EH1
CREE XP-G2 S3 LED
2X18650 Batteries (Built-in)
260 Lumens




EH1 Credential
Ex ib IIB T5 Gb
SHExC16.0341



EH1S
CREE XP-G2 S3 LED
1X18650 Battery (Built-in)
260 Lumens





Charging Rack Series

FEATURES	SPECIFICATIONS		
Model	NCR30	NCR60	NCR100
AC input	AC90-265V, 50~60Hz	AC90-265V, 50~60Hz	AC90-265V, 50~60Hz
DC output voltage	5V	5V	5V
DC output current	1A	1A	1A
Dimensions	1640*900*198 mm	1640*900*355 mm	1640*1380*355 mm
Weight	72kg	103kg	135kg
Charging time for EH1	8h	8h	8h
Charging time for EH1S	4h	4h	4h



Charger NCR01

FEATURES	SPECIFICATIONS
Model	NCR01
AC input	AC90-265V, 50~60Hz
DC input	10-15V
DC output voltage	5V
DC output current	1A
Dimensions	110*80*50mm
Weight	0.13 kg
Charging time for EH1	8h
Charging time for EH1S	4h



Adapter ACW

FEATURES	SPECIFICATIONS
Model	Adapter ACW
Output	5V, 2A
Charging time for EH1	8h
Charging time for EH1S	4h



Car adapter DCW

FEATURES	SPECIFICATIONS
Model	Car adapter DCW
Input	DC12-24V
Output	DC5V±0.25V, 2A
Material	ABS
Charging time for EH1	8h
Charging time for EH1S	4h

EFR/G/B/W1/W2




NEM

Mounting the EH1/
EH1S on a tripod



NEMC

Mounting the EH1/EH1S
on any metal surface



MAGNETIC



DIVING LIGHT SERIES

NITECORE Diving Light Series is specially designed for underwater sports. Integrated white light and red auxiliary light serve for supplementary lighting underwater. High-strength aerospace aluminum body is hard anodized with a Mil-Spec finish for extreme durability and corrosion resistance.

DL10 CREE XP-L HI V3 LED
1x18650 Battery
2xCR123 Batteries

1000 Lumens

10m
20m
30m
40m
50m




BIKE LIGHT SERIES

NITECORE Bike Light Series utilizes the patented diffuse reflection board to scatter beams evenly to the ground, which eliminates lighting dead zones to ensure users' safety. The innovative dual-distance beam allows for both near and far illumination. Onboard high definition OLED screen displays real-time data and the user-friendly switches provide easy operation. Ensuring users' safety and excellent riding experience in night riding, NITECORE bicycle light is the best choice for users.

BR35 2 CREE XM-L2 U2 LEDs
Rechargeable Li-ion battery

1800 Lumens

OLED Micro-USB 6800mAh 3 Modes





CONCEPT SERIES


As the flagship product series of NITECORE flashlights, the Concept Series combines the revolutionary performance with innovative design, intending to make a breakthrough in current illumination industry and bring a brand new illumination experience to users.



Two Modes

 **General Mode** from Standby
Tap the side switch 3 times quickly to enter Turbo

 **Tactical Mode** from Standby
Tap the side switch 3 times quickly to enter Strobe






GEM SERIES



Industrial
workplace



HUNTING KITS

ACCESSORIES LIST :

INCLUDED

- Flashlight
- 18650 Li-ion Battery
- Tactical Ring
- Weapon Mount (optional GM02/GM03/GM04)
- USB Cable
- RSW1 Remote Switch
- Holster
- Lanyard
- Filter *2 (optional)



For more hunting kits, please visit www.nitecore.com



MH25GT
HUNTING KIT



P30
HUNTING KIT



P16 TAC
HUNTING KIT



MH40GT
HUNTING KIT

CHARGER





NEW PRODUCT

Superb Charger Series: Up to 3A charging speed in a single slot



SC4

SC4 SPEC

Input:	AC 100~240V 50/60Hz 1A(MAX) 40W
DC 12V 3A	
Output voltage:	Battery: 4.35V±1% / 4.2V±1% / 3.7V±1% / 1.48V±1%
Output current:	3A*2(MAX) 1.5A*4 USB:2.1A(MAX)

SC4 & SC2 COMPATIBLE WITH

Li-ion / IMR / LiFePO4:
10340, 10440, 10500, 12340, 12500, 12650, 13450, 13500, 13650, 14350, 14430, 14500, 14650, 16500, 16340(RCR123), 16650, 17350, 17500, 17670, 17700, 18350, 18490, 18500, 18650, 18700, 20700, 21700, 22500, 22650, 25500, 26500, 26650, 26700, 20700, 21700, 22700
Ni-MH/Ni-Cd: AA, AAA, AAAA, C, D



SC2

SC2 SPEC

Input:	AC 100~240V 50/60Hz 0.9A(MAX) 30W
DC 12V 2.5A	
Output voltage:	Battery: 4.35V±1% / 4.2V±1% / 3.7V±1% / 1.48V±1%

Output current: 3A+2A MAX USB:2.1A



D2

D2 SPEC

Input:	AC 100-240V 50/60Hz 0.25A(MAX), DC 12V 1A
Output voltage:	4.2V ±1% / 3.7V ±1% / 1.48V ±1%
Output current:	500mA x 2

D2 & D4 COMPATIBLE WITH

Li-ion / IMR / LiFePO4:
26650, 22650, 18650, 17670, 18490, 18350, 17500, 14500, 16340(RCR123), 10440
Ni-MH/Ni-Cd: AA, AAA, AAAA, C



D4

D4 SPEC

Input:	AC 100-240V 50/60Hz 0.35A(MAX), DC 12V 1A
Output voltage:	4.2V ±1% / 3.7V ±1% / 1.48V ±1%
Output current:	375mA x 4 / 750mA x 2



UM10

UM10 SPEC

Input:	Micro USB DC 5V ≥500mA
Output voltage:	4.2V ±1% / 5V
Output current:	1000mA / 500mA

UM10 & UM20 COMPATIBLE WITH

Li-ion / IMR: 18650, 18490, 18350, 17670, 17500, 16340(RCR123), 14500, 10440



UM20

UM20 SPEC

Input:	Micro USB DC 5V ≥500mA
Output voltage:	4.2V ±1% / 5V
Output current:	1000mA / 500mA

NITECORE®

NEW PRODUCT E-liquid Mixer

NFF01

NFF01 SPEC	
Input:	DC 12V 3000mA MAX
Motor:	70-1200 rpm
Motor output:	3W
Heat output:	30W
Control precision:	5°C / 10°F
Operating duration:	SMM: continuous PMM: 14 days



- ◆ Programmable
- ◆ Heating safely
- ◆ Clear user interface
- ◆ Simple operation

NFF01 MIXER is a magnetic liquid mixer specially designed for DIY vapers. It is the world's first product to apply the magnetic stirring technology in vaping industry. A simple mixing mode and a programmable mixing are optional so that the R.P.M.(Revolutions Per Minute) and temperature can be selected by users. The onboard screen displays R.P.M., time, temperature and mode.

V Series: In-car Speedy Battery Charger



NEW PRODUCT

V2



V2 SPEC

Input:	DC 12V 42W(MAX)
Battery:	4.2V±1%/3A*2(MAX)
Output:	1.48V±1%/2A*2 (MAX)
USB:	5V±5% 1A*2/2.1A*1 (MAX)

V2 COMPATIBLE WITH

Li-ion/IMR:
14500, 14650, 16500, 16340(RCR123), 16650, 17350, 17500, 17650, 17670, 18350, 18490, 18500, 18650, 22500, 22650, 25500, 26500, 26650, Unprotected batteries: 17700, 18700, 20700, 21700, 22700, 26700
Ni-MH(NiCd): AA, C

NEW PRODUCT

VCL10



VCL10 SPEC

Input:	DC 12V 23W (MAX)
Output:	DC 5V/2.1A 9V/2A 12V/1.5A 18W(MAX)



Intelligent Charger Series: Onboard Intelligent Charging System

NEW PRODUCT

i8



i8 SPEC

Input:	AC 100~240V 50/60Hz 0.6A(MAX) 30W DC 12V 3A
Output voltage:	Battery: 4.2V±1% / 1.48±1% / USB: 5V±5%
Output current:	1.5Ax2, 1Ax4, 0.75Ax4, 0.5Ax8 USB:5V*2.1A

i8 COMPATIBLE WITH

Li-ion / IMR:
10340, 10350, 10440, 10500, 12340, 12500, 12650, 13450, 13500, 13650, 14350, 14430, 14500, 14650, 16500, 16340(RCR123), 16650, 17350, 17500, 17650, 17670, 18350, 18490, 18500, 18650, 22500, 22650, 25500, 26500, 26650
Ni-MH/Ni-Cd: AA, AAA, C, D

Compatible with USB Devices



NEW i2

NEW i2 SPEC

Input:	AC 100~240V 50/60Hz 0.25A(MAX) 8W DC 9~12V
Output voltage:	4.35V ±1% / 4.2V±1% 3.7V ±1% / 1.48V ±1%
Output current:	500mA*2/1000mA *1

NEW i2 & NEW i4 COMPATIBLE WITH

Li-ion / IMR / LiFePO4:
10340, 10350, 10440, 10500, 12340, 12500, 12650, 13450, 13500, 13650, 14350, 14430, 14500, 14650, 16500, 16340(RCR123), 16650, 17350, 17500, 17650, 17670, 18350, 18490, 18500, 18650, 18700, 20700, 21700, 22500, 22650, 25500, 26500, 26650
Ni-MH/Cd:
AA, AAA, AAAA, C, D



NEW i4

NEW i4 SPEC

Input:	AC 100~240V 50/60Hz 0.25A(MAX) 10W DC 9~12V 1A
Output voltage:	4.35V±1% / 4.2V±1% 3.7V±1% / 1.48V±1%
Output current:	1.5A*1 / 0.75A*2 / 0.5A*2 / 0.375A*4

Flexible Power Bank Series: Up to 1A fast charging through Micro-USB input port



F1

F1 SPEC

Input:	DC 5V, ≥500mA
Output voltage:	4.2V±1% (Battery) / 5V±5% (USB)
Output current:	Battery: 1A MAX USB: 1A



F2

F2 SPEC

Input:	DC:5V , ≥0.5A
Output voltage:	4.2V±1% (Battery) / 5V±5% (USB)
Output current:	Battery: 2×1A MAX USB: 2A MAX

F1 & F2 COMPATIBLE WITH

Li-ion / IMR:
26650, 18650, 17670, 18490, 17500, 17335, 16340(RCR123), 14500, 10440

NOTE: Battery is not included.



NITECORE USB travel chargers designed specifically for Leica, Canon, Nikon, SONY, FUJIFILM and GoPro cameras. They all feature state of the art technologies and designs which make them some of the most sought-after products for enthusiastic photographers.



USN1 USB dual slot travel charger for Sony camera

2 BATTERY SLOTS

SONY NP-FW50

USN1 SPEC

Input:	DC 5V/2A
Output voltage:	Slot 1 8.4V±1% Slot 2 8.4V±1%
Output current:	1A


NP-FW50

Compatible With:

Sony a5000 Sony a6300 Sony a7 II Sony a7S
Sony a5100 Sony a6500 Sony a7R Sony a7S II
Sony a6000 Sony a7 Sony a7R II Sony DSC-RX10 III



CHARGING CURRENT UP TO
1000 mA



BATTERY HEALTH DETECTION

Battery Status
Charged Volume
Charging Temperature
Battery Level

Slot1 Good 28°C 1000 mAh
Slot1 Good 75V 1000 mA Good
Slot1 Normal 75V 1000 mA Normal

Slot1 Poor 75V 1000 mA Poor

USN2
USB Charger For SONY

SONY is a registered trademark of Sony Corporation.

FX1
USB Charger For FUJIFILM

FUJIFILM is a registered trademark of Fujifilm Holdings Corporation.

NP-BX1

Compatible With:

HX350 RX100M4 RX100
H400 WX500 RX100M2
HX400 HX90 RX100M3
RX100M5 WX350 RX1
RX1RM2 HX60 RX1R

NP-W126/NP-W126S

Compatible With:

X-Pro1 XA2 X-T10
X-T1 XM1
XE1 HS30
XE2 X-T2
XA1 X-E2S

UCN1
USB Charger For Canon

Canon is a registered trademark of Canon, INC.

UNK1
USB Charger For Nikon

Nikon is a registered trademark of Nikon, INC.

2 BATTERY SLOTS

Canon LP-E6/LP-E6N/LP-E8

UCN1 SPEC

Input voltage:	DC 5V/2A
Output voltage:	Slot 1 (LP-E6/LP-E6N) 8.4V±1% Slot 2 (LP-E8) 8.4V±1%
Output current:	1A

2 BATTERY SLOTS

Nikon EN-EL14/ EN-EL14a/ EN-EL15

UNK1 SPEC

Input voltage:	DC 5V/2A
Output voltage:	Slot 1 (EN-EL15) 8.4V±1% Slot 2 (EN-EL14/EN-EL14a) 8.4V±1%
Output current:	1A

LP-E6/LP-E6N

Compatible With:

Canon EOS 5D Mark II Canon EOS 5DS Canon EOS 7D Canon EOS 60Da
Canon EOS 5D Mark III Canon EOS 5DS R Canon EOS 7D Mark II Canon EOS 70D
Canon EOS 5D Mark III Canon EOS 6D Canon EOS 60D Canon XC10

LP-E8

Compatible With:

Canon EOS Rebel T2i Canon EOS Rebel T5i Canon EOS 650D Canon EOS Kiss X5
Canon EOS Rebel T3i Canon EOS 550D Canon EOS 700D Canon EOS Kiss X6
Canon EOS Rebel T4i Canon EOS 600D Canon EOS Kiss X4

EN-EL15

Compatible With:

Nikon D600 Nikon D800 Nikon D810A Nikon D7200
Nikon D610 Nikon D800E Nikon D7000 Nikon 1 V1
Nikon D750 Nikon D810 Nikon D7100 Nikon V1

EN-EL14/EN-EL14a

Compatible With:

Nikon D5500 Nikon D3100 Nikon Coolpix P7100 Nikon D5600
Nikon D5300 Nikon D3200 Nikon Coolpix P7000 Nikon D3400
Nikon D5200 Nikon D3300 Nikon Coolpix P7700 Nikon D3400
Nikon D5100 Nikon Df Nikon Coolpix P7800 Nikon D3400



NEW PRODUCT

UL109

Compatible with
BP-DC15-E/BLE9GK
Leica's D-lux typ109

USB Charger For Leica

* *Leica* is a registered trademark of Leica Microsystems IR GmbH

U series chargers that reign supreme when it comes to compatibility with Leica's camera batteries.



ULSL

Leica BP-SCL4

ULSL SPEC	
Input:	DC 5V/2A
Output voltage:	8.4V±1%
Output current:	1A



ULM240

Leica BP-SCL2

ULM240 SPEC	
Input:	DC 5V/2A
Output voltage:	8.2V±1%
Output current:	1A

BP-SCL4

Compatible With: Leica SL Typ601

BP-SCL2

Compatible With: Leica M(Typ262) Leica M(Typ240)
Leica M(Typ246) Leica M-P
Leica M240P



ULQ

Leica BP-DC12

ULQ SPEC	
Input:	DC 5V/2A
Output voltage:	8.4V±1%
Output current:	1A



ULM9

Leica BLI-312

ULM9 SPEC	
Input:	DC 5V/1A
Output voltage:	4.2V±1%
Output current:	1A

CHARGER SERIES

BLI-312

Compatible With:
Leica Q(Typ116) Leica V-Lux 4
Leica V-Lux(Typ114) Leica M8 Leica M8.2 Leica M9-P
Leica M Leica M9 Leica M-E

GP SERIES



Photography



Outdoor



EDC



NITECORE®



USB CHARGING
ACTION CAMERA LIGHT

GP3 CREE XP-G2 LED
1xNLGP3 battery (1180mAh)
1xGoPro AHDBT-302 battery
360 Lumens



USB CHARGING
ACTION CAMERA LIGHT

GP3 CRI NICHIA 219B LED
1xNLGP3 battery (1180mAh)
1xGoPro AHDBT-302 battery
270 Lumens


UGP SERIES



Outdoor



NEW PRODUCT



UGP5

2 BATTERY SLOTS

BATTERY : GoPro HERO5 BLACK BATTERY
COMPATIBLE WITH : GoPro HERO 5 BLACK

UGP5 SPEC

Input:	USB DC 5V >500mA
Output voltage:	4.35V ±1%
Output current:	750mA*2 MAX

**INTELLIGENT USB CHARGER
FOR GoPro HERO 5/4/3/3+ BATTERIES**



UGP4

2 BATTERY SLOTS

BATTERY : AHDBT-401 / 301 / 201
COMPATIBLE WITH : GoPro HERO 3/4

UGP4 SPEC

Input:	USB DC 5V ≥ 1A
Output voltage:	4.2V±1%/4.35V±1% / 5V
Output current:	800mA x 2 , USB 1500mA x 1

NOTE: Battery is not included.

ACCESSORY



NITECORE BATTERIES

NITECORE Batteries are compatible with various types of electronic products, featuring high capacity, high performance, safety and reliability. With protected circuits, all batteries have multiple protections to prevent overcharge, over-discharge, short circuit and overheat. Insured worldwide by Ping An Insurance(Group) Company of China, Ltd.

Primary Li-ion Batteries

Primary Li-ion batteries feature higher energy intensity, better power storage and longer runtime compared to other batteries, and environmental-friendly that can be recharged for over 500 times.



MODEL	SPECIFICATION	CAPACITY
NL1823	18650	2300mAh
NL1826	18650	2600mAh
NL1832	18650	3200mAh
NL1834	18650	3400mAh
NL1835	18650	3500mAh
NL166	16340	650mAh
NL1475	14500	750mAh

High Performance Batteries

Specially designed for high performance products, featuring high drain and excellent performance, resistant to extreme conditions, capable of driving high performance products to the ultimate performance.



MODEL	SPECIFICATION	CAPACITY	DISCHARGE CURRENT
NL1835HP	18650	3500mAh	8A
NL1829LTHP	18650	2900mAh	8A
IMR18650 3000mAh (for TM28)	18650	3000mAh	10A

Micro-USB Rechargeable Li-ion Batteries

With a built-in Micro-USB port, it is convenient to charge the rechargeable Li-ion batteries via a USB cable.



MODEL	SPECIFICATION	CAPACITY
NL1828R	18650	2600mAh
NL1829R	18650	2900mAh
NL1834R	18650	3400mAh
NL1835R	18650	3500mAh
NL1665R	16340	650mAh
NL1475R	14500	750mAh

Low-temperature Resistant Batteries

Specially designed for freezing environment like high altitude area or severe cold area, it is low temperature resistant even at the lowest of -40°C.



MODEL	SPECIFICATION	CAPACITY	DISCHARGE CURRENT
NL1829LTP	18650	2900mAh	4A
NL1829LTHP	18650	2900mAh	8A

IMR Batteries

Specially designed for vaping industry, featuring high performance and high drain, IMR batteries can be charged by multiple NITECORE chargers.



MODEL	SPECIFICATION	CAPACITY	PULSE DISCHARGE CURRENT
2100mAh 30A	18650	2100mAh	30A
2100mAh 38A	18650	2100mAh	38A
2500mAh 35A	18650	2500mAh	35A
2600mAh 40A	18650	2600mAh	40A
3100mAh 35A	18650	3100mAh	35A

Gun Mount

With HAlI military grade hard-anodized finish, gun mounts are suit for tactical flashlights with head diameter from 0.7" to 1.1" (18mm-28mm), used to fix tactical flashlights to the gun.

Model: GM02/GM02M fits flashlights with diameter of 1" (25.4mm)
GM03 fits flashlights with diameter of 0.7" - 1.1" (18mm-28mm)
GM04 fits flashlights with diameter of 0.7" - 0.98" (18mm-25mm)



NITECORE®

Bicycle Mount (BM02)

NITECORE Bicycle Mount fits any flashlight with 1" body diameter, providing quick and easy mounting without any tools, tightly fit different sizes of handlebars.



Helmet Clip (NHC10)

A helmet clip allows for mounting a headlamp on a thin-edged helmet that does not include headlamp clips.



Tactical Remote Switch

Noiseless pressure pad switch capable of accessing momentary-on and constant-on illumination, professional and convenient operation making it ideal for law enforcement, hunting and more scenarios.

Model: RSW1 fits flashlights with diameter of 1 inch, capable of accessing momentary-on and constant-on illumination;
RSW2 fits P20, P20UV, P10GT, P05, P05 PINK and R25, capable of changing brightness levels.



Tactical Tail Cap (NTC1)

Specially designed for law enforcement, NTC1 is constructed from aero grade aluminum alloy with HAlI military grade hard-anodized finish, providing momentary-on and constant-on illumination in emergency.



Tactical Lanyard (NTL10/NTL20)

Compatible with various types of flashlights, the lanyard enables lighting tools to be hung, suspended or fastened to other objects, thus preventing flashlights from falling or missing.



Tactical Holster (NTH30B for P20 & P20UV)

Specially designed for law enforcement, it can be used with tactical lanyard NTL10 or NTL20 to keep your hands free and offer tactical operation rapidly. It is 360° adjustable and equipped with a battery case.



Handle Mount (NHM10)

Specially designed for TM Series. Treated with HAlI military grade hard-anodized finish, it is impact and crush resistant, making the flashlight easy to carry.

Window Breaker (NWB10)

Constructed from stainless steel, it can serve as a window breaker or an escape tool in emergency. It is easy to mount and dismount.



Silicone Grease (SG7)

Silicone Grease is used for lubricating the threads of flashlights.



Crenulated Bezel

Stainless steel bezel features hardness, low friction and reliability, which improves tactical function of flashlights, ideal for law enforcement, tactical and rescuing applications.

Model:40mm crenulated bezel, 40mm PVD bezel



Traffic Wand

Made from PC material that features crush, wear and high temperature resistance, traffic wand can turn flashlights into an orange traffic wand for traffic control, road guide and distress signal.

Model:NTW25, NTW32, NTW34, NTW40



Diffuser

Constructed from ABS materials, diffuser can convert flashlight output into a soft, white and diffused flood beam, great for comfortable reading, camping and more.

Model:NDF25, NDF32, NDF34, NDF40



Filters

Utilized a toughened ultra-clear glass lens with anti-reflective coating that provides impact resistance and maximum light penetrability. Flashlights equipped with the red/green/blue filters to deliver soft red/green/blue light, suitable for short range reading.



MODEL	COMPATIBLE SIZE	COLOR
NFR23/NFG23/NFB23	22.5mm	RGB
NFR25/NFG25/NFB25	25.4mm	RGB
NFR34/NFG34/NFB34	34mm	RGB
NFR40/NFG40/NFB40	40mm	RGB
NFR50/NFG50/NFB50	50mm	RGB
NFR60/NFG60/NFB60	60mm	RGB
NFD23	22.5mm	White
NFD25	25.4mm	White
NFD34	34mm	White
NFD40	40mm	White
NFD60	60mm	White

Titanium Pen (NTP10)

Constructed from titanium alloy, with Fisher Space Pen pressurized refill for smooth writing, oil tight and non-volatile. Tungsten steel tapered tip makes it so rugged that can double as a window breaker or a self-defense tool.



Emergency Whistle

The NWS10/20 is constructed from a single piece of TC4 titanium alloy, thus it is compact and lightweight, with sound intensity up to 120 decibels. Perfect for everyday carry.

Model:NWS10, NWS20





**NEW
PRODUCT**

BP20



Multi-purpose Backpack



Ventilated back enhances air circulation and lightens the burden

**NEW
PRODUCT**

NEB10/NEB20

Excursion Bag



NEB10



NEB20



NHL02S



NHL03



NHL04



NHL01



**NEW
PRODUCT**

NTC10

Tactical Case



Reinforced
handheld grip

Hypalon
Synthetic Rubber

Hard-Use Military-Spec
1050D Nylon

NITECORE®



NDP10



NDP20



NUP10



NUP20



NCP40
Holster



NCP30
Holster

Tactical Holster

NCP30 tactical holster is lightweight and durable, with convenient hook and loop fastener and modular design that enables fast mounting on MOLLE systems.

Model:NCP40, NCP30



Headband

Strengthened sewing design provides secure fit for headlamp, a hidden silicone gripper prevents slip by sweat.

Model:HB02, HB03

Model	LED	Output / Runtime					Beam Diameter	Beam Intensity	Water-Proof	Battery Options	Dimensions			Weight	Model		
		Turbo	High	Mid	Low	Lower					Length	Head Diameter	Tube Diameter				
Tiny Monster Series	TM38	CREE XHP35 HI D4	1800LUMENS *4 h	800LUMENS 11h	400LUMENS 22h	200LUMENS 40h	50LUMENS 120h	1400m	490000cd	IPX8	NBP68 HD	278mm (10.94")	90mm (3.54")	50mm (1.97")	1260.3g (44.46oz)	TM38	Tiny Monster Series
	TM38 Lite	CREE XHP35 HI D4	1800LUMENS *2h	800LUMENS 5h30min	400LUMENS 11h	200LUMENS 20h	50LUMENS 60h	1400m	490000cd	IPX8	4x18650	195mm (7.68")	90mm (3.54")	50mm (1.97")	780g (27.51oz)	TM38 Lite	
	TM28	4 CREE XHP35 HI LEDs	6000LUMENS *45min	2300LUMENS *2h	1000LUMENS 4h30min	320LUMENS 11h15min	2LUMENS 1000h	655m	107200cd	IPX8	4x IMR18650 / 4x18650 / NBP68 HD	142mm (5.59")	2.24"x2.24"(57mmx57mm) (Height/Width)	50mm (1.97")	414g (14.6oz)	TM28	
	TM26GT	4 CREE XP-L HI V3 LEDs	3500LUMENS 1h15min	1700LUMENS 3h15min	540LUMENS 9h45min	95LUMENS 48h	3LUMENS 1000h	704m	124000cd	IPX8	4x18650 / 8xCR123	142mm (5.59")	2.24"x2.24"(57mmx57mm) (Height/Width)	50mm (1.97")	442g (15.50oz)	TM26GT	
	TM06S	4 CREE XM-L2 U3 LEDs	4000LUMENS 1h	1500LUMENS 4h	480LUMENS 11h15min	160LUMENS 32h	3LUMENS 560h	359m	32300cd	IPX8	4x18650	117mm (4.74")	50mm (1.97")	50mm (1.97")	266g (9.39oz)	TM06S	
	TM03	CREE XHP70	2800LUMENS 15min	1350LUMENS 45min	550LUMENS 2h15min	40LUMENS 30h	— —	289m	21000cd	IPX8	NI18650D battery (for TM03 only)	159mm (6.26")	40mm (1.57")	30mm (1.18")	213g (7.51oz)	TM03	
	TM03 CRI	CREE XHP70, CRI ≥ 80	2600LUMENS 15min	1350LUMENS 45min	550LUMENS 2h15min	40LUMENS 30h	— —	289m	21000cd	IPX8	NI18650D battery (for TM03 only)	159mm (6.26")	40mm (1.57")	30mm (1.18")	213g (7.51oz)	TM03 CRI	
	TM16GT	4 CREE XP-L HI V3 LEDs	3600LUMENS 1h	1500LUMENS 3h15min	500LUMENS 7h15min	210LUMENS 21h	5LUMENS 610h	1003m	252000cd	IPX8	4x18650	182mm (7.17")	89mm (3.5")	53mm (2.09")	521g (18.38oz)	TM16GT	
Precise Series	P05	CREE XM-L2 U2	— —	460LUMENS *30min	170LUMENS 1h	60LUMENS 1h45min	— —	150m	5650cd	IPX8	RCR123 / CR123	101mm (3.97")	25.4mm (1")	25.4mm (1")	60.5g (2.13oz)	P05	Precise Series
	P05 PINK	CREE XM-L2 U2	— —	460LUMENS *30min	170LUMENS 1h	60LUMENS 1h45min	— —	150m	5650cd	IPX8	RCR123 / CR123	101mm (3.97")	25.4mm (1")	25.4mm (1")	60.5g (2.13oz)	P05 PINK	
	P10GT	CREE XP-L HI V3	— —	HIGH (M1/M2/M3) 900LUMENS	MID (M3) 300LUMENS	LOW (M2) 190LUMENS	LOW (M3) 60LUMENS	286m	20500cd	IPX8	2xCR123 / 1x18650	135mm (5.3")	25.4mm (1")	25.4mm (1")	82g (2.89oz)	P10GT	
	P12	CREE XM-L2 U2	— —	1000LUMENS 1h15min	240LUMENS 6h	70LUMENS 28h	1LUMEN 520h	232m	13500cd	IPX8	1x18650 / 2xCR123	139mm (5.47")	25.4mm (1")	25.4mm (1")	88g (3.1oz)	P12	
	P12GT	CREE XP-L HI V3	— —	1000LUMENS 1h	280LUMENS 5h15min	55LUMENS 28h	1LUMEN 520h	320m	25700cd	IPX8	1x18650 / 2xCR123	140mm (5.51")	25.4mm (1")	25.4mm (1")	91g (3.21oz)	P12GT	
	P15	CREE XP-G2 R4	— —	430LUMENS 2h15min	150LUMENS 8h15min	35LUMENS 37h	1LUMEN 520h	278m	19321cd	IPX8	1x18650 / 2xCR123	151mm (5.94")	40mm (1.57")	25.4mm (1")	132g (4.66oz)	P15	
	P16 TAC	CREE XM-L2 U3	1000LUMENS *1h15min	240LUMENS 7h	60LUMENS 33h	1LUMEN 600h	— —	300m	22000cd	IPX8	1x18650 / 2xCR123	151mm (5.94")	40mm (1.57")	25.4mm (1")	141g (4.97oz)	P16 TAC	
	P20	CREE XM-L2 U2	— —	800LUMENS 1h30min	400LUMENS 2h30min	70LUMENS 10h30min	— —	210m	11100cd	IPX8	2xCR123 / 1x18650	134mm (5.28")	31.8mm (1.25")	25.4mm (1")	101g (3.56oz)	P20	
	P20UV	CREE XM-L2 U2	— —	800LUMENS 1h30min	400LUMENS 2h30min	80LUMENS 8h	— —	180m	8100cd	IPX8	2xCR123 / 1x18650	134mm (5.28")	31.8mm (1.25")	25.4mm (1")	104g (3.67oz)	P20UV	
	P30	CREE XP-L HI V3	1000LUMENS *1h	400LUMENS 3h	220LUMENS 5h	70LUMENS 17h	1LUMEN 680h	618m	95500cd	IPX8	1x18650 / 2xCR123	141.5mm (5.57")	50mm (1.97")	25.4mm (1")	165g (5.83oz)	P30	
	P36	CREE MT-G2	2000LUMENS 45min	1500LUMENS 1h	380LUMENS 7h30min	2LUMENS 325h	— —	300m	22300cd	IPX8	2x18650 / 4xCR123	173mm (6.81")	50mm (1.97")	28mmx42mm (1.1"x1.65")	252g (8.89oz)	P36	
Smart Ring Tactical Series	SRT3	CREE XM-L2 U2	550LUMENS 45min	— —	— —	— —	0.1LUMEN 150h	134m	4500cd	IPX8	1xCR123 / 1xCR123 / 1xAA	100mm (3.9") 117mm (4.6") (with a body extender)	25.4mm (1")	24.3mm (0.96")	73g (2.57oz) / 87g (3.07oz) (with a body extender)	SRT3	Smart Ring Tactical Series
	SRT7GT	CREE XP-L HI V3	1000LUMENS 1h15min	— —	— —	— —	0.1LUMEN 240h	450m	50900cd	IPX8	1x18650 / 2xCR123	158mm (6.22")	40mm (1.57")	25.4mm (1")	173g (6.1oz)	SRT7GT	
	SRT9	CREE XHP50	2150LUMENS *1h	— —	— —	— —	0.1LUMEN 250h	246m	15100cd	IPX8	2x18650 / 4xCR123	148mm (5.83")	40mm (1.57")	40mmx34.9mm (1.57"x1.37")	224.3g (7.91oz)	SRT9	

NOTE: Runtime has been measured with the first battery type stated in battery options.

* The runtime for Turbo/High mode is the testing result before starting temperature regulation.

Model	LED	Output / Runtime					Beam Diameter	Beam Intensity	Waterproof	Battery Options	Dimensions			Weight	Model	
		Turbo	High	Mid	Low	Lower					Length	Head Diameter	Tube Diameter			
Chameleon Series	CR6	CREE XP-E R2	440LUMENS 1h45min	280LUMENS 3h30min	160LUMENS 7h	25LUMENS 43h	1LUMEN 400h	190m	9000cd	IPX8	1x18650 / 2xCR123	143mm (5.63")	40mm (1.57")	25.4mm (1")	138g (4.87oz)	CR6
	CG6	CREE XP-E G2	440LUMENS 1h45min	280LUMENS 3h30min	160LUMENS 7h	25LUMENS 43h	1LUMEN 400h	190m	9000cd	IPX8	1x18650 / 2xCR123	143mm (5.63")	40mm (1.57")	25.4mm (1")	138g (4.87oz)	CG6
	CB6	CREE XP-E D4	440LUMENS 1h45min	280LUMENS 3h30min	160LUMENS 7h	25LUMENS 43h	1LUMEN 400h	190m	9000cd	IPX8	1x18650 / 2xCR123	143mm (5.63")	40mm (1.57")	25.4mm (1")	138g (4.87oz)	CB6
	Cl6	CREE XP-G2 R5	440LUMENS 1h45min	280LUMENS 3h30min	160LUMENS 7h	25LUMENS 43h	1LUMEN 400h	190m	9000cd	IPX8	1x18650 / 2xCR123	143mm (5.63")	40mm (1.57")	25.4mm (1")	138g (4.87oz)	Cl6
	CU6	CREE XP-G2 R5	440LUMENS 1h45min	280LUMENS 3h30min	160LUMENS 7h	25LUMENS 43h	1LUMEN 400h	190m	9000cd	IPX8	1x18650 / 2xCR123	143mm (5.63")	40mm (1.57")	25.4mm (1")	138g (4.87oz)	CU6
Rechargeable Series	R25	CREE XP-L HI V3	—	HIGH (M1/M2/M3)	MID (M3)	MID (M2)	LOW (M3)	321m	25800cd	IPX8	1x18650 / 2xCR123	141mm (5.55")	31.8mm (1.25")	25.4mm (1")	108.1g (3.81oz)	R25
			—	800LUMENS	230LUMENS	120LUMENS	50LUMENS									
			—	1h	9h	12h	15h									
R40	CREE XP-L HI V3	1000LUMENS	420LUMENS	200LUMENS	50LUMENS	1LUMEN	520m	67700cd	IPX8	1x26650	151.3mm (5.95")	40mm (1.57")	38.6mm (1.55")	194.5g (6.86oz)	R40	
		*1h30min	4h30min	10h30min	32h	1000h										
MH10	CREE XM-L2 U2	—	1000LUMENS	240LUMENS	70LUMENS	1LUMEN	232m	13500cd	IPX8	1x18650 / 2xCR123	130mm (5.12")	25.4mm (1")	25.4mm (1")	75g (2.65oz)	MH10	
		—	1h15min	6h	28h	520h										
MH12GT	CREE XP-L HI V3	—	1000LUMENS	280LUMENS	55LUMENS	1LUMEN	320m	25700cd	IPX8	1x18650 / 2xCR123	139.2mm (5.48")	25.4mm (1")	25.4mm (1")	87g (3.07oz)	MH12GT	
		—	*1h15min	6h	28h	520h										
MH20	CREE XM-L2 U2	1000LUMENS	410LUMENS	230LUMENS	50LUMENS	1LUMEN	220m	12500cd	IPX8	1x18650 / 2xCR123	105mm (4.13")	31.8mm (1.25")	25.4mm (1")	87.3g (3.08oz)	MH20	
		2h	2h45min	5h45min	15h45min	235h										
MH20GT	CREE XP-L HI V3	1000LUMENS	410LUMENS	230LUMENS	50LUMENS	1LUMEN	362m	33000cd	IPX8	1x18650 / 2xCR123	111mm (4.37")	31.8mm (1.25")	25.4mm (1")	88.8g (3.13oz)	MH20GT	
		1h	3h	6h45min	22h	680h										
MH23	CREE XHP35 HD	1800LUMENS	760LUMENS	260LUMENS	55LUMENS	1LUMEN	294m	21600cd	IPX8	1xIMR18650 / 1x18650 / 2xCR123	111.3mm (4.38")	31.8mm (1.25")	25.4mm (1")	96.2g (3.39oz)	MH23	
		*30min	1h45min	4h45min	19h	300h										
MH27	CREE XP-L HI V3	1000LUMENS	250LUMENS	55LUMENS	1LUMEN	—	462m	53500cd	IPX8	1x18650 / 2xCR123	154mm (6.06")	40mm (1.57")	25.4mm (1")	170g (6oz)	MH27	
		1h	6h15min	28h	708h	—										
MH27 UV	CREE XP-L HI V3	1000LUMENS	250LUMENS	55LUMENS	1LUMEN	—	462m	53500cd	IPX8	1x18650 / 2xCR123	154mm (6.06")	40mm (1.57")	25.4mm (1")	170g (6oz)	MH27 UV	
		1h	6h15min	28h	708h	—										
MH40GT	CREE XP-L HI V3	1000LUMENS	325LUMENS	88LUMENS	13LUMENS	—	803m	161300cd	IPX8	2x18650 / 4xCR123	250mm (9.84")	60mm (2.36")	25.4mm (1")	302g (10.65oz)	MH40GT	
		2h15min	6h45min	27h	130h	—										
MH41	CREE XHP50	2150LUMENS	1230LUMENS	580LUMENS	90LUMENS	1LUMEN	495m	61400cd	IPX8	2x18650 / 4xCR123	250mm (9.84")	60mm (2.36")	25.4mm (1")	321g (11.32oz)	MH41	
		1h	2h30min	5h45min	32h15min	850h										
MH25GT	CREE XP-L HI V3	1000LUMENS	300LUMENS	110LUMENS	50LUMENS	—	452m	51100cd	IPX8	1x18650 / 2xCR123	160mm (6.3")	40mm (1.57")	25.4mm (1")	143g (5oz)	MH25GT	
		1h	4h	10h45min	36h	—										
MT1U	UV	—	—	—	—	—	—	—	IPX8	1x18650 / 2xCR123	124mm (4.88")	25.4mm (1")	25.4mm (1")	75g (2.65oz)	MT1U	
		—	—	—	—	—										
MT20C	CREE XP-G2 R5	460LUMENS 1h														

Model	LED	Output / Runtime					Beam Diameter	Beam Intensity	Waterproof	Battery Options	Dimensions			Weight	Model	
		Turbo	High	Mid	Low	Lower					Length	Head Diameter	Tube Diameter			
Multi-Task Series	MT22A	CREE XP-G2 S3	—	260LUMENS	45LUMENS	1LUMEN	—	98m	2400cd	IPX8	2xAA	80.9mm (3.19")	40.7mm (1.6") (Width)	21mm (0.83") (Depth)	49g (1.73oz)	MT22A
			—	*2h15min	18h	180h	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	MT1C
	MT1C	CREE XP-G2 R5	345LUMENS	138LUMENS	66LUMENS	22LUMENS	—	152m	5800cd	IPX8	1xCR123	88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	MT1C
			1h15min	3h15min	8h	23h	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	MT1C
	MT40GT	CREE XP-L HI V3	1000LUMENS	500LUMENS	250LUMENS	90LUMENS	—	618m	95400cd	IPX8	2x18650 / 4xCR123	221.5mm (8.72")	50mm (1.97")	25.4mm (1")	245g (8.64oz)	MT40GT
			2h15min	4h15min	9h30min	31h	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	MT40GT
	EA41	CREE XM-L2 U2	1020LUMENS	580LUMENS	160LUMENS	50LUMENS	1LUMEN	335m	28276cd	IPX8	4xAA	117mm (4.6")	40mm (1.57")	41.8mm (1.65")	151g (5.33oz)	EA41
			1h45min	2h45min	12h	30h	400h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EA41
	EA81	CREE XHP50	2150LUMENS	1200LUMENS	460LUMENS	80LUMENS	1LUMEN	462m	53300cd	IPX8	8xAA	193mm (7.6")	60mm (2.36")	41.8mm (1.65")	282g (9.95oz)	EA81
			1h45min	2h30min	7h	32h	810h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EA81
Explorer Series	EC20	CREE XM-L2 U2	—	960LUMENS	210LUMENS	50LUMENS	1LUMEN	222m	12450cd	IPX8	1x18650 / 2xCR123	128mm (5")	25.4mm (1")	25.4mm (1")	76g (2.68oz)	EC20
			—	1h15min	6h	28h	520h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC20
	EC23	CREE XHP35 HD E2	1800LUMENS	980LUMENS	300LUMENS	55LUMENS	1LUMEN	255m	16200cd	IPX8	1x18650 / 1xIMR18650 / 2xCR123	128.7mm (5.07")	25.4mm (1")	25.4mm (1")	78g (2.75oz)	EC23
			*30min	*1h30min	4h45min	22h	330h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC23
	EC4S	CREE XHP50	2150LUMENS	1100LUMENS	400LUMENS	80LUMENS	2LUMENS	280m	19600cd	IPX8	2x18650 / 4xCR123	150mm (5.9")	40mm (1.57")	39mmx28mm (1.54"x1.1")	171g (6.03oz)	EC4S
			45min	2h15min	6h15min	30h45min	325h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC4S
	EC11	CREE XM-L2 U2	900LUMENS	300LUMENS	160LUMENS	70LUMENS	1LUMEN	190m	9000cd	IPX8	1xIMR18350 / 1xCR123	75mm (2.95")	25.4mm (1")	25.4mm (1")	45.3g (1.6oz)	EC11
			30min	45min	1h30min	2h30min	12h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC11
	EC4GT	CREE XP-L HI V3	1000LUMENS	420LUMENS	200LUMENS	50LUMENS	1LUMEN	475m	56500cd	IPX8	2x18650 / 4xCR123	155mm (6.1")	40mm (1.57")	40mmx29mm (1.57"x1.12")	171g (6.03oz)	EC4GT
			2h	4h45min	10h	25h	380h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC4GT
	EA11	CREE XM-L2 U2	900LUMENS	300LUMENS	160LUMENS	70LUMENS	1LUMEN	190m	9000cd	IPX8	1xIMR14500 / 1xAA	92mm (3.62")	25.4mm (1")	20mm (0.79")	53g (1.87oz)	EA11
			30min	45min	1h30min	2h30min	12h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EA11
	EA42	CREE XHP35 HD	1800LUMENS	850LUMENS	300LUMENS	55LUMENS	1LUMEN	353m	31200cd	IPX8	4xAA Ni-MH	168mm (6.61")	40mm (1.57")	34.6mmx19.6mm (1.36"x0.77")	127.7g (4.5oz)	EA42
			*30min	1h45min	4h45min	20h	280h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EA42
	EC21	CREE XP-G2 R5	460LUMENS	210LUMENS	100LUMENS	20LUMENS	1LUMEN	194m	9400cd	IPX8	1x18650 / 2xCR123	108mm (4.25")	25.4mm (1")	25.4mm (1")	59.5g (2.1oz)	EC21
			1h45min	4h45min	12h	50h	430h					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	EC21
T Series	Thumb	2 High Performance LEDs	—	85LUMENS	30LUMENS	2LUMENS	—	26m	170cd	IP65	Built-in rechargeable Li-ion battery	74mm (2.91") (Length)	24mm (0.94") (Width)	15.8mm (0.62") (Depth)	25g (0.88oz)	Thumb
			—	45min	2h15min	22h	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	Thumb
	Thumb LEO	2 High Performance LEDs	45LUMENS	—	—	—	—	24m	150cd	IP65	Built-in rechargeable Li-ion battery	74mm (2.91") (Length)	24mm (0.94") (Width)	15.8mm (0.62") (Depth)	25g (0.88oz)	Thumb LEO
			2h	—	—	—	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	Thumb LEO
	TINI	CREE XP-G2 S3	380LUMENS	145LUMENS	38LUMENS	1LUMEN	—	64m	1020cd	IP54	Built-in rechargeable Li-ion battery	43.3mm (1.7") (Length)	25.4mm (1") (Width)	11.5mm (0.45") (Depth)	13.4g (0.47oz)	TINI
			*15min	1h	4h	60h	—					88mm (3.46")	22.56mm (0.89")	21.5mm (0.85")	42g (1.48oz)	TINI
	TUBE	High Performance LED	—	45LUMENS	—	1LUMEN	—	24m	150cd	IP65	Built-in rechargeable Li-ion battery	56.5mm (2.22") (Length)	21mm (0.83") (Width)	8mm (0.31") (Depth)	9.6g (0	

Model	LED	Output / Runtime					Beam Diameter	Beam Intensity	Waterproof	Battery Options	Dimensions			Weight	Model		
		Turbo	High	Mid	Low	Lower					Length	Head Diameter	Tube Diameter				
NU Series	NU05	4 High Performance LEDs	35LUMENS	—	—	—	—	—	IP66	Built-in rechargeable Li-ion battery	30.3mm (1.19") (Length)	29.5mm (1.16") (Width)	16.3mm (0.64") (Depth)	10.4g (0.37oz)	NU05	NU Series	
		1h	—	—	—	—	—	—	IP66	Built-in rechargeable Li-ion battery	60.5mm (2.38") (Length)	35mm (1.38") (Width)	29mm (1.15") (Depth)	65g (2.29oz)	NU10		
	NU10	5 High Performance LEDs	—	160LUMENS	35LUMENS	1LUMEN	—	35m	310cd	IP66	Built-in rechargeable Li-ion battery	60.5mm (2.38") (Length)	35mm (1.38") (Width)	29mm (1.15") (Depth)	65g (2.29oz)	NU10	
		—	7h	8h45min	150h	—	—	—	IP66	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20		
	NU10 CRI	High Colour Rendering Capability , CRI ≥ 90	—	115LUMENS	22LUMENS	1LUMEN	—	30m	220cd	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20 CRI	
		—	7h	8h45min	150h	—	—	—	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20 CRI		
	NU20	CREE XP-G2 S3	360LUMENS	220LUMENS	40LUMENS	1LUMEN	—	80m	1600cd	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20	
			*30min	6h	7h45min	100h	—	—	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20 CRI		
Headlamp Series	NU20 CRI	Nichia 219B , CRI ≥ 90	270LUMENS	170LUMENS	30LUMENS	1LUMEN	—	69m	1200cd	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20 CRI	Headlamp Series
		—	*30min	6h	7h45min	100h	—	—	IPX7	Built-in rechargeable Li-ion battery	55.5mm (2.18") (Length)	33mm (1.29") (Width)	21mm (0.82") (Depth)	47g (1.66oz)	NU20 CRI		
	NU25	CREE XP-G2 S3	360LUMENS	190LUMENS	38LUMENS	1LUMEN	—	81m	1650cd	IP66	Built-in rechargeable Li-ion battery	55.5mm (2.19") (Length)	34.6mm (1.36") (Width)	23.2mm (0.91") (Depth)	28g (0.99oz)	NU25	
			*30min	5h	8h	160h	—	—	IP66	Built-in rechargeable Li-ion battery	55.5mm (2.19") (Length)	34.6mm (1.36") (Width)	23.2mm (0.91") (Depth)	28g (0.99oz)	NU25		
	NU30	CREE XP-G2 S3	400LUMENS	180LUMENS	36LUMENS	1LUMEN	—	121m	3700cd	IP67	Built-in rechargeable Li-ion battery	63mm (2.48") (Length)	43.5mm (1.71") (Width)	31.5mm (1.24") (Depth)	84.8g (2.99oz)	NU30	
			*1h15min	22h	25h15min	330h	—	—	IP67	Built-in rechargeable Li-ion battery	63mm (2.48") (Length)	43.5mm (1.71") (Width)	31.5mm (1.24") (Depth)	84.8g (2.99oz)	NU30		
	HC30	CREE XM-L2 U2	1000LUMENS	400LUMENS	210LUMENS	70LUMENS	1LUMEN	162m	6600cd	IPX8	1x18650 / 2xCR123	98mm (3.86")	24.2mm (0.95")	23.8mm (0.94")	40.3g (1.42oz)	HC30	
			1h	3h30min	7h15min	15h15min	330h	—	IPX8	1x18650 / 1xIMR18650 / 2xCR123	105.3mm (4.15")	25.5mmx24.2mm (1"x0.95")	23.8mm (0.94")	51.2g (1.81oz)	HC33		
Headlamp Series	HC33	CREE XHP35 HD	1800LUMENS	780LUMENS	240LUMENS	70LUMENS	1LUMEN	187m	8750cd	IP68	1x18650 / 1xIMR18650 / 2xCR123	79mmx27mmx18.5mm (3.11"x1.06"x0.73")	—	98.5g (3.47oz)	HC60	Headlamp Series	
			*30min	*1h45min	5h45min	16h30min	330h	—	IPX7	1x18650 / 2xCR123	82.7mmx33.3mmx26.7mm (3.26"x1.31"x1.05")	—	62.7g (2.21oz)	HC65			
	HC60	CREE XM-L2 U2	1000LUMENS	420LUMENS	210LUMENS	38LUMENS	1LUMEN	117m	3400cd	IPX7	1x18650 / 2xCR123	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	98.5g (3.47oz)	HC60	
			1h	2h30min	7h15min	25h	680h	—	IPX7	1x18650 / 2xCR123	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	98.5g (3.47oz)	HC65		
	HC70	CREE XM-L2 U2	1000LUMENS	550LUMENS	240LUMENS	65LUMENS	1LUMEN	182m	8300cd	IP67	2x18650	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	97.9g (3.45oz)	HC70
			*2h15min	*4h	10h	30h	220h	—	IP67	2x18650	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 110.2mmx48.5mmx28mm (4.34"x1.91"x1.1")	176.7g (6.23oz)	HC70	
	HA40	CREE XM-L2 U2	1000LUMENS	500LUMENS	210LUMENS	45LUMENS	1LUMEN	182m	8300cd	IP66	4xAA	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	126.7g (4.47oz)	HA40
			*1h	*2h15min	6h30min	38h	430h	—	IP66	4xAA	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	Head size : 64mmx36mmx56mm (2.52"x1.42"x2.2") Head diameter : 32mm (1.26") Battery Case : 70mmx26.3mmx67.3mm (2.76"x1.04"x2.65")	42.7g (1.51oz)	LA10	
Lantern Series	LA10	CREE XP-G2 S3	—	135LUMENS	40LUMENS	10LUMENS	—	—	IPX6	1xAA	78.5mm (3.09")	22.6mm (0.89")	—	42.7g (1.51oz)	LA10	Lantern Series	
			—	1h30min	6h	23h	—	10m (Beam Diameter)	IPX6	1xAA	78.5mm (3.09")	22.6mm (0.89")	—	42.7g (1.51oz)	LA10 CRI		
	LA10 CRI	Nichia 219B, CRI≥90	—	85LUMENS	30LUMENS	9LUMENS	—	—	IPX6	1xAA	78.5mm (3.09")	22.6mm (0.89")	—	42.7g (1.51oz)	LA10 CRI		
		—	1h30min	6h	23h	—	—	10m (Beam Diameter)	IPX6	1xAA	78.5mm (3.09")	22.6mm (0.89")</					

Model	LED	Output / Runtime					Beam Diameter	Beam Intensity	Waterproof	Battery Options	Dimensions			Weight	Model								
		Turbo	High	Mid	Low	Lower					Length	Head Diameter	Tube Diameter										
Bike Light Series	BR35	2 CREE XM-L2 U2 LEDs	800LUMENS	465LUMENS	285LUMENS	150LUMENS	Short Range Beam	176m	7750cd	IPX7	Built-in rechargeable Li-ion battery	109.3mmx48.9mmx40.9mm (4.3"x1.93"x1.61")	234.5g (8.27oz)	BR35	Bike Light Series								
			*2h	5h45min	8h30min	17h																	
			1000LUMENS	550LUMENS	330LUMENS	180LUMENS	Long Range Beam																
			*2h	5h45min	8h30min	17h																	
			1800LUMENS	1015LUMENS	615LUMENS	300LUMENS	Dual Range Beam																
Concept Series	Concept1	CREE XHP35 HD E2	1800LUMENS	810LUMENS	300LUMENS	80LUMENS	1LUMEN	220m	12100cd	IPX8	1xIMR18650 / 1x18650 / 2xCR123	111.5mm (4.39")	24.5mm (0.96")	23.8mm (0.94")	61.9g (2.18oz)	Concept1	Concept Series						
			*30min	*1h30min	4h	15h	300h																
GP Series	GP3	CREE XP-G2	360LUMENS	230LUMENS	95LUMENS	30LUMENS	1LUMEN	105m	2770cd	IPX8	NLGP3 / GoPro AHDBT-302	57.5mm (2.26") (Length)	25.4mm (1") (Width)	85.8mm (3.38") (Depth)	82g (2.89oz)	GP3	GP Series						
			45min	1h45min	4h45min	11h	235h																
GP3 CRI	GP3 CRI	Nichia 219B , CRI ≥ 90	270LUMENS	175LUMENS	70LUMENS	20LUMENS	1LUMEN	70m	1200cd	IPX8	NLGP3 / GoPro AHDBT-302	57.5mm (2.26") (Length)	25.4mm (1") (Width)	85.8mm (3.38") (Depth)	82g (2.89oz)	GP3 CRI	GP Series						
			*45min	1h45min	4h45min	11h	235h																

NOTE: Runtime has been measured with the first battery type stated in battery options.

* The runtime for Turbo/High mode is the testing result before starting temperature regulation.

NITECORE®

KEEP INNOVATING



Model		Dimensions	Weight	Battery Slots
SC Series	SC2	155mmx80mmx44mm (6.1"x3.16"x1.73")	263g (9.28oz)	2
	SC4	165mmx110mmx45mm (6.5"x 4.33"x 1.77")	385g(13.59oz)	4
D Series	D2	143mmx74mmx36mm (5.63"x2.91"x1.42")	168g (5.92oz)	2
	D4	143mmx99mmx36mm (5.63"x3.9"x1.42")	239g (8.43oz)	4
UM Series	UM10	100mmx 38mmx35mm (3.94"x1.5"x1.38")	57g(2.01oz)	1
	UM20	100mmx 56mmx35mm (3.94"x2.2"x1.38")	77.2g(2.72oz)	2
i Series	NEW i2	132mmx70mmx35mm (5.2"x2.76"x1.38")	126g(4.44oz)	2
	NEW i4	140mmx94.8mmx37mm (5.51"x3.73"x1.45")	202g(7.12oz)	4
	i8	117mmx101mmx134.5mm (4.61"x3.98"x5.30")	488.2g(17.22oz)	8
F Series	F1	87.2mmx24mmx29.3mm (3.43"x0.94"x1.15")	30.4g (1.07oz)	1
	F2	94mmx44mmx25mm (3.7"x1.73"x0.98")	46.5g(1.64oz)	2
Q Series	Q2	125.4mmx59.6mmx36.2mm (4.94"x2.35"x1.43")	92g(3.25oz)	2
	Q4	125.4mmx95.6mmx36.2mm (4.94"x3.76"x1.43")	150.3g(5.3oz)	4
Camera Charger	V2	67mmx65mmx125mm (2.36"x2.29"x4.41")	197.6g (6.94oz)	2
	UCN1	85mmx50mmx25mm (3.34"x1.96"x0.98")	55.7g(1.96oz)	2
	UNK1	85mmx50mmx25mm (3.34"x1.96"x0.98")	59g(2.09oz)	2
	USN1	85mmx50mmx26.5mm (3.35"x1.97"x1.04")	58.9g(2.08oz)	2
	ULM9	85mmx50mmx30mm (3.34"x1.96"x1.18")	50.5g(1.78oz)	1
	ULM240	85mmx50mmx26.5mm (3.34"x1.96"x1.04")	52g(1.83oz)	1
	ULSL	85mmx50mmx29.5mm (3.34"x1.96"x1.16")	55.8g(1.96oz)	1
	ULQ	85mmx50mmx26.5mm (3.34"x1.96"x1.04")	53g(1.9oz)	1
	UGP3	67mmx44mmx24mm (2.64"x1.73"x0.94")	44.2g(1.56oz)	2
UGP Series	UGP4	84mmx45mmx27mm (3.3"x1.77"x1.06")	55.3g(1.95oz)	2
	UGP5	97mmx50mmx26.5mm (3.82"x1.97"x1.04")	67.5g (2.38oz)	2



Thanks again for choosing NITECORE!

NITECORE Warranty Service

If you have any questions regarding the use of your NITECORE product, please feel free to contact your local distributor, reseller or retailer. Alternatively, contact SYSMAX directly using the details below:

Phone: +86 20 8386 2000

Fax: +86 20 8388 2723

E-mail: info@nitecore.com

All images, text and statements specified here in this catalogue are for reference purpose only. Should any discrepancy occurs between this catalogue and information specified on www.nitecore.com, information on our official website shall prevail. Sysmax Industry Co., Ltd. reserves the rights to interpret and amend the content of this document at any time without prior notice.