

LOREX WIRELESS HD NETWORK CAMERA

VIEW WHAT MATTERS-INSTANTIY IN HD

- ¬ View, record & playback in real-time HD
- ▼ Free app & advanced software
- → Multiple users, many locations
- → Hd 720p day & night video
- ¬ Listen & talk with two-way audio
- ¬ Quickscan set-up



RECORD, PLAYBACK & SHARE IN HD

Record Real-Time HD directly to the camera with a microSD™, your Smartphone/Tablet 6, or to your NAS 7 personal cloud network.*

EXPANDABLE SOLUTION

Conveniently monitor various properties at once, up to 16 locations and 20 simultaneous devices.⁴

AUDIO & MOTION DETECTION

Superior alert accuracy with PIR motion sensors, smart video motion detection and sound activation.

PUSH NOTIFICATIONS

Receive emails with snapshot attachments of the detected event.

SIMPLE INSTALLATION

Activate your camera by simply scanning a QR code with your smartphone or tablet.









LOREX WIRELESS HD NETWORK CAMERA

FEATURES:

- Mega-pixel for up to 1280x800 resolution in Real-Time 30fps
- iOS, Android, PC and Mac compatible*
- Wi-Fi & wired internet connectivity. Easy connection to Wi-Fi networks with WPS1
- Night vision up to 30ft with single high-power IR LED²
- microSD recording & playback supported³
- 5 second pre-recording on SD card
- Dual motion detection: PIR & video
- Built-in speaker and microphone for 2-way audio. Sound activated alerts
- Infrared thermometer and temperature alarm control
- Push notification of events & email alerts with snap shot attachment
- H.264 video compression
- Triple streaming for simultaneous SD card, PC and mobile recording
- Supports up to 20 simultaneous users⁴
- Flexible indoor mounting (counter, wall, ceiling)
- Expandable up to 16 cameras⁵

EASY 3 STEP SETUP:



Tablet & mobile phones are not included











• Mobile Application - iPad, iPhone & Android App shown. (tablet and mobile phones not included)





LOREX WIRELESS HD NETWORK CAMERA

SPECIFICATIONS


Mode:	Day & Night				
Power:	5V (USB) - 12V, 1A				
Processors:	RISC CPU, hardware video processing and compression.				
Network interface:	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45				
Wireless interface:	IEEE 802.11b / g / n				
Image sensor:	HD up to 1280x800 resolution 1/4" Megapixel Color CMOS Separate sensors for day and night with automatic gain, white balance, exposure and brightness control				
PIR sensor:	Effective distance - 7 meters				
Light sensitivity:	0.2 Lux (IR LED off) 0 Lux (with 9 meters IR LED on) Automatically turn on the IR LED on low light environment.				
Infrared thermometer:	Infrared Range: -40 $^{\sim}$ 115 °C, accuracy:+-0.5 °C				
Lens:	4.2 mm, F2.4, viewing angle: 66°, fixed iris. Day and night separate lens				
Buttons:	One reset button, to factory default settings One WPS button for automatic WiFi setup				
Indicators:	One LED for Internet connection status indication One LED for Ethernet connection indication One LED for SD card recording indication				
Video compression:	H.264, baseline profile level 3.1				
Video streaming:	Separate frame rate/resolution/bandwidth settings for PC and mobile.				
Resolution:	1280x800, 1024x768, VGA(640x480), QVGA(320x240)				
Bandwidth:	64Kbps ~ 3Mbps				
Frame rate:	1~30 fps				
Audio:	Built-in 0.5W speaker for alarm and half-duplex two-way audio. Speaker jack for external speaker				

Video management software:					
-	L-View software for viewing and recording up to 16 cameras (PC/Mac) Lorex Ping app for viewing cameras on mobile (iOS/Android™)				
Security:	Web management username/password protection Video display ID/password protection WiFi WEP and WPA/WPA2 security mode				
Installation, management and maintenance:					
	Plug & play by ID/password. Firmware upgrades via FTP L-View SW upgrade Push Notification				
Users:	Up to 20 simultaneous users (depends on video settings and internet bandwidth)				
Alarm and event man	agement: Events triggered by PIR and sound detection Email/ftp alarm message Temperature alarm for low/high room temperature Push notification on supported mobile devices.				
Dimensions:	68 x 25 x 95mm/2.8 x 1.0 x 3.7" (W x D x H)				
Weight:	0.28kg/0.62lbs (including camera bracket)				
Approvals:	EMC - CE, FCC Part 15 Subpart B Class B, IC Class B Wireless RF - CE, FCC Part 15 Subpart C, RSS210 Power supply: CE, FCC, UL, EN 60950				
Operating conditions:	0.50 °C Humidity 20 – 80% RH (non-condensing)				

PRODUCT INFORMATION

MODEL	CONFIGURATION	PACKAGE	WxDxH	WEIGHT	CUBE	UPC Code		
LNC216	Wireless Network Camera	Retail Giftbox	162 x 89 x 162mm/ 6.4 x 3.5 x 6.4"	0.53 kg/1.2 lbs	0.0024 CBM x 0.085 CBF	7-78597-00216-4		
Includes:	1 x IP Camera, 1 x Camera Bracket, 1 x Ethernet cable, 1 x Power adapter, Quick Start Guide, CD (user manual included on CD)							

DIMENSIONS:



DISCLAIMERS:

- 1. Compatible with WPS enabled routers (not included).
- 2. Infrared illumination range under ideal conditions. Actual range and clarity may vary depending on scene/object reflection and camera application.
- 3. microSD Card not included (supports up to 32GB).
- 4. Connection speed may vary depending internet bandwidth.
- 5. Additional cameras sold separately.
- 6. Up to 16 simultaneous camera views available on PC, Mac and 6 on iPad. Selectable single camera viewing on smartphones.
- 7. NAS (Network Attached Storage), not included, please check the Lorex website for compatible NAS devices.

iPhone®, iPad®, iPod touch® Requirements:

Android™ Requirements:

• 2.3 & above

PC Requirements:

- CPU: 2.0 GHz (dual-core is preferable) • RAM: 2 GB
- HDD: 5~10 GB (depending on recording

Mac Requirements:

- 1 GHz or higher Intel processor
- PowerPC™ not supported

Lorex Technology Inc.

250 Royal Crest Court Markham, Ontario L3R 3S1 Canada

901 Elkridge Landing Road, Suite 100 Linthicum, Maryland 21090 USA

www.lorextechnology.com

©2013 Lorex Technology Inc.