

Combined LED Emergency Control Gear

Highest flexibility with just one unit

EM powerLED ST FX C/SR 45 W



TRIDONIC

Combined LED Emergency Control Gear

EM powerLED ST FX C/SR 45 W

- Independent and built-in combined emergency LED Driver
- General lighting and auto test emergency lighting with just one unit

For general lighting

- 6 W to 45 W output power
- 20 V to 50 V forward voltage
- 300 mA to 1,400 mA selectable with I-SELECT 2 resistor
- Dimensions: built-in 175 x 82 x 34 mm, independent 209 x 82 x 34 mm
- SELV < 60 V



EM powerLED ST FX SR 45W



EM powerLED ST FX C 45W

For emergency lighting

- Automatic selftest function
- Power controlled – automatic adjustment of the LED current in emergency mode
- NiCd and NiMH variants for optimal performance
- 1, 2 or 3 hour duration selectable with dip switch

Ordering data

Type	Article number	Rated duration	Number of cells	Packaging, carton	Packaging, pallet
EM powerLED ST FX 103 C NiCd 45W 50V	89800431	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED ST FX 104 C NiCd 45W 50V	89800413	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED ST FX 103 C NiMH 45W 50V	89800502	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED ST FX 104 C NiMH 45W 50V	89800506	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED ST FX 103 SR NiCd 45W 50V	89800432	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED ST FX 104 SR NiCd 45W 50V	89800414	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED ST FX 103 SR NiMH 45W 50V	89800503	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED ST FX 104 SR NiMH 45W 50V	89800507	1/2/3 h	4	10 pc(s).	400 pc(s).