

OSQ Series

OSQ™ LED Area/Flood Luminaire – Medium

Rev. Date: V20 08/16/2019

Product Description

The OSQ™ Area/Flood luminaire blends extreme optical control, advanced thermal management and modern, clean aesthetics. Built to last, the housing is rugged cast aluminum with an integral, weathertight LED driver compartment. Versatile mounting configurations offer simple installation. Its slim, low-profile design minimizes wind load requirements and blends seamlessly into the site providing even, quality illumination. The 'B' Input power designator is a suitable upgrade for HID applications up to 250 Watt, and the 'K' Input power designator is a suitable upgrade for HID applications up to 400 Watt.

Applications: Parking lots, walkways, campuses, car dealerships, office complexes, tunnels, underpasses, and internal roadways

Performance Summary

NanoOptic® Precision Delivery Grid™ optic

Assembled in the U.S.A. of U.S. and imported parts

Initial Delivered Lumens: Up to 17,291

Efficacy: Up to 136 LPW

CRI: Minimum 70 CRI (3000K, 4000K & 5700K); 90 CRI (5000K)

CCT: 3000K, 4000K, 5000K, 5700K

Limited Warranty*: 10 years on luminaire/10 years on Colorfast DeltaGuard® finish

*See <http://creelighting.com/warranty> for warranty terms

Accessories

Field-Installed	
Backlight Shield OSQ-BLSMF - Front facing optics OSQ-BLSMR - Rotated optics	Hand-Held Remote XA-SENSREM - For successful implementation of the programmable multi-level option, a minimum of one hand-held remote is required Bird Spikes OSQ-MED-BRDSPK

Ordering Information

Fully assembled luminaire is composed of two components that must be ordered separately:

Example: **Mount:** OSQ-B-AASV + **Luminaire:** OSQ-A-NM-2ME-B-40K-UL-SV


Mount (Luminaire must be ordered separately)*	
OSQ-	
OSQ-B-AA Adjustable Arm OSQ-DA Direct Arm OSQ-M-TSP Transportation Mount (stainless steel; do not specify color) OSQ-TM Trunnion Mount	Color Options: SV Silver BZ Bronze BK Black WH White

* Reference EPA and pole configuration suitability data beginning on page 9

Luminaire (Mount must be ordered separately)								
OSQ	A	NM						
Product	Version	Mounting	Optic	Input Power Designator	CCT	Voltage	Color Options	Options
OSQ	A	NM No Mount	Asymmetric 2ME* Type II Medium 4ME* Type IV Medium 3ME* Type III Medium Symmetric 5ME Type V Medium 25D 25° Flood 40D 40° Flood 55H Type V Short 60D 60° Flood WSN Wide Sign 15D 15° Flood	B 86W K 130W Z 53W	30K 3000K, 70 CRI 40K 4000K, 70 CRI 50K 5000K, 90 CRI 57K 5700K, 70 CRI	UL Universal 120-277V UH Universal 347-480V - Available with B & K Input Power Designators only	BK Black BZ Bronze SV Silver WH White	PML Programmable Multi-Level, up to 40' Mounting Height - Refer to PML spec sheet for details - Intended for downlight applications at 0° tilt PML2 Programmable Multi-Level, 10-30' Mounting Height - Refer to PML spec sheet for details - Intended for downlight applications at 0° tilt Q9/Q6/Q5/Q4/Q3/Q2/Q1 Field Adjustable Output - Must select Q9, Q6, Q5, Q4, Q3, Q2, or Q1 - Offers full range adjustability - Refer to pages 11-12 for power and lumen values - Available with B & K Input Power Designators only - Not available with PML or PML2 options
								R NEMA® 7-Pin Photocell Receptacle - 7-pin receptacle per ANSI C136.41 - Intended for downlight applications with maximum 45° tilt - Factory connected 0-10V dim leads - 18" [457mm] seven-conductor cord exits luminaire - Photocell or shorting cap by others RL Rotate Left - LED and optic are rotated to the left - Refer to RR/RL configuration diagram on page 13 for optic directionality RR Rotate Right - LED and optic are rotated to the right - Refer to RR/RL configuration diagram on page 13 for optic directionality

* Available with Backlight Shield when ordered with field-installed accessory (see table above)

DA Mount



Weight

28.9 lbs. [13.1kg]



CREE LIGHTING

US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

Product Specifications

CONSTRUCTION & MATERIALS


- Slim, low profile design minimizes wind load requirements
- Luminaire housing is rugged die cast aluminum with an integral, weathertight LED driver compartment and high-performance heat sink
- Convenient interlocking mounting method on direct arm mount. Mounting adaptor is rugged die cast aluminum and mounts to 3-6" (76-152mm) square or round pole, secured by two 5/16-18 UNC bolts spaced on 2" (51mm) centers
- Mounting for the adjustable arm mount adaptor is rugged die cast aluminum and mounts to 2" (51mm) IP, 2.375" (60mm) O.D. tenon
- Adjustable arm mount can be adjusted 180° in 2.5° increments
- Transportation mount is constructed of 316 stainless steel and mounts to surface with (4) 3/8" fasteners by others
- Trunnion mount is constructed of A500 and A1011 steel and is adjustable from 0-180° in 15° degree increments. Trunnion mount secures to surface with (1) 3/4" bolt or (2) 1/2" or 3/8" bolts
- Includes 18" (340mm) 18/5 or 16/5 cord exiting the luminaire. When ordered with R option, 18" (340mm) 18/7 or 16/7 cord is provided
- Designed for uplight and downlight applications
- Exclusive Colorfast DeltaGuard® finish features an E-Coat epoxy primer with an ultra-durable powder topcoat, providing excellent resistance to corrosion, ultraviolet degradation and abrasion. Silver, bronze, black, and white are available
- **Weight:** OSQ-DA: 28.9 lbs. (13.1kg); OSQ-B-AA: 28.4 lbs. (12.9kg); OSQ-M-TSP: 42 lbs. (19.1kg); OSQ-TM: 32.6 lbs. (14.8kg)

ELECTRICAL SYSTEM

- **Input Voltage:** 120-277V or 347-480V, 50/60Hz, Class 1 drivers
- **Power Factor:** > 0.9 at full load
- **Total Harmonic Distortion:** < 20% at full load
- Integral 10kV surge suppression protection standard
- When code dictates fusing, a slow blow fuse or type C/D breaker should be used to address inrush current
- Consult factory if in-luminaire fusing is required
- Designed with 0-10V dimming capabilities. Controls by others
- Refer to Dimming spec sheet for details
- **Maximum 10V Source Current:** 1.0mA

REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus Listed
- Suitable for wet locations
- Enclosure rated IP66 per IEC 60529 when ordered without R option
- Consult factory for CE Certified products
- Certified to ANSI C136.31-2001, 3G bridge and overpass vibration standards with AA, DA, TM, and TSP mounts
- ANSI C136.2 10kV surge protection, tested in accordance with IEEE/ANSI C62.41.2
- Meets FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions
- Luminaire and finish endurance tested to withstand 5,000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- Meets Buy American requirements within ARRA
- DLC and DLC Premium qualified versions available with 70 CRI. Some exceptions apply. Please refer to <https://www.designlights.org/search/> for most current information
- RoHS compliant. Consult factory for additional details
- Dark Sky Friendly, IDA Approved when ordered with 30K CCT and direct or transportation mounts only. Please refer to <http://darksky.org/fsa/fsa-products/> for most current information

 **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – www.p65warnings.ca.gov

Electrical Data*							
Input Power Designator	System Watts 120-480V	Total Current (A)					
		120V	208V	240V	277V	347V	480V
B	86	0.73	0.43	0.37	0.32	0.25	0.19
K	130	1.09	0.65	0.56	0.49	0.38	0.28
Z	53**	0.46	0.26	0.22	0.19	N/A	N/A

* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347-480V +/- 10%

** Available with UL voltage only

OSQ Series Ambient Adjusted Lumen Maintenance ¹						
Ambient	Optic	Initial LMF	25K hr Reported ² LMF	50K hr Reported ² LMF	75K hr Reported ² / Estimated ³ LMF	100K hr Reported ² / Estimated ³ LMF
5°C (41°F)	Asymmetric	1.04	1.02	1.01	1.00 ³	0.99 ³
	Symmetric	1.05	1.04	1.03	1.03 ²	1.02 ²
15°C (59°F)	Asymmetric	1.02	1.00	0.99	0.98 ³	0.97 ³
	Symmetric	1.02	1.02	1.01	1.00 ²	0.99 ²
25°C (77°F)	Asymmetric	1.00	0.98	0.97	0.96 ³	0.95 ³
	Symmetric	1.00	0.99	0.98	0.98 ²	0.97 ²

¹ Lumen maintenance values at 25°C (77°F) are calculated per IES TM-21 based on IES LM-80 report data for the LED package and in-situ luminaire testing. Luminaire ambient temperature factors (LATF) have been applied to all lumen maintenance factors. Please refer to the [Temperature Zone Reference Document](#) for outdoor average nighttime ambient conditions.

² In accordance with IES TM-21, Reported values represent interpolated values based on time durations that are up to 6x the tested duration in the IES LM-80 report for the LED


³ Estimated values are calculated and represent time durations that exceed the 6x test duration of the LED

OSQ™ LED Area/Flood Luminaire – Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

2ME




RESTL Test Report #: PL08877-001A
OSQ-A-**-2ME-B-30K-UL
Initial Delivered Lumens: 10,381




OSQ-A-**-2ME-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,424
Initial FC at grade

Type II Medium Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	10,738	B2 U0 G2	11,424	B2 U0 G2	9,350	B2 U0 G2	11,648	B2 U0 G2
K	16,022	B3 U0 G3	16,959	B3 U0 G3	14,000	B3 U0 G2	17,291	B3 U0 G3
Z	6,481	B2 U0 G1	6,896	B2 U0 G1	5,750	B1 U0 G1	7,031	B2 U0 G1

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt



CESTL Test Report #: PL07700-001A
OSQ-A-**-2ME-U-57K-UL w/OSQ-BLSLF
Initial Delivered Lumens: 22,822



OSQ-A-**-2ME-B-40K-UL w/OSQ-BLSMF
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 8,779
Initial FC at grade

Type II Medium w/BLS Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM 15 11	Initial Delivered Lumens*	BUG Ratings** Per TM 15 11	Initial Delivered Lumens*	BUG Ratings** Per TM 15 11	Initial Delivered Lumens*	BUG Ratings** Per TM 15 11
B	8,251	B2 U0 G2	8,779	B2 U0 G2	7,200	B1 U0 G1	8,950	B2 U0 G2
K	12,312	B2 U0 G2	13,032	B2 U0 G2	10,750	B2 U0 G2	13,286	B2 U0 G2
Z	4,980	B1 U0 G1	5,299	B1 U0 G1	4,420	B1 U0 G1	5,402	B1 U0 G1


* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

OSQ™ LED Area/Flood Luminaire – Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

3ME




RESTL Test Report #: PL08876-001A
OSQ-A--3ME-B-30K-UL**
Initial Delivered Lumens: 10,421




OSQ-A--3ME-B-40K-UL**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,424
 Initial FC at grade

Type III Medium Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	10,738	B3 U0 G3	11,424	B3 U0 G3	9,350	B2 U0 G2	11,648	B3 U0 G3
K	16,022	B3 U0 G3	16,959	B3 U0 G3	14,000	B3 U0 G3	17,291	B3 U0 G3
Z	6,481	B2 U0 G2	6,896	B2 U0 G2	5,750	B2 U0 G2	7,031	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
 ** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt



CESTL Test Report #: PL07699-001A
OSQ-A--3ME-U-57K-UL w/OSQ-BLSLF**
Initial Delivered Lumens: 23,601



OSQ-A--3ME-B-40K-UL w/OSQ-BLSMF**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 9,019
 Initial FC at grade


Type III Medium w/BLS Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	8,477	B1 U0 G2	9,019	B1 U0 G2	7,400	B1 U0 G2	9,196	B1 U0 G2
K	12,649	B2 U0 G2	13,389	B2 U0 G2	11,050	B2 U0 G2	13,650	B2 U0 G2
Z	5,117	B1 U0 G1	5,444	B1 U0 G1	4,540	B1 U0 G1	5,551	B1 U0 G1

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
 ** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

4ME




RESTL Test Report #: PL08878-001A
OSQ-A-**-4ME-B-30K-UL
Initial Delivered Lumens: 10,230




OSQ-A-**-4ME-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,424
Initial FC at grade

Type IV Medium Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	10,738	B2 U0 G2	11,424	B2 U0 G2	9,350	B2 U0 G2	11,648	B2 U0 G2
K	16,022	B3 U0 G3	16,959	B3 U0 G3	14,000	B3 U0 G3	17,291	B3 U0 G3
Z	6,481	B2 U0 G2	6,896	B2 U0 G2	5,750	B2 U0 G1	7,031	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt



CESTL Test Report #: PL07692-001A
OSQ-A-**-4ME-U-57K-UL w/OSQ-BLSLF
Initial Delivered Lumens: 22,793



OSQ-A-**-4ME-B-40K-UL w/OSQ-BLSMF
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 8,779
Initial FC at grade

Type IV Medium w/BLS Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	8,251	B1 U0 G2	8,779	B1 U0 G2	7,200	B1 U0 G2	8,950	B1 U0 G2
K	12,312	B2 U0 G2	13,032	B2 U0 G2	10,750	B2 U0 G2	13,286	B2 U0 G2
Z	4,980	B1 U0 G1	5,299	B1 U0 G1	4,420	B1 U0 G1	5,402	B1 U0 G1



* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

OSQ™ LED Area/Flood Luminaire – Medium

Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

5ME





RESTL Test Report #: PL08534-001B
OSQ-A-**-5ME-B-40K-UL
Initial Delivered Lumens: 10,519

OSQ-A-**-5ME-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 10,867
Initial FC at grade

Type V Medium Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	10,232	B4 U0 G3	10,867	B4 U0 G3	10,000	B4 U0 G3	11,056	B4 U0 G3
K	15,063	B4 U0 G4	15,999	B4 U0 G4	14,925	B4 U0 G4	16,277	B4 U0 G4
Z	5,257	B3 U0 G3	6,086	B3 U0 G3	6,175	B3 U0 G3	6,192	B3 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

5SH



CESTL Test Report #: PL10754-001A
OSQ-A-**-5SH-U-40K-UL
Initial Delivered Lumens: 25,679

OSQ-A-**-5SH-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,478
Initial FC at grade


Type V Short Distribution								
Input Power Designator	3000K (70 CRI)		4000K (70 CRI)		5000K (90 CRI)		5700K (70 CRI)	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
B	10,806	B4 U0 G2	11,478	B4 U0 G2	10,575	B4 U0 G2	11,678	B4 U0 G2
K	15,909	B4 U0 G3	16,897	B4 U0 G3	15,800	B4 U0 G3	17,191	B4 U0 G3
Z	5,552	B3 U0 G1	6,428	B3 U0 G2	6,525	B3 U0 G2	6,539	B3 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

15D



CESTL Test Report #: PL07689-001A
OSQ-A-**-15D-U-30K-UL
Initial Delivered Lumens: 23,254




OSQ-A-**-15D-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G., 60° Tilt
Initial Delivered Lumens: 11,478
Initial FC at grade

15° Flood Distribution


Input Power Designator	3000K (70 CRI)	4000K (70 CRI)	5000K (90CRI)	5700K (70 CRI)
	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*
B	10,806	11,478	10,575	11,678
K	15,909	16,897	15,800	17,191
Z	5,552	6,428	6,525	6,539

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

25D



CESTL Test Report #: PL07696-001A
OSQ-A-**-25D-U-30K-UL
Initial Delivered Lumens: 23,265




OSQ-A-**-25D-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G., 60° Tilt
Initial Delivered Lumens: 11,478
Initial FC at grade

25° Flood Distribution


Input Power Designator	3000K (70 CRI)	4000K (70 CRI)	5000K (90CRI)	5700K (70 CRI)
	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*
B	10,806	11,478	10,575	11,678
K	15,909	16,897	15,800	17,191
Z	5,552	6,428	6,525	6,539

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

40D



CESTL Test Report #: PL07697-001A
OSQ-A-**-40D-U-30K-UL
Initial Delivered Lumens: 22,943



OSQ-A-**-40D-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G., 60° Tilt
Initial Delivered Lumens: 11,478
Initial FC at grade

40° Flood Distribution


Input Power Designator	3000K (70 CRI)	4000K (70 CRI)	5000K (90 CRI)	5700K (70 CRI)
	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*
B	10,806	11,478	10,575	11,678
K	15,909	16,897	15,800	17,191
Z	5,552	6,428	6,525	6,539

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/area/osq-series>

60D



CESTL Test Report #: PL08100-001B
OSQ-A-**-60D-B-30K-UL
Initial Delivered Lumens: 10,079




OSQ-A-**-60D-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G., 60° Tilt
Initial Delivered Lumens: 11,478
Initial FC at grade


60° Flood Distribution				
Input Power Designator	3000K (70 CRI)	4000K (70 CRI)	5000K (90 CRI)	5700K (70 CRI)
	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*
B	10,806	11,478	10,575	11,678
K	15,909	16,897	15,800	17,191
Z	5,552	6,428	6,525	6,539

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

WSN



CESTL Test Report #: PL07695-001A
OSQ-A-**-WSN-U-30K-UL
Initial Delivered Lumens: 23,116











OSQ-A-**-WSN-B-40K-UL
Mounting Height: 25' (7.6m) A.F.G., 60° Tilt
Initial Delivered Lumens: 11,478
Initial FC at grade

Wide Sign Distribution				
Input Power Designator	3000K (70 CRI)	4000K (70 CRI)	5000K (90 CRI)	5700K (70 CRI)
	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*	Initial Delivered Lumens*
B	10,806	11,478	10,575	11,678
K	15,909	16,897	15,800	17,191
Z	5,552	6,428	6,525	6,539

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt

Luminaire EPA

Adjustable Arm Mount – OSQ-B-AA Weight: 28.4 lbs. (12.9kg)							
Single	2 @ 180°	2 @ 90°	3 @ 90°	3 @ 120°	3 @ 180°	4 @ 180°	4 @ 90°
Tenon Configuration (0° -80° Tilt); If used with Cree Lighting tenons, please add tenon EPA with Luminaire EPA							
							
PB-1A*; PT-1; PW-1A3**	PB-2A*; PB-2R2.375; PD-2A4(180); PT-2(180); PW-2A3**	PB-2A*; PD-2A4(90); PT-2(90)	PB-3A*; PD-3A4(90); PT-3(90)	PB-3A*; PT-3(120)	PB-3A*; PB-3R2.375	PB-4A*(180)	PB-4A*(90); PB-4R2.375; PD-4A4(90); PT-4(90)
0° Tilt							
0.74	1.48	1.19	1.93	1.63	3.33	4.66	2.38
10° Tilt							
0.75	1.48	1.49	2.23	2.15	4.22	5.84	2.98
20° Tilt							
1.12	1.48	1.86	2.60	2.85	5.31	7.32	3.72
30° Tilt							
1.46	1.48	2.20	2.94	3.56	6.34	8.68	4.40
45° Tilt							
1.96	1.96	2.69	3.43	4.54	7.83	10.68	5.38
60° Tilt							
2.33	2.33	3.07	3.81	5.11	8.94	12.16	6.14
70° Tilt							
2.49	2.49	3.23	3.97	5.11	9.43	12.80	6.46
80° Tilt							
2.58	2.58	3.32	4.06	5.11	9.71	13.16	6.64
Tenon Configuration (90° Tilt); If used with Cree Lighting tenons, please add tenon EPA with Luminaire EPA							
PB-1A*; PT-1; PW-1A3**	PB-2A*; PB-2R2.375; PD-2A4(180); PT-2(180); PW-2A3**	PB-2A*	PB-3A*	PB-3A*; PT-3(120)	PB-3A*; PB-3R2.375	PB-4A*(180)	PB-4A*(90); PB-4R2.375
90° Tilt							
2.61	2.61	4.44	6.05	5.11	9.79	13.28	10.39

* Specify pole size: 3 [3"], 4 [4"], 5 [5"], or 6 [6"] for single, double or triple luminaire orientation or 4 [4"], 5 [5"], or 6 [6"] for quad luminaire orientation
 ** These EPA values must be multiplied by the following ratio: Fixture Mounting Height/Total Pole Height. Specify pole size: 3 [3"], 4 [4"], 5 [5"], or 6 [6"]

Tenon EPA







Part Number	EPA
PB-1A*	None
PB-2A*	0.82
PB-3A*	1.52
PB-4A*(180)	2.22
PB-4A*(90)	1.11
PB-2R2.375	0.92
PB-3R2.375	1.62
PB-4R2.375	2.32
PD Series Tenons	0.09
PT Series Tenons	0.10
PW-1A3**	0.47
PW-2A3**	0.94
WM-2	0.08
WM-4	0.25
WM-DM	None

* Specify pole size: 3 [3"], 4 [4"], 5 [5"], or 6 [6"] for single, double or triple luminaire orientation or 4 [4"], 5 [5"], or 6 [6"] for quad luminaire orientation
 ** These EPA values must be multiplied by the following ratio: Fixture Mounting Height/Total Pole Height. Specify pole size: 3 [3"], 4 [4"], 5 [5"], or 6 [6"]

Tenons and Brackets* (must specify color)	
<p>Square Internal Mount Vertical Tenons (Steel) - Mounts to 3-6" (76-152mm) square aluminum or steel poles</p> <p>PB-1A* – Single PB-4A*(90) – 90° Quad PB-2A* – 180° Twin PB-4A*(180) – 180° Quad PB-3A* – 180° Triple</p>	<p>Round External Mount Vertical Tenons (Steel) - Mounts to 2.375" (60mm) O.D. round aluminum or steel poles or tenons</p> <p>PB-2R2.375 – Twin PB-4R2.375 – Quad PB-3R2.375 – Triple</p>
<p>Square Internal Mount Horizontal Tenons (Aluminum) - Mounts to 4" (102mm) square aluminum or steel poles</p> <p>PD-2A4(90) – 90° Twin PD-3A4(90) – 90° Triple PD-2A4(180) – 180° Twin PD-4A4(90) – 90° Quad</p>	<p>Round External Mount Horizontal Tenons (Aluminum) - Mounts to 2.375" (60mm) O.D. round aluminum or steel poles or tenons</p> <p>- Mounts to square pole with PB-1A* tenon</p> <p>PT-1 – Single (Vertical) PT-3(90) – 90° Triple PT-2(90) – 90° Twin PT-3(120) – 120° Triple PT-2(180) – 180° Twin PT-4(90) – 90° Quad</p>
<p>Wall Mount Brackets - Mounts to wall or roof</p> <p>WM-2 – Horizontal for OSQ-B-AA mount WM-4 – L-Shape for OSQ-B-AA mount WM-DM – Plate for OSQ-DA mount</p>	<p>Mid-Pole Bracket - Mounts to square pole</p> <p>PW-1A3** – Single PW-2A3** – Double</p>
<p>Ground Mount Post - For ground-mounted flood luminaires PGM-1 - for OSQ-B-AA mount</p>	

* Refer to the [Bracket and Tenons spec sheet](#) for more details

Luminaire EPA

Direct Arm Mount – OSQ-DA Weight: 28.9 lbs. (13.1kg)					
Single	2 @ 180°	2 @ 90°	3 @ 90°	3 @ 120°	4 @ 90°
					
0.74	1.48	1.19	1.93	1.63	2.38

Direct Mount Configurations

Compatibility with OSQ-DA Direct Mount Bracket					
Input Power Designator	2 @ 90°	2 @ 180°	3 @ 90°	3 @ 120°	4 @ 90°
3" Square					
B, K & Z	N/A	✓	N/A	N/A	N/A
3" Round					
B, K & Z	N/A	✓	N/A	N/A	N/A
4" Square					
B, K & Z	✓	✓	✓	N/A	✓
4" Round					
B, K & Z	✓	✓	✓	✓	✓
5" Square					
B, K & Z	✓	✓	✓	N/A	✓
5" Round					
B, K & Z	✓	✓	✓	✓	✓
6" Square					
B, K & Z	✓	✓	✓	N/A	✓
6" Round					
B, K & Z	✓	✓	✓	✓	✓

Luminaire EPA

Trunnion Mount – OSQ-TM Weight: 32.6 lbs. (14.8kg)	
Single	
0° Tilt	
0.75	
15° Tilt	
0.99	
30° Tilt	
1.57	
45° Tilt	
2.07	
60° Tilt	
2.46	
75° Tilt	
2.67	
90° Tilt	
2.33	

Field Adjustable Output (Q9/Q6/Q5/Q4/Q3/Q2/Q1) Option Description:

The Field Adjustable Output option enables the OSQ area luminaires to be tuned to the exact needs of a particular application through multiple levels of adjustment. When ordered with the Q option, the luminaire will be shipped from the factory at the selected Q setting and will be fully adjustable between the nine settings.

Q Option Power & Lumen Data – Designator B

Q Option Setting	CCT/CRI	System Watts	Lumen Values						Optics Qualified on DLC QPL	
			120-480V	Asymmetric	5ME	5SH & Floods	2ME w/ BLS	3ME w/ BLS	4ME w/BLS	Standard
Q9 (Full Power)	30K (70 CRI)	86	10,738	10,232	10,806	8,251	8,477	8,251	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		11,424	10,867	11,478	8,779	9,019	8,779	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		9,350	10,000	10,575	7,200	7,400	7,200	TBD	TBD
	57K (70 CRI)		11,648	11,056	11,678	8,950	9,196	8,950	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q6	30K (70 CRI)	77	9,449	9,004	9,509	7,261	7,460	7,261	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		10,053	9,563	10,101	7,726	7,937	7,726	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		8,350	8,950	9,450	6,425	6,600	6,425	TBD	TBD
	57K (70 CRI)		10,250	9,729	10,277	7,876	8,092	7,876	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q5	30K (70 CRI)	72	8,913	8,492	8,969	6,848	7,036	6,848	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		9,482	9,020	9,527	7,287	7,486	7,287	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		7,525	8,050	8,525	5,775	5,950	5,775	TBD	TBD
	57K (70 CRI)		9,668	9,176	9,693	7,429	7,633	7,429	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q4	30K (70 CRI)	62	7,731	7,367	7,780	5,941	6,103	5,941	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		8,225	7,824	8,264	6,321	6,494	6,321	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		6,575	7,025	7,425	5,050	5,175	5,050	TBD	TBD
	57K (70 CRI)		8,387	7,960	8,408	6,444	6,621	6,444	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q3	30K (70 CRI)	53	6,550	6,241	6,592	5,033	5,171	5,033	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		6,969	6,629	7,002	5,355	5,502	5,355	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		5,575	5,975	6,325	4,290	4,410	4,290	TBD	TBD
	57K (70 CRI)		7,105	6,744	7,124	5,460	5,610	5,460	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q2	30K (70 CRI)	45	5,476	5,218	5,511	4,208	4,323	4,208	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		5,826	5,542	5,854	4,477	4,600	4,477	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		4,550	4,890	5,175	3,500	3,590	3,500	TBD	TBD
	57K (70 CRI)		5,940	5,639	5,956	4,565	4,690	4,565	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q1	30K (70 CRI)	34	4,188	3,990	4,214	3,218	3,306	3,218	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		4,455	4,238	4,476	3,424	3,517	3,424	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		3,500	3,770	3,980	2,690	2,760	2,690	TBD	TBD
	57K (70 CRI)		4,543	4,312	4,554	3,491	3,586	3,491	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN

Field Adjustable Output (Q9/Q6/Q5/Q4/Q3/Q2/Q1) Option Description:

The Field Adjustable Output option enables the OSQ area luminaires to be tuned to the exact needs of a particular application through multiple levels of adjustment. When ordered with the Q option, the luminaire will be shipped from the factory at the selected Q setting and will be fully adjustable between the nine settings.

Q Option Power & Lumen Data – Designator K

Q Option Setting	CCT/CRI	System Watts	Lumen Values						Optics Qualified on DLC QPL	
			120-480V	Asymmetric	5ME	5SH & Floods	2ME w/BLS	3ME w/BLS	4ME w/BLS	Standard
Q9 (Full Power)	30K (70 CRI)	130	16,022	15,063	15,909	12,312	12,649	12,312	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		16,959	15,999	16,897	13,032	13,389	13,032	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		14,000	14,925	15,800	10,750	11,050	10,750	TBD	TBD
	57K (70 CRI)		17,291	16,277	17,191	13,286	13,650	13,286	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q6	30K (70 CRI)	117	14,099	13,255	14,000	10,835	11,131	10,835	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		14,924	14,079	14,869	11,468	11,782	11,468	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		12,500	13,350	14,100	9,600	9,875	9,600	TBD	TBD
	57K (70 CRI)		15,216	14,324	15,128	11,692	12,012	11,692	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q5	30K (70 CRI)	110	13,298	12,502	13,204	10,219	10,499	10,219	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		14,076	13,279	14,025	10,817	11,113	10,817	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		11,250	12,050	12,725	8,650	8,900	8,650	TBD	TBD
	57K (70 CRI)		14,352	13,510	14,269	11,027	11,330	11,027	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q4	30K (70 CRI)	93	11,536	10,845	11,454	8,865	9,107	8,865	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		12,210	11,519	12,166	9,383	9,640	9,383	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		9,825	10,525	11,100	7,550	7,750	7,550	TBD	TBD
	57K (70 CRI)		12,450	11,719	12,378	9,566	9,828	9,566	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q3	30K (70 CRI)	80	9,773	9,188	9,704	7,510	7,716	7,510	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		10,345	9,759	10,307	7,950	8,167	7,950	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		8,350	8,950	9,475	6,425	6,600	6,425	TBD	TBD
	57K (70 CRI)		10,548	9,929	10,487	8,104	8,327	8,104	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q2	30K (70 CRI)	67	8,171	7,682	8,114	6,279	6,451	6,279	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		8,649	8,159	8,617	6,646	6,828	6,646	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		6,825	7,325	7,725	5,250	5,375	5,250	TBD	TBD
	57K (70 CRI)		8,818	8,301	8,767	6,776	6,962	6,776	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
Q1	30K (70 CRI)	51	6,249	5,875	6,205	4,802	4,933	4,802	5ME	2ME, 3ME, 4ME, 5SH, 15D, 25D, 40D, 60D, WSN
	40K (70 CRI)		6,614	6,240	6,590	5,082	5,222	5,082	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN
	50K (90 CRI)		5,250	5,650	5,975	4,030	4,150	4,030	TBD	TBD
	57K (70 CRI)		6,743	6,348	6,704	5,182	5,324	5,182	N/A	2ME, 3ME, 4ME, 5ME, 5SH, 15D, 25D, 40D, 60D, WSN


OSQ™ LED Area/Flood Luminaire – Medium

AA Mount




Weight

28.4 lbs. (12.9kg)



RR/RL Configuration





TSP Mount



Weight

42.0 lbs. (19.1kg)

OSQ Large luminaire shown.





TM Mount



Weight

32.6 lbs. (14.8kg)

OSQ Large luminaire shown.



© Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. Cree® and the Cree logo are registered trademarks of Cree, Inc. NanoOptic® and Colorfast DeltaGuard® are registered trademarks, and Precision Delivery Grid™ and OSQ™ are trademarks of Cree Lighting, A company of IDEAL INDUSTRIES. The UL logo is a registered trademark of UL LLC. NEMA® is a registered trademark of the National Electrical Manufacturers Association. The DLC QPL logo and the DLC QPL Premium logo are registered trademarks of Efficiency Forward, Inc.

US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

CREE ⇄ **LIGHTING**

A COMPANY OF IDEAL INDUSTRIES, INC.