

SUNLITE-EC



Sunlite Suite USB & Ethernet DMX Controller

Overview

Featuring 1024 DMX channels, the SUNLITE-EC is compatible with Sunlite Suite 2 and 3 running in express mode out of the box. The Ethernet connection allows a range of connectivity options.

As well as live performance, this interface can operate as a Stand Alone DMX controller, for use with RGB/RGBW and more advanced moving and color mixing luminaires.

SUT (Smart Upgrade Technology) enables upgrades such as Artnet universes and compatibility with additional software and apps when purchased at store.dmxsoft.com.

www.sunlitepro.com



Key Features

- 2x DMX512 universes in live mode
- 1x DMX512 universes in stand alone mode
- Expandable from 2 to 4 DMX512 universes
- Intuitive backlit keyboard with 10 presets
- Standalone mode with 99 scenes across 5 zones
- USB & Ethernet for programming/control
- Multi-zone microSD memory
- 16 dry contact trigger ports via HE20 connector
- Clock and calendar triggering (optional)
- Phone/iPad/Android remote and programming apps
- Metal bracket, mount to a wall or under a desk
- DMX in or out. RDM ready.
- Ingenious USB-C Protection
- Smart Upgrade Technology (SUT)

Technical Data

Input Power	5-5.5V DC 0.6A
Output Protocol	DMX512
Connections	Type C USB, XLR3, Ethernet, HE20, battery
Memory	microSD SD & SDHC (32Gb Max)
Environment	IP20. 0°C - 50°C
Buttons	10 buttons for direct access 2 buttons to change scene + 1 button to change zone
Dimensions	160x90x45mm 268g
OS Requirements	Mac OS X 10.8-10.15 Windows 7/8/10 64bit
Standards	EC, EMC, ROHS

Optional Accessories

POWER1_EU/UK/US 5V ACDC power supply with EU/UK/US plug

CONNECTIVITY

Live use with a computer



Stand Alone or live use with a smartphone/tablet

