

CERTIFICATE OF COMPLIANCE

Certificate Number 20201016- R9700
Report Reference R9700
Issue Date 2020-October-16

Issued to: 3M COMPANY 3M FIRE PROTECTION PRODUCTS
3M CENTER
SAINT PAUL, MN 55144-1001 USA

**This certificate confirms that
representative samples of**

Fill, Void or Cavity Materials

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 1479, "Fire Tests of Penetration Firestops"
Fourth Edition
ANSI/UL 2079, "Tests for Fire Resistance of Building Joint
Systems" - Fourth Edition
ANSI/ASTM E2307, "Standard Test Method for Determining
Fire Resistance of Perimeter Fire Barriers Using
Intermediate-Scale, Multi-story Test Apparatus."

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20201016- R9700
Report Reference R9700
Issue Date 2020-October-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

FireDam™ Spray 200 for use in Joint System Nos. BW-S-0008, FF-D-0002, FF-D-0014, FF-D-1042, FW-D-0004, FW-D-0011, FW-D-1040, HW-D-0020, HW-D-0021, HW-D-0022, HW-D-0023, HW-D-0029, HW-D-0030, HW-D-0031, HW-D-0038, HW-D-0040, HW-D-0101, HW-D-0118, HW-D-0122, HW-D-0123, HW-D-0192, HW-D-0248, HW-D-0265, HW-D-0376, HW-D-0379, HW-D-0384, HW-D-0385, HW-D-0447, HW-D-0465, HW-D-0478, HW-D-0479, HW-D-0552, HW-D-0575, HW-D-0604, HW-D-0633, HW-D-0755, HW-D-0807, HW-D-1010, HW-D-1020, HW-D-1059, HW-D-1079, HW-D-1080, HW-D-1123, WW-D-0215, WW-D-0227, WW-D-0228, WW-D-1202, WW-D-1203, WW-D-1204, WW-D-1239, WW-D-1240, WW-D-1241.

FireDam™ Spray 200 for use in Perimeter Fire Containment System Nos. CW-D-1017, CW-D-2055, CW-S-2004, CW-S-2005, CW-S-2007.

FireDam™ Spray 200 for use in Through-Penetration Firestop System Nos. C-AJ-1275, C-AJ-8106, W-L-8033, W-L-8034.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

