

Dulux®

RENOVATION

RANGE

TRANSFORMATION MADE EASY

SPLASHBACK

EASY HOW-TO PROJECT GUIDE



Dulux
Natural White™



SPLASHBACK

Dulux® Renovation Range Tiles & Benchtops is a revolutionary, water based interior coating perfect for transforming your splashback.

Shopping List

- ✓ Dulux® Renovation Range Tiles & Benchtops in your chosen colour
- ✓ Dulux® Renovation Range Clear Coat
- ✓ 38–50mm high quality angled sash cutter
- ✓ 4mm nap 100mm wide microfibre roller
- ✓ Paint stirrer and drop sheet
- ✓ Painters tape
- ✓ P400 sanding paper
- ✓ Selleys® Sugar Soap
- ✓ Selleys® Silicone Remover
- ✓ Selleys® Rapid Mould Killer™
- ✓ Dulux® Renovation Range Grout Pen – optional

EXPERT TIP

Use the *Dulux* Renovation Range Grout Pen to recreate the look of grout lines after you've painted.

Preparation

Dulux Renovation Range Tiles & Benchtops, requires a clean surface to adhere. All grease and dirt contamination **MUST** be removed, or the paint will not adhere and will peel or flake off.

Previously Painted Surfaces:

On ALL surfaces cleaning is the most important step.

- Scrub down all areas with Selleys® Sugar Soap and rinse with clean water to remove any dirt, oil or grease. Use a plastic scouring pad on heavily contaminated surfaces.
- Repeat this process using clean water, at least twice.

IMPORTANT: Do not use abrasive cleaning detergents.

- Completely remove any loose and flaking paint. Fill any cracks or holes with a suitable hard epoxy based filler such as Selleys® Knead-IT® Aqua.
- Sand glossy and semi gloss finishes to a dull flat finish using p400 paper before coating.
- Use a clean damp cloth to remove any dust.

Tiles and Glass – Wall and Splashback:

- For grout lines ensure to remove all grease and oil.
- Thoroughly clean surface using Selleys® Rapid Mould Killer™. Remove all silicone sealant from joints using Selleys® Silicone Remover.

- Wash down well with water.
- Sand with p400 paper all areas where silicone has been removed.
- Wash with Selleys® Sugar Soap and use a scrubbing brush or a toothbrush to properly clean grout lines.
- Rinse with clean water and dry with a clean cloth.
- Allow grout lines to dry for a minimum 2 hours before painting. Mask using a good quality painters tape.

Mixing:

Add all of the Additive found underneath the blue lid to the paint.

Stir well for approximately 2-5 minutes with a broad flat paddle, using an up and down scooping action until the additive is completely mixed into the paint.

Once mixed the product is suitable to use for up to 10 days.



Sand surface



Add the additive and mix together

Application

Topcoat

After the additive has been added and stirred, apply at least two coats of *Dulux Renovation Range Tiles & Benchtops* ensuring that the previous coat is left for a minimum of 8 hours before recoating.

1. Cut in as necessary using a 38–50mm high quality angled sash cutter brush.
2. Coat surface using a 4mm nap 100mm wide microfibre roller.
3. Lay off. Once each section is coated, gently go over the surface in the same direction with an unloaded roller using minimal pressure. This will give a smooth consistent finish.

Clear Coat

On benchtop and splashback areas apply *Dulux Renovation Range Clear Coat* as the final coating. This will add a layer of protection to the *Dulux Renovation Range* topcoat.



Scrub tiles before applying topcoat



Roll on topcoat

THE PERFECT RENOVATION SYSTEM

This revolutionary range works as a three step system. For the best possible result, ensure you always follow all three steps.*

1. CLEAN & PREP



Cleaning

Clean with Selley's® Sugar Soap.

2. TOPCOAT



Topcoat

Tiles & Benchtops.

3. FINAL TOUCHES



Clear Coat

Available in satin and gloss clear coat.

NEED HELP & ADVICE?



CALL: Aust 13 25 25
NZ 0800 800 424



ONLINE & LIVE CHAT:
dulux.com.au, dulux.co.nz



For 'How To' videos,
helpful tips and more,
scan here!

FRONT COVER: Tiles: **Dulux Renovation Range Tiles & Benchtops** in *Dulux Natural White*™.
Cupboards: **Dulux Renovation Range Cabinet Doors** in *Dulux Silkworth*.

Disclaimers: Colours shown are as close as possible to actual paint colours. Please note, due to limitations of the printing process, photographic and printed images may not represent the true colour. Always confirm your choice with a *Dulux* Sample Pot.

*For full use instructions please see the *Dulux* website and review the Data Sheet, Application and FAQ information. *The *Dulux* Renovation Range Floor product does not require a clear coat as it will reduce the non-slip performance.

Registered trade mark information: Dulux, Worth doing, worth Dulux, Selleys and Knead-IT are registered trademarks and Natural White and Rapid Mould Killer are trade marks of DuluxGroup (Australia) Pty Ltd.