

# T20 Daily Operational Checklist



Before cleaning with your machine there are a few pre-operational checks that need to be done to confirm your machine is ready to be used.

- Check the hydraulic fluid level.
- Check the fuel level.
- Check the condition of the main brushes.  
Remove any string, banding, plastic wrap, or other debris wrapped around the brushes.
- Check the main brush compartment right hand skirt and squeegee for damage and wear.
- Check the optional side scrubbing brush.  
Remove any string, banding, plastic wrap, or other debris wrapped around the brush.
- Check the condition of the side brush squeegee.
- Confirm the radiator and hydraulic cooler fins are clean.
- Check the engine coolant level.
- Check the engine oil level.
- Check the main brush compartment left hand skirt and squeegee for damage and wear.
- Check the left solution tank cover seal for damage and wear.
- Check the recovery tank cover seal for damage and wear.
- Confirm the vacuum fan screen is clean.
- Confirm the optional ES filter is clean.
- Confirm the recovery tank is drained and clean.
- Check the right solution tank cover seal for damage and wear.
- Check the vacuum hoses for debris or blockage.
- Check the squeegees for damage and wear.
- Check the optional FaST-PAK™ detergent concentrate level and replace as needed.
  - Ensure all conventional cleaning agents are drained and rinsed from the solution tank.  
NOTE: When FaST™ Scrubbing: Ensure the solution tank is filled with **clear cool water only**.
- Check the headlights, taillights and safety lights.
- Check the steering and brakes for proper operation.
- Check the service records to determine maintenance requirements.

List below any problems that occurred during operation.

---

---

---

OPERATOR \_\_\_\_\_ DATE \_\_\_\_\_

SUPERVISOR \_\_\_\_\_ DATE \_\_\_\_\_