

ECS4100-28T-DC

L2+ Gigabit Ethernet Access Switch



Product Overview

The Edgecore ECS4100-28T-DC switch is a Gigabit Ethernet access switch with four 1G uplink ports. The switch is ideal for Internet Service Providers (ISPs) and Multiple System Operators (MSOs) to provide home users with triple-play services with up to a Gigabit of bandwidth. It is also an ideal Gigabit access switch for SMB, enterprise, and campus networks. The ECS4100-28T-DC switch is packed with features that bring high availability, comprehensive security, robust multicast control, and advance QoS to the network edge, while maintaining simple management. The switch also supports the most advance IPv6 management, IPv6 security, and IPv6 multicast control in accordance with the growth of IPv6 deployment. ISPs can expand their services from home to business users by providing a more reliable and resilient network (ITU-T G.8032 ERPS), L2 VPNs, and advanced OAM (Operations, Administration, and Maintenance) functions to ensure service-level agreements.

Key Features and Benefits

Performance and Scalability

The Edgecore ECS4100-28T-DC is a high-performance Gigabit Ethernet Layer 2+ managed switch with 56 Gbps switching capacity. The switch delivers wire-speed switching performance on all Gigabit ports, taking full advantage of existing high-performance Gigabit CPEs, PCs, 11n/ac Wi-Fi APs etc, significantly improving the responsiveness of applications and file transfer times.

The four 1G SFP ports provide uplink flexibility, allowing the insertion of fiber or copper gigabit transceivers, to create up to 4Gbps high-speed uplinks to service provider, corporate, campus networks, reducing bottlenecks and increasing the performance of the access network.

The fanless design ensures noiseless operation and increases the reliability of the system.

Reliability and Energy Efficiency

The design of the ECS4100-28T-DC incorporates high energy efficiency in order to reduce the impact on the environment. The Green Ethernet power-saving features and fanless design significantly reduce power consumption.

Continuous Availability

The IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability.

The IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base, providing Layer 2 load sharing on redundant links up to 64 instances.

The ECS4100-28T-DC supports IEEE 802.3ad Link Aggregation Control Protocol (LACP). It increases bandwidth by automatically aggregating several physical links together as a logical trunk and offers load balancing and fault tolerance for uplink connections.

The ECS4100-28T-DC supports G.8032 Ethernet Ring Protection Switching with the ability for the network to detect and recover from incidents without impacting users, meeting the most demanding quality and availability requirements. Rapid recovery time when problems do occur is as low as 50 ms.

Enhanced Security

Port security limits the total number of devices using a switch port and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. When a user is authenticated, the VLAN, QoS, and security policy are automatically applied to the port where the user is connected, otherwise the port is grouped in a guest VLAN with limited access.

DHCP snooping allows a switch to protect a network from rogue DHCP servers that offer invalid IP addresses.

IP Source Guard prevents people from using IP addresses that were not assigned to them.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, or TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Secure Shell (SSH) and Secure Sockets Layer (SSL/HTTPS) encrypt Telnet and web access to the switch, providing secure network management.

Private VLANs (traffic segmentation per port) isolate edge ports to ensure user privacy.

Dynamic ARP Inspection (DAI) is a security feature that validates Address Resolution Protocol (ARP) packets in a network. DAI allows a network administrator to intercept, log, and discard ARP packets with invalid MAC-to-IP address bindings.

The ECS4100-28T-DC also supports both RADIUS and TACACS+ authentication methods to secure your network.

Key Features and Benefits

Comprehensive QoS

The ECS4100-28T-DC offers advanced QoS for marking, classification, and scheduling to deliver best-in-class performance for data, voice, and video traffic at wire speed. Eight egress queues per port enable differentiated management of up to eight traffic types through the switch.

Traffic is prioritized according to 802.1p and DSCP to provide optimal performance for real-time applications.

Weighted Round Robin (WRR) and strict priority ensure differential prioritization of packet flows and avoid congestion of ingress and egress queues.

Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allows maximum control of network resources.

Robust Multicast Control

IGMP snooping prevents the flooding of multicast traffic by dynamically configuring switch ports so that multicast traffic is forwarded to only those ports associated with an IP multicast receiver. IGMP increases the performance of networks by reducing multicast traffic flooding.

IGMP groups allow you to create customer packages for IP-TV channels, making switch configuration easy. IGMP Filtering prevents subscribers seeing unsubscribed IP-TV channels. And, IGMP Throttling allows you to set how many IP-TV channels a subscriber can receive simultaneously.

Multicast VLAN Registration (MVR) is designed for applications such as Media-on-Demand that send multicast traffic across an Ethernet network. Multicast VLANs are shared in the network, while subscribers remain in separate VLANs. This increases network security and saves bandwidth on core links. Multicast streams do not have to be routed in core L3 switches, which saves CPU power.

IPv6 Support

The switch supports a number of IPv6 features, including IPv6 Management, DCHPv6 Snooping with Option 37, IPv6 Source Guide, and MVR6.

Superior Management

An industry-standard command-line interface (CLI), accessed through the console port or Telnet, provides a familiar user interface and command set for users to manage the switch.

An embedded user-friendly web interface helps users to quickly and simply configure switches.

The ECS4100-28T-DC supports SNMPv1,2c,3 and four-group RMON. The switch provides a complete private MIB for the configuration of most functions via the SNMP protocol.

Administrators can backup and restore firmware and configuration files via TFTP or FTP. The switch also provides the configuration of auto-provision for ease of use in large deployments.

AAA (Authentication, Authorization and Accounting) via RADIUS, TACACS+, enables centralized control of the switches. Access rights can be authorized per user and account for all actions performed by administrators.

Service Monitoring and Management

The ECS4100-28T-DC supports IEEE 802.1ag and ITU-T Y.1731, allowing service providers to monitor end-to-end services, identify connectivity and performance issues, and isolate problems from a remote location without dispatching an engineer onsite.


The switch also provides the capability to monitor service availability, delay, and delay variation for verifying SLA conformance (for billing purposes) and providing advance indication of performance degradation before a service outage occurs.

Virtual Private Networks

The ECS4100-28T-DC supports Layer 2 VPNs by using Q-in-Q functions, where an 802.1Q tag from a customer VLAN (called CE-VLAN ID) is encapsulated in a second 802.1Q tag from a service-provider network (called an SP-VLAN ID). The switch supports rewriting the VLAN tag of egress traffic when the ingress traffic is tagged.

The switch also supports Layer 2 Protocol Tunneling for STP, CDP, VTP, PVST+, with Cisco-proprietary multicast address (01-00-0c-cd-cd-d0) replacement.

Features

Product Model		ECS4100-28T-DC
Product Image		
Port	RJ-45 10/100/1000 BASE-T Ports	24
	100/1000 BASE-X SFP Ports	4
	Combo Gigabit (RJ-45/SFP) Ports	0
	SFP+ 10 Gigabit Uplink Ports	0
	GE out-of-band Management Port	No
	RJ-45 Console Port	1
Performance	Switching Capacity	56 Gpbs
	Forwarding Rate	41.6 Mpps
	Flash Memory	32 MB
	DRAM	256 MB
	MAC Address Table Size	16 K
	Jumbo Frames	12 K
	Auto-negotiation, Auto-MDI/MDIX	Yes
Mechanical	Rack Space	19"-1 RU
	Dimension (W x D x H) cm	44 x 22 x 4.4
	Weight	2.2 kg
Power Supply	DC Power Input (36-60 V)	Yes
	Max System Power Consumption (Watts)	20 W
Environmental	Operating Temperature	0°C to 50°C
	Storage Temperature	-40°C to 70°C
	Operating Humidity (non-condensing)	10% to 90%
	Storage Humidity (non-condensing)	10% to 90%
	Environmental Regulation compliance: WEEE	Yes
	Environmental Regulation compliance: RoHS	Yes
Certification	FCC Class A	Yes
	CE	Yes
	BSMI	Yes
	Safety Compliance: CB	Yes
	Safety Compliance: UL	Yes

Features

L2 Features

Tri-speed (10/100/1000BASE-T) copper interfaces
Auto-negotiation for port speed and duplex mode
Auto MDI/MDI-X
Dual-speed (100 M and 1G) SFP fiber interfaces
SFP ports support:
 IEEE 802.3u (100BASE-FX) transceivers
 IEEE 802.3z (1000BASE-SX/LX/LHX/ZX) transceivers
Digital Diagnostic Monitoring (DDM) on 1G SFP port
Flow Control:
 IEEE 802.3x for full-duplex mode
 Back-pressure for half-duplex mode
Jumbo frames: 12KB
Broadcast/Multicast/Unknown Unicast Storm Control
Spanning Tree Protocol:
 IEEE 802.1D Spanning Tree Protocol (STP)
 IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 IEEE 802.1s Multiple Spanning Tree Protocol (MSTP), 64 instances
BPDU Guard
BPDU Filter
Root Guard
Loopback detection
Non-Spanning Tree Loopback detection
ITU-T G.8032 Ethernet Ring Protection:
 Sub 50 msec convergence
 Revertive operation mode
 Multiple-ring network
VLANs:
 Supports 4K VLAN
 Port-based VLAN
 IEEE 802.1Q VLAN
 GVRP
 IEEE 802.1v protocol-based VLAN
 IP Subnet-based VLAN
 MAC-based VLAN
 Traffic Segmentation
L2 Virtual Private Network
 Q-in-Q
 L2 Protocol tunneling (xSTP, CDP, VTP & PVST+, LLDP)
 CDP/PVST+ Filtering
Link Aggregation:
 Static trunk
 IEEE 802.3ad Link Aggregation Control Protocol
 Trunk groups: 16, up to 8 GE ports per group
 Load Balancing: SA+DA, SA, DA, SIP+DIP, SIP, DIP
IGMP Snooping:
 IGMP v1/v2/v3 Snooping
 IGMP Proxy reporting
 IGMP Filtering
 IGMP Throttling
 IGMP Immediate Leave
 IGMP Querier
MVR (Multicast VLAN Registration): Support for 5 multicast VLANs
Port mirroring
Remote port mirror (RSPAN)

QoS Features

Priority Queues: 8 hardware queues per port
Traffic classification:
 IEEE 802.1p CoS
 DSCP
 MAC access control list (Source/Destination MAC, Ether type, Priority ID/ VLAN ID)
 IP standard access control list (Source IP)
 IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)
Traffic Scheduling:
 Strict priority
 Weighted Round Robin
 Strict + WRR
 Ingress policy map (police rate, remark CoS)
 Egress policy map (police rate, remark CoS/DSCP)
Rate limiting (ingress and egress, per port base):
 GE: Resolution 64 Kbps ~ 1,000 Mbps

Security

Port security
IEEE 802.1X port-based and MAC-based authentication
Dynamic VLAN assignment
MAC authentication
Web authentication
Voice VLAN
Guest VLAN
L2/L3/L4 Access Control List:
 MAC Access control list (Source/Destination MAC, Ether type, Priority ID/ VLAN ID)
 IP standard access control list (Source IP)
 IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)
IPv6 ACL
DHCP Snooping
DHCP Option 82
IP Source Guard
PPPoE IA
Dynamic ARP Inspection
Denial of Service Protection
Login Security
RADIUS authentication
RADIUS accounting
TACACS + authentication
TACACS + accounting
TACACS + authorization
Management Interface access filtering (SNMP, Web, Telnet)
SSH (v1.5/v2.0) for security Telnet
SSL for HTTPS

Green Ethernet

IEEE 802.3az Energy-Efficient Ethernet (EEE)

Features

IPv6 Features

- IPv4/IPv6 dual protocol stack
- IPv6 address types stack: Unicast
- IPv6 neighbor discovery:
 - Duplicate address
 - Address resolution
 - Unreachable neighbor detection
- Stateless auto-configuration
- Manual configuration
- Remote IPv6 ping
- IPv6 Telnet support
- HTTP over IPv6
- SNMP over IPv6
- IPv6 Syslog support
- IPv6 TFTP support
- MLD Snooping v1/v2
- IPv6 source guard
- DHCPv6 snooping
- MVR6

Management

- Switch Management:
 - CLI via console port or Telnet
 - Web management
 - SNMP v1, v2c, v3
- Firmware and Configuration:
 - Firmware upgrade via TFTP/HTTP/FTP/SFTP server
 - Multiple configuration files
 - Configuration file upload/download via TFTP/HTTP/FTP/SFTP server
- RMON (groups 1, 2, 3 and 9)
- DHCP client for IP address assignment
- DHCP dynamic provision option 66,67
- SNTP
- Syslog (local flash)
- Remote log (RFC3164)
- SMTP (email notification)
- Supports LLDP (802.1ab)
- sFlow v4, v5
- Cable diagnostic
- (Optional) ECView Pro, a powerful network management software that maximizes the managed capabilities of Edgecore devices with:
 - Topology management
 - Performance management
 - Configuration management
 - Event management
 - SNMP management

Routing

- IPv4 Static Route

OAM

- IEEE 802.3ah Link Dying gasp
- IEEE 802.1ag Connectivity Fault Management
 - Connectivity check
 - Loopback
 - Linktrace
- ITU-T Y.1731 Performance and Throughput Management
 - Frame Delay
 - Frame Delay variation

Safety

- UL (CSA 22.2. NO 60950-1 & UL60950-1)
- CB (IEC60950-1)

Electromagnetic Compatibility

- CE Mark
- FCC Class A
- CISPR Class A
- BSMI

Environmental Specifications

- Temperature:
 - 0° C to 50° C (32° F to 122° F) standard operating
- Humidity: 10% to 90% (non-condensing)

Power Supply

- Power input
 - DC power input: 36-60 V

Warranty

Please check www.edge-core.com for the warranty terms in your country.

For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit www.edge-core.com.

About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore Data Center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2017 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

Optional Accessories	Product Description
ET4201-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm)
ET4201-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET4201-LHX	1Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)
ET4201-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)
ET4201-RJ45	1000BASE-T RJ45 transceiver, 100 m
ET4202-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm, DDM)
ET4202-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm, DDM)
ET4202-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm, DDM)
ET4203-BX20	1Gbps, SFP (Distance: 20 km; Wavelength: Tx1310 nm / Rx1490 nm)
ET4203-BX20D	1Gbps, SFP (Distance: 20 km; Wavelength: Tx1490 nm / Rx1310 nm)
ET4204-BX10	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1310 nm / Rx1550 nm)
ET4204-BX10D	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1550 nm / Rx1310 nm)
ET4204-BX10DDMi	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1310 nm / Rx1550 nm, DDM)
ET4204-BX10DDDMi	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1550 nm / Rx1310 nm, DDM)
ECView Pro	Network Management Software