

SAFETY DATA SHEET

1. Identification	
Important information	*** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. ***
Product identifier	MLT-B704Series
Other means of identification	None.
Recommended use	This product is a toner mixture that is used in printing systems.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier	/Distributor information
	HP Canada Co.
	5150 Spectrum Way, Floor 6
	Mississauga, Ontario, Canada L4W 5G1
Telephone	1-905-206-4725
	or 1-888-447-4636
HP Inc. health effects line	
(Toll-free within the US)	1-800-457-4209
(Direct)	1-760-710-0048
HP Inc. Customer Care Line	
(Toll-free within the US)	1-800-474-6836
(Direct)	1-208-323-2551
Email:	hpcustomer.inquiries@hp.com
Emergency Telephone Number	1-760-710-0048
Supplier	Not available.
2. Hazard identification	
Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	Not available.
Precautionary statement	
Prevention	Not available.
Response	Not available.
Storage	Not available.
Disposal	Not available.
Other hazards	Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present this carcinogenic risk. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Styrene acrylic resin		Proprietary	<85%
Wax		Proprietary	<10%
Amorphous silica	Amorphous silica	Proprietary	<5%
Black Pigment		Proprietary	<5%

4. First-aid measures

Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Ingestion	Rinse mouth with water. Drink one to two glasses of water. DO NOT induce vomiting. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Difficulty in breathing. Coughing.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical, foam, carbon dioxide, water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Avoid the generation of dusts during clean-up. Use explosion proof electric equipment. Collect dust using a vacuum cleaner equipped with HEPA filter. The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Sweep up or vacuum up spillage and collect in suitable container for disposal.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Minimize dust generation and accumulation. Use local exhaust ventilation. Avoid prolonged exposure. Practice good housekeeping.
Conditions for safe storage, including any incompatibilities	Store in tightly closed original container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

	ersonal protection		
upational exposure limits US. ACGIH Threshold Lin	mit Values	Value	Form
Components	Туре	Value	
Black Pigment	TWA	3 mg/m3	Inhalable fraction.
Wax	TWA	2 mg/m3	Fume.
Canada. Alberta OELs (C Components	Dccupational Health & Safety Code, Sche Type	edule 1, Table 2) Value	Form
Black Pigment	TWA	3.5 mg/m3	
Wax	TWA	2 mg/m3	Fume.
Safety Regulation 296/97	-		-
Components	Туре	Value	Form
Black Pigment	TWA	3 mg/m3	Inhalable
Wax	TWA	2 mg/m3	Fume.
Canada. Manitoba OELs	(Reg. 217/2006, The Workplace Safety A	nd Health Act)	
Components	Туре	Value	Form
Black Pigment	TWA	3 mg/m3	Inhalable fraction.
Wax	TWA	2 mg/m3	Fume.
Canada. Ontario OELs. (Components	Control of Exposure to Biological or Che Type	emical Agents) Value	Form
Black Pigment	TWA	3 mg/m3	Inhalable fraction.
		-	
Wax	TWA	2 mg/m3	Fume.
	TWA (Ministry of Labor - Regulation respecting Type	·	
Canada. Quebec OELs. ((Ministry of Labor - Regulation respecting	g occupational health and s	afety)
Canada. Quebec OELs. (Components	(Ministry of Labor - Regulation respecting Type	g occupational health and s Value	afety)
Canada. Quebec OELs. (Components Black Pigment Wax	(Ministry of Labor - Regulation respecting Type TWA	g occupational health and so Value 3.5 mg/m3 2 mg/m3	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan ((Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re	g occupational health and so Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21)	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type	g occupational health and so Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components Black Pigment	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute 8 hour	g occupational health and so Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute	g occupational health and so Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3 r the ingredient(s).	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components Black Pigment Black Pigment	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute 8 hour No biological exposure limits noted for	g occupational health and si Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3 r the ingredient(s). otal Dust)	afety) Form
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components Black Pigment Black Pigment	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute 8 hour No biological exposure limits noted for USA OSHA (TWA/PEL): 10 mg/m3 (T	g occupational health and si Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3 r the ingredient(s). otal Dust) able Particulate) sed. Ventilation rates should b boal exhaust ventilation, or oth mended exposure limits. If exp to an acceptable level. If engir of dust particulates below the C must be worn. If material is gr use appropriate local exhaust	e matched to conditions. If er engineering controls to posure limits have not beer beering measures are not Occupational Exposure Lim ound, cut, or used in any
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components Black Pigment Black Pigment logical limit values bosure guidelines	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute 8 hour No biological exposure limits noted for USA OSHA (TWA/PEL): 10 mg/m3 (T ACGIH (TWA/TLV): 15 mg/m3 (Inhala Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recommestablished, maintain airborne levels below recommestablished, maintain airborne levels to sufficient to maintain concentrations of (OEL), suitable respiratory protection operation which may generate dusts,	g occupational health and so Value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3 r the ingredient(s). Total Dust) able Particulate) sed. Ventilation rates should b bocal exhaust ventilation, or oth mended exposure limits. If exp to an acceptable level. If engir of dust particulates below the C must be worn. If material is gr use appropriate local exhaust nits.	e matched to conditions. If er engineering controls to posure limits have not beer beering measures are not Occupational Exposure Lim ound, cut, or used in any
Canada. Quebec OELs. (Components Black Pigment Wax Canada. Saskatchewan (Components Black Pigment Black Pigment logical limit values bosure guidelines	(Ministry of Labor - Regulation respecting Type TWA TWA OELs (Occupational Health and Safety Re Type 15 minute 8 hour No biological exposure limits noted for USA OSHA (TWA/PEL): 10 mg/m3 (T ACGIH (TWA/TLV): 15 mg/m3 (Inhala Good general ventilation should be us applicable, use process enclosures, la maintain airborne levels below recom established, maintain airborne levels t sufficient to maintain concentrations o (OEL), suitable respiratory protection operation which may generate dusts, below the recommended exposure limite res, such as personal protective equipme	g occupational health and seven value 3.5 mg/m3 2 mg/m3 egulations, 1996, Table 21) Value 7 mg/m3 3.5 mg/m3 r the ingredient(s). Total Dust) able Particulate) sed. Ventilation rates should be boal exhaust ventilation, or othe mended exposure limits. If exp to an acceptable level. If engir of dust particulates below the C must be worn. If material is gr use appropriate local exhaust nits. ent (or goggles).	e matched to conditions. If er engineering controls to posure limits have not beer beering measures are not Occupational Exposure Lim ound, cut, or used in any

Respiratory protection	No personal respiratory protective equipment required under normal conditions of use. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

-	• •
Appearance	
Physical state	Not available.
Form	Solid. Fine powder
Color	Black.
Odor	Odorless
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	No information available
Initial boiling point and boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not flammable
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not applicable
Vapor density	Not applicable
Solubility(ies)	
Solubility (water)	Insoluble in water.
Solubility (other)	Partially soluble in toluene, chloroform and tetrahydrofurane
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	No data available
Decomposition temperature	> 392 °F (> 200 °C)
Viscosity	Not applicable
Other information	Not available.
Oxidizing properties	No information available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal storage conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the decomposition temperature. Contact with incompatible materials.
Incompatible materials	This product may react with strong oxidizing agents.
Hazardous decomposition products	Carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Not available.

Information on toxicological effects

Based on available data, the classification criteria are not met. LD50/oral/rat >5000 mg/kg.

> 10000 mg/kg
available data, the classification criteria are not met. wn irritant. (OECD 404).
available data, the classification criteria are not met. wn irritant. (OECD 405).
piratory sensitizer.
uct is not expected to cause skin sensitization.
available data, the classification criteria are not met. Ames Test (Test strains: Salmonella typhimurium).
available data, the classification criteria are not met.
ack is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group y the State of California under Proposition 65. In their evaluations of carbon black, both ons indicate that exposure to carbon black, per se, does not occur when it remains hin a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a m in this preparation.
of Carcinogenicity
3 Not classifiable as to carcinogenicity to humans.
la io r

Amorphous sinca (CAS FI	ophetaly) 5 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Further information

Complete toxicity data are not available for this specific formulation Refer to Section 2 for potential health effects and Section 4 for first aid measures.

In a study in rats (H.Muhle) by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of the rats in the concentration(16mg/m3) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animals in the middle (4mg/m3) exposure group. But no pulmonary changes was reported in the lowest (1mg/m3) exposure group, the most relevant level to potential human exposures.

In 1996, the IARC revaluated carbon black as a GROUP 2B carcinogen (possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the developer of lung tumors in rat receiving chronic inhalation exposures to free carbon black at level that induce particle overload of the lung. Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumors. Moreover, a two-year cancer bioassay using a typical toner preparation containing carbon black demonstrated no association between toner exposure and tumor development in rats.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Other adverse effects	This product has not been tested for ecological effects.

13. Disposal considerations

Disposal instructions	Dispose of in compliance with federal, state, and local regulations. Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Do not put toner container into fire; heated toner may cause severe burns. Do not incinerate. Do not allow this material to drain into sewers/water supplies.
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.
Waste from residues / unused products	Not available.
Contaminated packaging	Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

Further information

Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated.

Stockholm Convention Not applicable. Rotterdam Convention Not applicable. Kyoto protocol

Not applicable. Montreal Protocol Not applicable. Basel Convention All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

Not applicable.	
16. Other information	
Issue date	18-Mar-2018
Revision date	17-Oct-2020
Version #	06
Other information	This SDS was prepared in accordance with Canada Controlled Product Regulations.
Disclaimer	This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
	This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds