Architectural Door Accessories

Rockwood Locking Pull System



Experience a safer and more open world



LOCKING PULL SYSTEM



SIMPLE, DURABLE,

BEAUTIFUL DESIGN

FOR SWINGING AND

SLIDING DOORS

The Rockwood Locking Pull System integrates a contemporary Post

Mount or GeoMetek style door pull with deadbolt locking. Engineered for smooth operation, the locking pull is manufactured to ensure strength and durability with clean appealing lines.



Features

- Key operated from outside; turn piece on inside
- Cylinder options: Yale® 1109 rim cylinder, Yale K680 SFIC housing, dummy or less cylinder
- Door types: 3/8" 7/8" thick glass, 13/8" 21/2" thick aluminum, hollow metal or wood doors
- Multiple locking options: floor, head or both
- Bolt location: 2" from face of door to centerline of bolt
- Bolt has 13/16" travel with fine adjustment
- Horizontal push/pull bar option
- Designed to Suite with Rockwood architectural door pulls and accessories
- Dummy versions available

Benefits

- Cylinder and thumbturn location eliminates physical strain when locking and unlocking
- Glass door applications secure the opening and allow for more natural light
- Bolt concealed inside pull provides a clean, streamlined look
- Simple door preparation allows for faster installation
- Suites with popular Rockwood door pulls, CORBIN RUSSWIN and SARGENT lever handles, McKinney hinges, creating a continuum of design
- Offers flexibility in custom sizes for a variety of applications



AESTHETIC OPTIONS







LP3301 Series

PostMount - This basic post mounted pull is a clean and simple design. The simplicity adds contemporary beauty to standard entrance doors.

LP3401 Series

GripZone - This beautiful bright and brushed two-tone finish provides a "wear" area for gripping the pull. This minimizes the appearance of small scratches caused by rings and keys.



LP6061 Series

English Bridle Leather Wrapped - Authentic J & E Sedgwick & Co. Ltd. bridle leather imported from Walsall, England is hand sewn by a talented craftsman. Typically used for saddles and equestrian products, this smooth durable leather is suitable for both interior and exterior applications.



LP6161 Series

Upholstery Leather Wrapped - Supple yet durable leather makes a discriminating statement. Paired with the PostMount Locking Pull, this glove soft leather will add a level of sophistication to your interior.





LP7901 Series

GeoMetek - This series offers a streamlined profile and crisp lines. The square pull complements the shape of the opening creating symmetrically balanced design.



LP6440 Series

Upholstery Leather Wrapped - Beautifully crafted, the GeoMetek and Upholstery Leather combination produces an elegant composition. The leather is tightly wrapped and neatly sewn on the back and is offered in a plethora of custom colors.

SUITING OPTIONS

The Locking Pull System was designed to suite with Rockwood Architectural door pulls, and accessories. In addition, complementary hardware is available through Corbin Russwin, Pemko Products, McKinney Products, and SARGENT.



McKinney two knuckle hinge with flat tips



Rockwood coat hook (left) and door stop (right)



Leather wrapped lever from Corbin Russwin and Sargent



Rockwood leather cabinet pull



Rockwood leather





McKinney square barrel hinge





Rockwood coat hook (left) and door stop (right)



Square lever and rose from Corbin Russwin and Sargent



Square lever with return and rose from Corbin Russwin and Sargent



Rockwood door pull

the $good \, design \, studio$

The Good Design Studio — your resource for beautiful doors, frames and hardware from ASSA ABLOY Group brands.

Visit www.thegooddesignstudio.com to learn more.





AESTHETIC OPTIONS



Full Height Pull - Single and Dual Bolt Models

FHD (Full Height Down) - Bolts Down FHU (Full Height Up) - Bolts Up FHB (Full Height Both) - Bolts Up and Down






Notes:


- 1. Pulls are available in various sizes to fit job conditions. For ADA requirements, cylinder must be located 34" to 48" above finished floor.
- **2.** Minimum clearance from pull to finished floor is $\frac{3}{8}$ " at factory settings.

SUITING OPTIONS

Half Height Pull - Bolts Up DBU (Dead Bolt Up)




Half Height Pull - Bolts Down DBD (Dead Bolt Down)





Clearance and Half Height Pull - Bolts Down (LP3305)

DBD (Dead Bolt Down)



HORIZONTAL PUSH/PULL BAR



Features


- Horizontal push/pull bar option for locking pull system
- PostMount or bent end design offered
- Available for half height DBD and DBU models only*
 - Bar options single sided (thumbturn or cylinder side only) and double sided (bar on both sides)
- Offered on aluminum, glass, hollow metal doors or wood doors

Benefits


- Keeps glass clean and free of hand prints
- Provides greater push/pull area while maintaining clean aesthetic
- Contemporary design that suites with popular Rockwood door pulls


HORIZONTAL PUSH/PULL BAR

Single Sided (Thumbturn or Cylinder)




Double Sided






Glass doors

Location from Door



All glass door applications include a bushing and washer to insulate the glass from the pull. Sturdy fasteners securely attach the pull to the door making for a durable, trouble free installation. Simple glass prep requires two (or three) round holes.

Bolt Adjustment



Adjusts 1/4" in and out from the shown factory settings.


Bolt into Floor Models - Detail at Floor

DBD - Half Height Pull - Bolts Down

FHD - Full Height Pull - Bolts Down

FHB - Full Height Pull - Bolts Up and Down

Bottom Detail with Threshold




Bolt into Head Models - Detail at Head

DBU - Half Height Pull - Bolts Up


FHU - Full Height Pull - Bolts Up

 $\ensuremath{\mathsf{FHB}}\xspace$ - Full Height Pull - Bolts Up and Down




Aluminum, wood and hollow metal doors

Location from Door



Locking pulls are available for $1^{3}/_{8}$ " to $2^{1}/_{2}$ " thick aluminum, wood or hollow metal doors.

Bolt Adjustment




Adjusts $^{1}/_{4}$ " in and out from the shown factory settings.

Bolt into Floor Models - Detail at Floor

DBD - Half Height Pull - Bolts Down FHD - Full Height Pull - Bolts Down

FHB - Full Height Pull - Bolts Up and Down


Bottom Detail with Threshold




Bolt into Head Models - Detail at Head

DBU - Half Height Pull - Bolts Up FHU - Full Height Pull - Bolts Up

FHB - Full Height Pull - Bolts Up and Down





Installation reference




Holes Sizes Required

Glass Door

- End Posts: 5/8" ø
 for 1/2" glass thickness
- Lock Housing: 13/16" Ø

Aluminum, Wood, Hollow Metal Doors:

- End Posts: 11/32"
- Lock Housing: 13/16"



Notes:

- 1. Only drill the holes required for the model you are installing.
- 2. Only full height locking pulls require all three holes.

Strike options

Top Strike Options

Custom Strikes Available

LPS01



• 3/4" x 11/2" x 3"

LPS02



- $^{3}/_{4}$ " x $2^{1}/_{2}$ " x 3"
- Rubber Stop

LPS03



• .050" x 11/8" x 21/4"

LPS04



• 11/4" dia. x 41/2" h

LPS05



• 11/4" sq. x 41/2" h

LPS06



• 2" dia

Bottom Strike Option

570



Dust Proof Strike

Face Plate: 13/8" x 27/8"



ORDERING INFORMATION

Series*	Description
LP3301	Plain PostMount
LP3305**	Plain PostMount Clearance
LP3401	PostMount GripZone
LP6061	PostMount English Bridle Leather Wrapped
LP6161	PostMount Upholstery Leather Wrapped
LP7901	Plain GeoMetek
LP6440	GeoMetek Upholstery Leather Wrapped

^{*} Specify "DP" in front of series number for dummy locking pull. Example: DP3301

^{**}LP3305 offered with DBD only.

Options	Code*
Large Thumbturn	ADA
Thumbturn Only, No Cylinder	Π
Custom Engraving	CE

^{*}Specify code after suffix



Suffix	Description
DBD	Half Height, Bolts Down
DBU	Half Height, Bolts Up
FHD	Full Height, Bolts, Down
FHU	Full Height, Bolts Up
FHB	Full Height, Bolts Up and Down

Cylinder Options	Code
Yale® 1109 rim cylinder, 6-pin, 1147 tailpiece, E1R keyway (keyed random)	01
Yale® K680 Small format interchangeable core housing (SFIC) Standard	02
Yale® K680 Small format interchangeable core housing, w/ plastic construction core (SFIC)	03
Supplied cylinder	05
Dummy cylinder	07
7 Pin SFIC Housing with Yale Core	09

Push Bar Suffix*	Description
BEPT	Bent End Horizontal Bar - Thumbturn Side
BEPC	Bent End Horizontal Bar - Cylinder Side
BEPB	Bent End Horizontal Bar - Both Sides
PMPT	Post Mount Horizontal Bar - Thumbturn Side
PMPC	Post Mount Horizontal Bar - Cylinder Side
PMPB	Post Mount Horizontal Bar - Both Sides

^{*} Available on DBD and DBU models only. Not offered with LP7901 or LP6440. Specify horizontal CTC and handing; sized to order.

How to Order Example:

For a quick and efficient ordering process, use the order forms on assaabloydooraccessories.us (Resource Library > Order Forms > Rockwood Products).

Quantity	Series		Push Bar Suffix	Finish	Door Material	Door Thickness	Device Dimensions	Door Clearance	Strike	Cylinder
1	LP3301	DBD	BEPT	630	Glass	1/2"	831/2"	¹/₄" at Bottom		01
2	LP7901	DBD	N/A	629	Wood	13/4"	931/4"	¹/s" at Top	LPS02	

PostMount Finishes:

Polished Brass	605	(US3)
Satin Brass	606	(US4)
Satin Oxidized Clear Coated	614	(US10BL)
Dark Satin Bronze Equivalent	613E	(US10BE)
Polished Stainless Steel	629	(US32)
Satin Stainless Steel	630	(US32D)
Satin Stainless Steel with MicroShield®	-	(US32DMS)
Polished Stainless Steel with MicroShield®	_	(US32MS)
Black Suede Powder Coat	BSP	

Black Suede Powder Coat White Suede Powder Coat

Stock Powder Coats

GeoMetek Finishes:

Dark Satin Bronze Equivalent	613E	(US10BE)
Polished Stainless Steel	629	(US32)
Satin Stainless Steel	630	(US32D)
Satin Stainless Steel with MicroShield®	-	(US32DMS)
Polished Stainless Steel with MicroShield®	_	(US32MS)
Black Suede Powder Coat	BSP	

Stock Powder Coats

White Suede Powder Coat

Leather Finish Standard Color Selections:

English Bridle Leather



B-LBRN



B-BUR



WSP



B-DBRN



Upholstery Leather





WSP

Custom colors available

Accessories

- LPS01 Top Strike
- LPS02 Top Strike
- LPS03 Top Strike
- LPS04 Transom Strike
- LPS05 Transom Strike
- LPS06 Mortised Header Strike
- 570 Dust Proof Bottom Strike
- RM850 Door Stop
- Custom Strikes for unique conditions
- ADA Thumbturn





RM850 Door Stop

Thumbturns:







ADA Thumbturn



MicroShield®

As part of their promise to provide innovative solutions to their customers, certain ASSA ABLOY Group brands offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the growth of bacteria.

MicroShield* is a registered trademark of Yale Security Inc., an ASSA ABLOY Group company.

The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, locks, perimeter fencing



