

**Peterbilt of Atlanta P801
172 Van Mar Blvd**

Jackson, Georgia United States 30233
Phone: (404) 592-9980
Fax:
Email:

Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs)	21000
Description:		G.C.W. (lbs):	33000
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	Flatbed		6
Length (ft):	20	Wheelbase (in):	239
Height (ft):	13.5	Overhang (in):	81.79999
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	72.2
Trailer		Cab to Axle (in):	166.8
No. of Trailer Axles:	0	Cab to EOF (in):	248.6
Type:		Overall Comb. Length (in):	341
Length (ft):	0		
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	United States Registry	
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by:

Date:

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 7/19/2017 5:37:30 PM **Complete** Model Number: Model 337
Effective Date: Jan 1, 2017 Quote/DTPO/CO: Q42980323
Prepared by: ID: davidmarshall Version Number: 34.20

Peterbilt of Atlanta P801
172 Van Mar Blvd

MILLER INDUSTRIES
8503 Hilltop Drive

Jackson, Georgia United States 30233
Phone: (404) 592-9980
Fax:
Email:

Ooltewah, Tennessee United States 37363
Phone: (800) 292-0330
Fax:
Contact Email:
Prepared for: VINCE TIANO

Data	Code	Description	\$ List	Weight
Base Model				
0003371	O	Model 337	10,070	
0091200	O	Other Commodity	0	
0093340	O	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	
0095020	O	Flatbed	0	
0098170	O	United States Registry	0	
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	
Frame & Equipment				
0515010	O	10-5/8in Steel Rails 326-384 in 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	349	
0612230	O	Custom Wheelbase or Overhang Engineering approval may be required.	0	
0613090	O	Three-Piece Crossmembers	0	
0644090	S	EOF Square without Xnbr For use with body builder installed crossmember.	0	
0651090	S	Omit Rear Mudflaps and Hangers	0	
Front Axle & Equipment				
1011875	O	Dana Spicer E1202IL 12,000 lb. Axle is designed for applications with a gross axle weight rating (GAWR) from 10,000 to 13,200 pounds. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0	
1111190	O	Taper Leaf Springs, Shocks 12,000 lb	0	
1233100	O	Power Steering TRW THP60 For use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	
1250180	O	Power Steering Reservoir Frame Mounted	0	
1354795	O	PHP10 Iron LMS Hubs-Air Disc	184	
1354870	O	Severe Service Disc Brake Rotor For refuse applications	243	
1380240	O	Dana Spicer Wide Track IPO Std, Front Axle 71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles. For improved turning radius.	5	
1380290	O	Air Disc Front Brakes Complies with reduced stopping distance regulations.	0	
1391490	O	Pad And Rotor Dust Shields for Air Disc Brakes; Front Axle	0	

Rear Axle & Equipment

1513160	O	Dana Spicer S21-170 21,000 lb Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	225
1616300	O	PHP10 Iron PreSet PLUS Hubs	0
1616310	O	Severe Service Disc Brake Rotor For Refuse Applications	14
1631310	S	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	0
1660020	O	Pad and Rotor Dust Shields For Air Disc Brakes, Drive Axle(s)	15
1671040	O	Diff Lock Rear-Rear Or Single Drive Axle (Air Rocker Switch occupies the space of one gauge)	24
1680280	O	Bendix Smart ATC Traction Control	2
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680950	S	Stability System Not Selected or Not Available	0
1681337	S	Single Drive Axle (Model 337)	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0
1687080	O	Air Disc Rear Brakes, Single Drive Axle	0
1704300	O	Ratio 4.30 Rear Axle	0
1811210	O	Peterbilt Air Trac 23,000 lb Light Weight	175
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	0
1922260	O	Dash Mtd Dump Switch With Indicator Light For suspension	2

Engine & Equipment

2074604	O	PACCAR PX-9 380@1900 GOV@2100 1250@1400 Performance (2017 Emissions) N21320 N205 120..Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21340 P005 120..Hard Maximum Speed Limit N21350 P001 86...Maximum Accelerator Pedal Vehicle Speed N21370 P059 86...Maximum Cruise Speed N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 NO...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Overrule N21590 P230 YES..Enable Hot Ambient Automatic Overrule N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold	0
---------	---	--	---

		N21630 P171 80...High Ambient Temperature Threshold	
2091310	O	Engine Idle Shutdown Timer Disabled	0
2091315	O	Enable EIST Ambient Temp Overrule	0
2091372	O	Eff EIST NA Expiration Miles	0
2091640	O	Effective VSL Setting NA	0
2140150	O	Remote PTO And Throttle Provision	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2140320	O	Remote Throttle/PTO Control Switch & Wiring EOF W/ Park Brake	4
2513060	S	PACCAR 160 Amp Alternator, Brushed	0
2521090	O	Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
2522050	S	PACCAR 12V Starter	0
2535040	O	3 Optima DT31T Batteries 2700 CCA Threaded Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	55
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	4
2621030	O	On/Off Fan Clutch	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2812140	O	C-Brake By Jacobs, PX-9	90
2921160	O	Spin-On Fuel/Water Separator	0
2921210	O	No Fluid Heat Option for Fuel Filter	0
2921320	O	12V Heat for Fuel Filter	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3365290	O	Exhaust Single RH Horizontal DPF/SCR RH Under Frame (2017).	-158

Transmission & Equipment

4020170	O	Eaton FAO14810C-EA3 10-Speed, Advantage Series Automated, No Cooler Required. Forward Ratios: 1st-12.80, 2nd-9.25, 9th-1.00, 10th-0.73 / Reverse Ratios: Low-13.63, High-2.78	255
4210330	O	1760 HD Driveline, 2 Midship Bearings	80
4233030	O	(1) Dash Mounted Single Acting Air PTO Control Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. Specing PTO switch does not ensure the PTO will fit.	0
4250790	O	Aluminum Transmission Bell Housing IPO Iron Eaton transmission 1450 torque and above	-52
4252150	O	Tower Mounted Lever Shifter	0
4380270	O	Remote Lube Hoses for Clutch Linkage, Release	6

Air & Trailer Equipment

4510320	S	Bendix AD-IS Air Dryer W/Heater And Coalescing Filter	0
4520420	O	Pull Cords All Air Tanks	0
4540260	O	Wrecker A&E Connection EOF on Movable Xnbr Dash mounted air Toggle Valve plumbed to Service Brakes and Steering Column-mounted hand valve plumbed to EOF air lines. Includes 7-way Socket.(Occupies the space of one gauge) Includes Winch Brake switch on the dash.	4
4540420	S	Nylon Chassis Hose	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4611930	O	Body Connections 5ft BOC Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	4

Tires & Wheels

5056840	O	FF: MN 16ply 11R22.5 X Line Energy Z	0
5156470	O	RR: MN 16ply 11R22.5 X Works Z	68
5190004	O	Code-rear Tire Qty 04	0
5221750	O	FF: Peterbilt 886677 22.5X8.25 Clean Buff Finish Aluminum	-42
5321750	O	RR: Peterbilt 886677 22.5X8.25 Clean Buff Finish Aluminum	-84
5390004	O	Code-rear Rim Qty 04	0
5407640	O	FF: Polish Wheels, Outer Surface, SGL/TDM Steer Polish outer surface of outer wheel. Without chrome wheel nuts.	0
5407650	O	RR: Polish Wheels, Outer Surface, Single Drive Without chrome wheel nuts. Polish outer surface of outer wheel.	0

Fuel Tanks

5551160	O	26in Aluminum 90 Gallon Fuel Tank RH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	-112
5555040	O	26in Aluminum 50 Gallon Fuel Tank LH U/C Addl Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	101
5601090	O	Location RH U/C 90 Gallon	0
5602050	O	Location LH U/C 50 Gallon	0
5650550	O	Polish (2) Non-Slip Fuel Tank Steps,U/C Tank Only	0
5650820	O	Polish (2) Aluminum Fuel Tanks	0
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to Rectangular Def Tank straps.	0
5652900	O	DEF Tank Mounted LH Under Cab	0
5652990	O	Standard DEF To Fuel Ratio 2:1 Or Greater	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	0
5655019	O	DEF Tank Small	0

Battery Box & Bumper

6010390	O	Omit Standard Battery Box (For use with passenger seat/in-cab battery box codes only)	-45
---------	---	---	-----

6121200	O	Steel Styled Aero Bumper Chrome Two Tow Pins	0
Cab & Equipment			
6515640	O	Alum Cab 110in BBC Metton Hood With bright finish crown. Includes view window RH door and convex mirror over RH door.	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	39
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
6540720	O	10 Inch Extension for Ultra Day Cab Add additional 10" to the loadspace dimension-- refer to the horizontal dimension workscreen.	163
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the driver's door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	2
6911710	O	Peterbilt Premium UltraRide Driver Seat	4
6921700	O	Peterbilt UltraRide Passenger Seat	0
6930060	O	Driver Seat Heated Includes heating elements in the lower cushion and backrest. Temperature is preset for optimum comfort and controlled by a high/low switch and an on/off switch next to the adjustment valves on the seat. Available w/Peterbilt, Ultraride and Sears seats.	4
6930090	O	Passenger Seat Heated Includes heating elements in the lower cushion and backrest. Temperature is preset for optimum comfort and controlled by a high/low switch and an on/off switch next to the adjustment valves on the seat. Available w/Peterbilt and UltraRide seats.	4
6930230	O	Seat Skirt - All Eligible Air Seats	2
6930580	O	Drivers Armrests - LH & RH Required in Model 587 with Evolution LX seats, optional with Evolution ST and Rolltek Seats.	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	2
6939070	O	Mounted On In-Cab Battery Box For use with non-air passenger seats only. Includes battery quick disconnect located under driver side door.	39
6939400	O	Air Ride Driver	0
6939420	S	High Back Driver	0
6939450	O	Leather Driver	0
6939520	O	High Back Passenger	0
6939550	O	Leather Passenger	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	11
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
7036120	S	Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
7210420	O	Dark Window Tint ipo STD Tint - Day Cab	0
7210540	S	Day Cab Rear Window	0

7230060	S	One Piece Curved Windshield	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	4
7330700	O	Peterbilt Comfort Control - Cab	6
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	4
7561180	O	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	4
7564110	O	Power Package Includes power door locks and power windows.	0
7565180	O	Polished Lower Mirror Bracket Covers	0
7620620	O	(2) Air Horns 24.5in Chrome - Round w/Horn Shield	16
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7740100	O	Cobra 40 Channel CB Radio w/Integral Speaker Includes illuminated front panel.	10
7748320	O	(2) 48 Inch CB Antennas	0
7748500	O	CB Antenna Mounting, LH Mirror	0
7748510	O	CB Antenna Mounting, RH Mirror	0
7749490	O	Sirius-XM Satellite Radio Service Provider Option designates XM Satellite Radio - subscription required (800-852-9696).	0
7789620	O	SmartNav With Navigation Telematics and infotainment system, including integrated Audio, provides an expandable list of features and capabilities. Please see the Product Portfolio for details.	8
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7851970	O	Unibilt Cab Air Suspension Includes dual air bag suspension, leveling valve, and tracking rod.	25
7852010	O	Removable Ashtray In Cup Holder	0
7900090	O	Triangle Reflector Kit Shipped Loose	13
7900270	O	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	8
8011150	O	Main Transmission Oil Temperature Located in SmartNav display	0
8021015	O	Air Application Gauge Located in Driver Information Display	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping or firewall	0
8032420	O	Buzzer On Air Suspension Dump Valve Requires dash mounted dump valve (1922260)	0
8070120	O	Manifold Pressure, Boost Located in SmartNav display	0
8070170	O	DPF Status Located in SmartNav display	0
8070180	O	Fuel Economy Located in SmartNav display	0
8070190	O	Percent Torque Located in SmartNav display	0
8071340	O	Bright Bezel Gauges	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature,	0

low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.

8111110	S	Headlights Composite Fender Mounted Integral Park, Turn, and Side Marker	0
8121170	O	(5) Marker Lights, Bus LED Bullet Light Emitting Diodes	0
8131560	O	(2) Peterbilt Fog Lights Recessed in bumper	6
8133900	O	None Furnished Stop/Tail/Backup Lights Available with Full Truck only. Not available with Tractor.	0
8134070	O	(2) Addl Dome/Reading Lights, Ceiling Mounted	0

Paint

8500710	O	Standard Paint Color Selection	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE - STAND N85400 HOOD TOP L0006EY WHITE - STAND N85500 CAB ROOF L0006EY WHITE - STAND N85200 FRAME N0001EA BLACK N85300 FENDER L0006EY WHITE - STAND	0

Options Not Subject To Discount

9408931	O	PDI At Excellence Peterbilt Location	0
---------	---	---	---

Miscellaneous

9409800	O	2017 EPA Emissions Engine Warranty Only	0
9409960	O	Presentation Created Using Featured Spec For Model	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)

Freight Charge

Options Not Subject to Discount

Surcharges Not subject to Discount

Total Weight

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	7/19/2017 5:37:30 PM	Complete	Model Number:	Model 337
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q42980323
Prepared by:	ID: davidmarshall		Version Number:	34.20